

Index to 1985 NASA Tech Briefs

Volume 10, Numbers 1-4

APRIL 1987

N92-70026

Unclas
0048099

Z9/85

(NASA-TM-105114) INDEX TO 1985 NASA TECH
BRIEFS, VOLUME 10, NUMBERS 1-4 (NASA)
111 P



Electronic Components and Circuits

SAP \$10.00



Electronic Systems

48099



Physical Sciences

P-111



Materials



Computer Programs



Mechanics



Machinery



Fabrication Technology



Mathematics and Information Sciences



Life Sciences

This document was prepared by the NASA Scientific and Technical Information Facility operated for the National Aeronautics and Space Administration by RMS Associates. It is available from the NASA Scientific and Technical Information Facility, P.O. Box 8757, Baltimore, Maryland 21240, at \$10.00 per copy. Make checks payable to "RMS Associates."

INTRODUCTION

Tech Briefs are short announcements of new technology derived from the research and development activities of the National Aeronautics and Space Administration. These briefs emphasize information considered likely to be transferrable across industrial, regional, or disciplinary lines and are issued to encourage commercial application.

This *Index to NASA Tech Briefs* contains abstracts and four indexes — subject, personal author, originating Center, and Tech Brief Number — for 1985 Tech Briefs.

Availability of NASA Tech Briefs

Distribution of *NASA Briefs*, a bi-monthly free publication, is limited to engineers in U.S. Industry and to other domestic technology transfer agents.

Requests for individual Tech Briefs or for copies of the bi-monthly publication should be addressed to the Manager, Technology Transfer Office, P.O. Box 8757, Baltimore/Washington International Airport, Maryland 21240.

If you are seeking any information on NASA's Technology Utilization Program, its documents and services, please call (301) 859-5300, Ext. 241 or 243.

The January 1985 edition of the *NASA Thesaurus* (NASA SP-7053) is used as the authority for the indexing vocabulary that appears in the subject index. The *NASA Thesaurus* should be consulted in examining the current indexing vocabulary, including associated cross-reference structure. Only the subject terms that have been selected to describe the documents abstracted in this issue appear in the subject index. Copies of the *NASA Thesaurus* may be obtained from the National Technical Information Service at \$35.00 for Volume 1 and \$20.00 for Volume 2.

Originating Center Prefixes

ARC	Ames Research Center
GSC	Goddard Space Flight Center
HQN	NASA Headquarters
KSC	Kennedy Space Center
LAR	Langley Research Center
LEW	Lewis Research Center
MFS	Marshall Space Flight Center
MSC	Johnson Space Center (formerly Manned Spacecraft Center)
NPO	Jet Propulsion Laboratory/NASA Pasadena Office

TABLE OF CONTENTS

Abstract Section

Category 01	Electronic Components and Circuits	1
02	Electronic Systems	8
03	Physical Sciences	14
04	Materials	21
05	Life Sciences	30
06	Mechanics	31
07	Machinery	40
08	Fabrication Technology	48
09	Mathematics and Information Sciences	52

Indexes

Subject	I-1
Personal Author	I-27
Originating Center/Tech Brief Number	I-45
Tech Brief/Originating Center Number	I-49

TYPICAL ABSTRACT ENTRY

TECH BRIEF NUMBER
↓
B85-10468
TITLE → DETECTING TRACE CONTAMINANTS IN THE ATMOSPHERE
INOVATOR → S. K. SRIVASTAVA (Caltech)
DATE → Mar. 1986
ORIGINATING CENTER NUMBER → NPO-16225

Vol. 9, No. 4, P. 86 ← REFERENCE IN NASA TECH BRIEF

ABSTRACT ← Sensitive instrument uses two low-energy electron beams to detect certain molecules. Experimental instrument identifies and measures trace contaminants in atmosphere. When fully developed, portable instrument expected to measure contaminant concentrations of certain halogen containing molecules as low as one part per trillion. Instrument employs electron beams to ionize contaminant molecules by dissociative attachment of electrons.



Index to 1985 NASA Tech Briefs

APRIL 1987

Abstract Section

01 ELECTRONIC COMPONENTS AND CIRCUITS

B85-10001 **MEASURING RECOMBINATION VELOCITIES IN SOLAR CELLS**

O. VONROOS (CALTECH) and K. L. LUKE (CALTECH)
Jun. 1985

NPO-16243

Vol. 9, No. 1, P. 36

Electron-beam scanning method suggested for determining back-surface recombination velocity, SB, of back-surface-field (BSF) solar photovoltaic cell. Recombination velocity important because smaller value correlated with smaller saturation current and therefore higher cell efficiency. Method involves analyzing short-circuit current measured while electron beam scanned along edge of cell.

B85-10002 **HYBRID FIBER-OPTIC/CCD CHIP**

W. C. GOSS (CALTECH) and J. R. JANESICK (CALTECH)
Jun. 1985

NPO-16030

Vol. 9, No. 1, P. 38

Low noise and linearity of charge-coupled devices (CCD's) combined with optical waveguide components in hybrid, integrated chip package. Concept used to measure laser flux in fiber-gyro application using sensing fibers that range from several to several tens of kilometers in length. Potential applications include optical delay measurement and linear detector of light flux emanating from fiber-optic waveguides.

B85-10003 **DIGITAL HIGH-CURRENT MONITOR**

B. CASH (Martin Marietta Corporation)
Jun. 1985

LAR-13072

Vol. 9, No. 1, P. 39

Simple technique developed for monitoring direct currents up to several hundred amperes and digitally displaying values directly in current units. Used to monitor current magnitudes beyond range of standard laboratory ammeters, which typically measure 10 to 20 amperes maximum. Technique applicable to any current-monitoring situation.

B85-10004 **IMPROVED THICK DICHROIC REFLECTOR FOR MICROWAVE FEEDS**

P. D. POTTER (CALTECH)

Jun. 1985

NPO-13506

Vol. 9, No. 1, P. 39

Geometry of reflector plate adjusted to compensate for undesired effects. Design change reduces depolarization

and noise in thick microwave dichroic reflecting plate tilted 30 degrees from orientation broadside to incident beam.

B85-10005 **TILTMETER INDICATES SENSE OF SLOPE**

J. O. LONBORG (CALTECH)

Jun. 1985

NPO-16153

Vol. 9, No. 1, P. 40

Tiltmeter indicates sense and magnitude of slope used in locations where incline not visible to operator. Use of direct rather than alternating current greatly simplifies design of instrument capable of indicating sense of slope.

B85-10006 **DUAL-MODE HORN ANTENNA FOR MILLIMETER WAVELENGTHS**

H. M. PICKETT (CALTECH)

Jun. 1985

NPO-16297

Vol. 9, No. 1, P. 42

Millimeter-wave feed horn exhibits nearly equal beam-intensity patterns in E- and H-planes as well as low side-lobe levels. Horn includes circular waveguide step transition, and conical section. Design simplified version of Potter feed-horn design. New feed horn easier to construct, in part because of simpler shape. Reduction in phase change between step transition and aperture increases bandwidth, thereby reducing precision required to manufacture phase-sensitive dimensions of horn.

B85-10007 **FLUX COUPLING FOR WHEELCHAIR BATTERY CHARGERS**

C. W. MCILYMAN (CALTECH)

Jun. 1985

NPO-16269

Vol. 9, No. 1, P. 43

Battery-charger concept for wheelchairs includes magnetic-flux coupling instead of electrical connections between power sources and wheelchairs. Concept meant to facilitate operation by patients whose disabilities make it difficult or impossible to maneuver common electrical plugs into or out of ac wall outlets.

B85-10008 **SIGNAL PROCESSOR FOR MULTIRATE PSK SIGNALS**

R. J. HELGESEN (TRW, Inc.)

Jun. 1985

MSC-20195

Vol. 9, No. 1, P. 43

Any of six different data formats at any of five different data rates from phase-shift-key (PSK) modulated input signal extracted by digital radio receiver. Subcarrier Demodulator is Costas loop with hard limiter in inphase arm. There are six low-pass filters, each selectable for rate and format of data to be processed.

B85-10009 **SAW-MODULATED IMAGE DEVICE**

01 ELECTRONIC COMPONENTS AND CIRCUITS

H. F. BENZ

Jun. 1985

LAR-12633

Vol. 9, No. 1, P. 44

Imaging device uses surface-acoustic-wave (SAW) charge transfer for image readout. Spatial resolution of image changed electronically by changing frequency of applied signal. Surface acoustic waves create traveling longitudinal electric fields. These fields create potential wells that carry along stored charges. Charges injected into wells by photoelectric conversion when light strikes device.

B85-10010

DAMPING RELAXATION OSCILLATIONS IN LASER DIODES

J. KATZ (CALTECH), A. YARIV (CALTECH), and S. MARGAIT (CALTECH)

Jun. 1985

NPO-15980

Vol. 9, No. 1, P. 45

Proposed semiconductor laser modulated at frequencies up to near its resonant frequency more efficiently than older devices. New laser uses two different effective carrier lifetimes: one for dc and low-frequency operation and another for operation near resonant frequency. Laser part of bipolar transistor with capacitor that serves as ac short circuit.

B85-10011

PROTECTIVE COVER FOR IC PACKAGES

T. J. BORDEN (CALTECH)

Jun. 1985

NPO-15537

Vol. 9, No. 1, P. 46

Aluminized plastic protects integrated circuits from static discharge. Snap-on cover shorts leads of integrated-circuit flatpack to prevent damage from electrostatic discharges during transport, installation, or other handling before final testing. Cover removed only during lead bending and testing.

B85-10012

RECOVERING ENERGY FROM RELAYS

C. W. MCLYMAN (CALTECH)

Jun. 1985

NPO-16268

Vol. 9, No. 1, P. 47

Magnetic energy stored in relay recovered with aid of simple circuit. Circuit recovers more than 20 percent of energy stored in relay winding and returns it to powerline. New three-transistor driver circuit requires no additional winding.

B85-10013

RESISTIVE FINE TUNING OF RESONANT CIRCUIT

C. W. MCLYMAN (CALTECH)

Jun. 1985

NPO-16276

Vol. 9, No. 1, P. 47

Simple fixed-inductance/fixed-capacitance tank circuit modified for fine adjustment of resonant frequency by addition of small inductance with potentiometer across it. Additional winding built into full winding as integral part or added externally. Technique provides quick way of tuning reactance out of power-transformer circuit to maximize power transfer or to adjust frequency of oscillator. Applications include rotary transformers, servo amplifiers, and analog computer modules.

B85-10014

TELEPHONE INSTRUMENT FOR THE DEAF

W. H. BROWN

Jun. 1985

KSC-11303

Vol. 9, No. 1, P. 48

Telephone-communication scheme for deaf uses existing tone-encoded telephone equipment to transmit messages. Only special equipment required is decoder at receiving telephone.

B85-10015

DOUBLE LIGHT-EMITTING DIODE

R. L. JOHNSON (Hughes Aircraft Co.) and T. C. HALL

(Hughes Aircraft Co.)

Jun. 1985

GSC-12832

Vol. 9, No. 1, P. 49

Two GaAs light-emitting diodes packaged as single unit offer greater reliability than conventional single-diode package. One diode is primary light source. If it fails, backup diode switched in. Each diode has separate power lead, so either or both switched on or off at same time.

B85-10016

FAST-RECOVERY, HIGH-VOLTAGE POWER DIODE

G. SUNDBERG, A. BERMAN (Power Transistor Co.), V.

BALODIS (Power Transistor Co.), C. GAUGH (Power

Transistor Co.), J. DUFFIN (Power Transistor Co.), H.

KARATNICKI (Power Transistor Co.), and E. LARSON

(Power Transistor Co.)

Jun. 1985 See Also NASA CR-165411 (N81-32382/NSP)

and NASA CR-168196 (N84-13443/NSP)

LEW-14036

Vol. 9, No. 1, P. 49

New family of fast-recovery high-voltage power diodes compatible with D60T and D7ST transistors developed. Have wide range of applications in spacecraft and aircraft electrical distribution equipment, dc/dc inverters, and ac motor controllers for high-horsepower electric motors operating from 480-volt ac lines. Fast-Recovery 1,200-V Power Diodes use chip of hexagonal geometry to maximize effective silicon area.

B85-10017

COMPLEMENTARY-LOGIC FAULT DETECTOR

J. C. WAWRZYNEK (CALTECH)

Jun. 1985

NPO-15410

Vol. 9, No. 1, P. 51

Circuit for checking two-line complementary-logic bits for single faults used as building block for self-checking memory interface for Hamming-coded data. Intended for such applications as fault-tolerant computing, data handling, and data transmission. Circuit performs exclusive-OR function. Many such circuits combined produce complete memory interface with both detection and correction abilities.

B85-10018

HIGH-VOLTAGE ISOLATION TRANSFORMER

C. H. CLATTERBUCK and A. P. RUITBERG

Jun. 1985

GSC-12817

Vol. 9, No. 1, P. 52

Arcing and field-included surface erosion reduced by electrostatic shields around windings and ferromagnetic core of 80-kilovolt isolation transformer. Fabricated from high-resistivity polyurethane-based material brushed on critical surfaces, shields maintained at approximately half potential difference of windings.

B85-10019

FAST CLOCK RECOVERY FOR DIGITAL COMMUNICATIONS

R. G. TELL (CALTECH)

Jun. 1985

NPO-16083

Vol. 9, No. 1, P. 53

Circuit extracts clock signal from random non-return-to-zero data stream, locking onto clock within one bit period at 1-gigabit-per-second data rate. Circuit used for synchronization in optical fiber communications. Derives speed from very short response time of gallium arsenide metal/semiconductor field-effect transistors (MESFET's).

B85-10020

AIRCRAFT CONTROL-POSITION INDICATOR

D. V. DENNIS (Kentron International, Inc.)

Jun. 1985

LAR-12984

Vol. 9, No. 1, P. 54

Aircraft control-position indicator cockpit-mounted instrument that displays positions of elevator and ailerons to pilot. Display is cruciform array of lights: horizontal row of amber lights and vertical row of green lights representing aileron and elevator positions, respectively. Display used

extensively in spin testing and has been trouble-free, with no maintenance required after about 30 hours of operation.

B85-10021**SOLAR CELLS WITH MULTIPLE SMALL JUNCTIONS**
T. DAUD (CALTECH) and K. M. KOLIWAD (CALTECH)

Jun. 1985

NPO-16126

Vol. 9, No. 1, P. 55

Concept for improving efficiency of photovoltaic solar cells based on decreasing p/n junction area in relation to total surface area of cell. Because of reduced junction area, surface leakage drops and saturation current density decreases. Surface passivation helps to ensure short-circuit current remains at high value and response of cells to blue light increases.

B85-10022**LOWERING AMMETER INPUT IMPEDANCE**

C. M. SIEGEL (University of Virginia)

Jun. 1985

NPO-16067

Vol. 9, No. 1, P. 55

Feedback circuit operates in conjunction with sensitive microammeter or other current-measuring instrument to reduce input impedance of composite circuit. In contrast with older current-amplifier circuits, current much less subject to drift and noise, calibration not necessary, and values of components not critical.

B85-10023**INFRARED LINEAR IMAGING ARRAY**

G. C. BAILEY (CALTECH)

Jun. 1985

NPO-15805

Vol. 9, No. 1, P. 56

Photodiodes, multiplexer, and preamp reside in hybrid ceramic package. Hybrid microcircuit produces 128-element line images of infrared scenes. Each picture element is 0.008-in. (0.2-mm) square. Even without image data processing, microcircuit resolves temperature differences as small as 0.05 degrees C in infrared images.

B85-10024**POWER-FACTOR CONTROLLERS: HOW SAFE?**

K. LONG (Underwriters Laboratories, Inc.), W. CHRISTIAN (Underwriters Laboratories, Inc.), J. KOVACIK (Underwriters Laboratories, Inc.), and T. GRAZYK (Underwriters Laboratories, Inc.)

Jun. 1985

MFS-27016

Vol. 9, No. 1, P. 57

Potential safety problems with power-factor controllers (PFC's) evaluated. Based on study of PFCs in use with appliances, report recommends measures to prevent consumers from misapplying these energy saving devices. Device used on such appliances as refrigerators, sewing machines, pumps, hair dryers, and food processors. When misused, they fail to save energy and may cause damage.

B85-10025**PHOTOVOLTAICS IN JAPAN**

K. SHIMADA (CALTECH)

Jun. 1985

NPO-16330

Vol. 9, No. 1, P. 57

Report surveys status of research and development on photovoltaics in Japan. Report based on literature searches, private communications, and visits by author to Japanese facilities. Included in survey are Sunshine Project, national program to develop energy sources; industrial development at private firms; and work at academic institutions.

B85-10140**FERRORESONANT CIRCUIT WITH INCREASED EFFICIENCY**

C. W. T. MCLYMAN (Caltech)

Aug. 1985

NPO-16326

Vol. 9, No. 2, P. 30

Additional inductor reduces heating and increases stability. In modified circuit small inductor in series with

capacitor reduces criticality of tuning. Broadens commutating interval but decreases peak commutating current sufficiently to reduce net heating over complete cycle.

B85-10141**POWER SUPPLY FOR 25-WATT ARC LAMP**

B. D. LEIGHTY

Aug. 1985

LAR-13202

Vol. 9, No. 2, P. 32

Dual-voltage circuitry both strikes and maintains arc. New power supply designed (and several units already in use) that replaces relay/choke combination with solid-state starter. New power supply consists of two main sections. First section (low voltage power supply section) is 84-volt directcurrent supply. Second section (high-voltage starter circuit) is Cockcroft-Walton voltage multiplier. Used as light sources for schlieren, shadowgraph, and other flow-visualization techniques.

B85-10142**PORTABLE TEMPERATURE SET-POINT CONTROLLER**

J. F. MILNER (Rockwell International Corp.)

Aug. 1985

MSC-20056

Vol. 9, No. 3, P. 35

Two off-the-shelf instruments combine to control chamber temperature over wide range. Portable controller for environmental test chambers changes temperatures automatically over range of -300 degrees to +400 degrees F (-184 degrees to +204 degrees C). Unit controls rate of temperature change and time at given temperature. Controller developed to meet NASA Shuttle test requirements.

B85-10143**RECHARGING BATTERIES CHEMICALLY**

R. M. WILLIAMS (Caltech), J. ROWLETTE (Caltech), and J. GRAF (Caltech)

Aug. 1985

NPO-16024

Vol. 9, No. 2, P. 35

Iron/air batteries recharged chemically by solution of strong base in alcohol or by basic alcohol solution of reducing agent. Although method still experimental, it has potential for batteries in electric automobiles or as energy system in remote applications. Also used in quiet operations where noise or infrared signature of diesel engine is not desired.

B85-10144**ROLLING-CONTACT RHEOSTAT**

C. F. RUOFF (Caltech)

Aug. 1985

NPO-15567

Vol. 9, No. 2, P. 36

Contact noise in rheostats and potentiometers reduced by rolling contact design. Smooth rolling action eliminates sporadic variations in resistance caused by bouncing and stick/slip motion of conventional sliding contacts.

B85-10145**INCREMENTALLY VARIABLE HIGH-VOLTAGE SUPPLY**

D. W. POTTER (University of Washington), J. CHIN (University of Washington), H. R. ANDERSON (Science Applications, Inc.), and R. L. LOVELESS (Science Applications, Inc.)

Oct. 1985

MFS-28018

Vol. 9, No. 2, P. 38

Programmable power supply provides regulated output ranging from 2.5 to 2,500 volts. Exponential digital-to-analog converter provides low-voltage analog signal to power converter and to negative and positive high-voltage regulators. In response, converter furnishes voltage of approximate magnitude represented by analog signal, and regulators adjust voltage to precise magnitude. Entire voltage range covered in 169 steps. Total power consumption expected to be less than 2 watts.

B85-10146**LOW-VOLTAGE PROTECTION FOR VOLATILE COM-**

01 ELECTRONIC COMPONENTS AND CIRCUITS

PUTER MEMORIES

R. C. DETWILER (Caltech)

Aug. 1985

NPO-15909

Vol. 9, No. 2, P. 42

Short-circuit current provides minimum memory power. Protective circuit includes dc-to-dc converter that supplies keep-alive voltage to memories when short circuit occurs in any of system loads. Converter powered by low-voltage across two of three series diodes generated by short-circuit bus current. Relay switch is in open (short-circuit-detected) position. Protective circuit useful wherever necessary to improve reliability of volatile memories or other circuits that must not lose power.

B85-10147

COMPARATOR WITH NOISE SUPPRESSION

C. N. BATTS

Aug. 1985

LAR-13151

Vol. 9, No. 2, P. 43

Comparator continuously and automatically adjusts noise immunity period. High-gain amplifier used in conjunction with multivibrator 4 to provide clear pulse to multivibrator 1 at first negative-going zero crossing of input signal. Once multivibrator 1 cleared, output goes to zero volts and not retriggered until next time positive input exceeds reference level. Since input signal noise at zero crossing does not exceed reference level, no effect on multivibrator 1 operation. Circuit fabricated using standard solid-state operational amplifiers, multivibrators, OR gates, and passive elements.

B85-10148

REMOTE POWER CONTROLLERS FOR HIGH-POWER DC SWITCHING

J. C. STURMAN

Aug. 1985

LEW-14109

Vol. 9, No. 2, P. 44

Circuits combine functions of remotely controlled switch and circuit breaker. Circuits developed at different power levels but conceptually very similar. Selection of appropriate switching devices and minor modifications, circuits used to build RPC's covering range of voltage and power levels limited only by switching devices chosen. RPC's using GTO's have power capability ranging from 7.8 to 52 kW, while those using MOSFET's range from 8 to 15 kW. Applications include satellite, Space Station, commercial aircraft, naval vessels, and numerous industrial areas.

B85-10149

HIGH-OUTPUT INJECTION LASER

J. C. CONNOLLY (RCA Laboratories) and D. BOTEZ (RCA Laboratories)

Aug. 1985

LAR-13213

Vol. 9, No. 2, P. 45

Terraced double-heterojunction large optical cavity laser features high output in single optical mode. Semiconductor laser consists of body of single-crystal semiconductor material, typically composed of Group III to V compounds in form of rectangular parallelepiped. One of laser end faces partially transparent so that light may be emitted from it. Lateral thickness variation of active and guide layers in semiconductor laser produces confinement of propagating laser beam in lateral direction.

B85-10150

COMMUTATING PERMANENT-MAGNET MOTORS AT LOW SPEED

C. DOLLAND (AiResearch Manufacturing Co.)

Aug. 1985

MFS-25207

Vol. 9, No. 2, P. 46

Circuit provides forced commutation during starting. Forced commutation circuit diverts current from inverter SCR's and turns SCR's off during commutation intervals. Silicon controlled rectifier in circuit unnecessary when switch S10 replaced by high-current, high-voltage transistor. At present, high-current, low-voltage device must suffice.

B85-10151

REMOTELY-ADJUSTABLE VOLTAGE SUPPLY

W. T. SIMMS (Caltech)

Oct. 1985

NPO-15719

Vol. 9, No. 2, P. 48

Pulsed or steady outputs up to 20 kV produced by commercial components. Circuit produces adjustable high-voltage output in response to low-voltage input. Output voltage changes approximately linearly up to 20 kilovolts as input voltage varied from 0 to 5 volts. Output steady, or sine wave varied at rates up to 100 pulses per second. Output current about 100 microamperes. Reduction in output-filter capacitance confers additional benefit by reducing pulse rise time.

B85-10152

REED-SWITCH POSITION INDICATOR

F. E. WINNER (Martin Marietta Corp.)

Oct. 1985

KSC-11215

Vol. 9, No. 2, P. 49

Indicator for valves or other control mechanisms easy to mount, reliable, and explosion proof. Replaces slidewires expensive and difficult to mount. Used in hazardous areas that require nonexplosive electrical contacts, and controlling highly flammable fuels. Readily adapted to oil-refining and other chemical processing plants.

B85-10153

RETRODIRECTIVE-OPTICAL-TRANSPONDER CONCEPT

R. M. DICKINSON (Caltech)

Aug. 1985

NPO-16315

Vol. 9, No. 2, P. 50

Pointing errors and optical imperfections automatically corrected. Coherent optical transponder employs nearly-degenerate four-wave mixing in nonlinear optical element to produce signal traveling back toward source of incoming signal. Return signal modulated for communication, navigation, data transmission, tracking, and identification. When perfected concept finds important civilian and military applications in line-of-sight tracking, communication and identification.

B85-10154

ELECTRICALLY CONNECTING TO PRESSURE VESSELS

P. J. ROSSI (Rockwell International Corp.)

Oct. 1985

MSC-20709

Vol. 9, No. 2, P. 51

Resilient conductive disk eliminates need for holes in vessel walls. Grounding disk made from wire and solder and sandwiched between electrical-component support and pressure-vessel wall. Emplaced in component support, disk squeezed to 66 percent of its thickness. Disk conforms to surfaces of support and vessel wall when support attached to wall with adhesive. Disk thus forms reliable electrical contact from support (and its electrical component) to wall.

B85-10155

ORIENTING ARC LAMPS FOR LONGEST LIFE

J. KISS (ILC Technology, Inc.)

Oct. 1985

MSC-20562

Vol. 9, No. 2, P. 51

Temperature distribution strongly affects performance. Tests on floodlights for Space Shuttle payload bay show useful life of metal halide dc arc lamp prolonged by mounting 'anode down' and wiring for maximum heat conduction away from electrodes. Anode-down configuration, anode and cathode temperatures stabilize at 333 degrees and 313 degrees C, respectively, after 1 hour of operation. Temperatures both below limit for quartz-to-metal seals, and lamps able to withstand a 2,000-hour life test with satisfactory light output at end.

B85-10156

ROTARY POWER TRANSFORMER AND INVERTER CIRCUIT

01 ELECTRONIC COMPONENTS AND CIRCUITS

C. W. T. MCLYMAN (Caltech) and A. O. BRIDGEFORTH (Caltech)
Oct. 1985
NPO-16270

Vol. 9, No. 2, P. 52

Noise lower than with sliprings. Rotary transformer transfers electric power across rotary joint. No wearing contacts, no contact noise, and no contamination from lubricants or wear debris. Because additional inductor not required, size and complexity of circuit reduced considerably.

B85-10157
PULSE-WIDTH-TO-ANALOG-VOLTAGE CONVERTER
G. S. SOSACK (Rockwell International Corp.) and N. E. SIMMONS (Rockwell International Corp.)
Oct. 1985

Vol. 9, No. 2, P. 53

Peak output voltage varies linearly with input-pulse duration. Circuit converts pulses of varying widths (as from sound-velocity instrumentation or tachometers) into analog voltages. Peak voltage increases in proportion to pulse width. Voltage used to drive an x-y plotter or storage oscilloscope. Pulse-width-to-voltage converter has peak output voltage that varies with duration of input pulses.

B85-10158
MODELING 'SOFT' ERRORS IN BIPOLAR INTEGRATED CIRCUITS
J. ZOUTENDYK (Caltech), R. BENUMOF (Caltech), and O. VONROOS (Caltech)
Oct. 1985

NPO-16375; NPO-16384; NPO-16293 Vol. 9, No. 2, P. 54
Mathematical models represent single-event upset in bipolar memory chips. Physics of single-event upset in integrated circuits discussed in theoretical paper. Pair of companion reports present mathematical models to predict critical charges for producing single-event upset in bipolar randomaccess memory (RAM) chips.

B85-10159
STUDY OF CONTACT RESISTANCES IN INTEGRATED CIRCUITS
M. G. BUEHLER (Caltech), J. LAMBE (Caltech), and S. F. SUSZKO (Caltech)
Oct. 1985
NPO-16248

Vol. 9, No. 2, P. 55

Techniques explored in search for rapid, reliable test. Resistances of aluminum/silicon contacts and methods to measure subjects of NASA report. Study with three tasks undertaken to evaluate nature and reliability of large numbers of semiconductor contacts of type now being fabricated in integrated circuits: Develop yield analysis for series strings of contacts using wafer-level electrical measurements, and identify different types of faults by visual inspection; develop wafer-level tests to evaluate reliability of contact strings; and develop mathematical model for current flow in contacts and examine contact region for evidence of micro-alloying.

B85-10288
POLARIZING FILTER FOR INTEGRATED OPTICS
O. G. RAMER (Hughes Aircraft Co.), W. C. GOSS (Caltech), and R. GOLDSTEIN (Caltech)
Jan. 1986
NPO-16429

Vol. 9, No. 3, P. 36

Polarizing filter for titanium-doped lithium niobate light waveguide suppresses transverse magnetic (TM) mode of light propagation while allowing transverse electric (TE) mode to continue on its way. Filter - lithium niobate crystal - is expected to find many applications in integrated optical circuits.

B85-10289
SMOOTHLY ADJUSTABLE DC LOAD
C. G. PATOCKA (Rockwell International Corp.)
Jan. 1986
MSC-20853

Vol. 9, No. 3, P. 39

Load circuit for testing dc power supplies adjusted without momentary interruptions typical of rheostat loads. Load current passes through power transistor and fixed resistor instead of wire-wound rheostat. In new circuit potentiometer used to adjust bias of power transistor and thereby adjust load. Components are standard, commercially available parts, mounted on transistor heat sink, forming compact package.

B85-10290
FIBER-OPTIC ELECTRIC-FIELD METER
A. R. JOHNSTON (Caltech)
Jan. 1986
NPO-16435

Vol. 9, No. 3, P. 39

Sensor for measuring electric-field strength does not greatly alter field in which placed. Sensor used to map fields in electric power substation or under high-voltage transmission line. Also used for laboratory measurements. Fused-silica fibers guide light from source to photometer. Light emerges from tip of source fiber, passes through curved coupler, and enters tip of photometer fiber. Attenuation of coupler changes with distance between fiber tips.

B85-10291
EFFICIENT POWER AMPLIFIER FOR MOTOR CONTROL
R. J. BROWN (Navtrol Co.)
Jan. 1986
GSC-12807

Vol. 9, No. 3, P. 40

Pulse-width-modulated amplifier supplies high current as efficiently as low current needed for starting and running motor. Key to efficiency of motor-control amplifier is V-channel metal-oxide/semiconductor transistor Q1. Device has low saturation resistance. However, has large gate input capacitance and small margin between its turn-on voltage and maximum allowable gate-to-source voltage. Circuits for output stages overcome limitations of VMOS device.

B85-10292
PLUG-IN RF SELECTOR SWITCH
A. H. HWON (Transco Product, Inc.) and C. F. STEIDEL (Transco Product, Inc.)
Jan. 1986
MSC-20572

Vol. 9, No. 3, P. 41

Short, direct link between switch and filters reduces signal loss. New switch attaches directly to filter housing, eliminating cables and connectors. As result, losses in transmitter and receiver paths reduced by about 0.4 dB. Because connectors and cables are not used, RF path loss for selected signal through switch and filter is smaller than usual.

B85-10293
REMOVING HEAT FROM TOROIDAL INDUCTORS
C. W. T. MCLYMAN (Caltech)
Jan. 1986
NPO-16386

Vol. 9, No. 3, P. 41

Bracket for mounting toroidal inductors adapted for removing heat and providing support. Copper windings wound around bracket instead of directly on core. Heat-dissipating mounting bracket encircles hollow cylindrical magnetic core. Core wrapped with toroidal winding and encapsulated in usual way. Bracket provides direct path for heat to leave both core and windings.

B85-10294
ATTACHING AN ELECTRICAL GROUND TO AN ALUMINUM STRUCTURE
K. L. BILLINGTON (Rockwell International Corp.)
Jan. 1986
MSC-20668

Vol. 9, No. 3, P. 45

Method for creating low-resistance groundpath from electronic equipment to aluminum supporting structure requires no drilling or other penetration of structure. Method does not require costly silver-filled adhesive used previously. Ground connection is light weight, requires few parts,

01 ELECTRONIC COMPONENTS AND CIRCUITS

and not subject to galvanic corrosion. Placed at any convenient location on structure so interference with adjacent parts avoided.

B85-10295

TOUCH SENSOR FOR ROBOTS

H. C. PRIMUS (Caltech)

Jan. 1986

NPO-16230

Vol. 9, No. 3, P. 46

Touch sensor for robot hands provides information about shape of grasped object and force exerted by gripper on object. Pins projecting from sensor create electrical signals when pressed. When grasped object depresses pin, it contacts electrode under it, connecting electrode to common electrode. Sensor indicates where, and how firmly, gripper has touched object.

B85-10296

PREVENTING ELECTROSTATIC-DISCHARGE DAMAGE TO ELECTRONICS

W. S. READ (Caltech), P. C. DOZOIS (Caltech), and J. O. LONBORG (Caltech)

Jan. 1986

NPO-15953

Vol. 9, No. 3, P. 46

Booklet discusses damage to electronic components caused by electrostatic discharges during assembly. Describes procedure for setting up static-free workplace for handling and assembling electronic components.

B85-10297

SINGLE-EVENT-UPSET STUDIES: A COMPILATION

D. K. NICHOLS (Caltech), W. E. PRICE (Caltech), C. J. MALONE (Caltech), and L. S. SMITH (Caltech)

Jan. 1986

NPO-16362

Vol. 9, No. 3, P. 48

Document summarizes 15 studies of single-event upsets covering 60 different types of semiconductor devices. Studies discussed in document include verification of basic reactions induced by heavy ions and protons and surveys of latchup and bit-flip susceptibility of several types of devices and device-fabrication technologies.

B85-10298

OPTIMIZING A LINEAR ARRAY OF RADIATING ELEMENTS

S. J. BLANK (Caltech)

Jan. 1986

NPO-16352

Vol. 9, No. 3, P. 49

EOPS empirically optimizes linear array of radiating elements. Program directly addresses problem of minimizing maximum side-lobe level of fixed length, linear arrays of radiating elements under realistic 'on-the-vehicle' conditions. Used for both electromagnetic and acoustic arrays.

B85-10299

OPTIMIZATION OF ANTENNA-STRUCTURE DESIGN

R. LEVY (Caltech)

Jan. 1986

NPO-16158

Vol. 9, No. 3, P. 50

Conference paper describes application of optimality criterion to design of microwave dish antenna. For purpose of study, overall design objective is to minimize structural weight, subject to design constraints that antenna-pointing and microwave-path-length errors not exceed specified values. Design constraints and optimality criterion satisfied in same procedure.

B85-10300

CONNECTORS AND WIRING FOR CRYOGENIC TEMPERATURES

R. D. TURNER

Jan. 1986

LAR-13193

Vol. 9, No. 3, P. 50

Tests performed at Langley Research Center to find connectors, cables, and other electrical components suitable for use in cryogenic environment described. In addition,

several electrical cables have to flex under cryogenic conditions. Tests necessary to qualify materials for use in National Transonic Facility (NTF), which operates at temperature range from 175 degrees to - 300 degrees F (353 to 89 K).

B85-10428

PULSE COUPLING FOR LASER EXCITATION

T. J. PACALA (Caltech)

Mar. 1986

NPO-16403

Vol. 9, No. 4, P. 40

Tapered transmission line couples energy from magnetic switch to excimer laser. Transmission line provides constant impedance for pulses from switch and distributes pulses across length of laser as nearly uniform wave fronts. Allows smaller, more efficient magnetic core to be used in switch. Losses and circuit capacitance are less than for full-laser-width line and core.

B85-10429

GENERATING INDEPENDENT PREIONIZING PULSES FOR LASERS

T. J. PACALA (Caltech)

Mar. 1986

NPO-16402

Vol. 9, No. 4, P. 42

Simple pulse-coupling winding on saturable reactor core lets core act as pulse transformer, passing preionizing pulse from winding to tapered transmission line, then to laser. Laser prepared for independent firing pulse, which follows preionizing pulse. Winding is simple, light in weight, low in bulk and power consumption, and inexpensive.

B85-10430

MAGNETICALLY-SWITCHED, LONG-PULSE XECL LASER

T. J. PACALA (Caltech), I. S. MCDERMID (Caltech), and J. B. LAUDENSLAGER (Caltech)

Mar. 1986

NPO-16410

Vol. 9, No. 4, P. 42

Careful shaping of input pulses helps XeCl excimer laser produce low-divergence, narrow-band light beam. Long-pulse laser achieves narrow-band output by multiple passes of beam through precisely adjusted Fabry-Perot etalons. Pulse-forming network and saturable-inductor switch enable fast pulse rise to peak voltage, followed by long residence at peak.

B85-10431

OBTAINING ONE-DEGREE ACCURACY WITH SHAFT ENCODERS

J. M. FRANK, J. I. CLEMONS, and S. B. JONES

Mar. 1986

LAR-13321

Vol. 9, No. 4, P. 44

Circuit converts output of 1-pulse-per-revolution shaft encoder to precise 360-pulses-per-revolution output. Circuit allows shaft angular position to be measured with 1-degree accuracy. With simple modifications, circuit provides higher or lower resolution from single- or multiple-pulse-per-revolution sources. Circuit used to synchronize aircraft beacon transponder-based plan-position indicator (PPI) display to remote host interrogator search antenna. Constructed using standard, commercially available components.

B85-10432

MICROWAVE POWER COMBINER WITH SWITCHING DIODES

B. L. CONROY (Caltech), R. B. POSTAL (Caltech), and J. F. BOREHAM (Caltech)

Mar. 1986

NPO-15775

Vol. 9, No. 4, P. 46

In multiple-port microwave power combiner, each of outputs of two or more power amplifiers of same frequency and phase passed to common output port separately or together. Each amplifier connected to combiner through switch consisting of resonant structures, radio-frequency chokes, and diode. Switches not only permit flexibility in

01 ELECTRONIC COMPONENTS AND CIRCUITS

selection of amplifiers but isolate unused amplifiers from network, all while operating at relatively low power loss.

B85-10433
CASSEGRAIN-ANTENNA GAIN IMPROVEMENT
 V. GALINDO (Caltech), A. G. CHA (Caltech), and R. MITTRA (University of Illinois)
 Mar. 1986

NPO-15775 Vol. 9, No. 4, P. 48
 Modified antenna feed with dual-shaped subreflectors yields 10-to20-percent improvement in efficiency of existing large-aperture paraboloidal or Cassegrainian antennas. Such offset dual-shaped subreflector (DSS) feed brings gain of existing paraboloid or Cassegrain antennas up to that of reflector antennas of more recent design at cost considerably lower than for reshaping existing reflecting surfaces. Mathematical procedures developed for synthesizing nearly optimum shapes for DSS elements of new feeds.

B85-10434
MULTIPLE-WINDING OUTPUT INDUCTORS FOR POWER CONVERTERS

C. W. T. MCLYMAN (Caltech)
 Mar. 1986
NPO-16176 Vol. 9, No. 4, P. 49
 Design procedure developed for dc-to-dc power converters with multiple outputs having inductors wound on common core. With common core, minimum load current consistent with good output regulation is lower, output regulation is improved, and total inductor size and weight is reduced.

B85-10435
IMPROVED WAVEGUIDE LASER ARRAY
 S. MUKAI (Caltech), C. P. LINDSEY (Caltech), J. KATZ (Caltech), E. KAPON (Caltech), A. YARIV (Caltech), and S. MARGALIT (Caltech)

Mar. 1986
NPO-16500 Vol. 9, No. 4, P. 49
 Improved structure for integrated array of Al_xGa_{1-x}As diode lasers causes array to oscillate predominantly in fundamental supermode (with all units at same phase), thereby producing intense, narrow light beam. New structure differs from older ones in that gain in spaces between laser channels is approximately equal to gain in channels.

B85-10436
A QUICK VISUAL POWER-SUPPLY MONITOR
 L. W. TAYLOR (The Johns Hopkins University)

Mar. 1986
MFS-26014 Vol. 9, No. 4, P. 50
 Power-supply voltages quickly monitored by circuit equipped with light-emitting-diode (LED) display. Operator looking at display quickly spots whether power output voltage is above, below, or within acceptable limits. Tricolor LED displays high, low, and intermediate output voltages.

B85-10437
CONTROLLING TRANSISTOR TEMPERATURE DURING BURN-IN

B. C. SCOTT (Martin Marietta Corp.)
 Mar. 1986
MFS-28076 Vol. 9, No. 4, P. 52
 Boiling refrigerant provides simple temperature control for newly manufactured power transistors. Heat-transfer liquid is Fluorinert FC-77 (or equivalent). Liquid boils at 100 degrees C, which is specified temperature at which transistor cases should be maintained during burn-in with this technique.

B85-10438
KEYBOARD WITH VOICE OUTPUT
 W. C. HUBER

Mar. 1986
MSC-20869 Vol. 9, No. 4, P. 54
 Voice synthesizer tells what key is about to be de-

pressed. Verbal feedback useful for blind operators or where dim light prevents sighted operator from seeing keyboard. Also used where operator is busy observing other things while keying data into control system. Used as training aid for touch typing, and to train blind operators to use both standard and braille keyboards. Concept adapted to such equipment as typewriters, computers, calculators, telephones, cash registers, and on/off controls.

B85-10439
CONDUCTIVE CONTAINER FOR SEMICONDUCTOR DEVICES

J. T. RICE (Caltech)
 Mar. 1986
NPO-16110 Vol. 9, No. 4, P. 54
 Container for semiconductor components not only protects them against mechanical damage but ensures they are not harmed by electrostatic discharges. Container holds components in fixed positions so they can be serialized and identified from their locations. Suitable for holding components during both storing and shipping. Originally developed for microwave diodes, container concept readily adaptable to transistors and integrated circuits.

B85-10440
LOW-COST HUMIDITY SENSOR
 E. G. LAUE (Caltech)

Mar. 1986
NPO-16544 Vol. 9, No. 4, P. 55
 Electronic humidity sensor is simple, inexpensive, and produces output readily used by indicator or control circuits. Sensor operates at safe, low voltage and is relatively invulnerable to electrolysis effects. Sensor used to measure humidity in atmosphere, in soil, and industrial gases, for example.

B85-10441
FLOATING-EMITTER SOLAR-CELL TRANSISTOR
 C. T. SAH (Caltech) and L. J. CHENG (Caltech)

Mar. 1986
NPO-16467 Vol. 9, No. 4, P. 56
 Conceptual transistor embedded in photovoltaic diode promises to increase efficiency to more than 20 percent. Solar-cell transistor has front-surface contact, rear contact, and floating emitter. Variety of other contact and junction configurations possible, but do not offer ease of fabrication in combination with high performance.

B85-10442
TESTER FOR DISTRESS BEACONS
 W. R. WADE (Proteon, Inc.)

Mar. 1986
GSC-12892 Vol. 9, No. 4, P. 56
 Distress beacons on aircraft and boats checked for proper operation with aid of onboard monitor. Monitor mounted in aircraft cockpit or at wheel of boat. Connected to beacon electronics by cable. Monitor used with interface circuitry in beacon, which acts as buffer so that operation of beacon is not adversely affected if monitor is removed or if connecting cable is accidentally short circuited.

B85-10443
CONTROL ELECTRONICS FOR SOLAR/FLYWHEEL POWER SUPPLY

F. J. NOLA
 Mar. 1986
MFS-25978 Vol. 9, No. 4, P. 57
 Control circuit automatically directs flow of electrical energy to and from motor with flywheel that constitutes storage element of solar-power system. When insolation is sufficient for charging, power is supplied by solar-cell array to load and motor. During periods of darkness, motor made to act as generator, drawing kinetic energy from flywheel and supplying it to load.

01 ELECTRONIC COMPONENTS AND CIRCUITS

B85-10444

REDUCED-STRESS MOUNTING FOR THERMOCOUPLES

C. WOOD (Caltech)

Mar. 1986

NPO-16513

Vol. 9, No. 4, P. 58

Mounting accommodates widely different coefficients of thermal expansion. In new method, legs of thermocouple placed in separate n- and p-type arrays. Two arrays contact common heat pipe as source but have separate heatpipe sinks. Net expansion (or contraction) taken up by spring mounting on heat-pipe sinks.

B85-10445

DETERMINING INTERNAL CONNECTIONS IN CAPACITORS

F. M. OTT (Caltech) and M. F. HANNA (Caltech)

Mar. 1986

NPO-16499

Vol. 9, No. 4, P. 60

Simple electrical test shows which terminals connected to outer capacitor foil. Test makes it unnecessary to resort to X-ray inspection to distinguish terminals. When outer foil of capacitor is attached to ungrounded signal-generator output lead, oscilloscope displays higher waveform amplitude. When outer foil is joined to grounded signal-generator output lead, waveform amplitude is lower. Test also used to determine internal connections in multiple-element capacitors.

B85-10446

ACCELERATING CORROSION IN SOLAR-CELL TESTS

H. M. SHALABY (Caltech)

Mar. 1986

NPO-16096

Vol. 9, No. 4, P. 60

In simple electrochemical cell, two silicon solar cells serve as anode and cathode, respectively. Electrolytic medium and voltage between them accelerate corrosion and migration interactions between cell metal contacts and plastic encapsulant. Degradation of metal contacts becomes evident in few hours. Although developed specifically for cells with Ti/Pd/Ag contacts, technique readily adapted to other metal combinations.

television monitor. System also extracts digital portion of stored information and transfers it to solid-state memory.

B85-10028

HIGH-SPEED COMPUTER-CONTROLLED SWITCH-MATRIX SYSTEM

E. SPISZ, B. CORY (General Electric Co.), P. HO (Ford Motor Co.), and M. HOFFMAN (Mitre Corp.)

Jun. 1985 NASA CR-159682 (N80-12260/NSP) and NASA CR-168089 (N83-34998/NSP)

LEW-14050

Vol. 9, No. 1, P. 60

High-speed computer-controlled switch-matrix system developed for communication satellites. Satellite system controlled by onboard computer and all message-routing functions between uplink and downlink beams handled by newly developed switch-matrix system. Message requires only 2-microsecond interconnect period, repeated every millisecond.

B85-10029

LOW-COST TELECONFERENCE SYSTEM

R. F. RICE (CALTECH) and A. P. SCHLUTSMAYER (CALTECH)

Jun. 1985

NPO-16057

Vol. 9, No. 1, P. 61

Proposed video teleconferencing system displays drawings, photographs, and text for conferees. Although new system, called TELEDemo, does not present live scenes from conference locations, it cost far less than conventional teleconference services. Widely scattered participants communicate by voice, graphics, and images over telephone lines.

B85-10030

DYNAMIC-RAM DATA STORAGE UNIT

J. C. STURMAN

Jun. 1985

LEW-14017

Vol. 9, No. 1, P. 62

Dynamic random-access-memory (RAM) data delay and storage unit developed to insure data received from satellite is stored and not lost when satellite is not within range of ground station. Stores 256K of serial data, with independent read and write capability.

B85-10031

REDUNDANT ASYNCHRONOUS MICROPROCESSOR SYSTEM

G. MEYER, J. O. JOHNSTON, and W. R. DUNN (University of Southern Colorado)

Jun. 1985

ARC-11348

Vol. 9, No. 1, P. 63

Fault-tolerant computer structure called RAMPS (for redundant asynchronous microprocessor system) has simplicity of static redundancy but offers intermittent-fault handling ability of complex, dynamically redundant systems. New structure useful wherever several microprocessors are employed for control - in aircraft, industrial processes, robotics, and automatic machining, for example.

B85-10032

DESIGNING TEST CHIPS FOR CUSTOM INTEGRATED CIRCUITS

M. G. BUEHLER (CALTECH), T. W. GRISWOLD (CALTECH), C. A. PINA (CALTECH), and C. C. TIMOC (CALTECH)

Jun. 1985

NPO-15988

Vol. 9, No. 1, P. 64

Collection of design and testing procedures partly automates development of built-in test chips for CMOS integrated circuits. Testchip methodology intended especially for users of custom integrated-circuit wafers. Test-Chip Designs and Testing Procedures (including data-reduction procedures) generated automatically by computer from programed design and testing rules and from information supplied by user.

02 ELECTRONIC SYSTEMS

B85-10026

HIGH-VISIBILITY DATA DISPLAY

K. SLUSSER (Rockwell International Corp.)

Jun. 1985

MFS-19925

Vol. 9, No. 1, P. 58

Data-monitoring system continuously senses output voltages from transducers and provides large, easy-to-read displays of quantities represented by voltages. Measurements of power-supply voltages and currents, pressures, temperatures, strains, and masses displayed. System intended to operate 24 hours a day, producing uninterrupted readouts of critical parameters.

B85-10027

STORING DATA AND VIDEO ON ONE TAPE

J. H. NIXON (Southwest Research Institute) and J. P. CATER (Southwest Research Institute)

Jun. 1985

MSC-20705

Vol. 9, No. 1, P. 59

Microprocessor-based system originally developed for anthropometric research merges digital data with video images for storage on video cassette recorder. Combined signals later retrieved and displayed simultaneously on

B85-10033
SELF-IDENTIFYING REFLECTING TARGETS
 R. E. FRAZER (CALTECH)

Jun. 1985

NPO-16106

Vol. 9, No. 1, P. 65

Proposed scheme for target identification requires no radiation of energy by target itself. Instead, target alters light beam reflected from itself back to interrogating station in unique way. Interrogator then identifies target from its signature impressed on returned beam. Self-identifying target useful in surveying, navigation, and remote monitoring (for example, of mountain-climbing parties.)

B85-10034
FINDING BRIGHT-SPOT COORDINATES IN TELEVISION IMAGES

T. E. RICHARDSON (Martin Marietta Corp.) and J. C. TIETZ (Martin Marietta Corp.)

Jun. 1985

MFS-25999

Vol. 9, No. 1, P. 65

Circuit provides data for computer to calculate coordinates of bright spot of light in video image. Calculation performed while image being scanned, and results available immediately at end of video frame. Video-processing circuit has variety of potential uses in commerce and industry. For example, locates tagged-parts on factory assembly line or track airplane landing lights.

B85-10035
SYNCHRONIZING DATA-BUS MESSAGES

L. H. HARRIS (Lockheed Engineering and Management Services Co., Inc.)

Jun. 1985

MSC-20640

Vol. 9, No. 1, P. 66

Adapter allows communications among as many as 30 data processors without central bus controller. Adapter improves reliability of multiprocessor system by eliminating point of failure that causes entire system to fail. Scheme prevents data collisions and eliminates nonessential polling, thereby reducing power consumption.

B85-10036
FIFO BUFFER FOR ASYNCHRONOUS DATA STREAMS
 K. P. BASCLE (Harris Corporation)

Jun. 1985

MSC-20403

Vol. 9, No. 1, P. 67

Variable-rate, asynchronous data signals from up to four measuring instruments or other sources combined in first-in/first-out (FIFO) buffer for transmission on single channel. Constructed in complementary metal-oxide-semiconductor (CMOS) logic, buffer consumes low power (only 125 mW at 5V) and conforms to aerospace standards of reliability and maintainability.

B85-10037
SYNCHRONIZATION FOR OPTICAL PPM SIGNALS
 V. A. VILNROTTER (CALTECH)

Jun. 1985

NPO-16256

Vol. 9, No. 1, P. 68

Method based on statistical properties of weak pulse-position-modulated (PPM) signal enables synchronization of receiver clock with received-signal time base. Method applies to weak optical M-ary PPM signals, for which there is only one pulse of length T_p transmitted during one of timeslots of length T in each successive interval of M timeslots. Method requires small dead time, T_d , at beginning and end of each timeslot, during which pulse amplitude is zero.

B85-10038
HIGH-TEMPERATURE HALL-EFFECT APPARATUS
 C. WOOD (CALTECH), R. A. LOCKWOOD (CALTECH), A. B. CHEMIELEWSKI (CALTECH), J. B. PARKER (CALTECH), and A. ZOLTAN (CALTECH)

Jun. 1985

NPO-16279

Vol. 9, No. 1, P. 70

Compact furnace minimizes thermal gradients and electrical noise. Semiautomatic Hall-effect apparatus takes measurements on refractory semiconductors at temperatures as high as 1,100 degrees C. Intended especially for use with samples of high conductivity and low chargecarrier mobility that exhibit low signal-to-noise ratios, apparatus carefully constructed to avoid spurious electromagnetic and thermoelectric effects that further degrade measurements.

B85-10039
SINGLE-FREQUENCY MULTITRANSMITTER TELEMETRY

V. A. CARRENO

Jun. 1985

LAR-13006

Vol. 9, No. 1, P. 70

Telemetry technique for data collection on general aviation aircraft involved in aeronautical research consists of many sensor/transmitter units at different locations on aircraft. Individual signaling and logic at each sensor/transmitter send signals to single receiver in airplane. Transmitters operate independently on same frequency and are not synchronized to receiver, eliminating erroneous data resulting from two-transmitter overlap.

B85-10040
DOUBLY-DIFFERENCED MEASUREMENTS FOR ORBIT DETERMINATIONS

S. C. WU (CALTECH) and V. J. ONDRASKI (CALTECH)

Jun. 1985

NPO-16111

Vol. 9, No. 1, P. 71

Report describes accurate method of determining orbit of low-altitude Earth satellite. Method insensitive to clock errors and provides continuous determination of orbit. Report examines effects of employing fewer ground stations, applying different solution strategies, and introducing fictitious thrust parameters to minimize geopotential modeling error - one of major error sources.

B85-10160
FREQUENCY-DISCRIMINATING ACOUSTIC-EVENT COUNTER

F. E. SUGG (Rockwell International Corp.) and L. J. GRAHAM (Rockwell International Corp.)

Oct. 1985

MSC-20467

Vol. 9, No. 2, P. 56

Broadband events rejected. Acoustic-event counter discriminates against signals that simultaneously exceed preset amplitude thresholds in both low and high-frequency bands of its spectrum. Counter acts as spectral analyzer for mechanical vibrations. In combination with broadband acoustic transducer discriminates between signals and noise in acoustical destructive or nondestructive testing, vibration monitoring for machinery, burglar alarms, and other monitoring/warning systems.

B85-10161
ONLINE TESTER FOR A SYMBOL GENERATOR

D. JUDAY (International Business Machines Corp.) and K. MCCONAUGY (International Business Machines Corp.)

Oct. 1985

MSC-20357

Vol. 9, No. 2, P. 58

About 95 percent of faults detected. Programmable instrument periodically checks for failures in system that generates alphanumeric and other symbol voltages for cathode-ray-tube displays. Symbol-generator tester compares gated test-point voltages with predetermined voltage limits while circuit under test performs commanded operation. A go/no-go indication given, depending on whether test voltage is or is not within its specification. Tester in plug-in modular form, temporarily wired to generator test points, or permanently wired to these points.

B85-10162
PROGRAMMABLE DRIVER FOR VOLTAGE-CONTROLLED OSCILLATORS

02 ELECTRONIC SYSTEMS

L. E. FOWLER (Caltech) and J. A. MCNEIL (Caltech)
Oct. 1985

NPO-16364 Vol. 9, No. 2, P. 60

Electronically programmable read-only memory (EPROM) and digital-to-analog converter provide customized time-varying voltage for frequency modulation. Voltage used to modulate IMPATT oscillator that serves as microwave pump for solid-state maser in low-noise amplifier. EPROM simple to tailor voltage waveform to suit characteristics of given maser. Digital information for waveform programmed into EPROM chip; digital-to-analog converter reads information and produces corresponding analog wave. Principle readily adapted to other applications.

B85-10163
FAST CONTROL SEQUENCER

C. R. LAHMEYER (Caltech)

Oct. 1985

NPO-16116 Vol. 9, No. 2, P. 60

Unit faster than conventional circuits and contains fewer integrated circuits. Fast logic controller accommodates three delays before second half cycle of clock signal strobes status latch: Outputs of pipeline register must settle; selected input status line signal must propagate through status multiplexer and arrive at status latch; and it takes 3 nanoseconds for status latch set up before strobed. During second half cycle, output-enable line produces next instruction and applies it to pipeline register.

B85-10164
PROCESSING OF IMAGE DATA BY INTEGRATED CIRCUITS

R. W. ARMSTRONG (Caltech)

Oct. 1985

NPO-15059 Vol. 9, No. 2, P. 61

Sensors combined with logic and memory circuitry. Cross-correlation of two inputs accomplished by transversal filter. Position of image taken to point where image and template data yield maximum value correlation function. Circuit used for controlling robots, medical-image analysis, automatic vehicle guidance, and precise pointing of scientific cameras.

B85-10165
POINT SIMULATOR FOR SYNTHETIC-APERTURE RADAR

D. PSALTIS (Caltech), M. W. HANEY (Caltech), and K. H. WAGNER (Caltech)

Oct. 1985

NPO-16296 Vol. 9, No. 2, P. 62

Reflection from point target imitated electronically. SAR simulator produces amplitude and phase-modulated 60-MHz signal that resembles SAR return of point scatterer. Designed to test integrated optical SAR receivers, simulator applies phase modulation necessary to turn radio-frequency pulse train into electronic equivalent of unfocused radar image of target.

B85-10166
COMMUNICATIONS HEADGEAR WITH PROTECTIVE FEATURES

S. W. WARD

Oct. 1985

LAR-13156 Vol. 9, No. 2, P. 63

Uncomplicated, inexpensive Intercom protects head, face, and hearing. Adaptation of highly suitable stock helmet and face shield unit to stock intercom headset provided ideal unit, allowing wearer total use of hands and body while protecting head, face, and hearing. Unit allows wearer to work effectively, efficiently, and safely while communicating from remote areas that require special precautions. Total cost of fabricating unit, using stock parts and including labor, less than \$100.

B85-10167
AIRBORNE CLOUD DETECTOR

R. E. CAMPBELL and J. P. MCPHERSON
Oct. 1985

LAR-13137 Vol. 9, No. 2, P. 63

Bonded to aircraft skin, it facilitates cloud avoidance. Airborne cloud detector consists of three major components: Aluminum patch durably bonded to aircraft skin, surge arrester, and dual-sensitivity charge-rate amplifier. Operation based on fact that aircraft surfaces become charged when ice or water particles strike them. Using increased gain sensitivities, cloudparticle detector reliable, noise-free, low-cost, high-sensitivity indicator of type of clouds that cause most problems for LFC aircraft at cruise altitude.

B85-10168
RECOVERING MICROWAVE CROSS-POLARIZATION LOSSES

B. L. SEIDEL (Caltech), C. T. STELZRIED (Caltech), and J. E. OHLSON (Caltech)

Oct. 1985

NPO-15353; NPO-15354; NPO-15803 Vol. 9, No. 2, P. 64

Reception improved by adding normally discarded portion of signal. For signal enhancement, major and minor signals combined in slaved closed-loop receiver channels. Both receiver channels served by common local oscillator controlled by phase-locked loop in main channel. 10-MHz intermediate-frequency (IF) signals of channels coherently summed. For polarization tracking, phasemeter added to measure phase difference between points A and B. With new circuit, low-level signal used at receiver to augment main signal.

B85-10169
SATELLITE TIME- AND FREQUENCY-TRANSFER SYSTEM

R. F. C. VESSOT (Smithsonian Institution Astrophysical Observatory), H. PENFIELD (Smithsonian Institution Astrophysical Observatory), and E. MATTISON (Smithsonian Institution Astrophysical Observatory)

Oct. 1985

MFS-25991 Vol. 9, No. 2, P. 65

Time synchronized at distant points within nanosecond. Report describes satellite-borne time-and frequency-transfer system proposed for synchronization of clocks at stations around Earth. Orbiting hydrogen-maser clock and frequency standard communicate by microwave links with Earth stations using hydrogen masers as local clocks. Pulsed-laser time-transfer sub-system also operated concurrently, either synchronized or unsynchronized with microwave subsystems.

B85-10170
LATCHUP IN CMOS INTEGRATED CIRCUITS

K. A. SOLIMAN (Caltech) and D. K. NICHOLS (Caltech)

Oct. 1985

NPO-16304 Vol. 9, No. 2, P. 66

Sensitivity to ion beams is studied. Latchup effect subject of paper presenting results of testing 19 types of complementary metal-oxide semiconductor (CMOS) chips from six manufacturers. Report gives details of sensitivity of chips to latchup caused by argon and krypton ion beams. Identifies parasitic npnp paths and provides latchup cross section and qualitative explanation of latchup sensitivity for each chip type.

B85-10171
INTERFEROMETRY MEASURES ELLIPTICAL SATELLITE ORBITS

R. B. FRAUENHOLZ (Caltech) and J. ELLIS (Caltech)

Oct. 1985

NPO-16313 Vol. 9, No. 2, P. 66

Very-long-baseline interferometry offers advantages over conventional Doppler measurements. Conference paper shows feasibility of using data from very-long-baseline interferometry (VLBI) to locate and predict motion of satellites in highly elliptical orbits about Earth. VLBI data obtained from Deep Space Network. Data not only improves

navigation accuracy but also acquired with less use of worldwide network of ground stations.

B85-10172
PROGRAM PREDICTS NONLINEAR INVERTER PERFORMANCE
 R. R. AL-AYOUBI (Rockwell International Corp.) and T. S. OEPOMO (Rockwell International Corp.)
 Oct. 1985
MSC-20769

Vol. 9, No. 2, P. 67

Program developed for ac power distribution system on Shuttle orbiter predicts total load on inverters and node voltages at each of line replaceable units (LRU's). Mathematical model simulates inverter performance at each change of state in power distribution system.

B85-10301
WIDE-BRIGHTNESS-RANGE VIDEO CAMERA
 G. D. CRAIG
 Jan. 1986
MFS-25750

Vol. 9, No. 3, P. 52

Television camera selectively attenuates bright areas in scene without affecting dim areas. Camera views scenes containing extremes of light and dark without overexposing light areas and underexposing dark ones. Camera uses liquid-crystal light valve for selective attenuation. Feedback cathode-ray tube locally alters reflection characteristics of liquid-crystal light valve. Results in point-to-point optoelectronic automatic gain control to enable viewing of both dark and very bright areas within scene.

B85-10302
EXPERIMENTAL PARALLEL-PROCESSING COMPUTER
 J. W. MCGREGOR (Caltech) and M. A. SALAMA (Caltech)
 Jan. 1986
NPO-16043

Vol. 9, No. 3, P. 54

Master processor supervises slave processors, each with its own memory. Computer with parallel processing serves as inexpensive tool for experimentation with parallel mathematical algorithms. Speed enhancement obtained depends on both nature of problem and structure of algorithm used. In parallel-processing architecture, 'bank select' and control signals determine which one, if any, of N slave processor memories accessible to master processor at any given moment. When so selected, slave memory operates as part of master computer memory. When not selected, slave memory operates independently of main memory. Slave processors communicate with each other via input/output bus.

B85-10303
FAST REED-SOLOMON DECODER
 K. Y. LIU (Caltech)
 Jan. 1986
NPO-15867

Vol. 9, No. 3, P. 55

High-speed decoder intended for use with Reed-Solomon (RS) codes of long code length and high error-correcting capability. Design based on algorithm that includes high-radix Fermat transform procedure, which is most efficient for high speeds. RS code in question has code-word length of 256 symbols, of which 224 are information symbols and 32 are redundant.

B85-10304
SYSTOLIC VLSI REED-SOLOMON DECODER
 H. M. SHAO (Caltech), T. K. TRUONG (Caltech), L. J. DEUTSCH (Caltech), and J. H. YUEN (Caltech)
 Jan. 1986
NPO-16383

Vol. 9, No. 3, P. 56

Decoder for digital communications provides high-speed, pipelined Reed-Solomon (RS) error-correction decoding of data streams. Principal new feature of proposed decoder is modification of Euclid greatest-common-divisor algorithm to avoid need for time-consuming computations of inverse of certain Galois-field quantities. Decoder architecture suitable for implementation on very-large-scale integrated

(VLSI) chips with negative-channel metaloxide/silicon circuitry.

B85-10305
ELECTRO-OPTICAL SYSTEM MEASURES AIRCRAFT DEFLECTIONS
 B. FODALE (Grumman Aerospace Corp.), H. R. HAMPTON (Grumman Aerospace Corp.), H. R. SEYMOUR (Grumman Aerospace Corp.), and V. M. DEANGELIS (Dryden Flight Research Facility)
 Jan. 1986
ARC-11454

Vol. 9, No. 3, P. 56

In-flight deflections of aircraft surfaces are measured accurately over wide range of airspeeds and attitudes by electro-optical instrumentation system. Deflections caused by aerodynamic and acceleration forces are measured on wings, stabilizers, helicopter rotors, and other surfaces. Electro-optical system replaces 70-millimeter motor-driven camera previously used to observe deflections.

B85-10306
MODULAR VLSI REED-SOLOMON DECODER
 K. Y. LIU (Caltech)
 Jan. 1986
NPO-15837

Vol. 9, No. 3, P. 58

Proposed Reed-Solomon (RS) decoder assembled from very-large-scale integrated-circuit (VLSI) building blocks. Decoder exploits recursive forms in RS decoding algorithms. RS codes capable of correcting random or burst errors in telemetry and other data-communication signals. Because of small size and low power consumption, advantageous to employ several such decoders in parallel-processing scheme to increase decoding speed.

B85-10307
'SPEAKING' MICROCOMPUTER
 C. MANDY (The Boeing Co.) and J. ANNERTON (The Boeing Co.)
 Jan. 1986
MFS-25976

Vol. 9, No. 3, P. 62

Microcomputer system allows blind person to use portable computer and communicate with remote mainframe computer. System prepares data for transmission to mainframe, translates data transmitted from mainframe for its own use, and converts data ordinarily displayed on its video screen into synthesized speech.

B85-10308
SENSOR TRACKS THE SUN FROM ANY ANGLE
 M. BIRNBAUM, M. (Caltech) and R. L. BUNKER (Caltech)
 Jan. 1986
NPO-16211

Vol. 9, No. 3, P. 62

Sensor system locates Sun from any angle and generates error signals to point object toward Sun and follow its motion. Sun-sensor system includes three photodetectors, each with separate field of view defined by set of apertures. As equipment rotates about axis, detectors put out time-varying signals processed by external electronics to determine rotation rate and direction to Sun.

B85-10309
INTERFACE CIRCUITS FOR SELF-CHECKING MICRO-PROCESSORS
 D. A. RENNELS (Caltech) and R. CHANDRAMOULI (Caltech)
 Jan. 1986
NPO-15700

Vol. 9, No. 3, P. 63

Fault-tolerant-microcomputer concept based on enhancing 'simple' computer with redundancy and self-checking logic circuits detect hardware faults. Interface and checking logic and redundant processors confer on 16-bit microcomputer ability to check itself for hardware faults. Checking circuitry also checks itself. Concept of self-checking complementary pairs (SCCP's) employed throughout ICL unit.

02 ELECTRONIC SYSTEMS

B85-10310

CONTROLLERS FOR FLOW-FIELD SURVEY APPARATUS

J. ASHBY, GEORGE C. and M. D. VACCARELLI

Jan. 1986

LAR-13180

Vol. 9, No. 3, P. 64

Control systems of flow-field survey apparatuses of 22-inch (56centimeter) Hypersonic Helium Facility (two-dimensional) and 20-inch (51centimeter) Mach 6 Tunnel (three-dimensional) at Langley Research Center equipped with single-chip microcomputer and single-board microcomputer, respectively, to drive probes at selected speeds and perform other functions automatically. Various modes of operation programmed as need arises. Both of these control systems fabricated relatively inexpensively from commercially available stock components.

B85-10311

FAST VLSI VITERBI DECODER

C. C. WANG (Caltech)

Jan. 1986

NPO-16365

Vol. 9, No. 3, P. 65

Fast Viterbi decoder with fully parallel, pipeline architecture implemented on two VLSI NMOS chips. Decoder used with constraint-length-7, rate-1/2, convolutional error-correcting code widely used by NASA for deepspace telemetry data. With this (7,1/2) code, bit stream contains 2 bits per original data bit, and information about 1 data bit distributed over 7 pairs of bits. Design principles of decoder also applicable to Viterbi codes of other lengths and rates.

B85-10312

IMAGE INTERPOLATION WITH DEDICATED DIGITAL HARDWARE

R. HARTENSTEIN, G. WAGNER (TCG, Inc.), D. SIMONS (Ideas, Inc.), and J. COULSON (Ideas, Inc.)

Jan. 1986

GSC-12882

Vol. 9, No. 3, P. 66

Algorithm for interpolating two-dimensional image data to change picture-element spacing implemented in dedicated digital hardware for high-speed execution. System interpolates 100 times as fast as generalpurpose computer. Image resampling occurs first along one image axis and then along other, using two interpolation devices implemented in series.

B85-10313

LASER LINKS FOR INSTRUMENTATION SYSTEMS

P. S. BAILEY (McDonnell Douglas Corp.)

Jan. 1986

MSC-20863

Vol. 9, No. 3, P. 67

Laser Links eliminate costly cables connecting sensors to data-collection centers. Data-transmission scheme uses laser-based communication systems instead of cables. Sensor data transmitted by semiconductor-diode lasers effective over line-of-sight distances of up to several hundred meters. Use of lasers instead of cables simplifies number of installations.

B85-10314

COST AND PERFORMANCE MODEL FOR PHOTOVOLTAIC SYSTEMS

C. S. BORDEN (Caltech), J. H. SMITH (Caltech), M. C. DAVISSON (Caltech), and L. J. REITER (Caltech)

Jan. 1986

NPO-16404

Vol. 9, No. 3, P. 67

Lifetime cost and performance (LCP) model assists in assessment of design options for photovoltaic systems. LCP is simulation of performance, cost, and revenue streams associated with photovoltaic power systems connected to electric-utility grid. LCP provides user with substantial flexibility in specifying technical and economic environment of application.

B85-10315

COMPUTER-AIDED RELIABILITY ESTIMATION

S. J. BAVUSO, J. J. STIFFLER (Sequoia Systems, Inc.), L. A. BRYANT (Sequoia Systems, Inc.), and P. L. PETERSEN (Kentron International, Inc.)

Jan. 1986

LAR-13349

Vol. 9, No. 3, P. 68

CARE III (Computer-Aided Reliability Estimation, Third Generation) helps estimate reliability of complex, redundant, fault-tolerant systems. Program specifically designed for evaluation of fault-tolerant avionics systems. However, CARE III general enough for use in evaluation of other systems as well.

B85-10447

VIBRATION-FREE RAMAN DOPPLER VELOCIMETER

R. J. EXTON

Mar. 1986 See Also (N84-25433)

LAR-13268

Vol. 9, No. 4, P. 62

New method under development to measure flow velocity of molecules directly by nonintrusive laser techniques. This method, combined with vibration-free design, makes flow-velocity measurements practical in severe vibrational environments. Raman scattering and retroreflection combine to yield useful technique for wind-tunnel gas-flow mapping. Nonintrusive measurements of gas velocity, temperature, and pressure possible in highly vibrational environment.

B85-10448

MODULAR, FAST, TWO-DIMENSIONAL CYCLIC CONVOLVER

K. Y. LIU (Caltech)

Mar. 1986

NPO-16379

Vol. 9, No. 4, P. 63

Proposed high-throughput, real-time synthetic-aperture-radar (SAR) processor built using new, modular, two-dimensional cyclic convolver architecture based on polynomial factorization and designed for very-large-scale integrated (VLSI) circuitry. New architecture reduces cost, size, and power dissipation of SAR processor in comparison to high-speed array-processor approach. Processor also used for other image-and data-processing applications involving two-dimensional Fourier transforms.

B85-10449

ROTATING CAPACITOR MEASURES STEADY ELECTRIC FIELDS

A. R. JOHNSTON (Caltech), H. KIRKHAM (Caltech), and B. ENG (Caltech)

Mar. 1986

NPO-16550

Vol. 9, No. 4, P. 64

Portable sensor measures electric fields created by dc powerlines or other dc-high-voltage sources. Measures fields from 70 to 50,000 V/m with linearity of 2 percent. Sensor used at any height above ground. Measures both magnitude and direction of field and provides signals representing these measurements to remote readout device. Sensor functions with minimal disturbance of field it is measuring.

B85-10450

GENERATING TUNABLE FAR-INFRARED LASER SIDEBANDS

H. M. PICKETT (Caltech) and J. FARHOOMAND (Caltech)

Mar. 1986

NPO-16497

Vol. 9, No. 4, P. 65

New tunable source extends infrared spectroscopy into far infrared wavelengths. Frequency-Tunable far-infrared radiation produced by mixing of fixed-frequency far-infrared laser beam with output of frequency-tunable klystron. By sweeping klystron frequency in synchronism with video display of detector output, one obtains direct presentation of absorption-cell spectrum. Immediate applications are local oscillator for heterodyne systems and tunable source for spectroscopy.

B85-10451

CONVOLVER FOR PIPELINED-IMAGE PROCESSOR

B. WILCOX (Caltech)

Mar. 1986

NPO-16462

Vol. 9, No. 4, P. 66

3 x 3 convolver produces weighted sum of nine contiguous picture elements in square. Data processed through convolver at video scanning rate of current raster line. Two previous lines stored in external buffers (N-3) element delays. Specific choice of convolution weights determines whether convolver performs smoothing, spatial-frequency filtering, edge detection, or other forms of image processing.

B85-10452

SINGLE-CHIP VLSI REED-SOLOMON ENCODER

T. K. TRUONG (Caltech), L. J. DEUTSCH (University of Southern California), and I. S. REED (University of Southern California)

Mar. 1986

NPO-16122

Vol. 9, No. 4, P. 67

Reed-Solomon (RS) encoder based on Berlekamp bit-serial multiplier algorithm. RS code standard, based on code words of 255 8-bit symbols, of which 223 symbols convey information and remaining 32 are check symbols. This code enables correction of up to 16 erroneous information symbols per word. Berlekamp algorithm based on code-generating polynomial with 32 roots that occur in reciprocal pairs. Choice of algorithm permits compact design.

B85-10453

AUTOMATIC GUIDANCE FOR REMOTE MANIPULATOR

A. R. JOHNSTON (Caltech)

Mar. 1986

NPO-13386

Vol. 9, No. 4, P. 68

Position sensor and mirror guides manipulator toward object. Grasping becomes automatic when sensor begins to receive signal from reflector on object to be manipulated. Light-emitting diodes on manipulator produce light signals for reflector, which is composite of plane and corner reflectors. Proposed scheme especially useful when manipulator arm tends to flex or when object is moving. Sensor and microprocessor designed to compensate for manipulator arm oscillation.

B85-10454

TESTING ELECTRONIC DEVICES FOR SINGLE-EVENT UPSET

D. K. NICHOLS (Caltech), W. E. PRICE (Caltech), and C. J. MALONE (Caltech)

Mar. 1986

NPO-16468

Vol. 9, No. 4, P. 69

Report prepared describes equipment and summarizes both pretest and onsite procedures for testing of digital electronic devices for susceptibility to single-event upset. Term 'single-event upset' denotes variety of temporary or permanent bit flips or latchup induced by single particles of ionizing radiation. Vacuum chamber houses device under test while exposed to ion beam. Vacuum chamber and associated equipment must be brought to ion-beam facility for test.

B85-10455

MEASURING ANTENNA SIGNAL DELAYS

T. Y. OTOSHI (Caltech) and A. R. HOWLAND (Caltech)

Mar. 1986

NPO-15947

Vol. 9, No. 4, P. 70

Signal delays in large dish antennas measured by method based on commercial frequency-modulated instrument. Measurements accurate within 3 ns on primary path lengths of 60 ns or more. Major benefit of method is user distinguishes between delay along the primary signal path and delays along multiple-reflection signal paths (multipaths), so multipath errors minimized or made insignificant in calibration of antenna delays.

B85-10456

MULTIPLIER ARCHITECTURE FOR CODING CIRCUITS

C. C. WANG (Caltech), T. K. TRUONG (Caltech), H. M.

SHAO (Caltech), and L. J. DEUTSCH (Caltech)

Mar. 1986

NPO-16363

Vol. 9, No. 4, P. 74

Multipliers based on new algorithm for Galois-field (GF) arithmetic regular and expandable. Pipeline structures used for computing both multiplications and inverses. Designs suitable for implementation in very-large-scale integrated (VLSI) circuits. This general type of inverter and multiplier architecture especially useful in performing finite-field arithmetic of Reed-Solomon error-correcting codes and of some cryptographic algorithms.

B85-10457

IMPROVED ELECTRONIC CONTROL FOR ELECTROSTATIC PRECIPITATORS

D. F. JOHNSTON

Mar. 1986

LAR-13273

Vol. 9, No. 4, P. 76

Electrostatic precipitators remove particulate matter from smoke created by burning refuse. Smoke exposed to electrostatic field, and particles become electrically charged and migrate to electrically charged collecting surfaces. New microprocessor-based electronic control maintains precipitator power at maximum particulate-collection level. Control automatically senses changes in smoke composition due to variations in fuel or combustion and adjusts precipitator voltage and current accordingly. Also, sensitive yet stable fault detection provided.

B85-10458

PICTURE-ELEMENT COMPARATOR

D. B. GENNERY (Caltech)

Mar. 1986

NPO-16464

Vol. 9, No. 4, P. 77

Proposed circuit, called 'neighborhood comparison operator,' compares data from neighboring picture elements (pixels) to find peaks, ridges, and valleys in picture data. Circuit also able to expand or shrink pixel regions. Circuit concept developed for image-processing computers. Circuit handles data stream of 12-bit pixels rather than conventional 8 or 16 bits. Consist entirely of standard logic chips.

B85-10459

PROGRAMMABLE PIPELINED-IMAGE PROCESSOR

D. B. GENNERY (Caltech) and B. WILCOX (Caltech)

Mar. 1986

NPO-16463

Vol. 9, No. 4, P. 77

Computer serves as pipelined processor for imagery or other two-dimensional digital data. Processor does feature extraction, smoothing, edge detection, texture measurement, and stereoscopic area correlation. Also plans routes for obstacle avoidance by robots and solves two-dimensional partial differential equations. Image processor consists of modular units: each includes set of computing elements of types particularly useful in pipelined-image processing. Flexible interconnection scheme used to route data to subsequent stages of pipeline.

B85-10460

FUNCTION GENERATOR FOR IMAGE PROCESSOR

D. B. GENNERY (Caltech) and B. WILCOX (Caltech)

Mar. 1986

NPO-16461

Vol. 9, No. 4, P. 78

Basic elements of function generator are memory chips and interpolator chip, which incorporates multipliers and adders. Memory includes CMOS static random-access devices. 120 ns cycle time of devices allows real-time processing of image data.

B85-10461

DESIGN OF LINEAR QUADRATIC REGULATORS AND KALMAN FILTERS

B. LEHTINEN and L. GEYSER

Mar. 1986

LEW-14128

Vol. 9, No. 4, P. 79

AESOP solves problems associated with design of

03 PHYSICAL SCIENCES

controls and state estimators for linear time-invariant systems. Systems considered are modeled in state-variable form by set of linear differential and algebraic equations with constant coefficients. Two key problems solved by AESOP are linear quadratic regulator (LQR) design problem and steady-state Kalman filter design problem. AESOP is interactive. User solves design problems and analyzes solutions in single interactive session. Both numerical and graphical information available to user during the session.

03 PHYSICAL SCIENCES

B85-10041 PROTECTIVE PACKAGE FOR A GAMMA-RAY DETECTOR

M. FONG (CALTECH), C. LUCAS (CALTECH), A. METZGER (CALTECH), D. M. MOORE (CALTECH), R. OLIVER (CALTECH), and W. PETRICK (CALTECH)

Jun. 1985

NPO-16019

Vol. 9, No. 1, P. 72

Package for germanium gamma-ray detector protects semiconductor crystal from contamination, allows it to operate at high voltages, and isolates from shock and vibration. Package seals detector from its surroundings, whether in atmosphere or in vacuum of space. Main parts of package made of aluminum. Cover sealed to base by soft aluminum ring.

B85-10042 VARIABLE-TEMPERATURE-GRADIENT DEVICE FOR SOLIDIFICATION RESEARCH

W. F. KAUHLER (Kaukler, William F.)

Jun. 1985

MFS-26008

Vol. 9, No. 1, P. 73

Device for research in solidification and crystal growth allows crystallization of melt observed as occurs. Temperature gradient across melt specimen increased or decreased rapidly while solidification front proceeds at constant speed across sample. Device moves sample at same speed, thereby holding position of liquid/solid interface stationary within field of optical microscope. Device, variable-temperature-gradient microscope stage, used to study crystal growth at constant rate while thermal driving force is varied.

B85-10043 TELESCOPE WITH REFLECTING BAFFLE

W. I. LINLOR

Jun. 1985 NASA TM-84406 (N84-13985/NSP)

ARC-11502

Vol. 9, No. 1, P. 74

Telescope baffle made from combination of reflecting surfaces. In contrast with previous ellipsoidal reflecting baffles, new baffle reflects skew rays more effectively and easier to construct. For infrared telescopes, reflecting baffles better than absorbing baffles because heat load reduced, and not necessary to contend with insufficiency of infrared absorption exhibited by black coatings.

B85-10044 OUT-OF-FOCUS ALINEMENT OF SOLAR CONCENTRATORS

M. J. ARGOU (CALTECH) and E. W. DENNISON (CALTECH)

Jun. 1985

NPO-15563

Vol. 9, No. 1, P. 75

In new alignment technique, no attempt made to simulate infinitely distant light source, and all mirrors left uncovered throughout procedure. Light source placed at

distance of 1,650 feet (503 m); other distances used. Alinement of approximately 250 mirror facets of paraboloidal solar concentrator simplified by precalculated images reflected from all facets. Developed for large solar concentrators, technique used with other multiple-mirror or multiple-light-source systems for producing specified illuminance patterns.

B85-10045 MEASURING CLOUDS WITH MICROWAVES AND INFRARED

P. C. PANDEY (CALTECH), E. G. NJOKU (CALTECH), and J. W. WATERS (CALTECH)

Jun. 1985

NPO-16265

Vol. 9, No. 1, P. 75

Combination of microwave and infrared measurements from satellites yields data from which thicknesses and temperature of clouds inferred. Microwave radiation measured by satellite used to determine thickness of cloud and difference between cloud-top temperature and mean temperature of interior. Technique extends capability of previously established method in which infrared radiation returned to satellite by cloud used to determine temperature and altitude of cloud top and fractional area of Earth covered by cloud.

B85-10046 IMAGING SPECTROMETER FOR GEOPHYSICAL SURVEYS

C. C. LABAW (CALTECH)

Jun. 1985

NPO-16072

Vol. 9, No. 1, P. 76

Airborne spectrometer combines technologies of television imaging and spectroscopy to produce data for geophysical surveys, agricultural assessments, forest and land management, and exploration for oil and minerals. Designed for Small Size, infrared imaging spectrometer uses folded telescope and passes input and output of its monochromator through hole in monochromator grating. Instrument permits analysis of terrain at many infrared wavelengths.

B85-10047 NEARLY ANASTIGMATIC X-RAY TELESCOPE

D. KORSCH (Korsch Optics, Inc.)

Jun. 1985

MFS-25984

Vol. 9, No. 1, P. 77

Proposed X-ray telescope made of many concentric reflecting rings, each of which consists of two portions of cone. Proposed design is variation on conventional grazing incidence X-ray telescope, which has just one twosegment reflecting element but suffers from excessive astigmatism and field curvature. Using many short elements instead of single long element, new design gives nearly anastigmatic image.

B85-10048 THERMALLY-RECHARGEABLE ELECTROCHEMICAL CELL

R. RICHTER (CALTECH)

Jun. 1985

NPO-16273

Vol. 9, No. 1, P. 78

Proposed liquid-sodium/sulfur electrochemical cell recharged by heat, rather than electric generator. Concept suitable for energy storage for utilities, mobile electronic equipment, and solar thermoelectric power systems. Sodium ions driven across membrane with aid of temperature differential.

B85-10049 SPECTROPHOTOVOLTAIC POWER GENERATION

G. KNOWLES (Honeywell, Inc.) and J. CARROLL (Honeywell, Inc.)

Jun. 1985

MFS-27027

Vol. 9, No. 1, P. 78

Optical Components of spectrophotovoltaic system concentrate light from Sun and redirect short-wavelength

portion of spectrum to solar cell having large gap in energy band (gallium arsenide cell). Longer-wavelength portion of spectrum passes through beam splitter to cell with smaller gap in energy band (silicon band). Available energy in Sunlight thus exploited more fully and, improvements in energy-conversion efficiency possible.

B85-10050
METHANOL FUEL CELL
G. E. VOECKS (CALTECH)

Jun. 1985
NPO-15823

Vol. 9, No. 1, P. 79

In proposed fuel-cell system, methanol converted to hydrogen in two places. External fuel processor converts only part of methanol. Remaining methanol converted in fuel cell itself, in reaction at anode. As result, size of fuel processor reduced, system efficiency increased, and cost lowered.

B85-10051
MANIPULATOR FOR HEATING AND COOLING IN ULTRAHIGH VACUUM
R. OUTLAW and B. T. BAUGH

Jun. 1985
LAR-13040

Vol. 9, No. 1, P. 80

In sample-transfer system for use in ultrahigh vacuum, samples mounted on threaded circular holder transferred to flip mechanism of manipulator by simple translation and rotation. Flip mechanism contains electrode assembly and thermocouple that make direct contact with sample. Copper plate and flexible strap attached to receiving block to cool sample. Simple modifications allow broad range of sample temperatures (150 to 1,750 K) and direct temperature measurements, while retaining advantage of additional degree of freedom provided by flip mechanism of precise manipulator.

B85-10052
WIDE-ANGLE, WIDE-BAND CAMERA FOR REMOTE IMAGING

P. D. ATCHESON (University of Arizona)

Jun. 1985
NPO-15799

Vol. 9, No. 1, P. 81

Improved ultraviolet-to-infrared camera design combines high resolution and relatively wide field of view in remote-imaging system. Although design intended for satellite-borne system to give information on such Earth features as vegetation, pollution, and land formation mineral deposits, optical principle also useful in ground-based or airborne high-resolution television for imaging objects at great distances.

B85-10053
SEGMENTED DETECTOR FOR COSMIC GAMMA RAYS
L. S. VARNELL (CALTECH)

Jun. 1985
NPO-16245

Vol. 9, No. 1, P. 82

Segmented structure distinguishes gamma rays of cosmic origin from internal radioactivity. Preamplifier and discriminator channel connects each electrically independent segment of gamma-ray detector to logic circuitry. Logic compares and analyzes events in segments to determine sources. According to Monte Carlo calculations, sensitivity of detector two to three times better than conventional detectors because background interactions discerned and eliminated.

B85-10054
ALTERING FLASHLAMP OUTPUT FOR REALISTIC SOLAR SIMULATION

R. L. MUELLER (CALTECH) and C. H. SEAMAN (CALTECH)

Jun. 1985
NPO-16167

Vol. 9, No. 1, P. 82

Commercial glass optical filter corrects spectrum of xenon flashtubes used to test photovoltaic solar cells. Filter withstands thousands of flashes without perceptible altera-

tion of passband characteristics. With filter, calibration errors reduced to less than 1 percent.

B85-10055
ESTIMATES OF LATENT HEAT IN CLOUDS

P. J. SMITH (Purdue Research Foundation)

Jun. 1985
MFS-25977

Vol. 9, No. 1, P. 85

Release of latent heat in formation of clouds and precipitation estimated more accurately with simple technique that merges satellite cloud imagery with rawinsonde (tracked-radiosonde) data on air pressure, temperature, humidity, windspeed, and wind direction. Technique created to improve diagnosis of energy states and transformations in extratropical cyclones.

B85-10056
LASER-ASSISTED ANALYSIS OF AEROSOL PARTICLES

M. P. SINHA (CALTECH), C. E. GIFFIN (CALTECH), D. D. NORRIS (CALTECH), and S. K. FRIEDLANDER (CALTECH)

Jun. 1985
NPO-15308

Vol. 9, No. 1, P. 86

Proposed instrument makes rapid mass-spectrometric analyses of individual particles in aerosols. Each particle vaporized and ionized by intense laser pulse, which creates ions of minimum complexity. Ability to analyze single aerosol particles continuously makes technique suitable for detection of toxic aerosol particles on real-time basis and for identification of their sources.

B85-10057
ULTRAHIGH-VACUUM SAMPLE-TRANSFER SYSTEM

R. OUTLAW and B. T. BAUGH

Jun. 1985
LAR-12993

Vol. 9, No. 1, P. 86

Ultrahigh-vacuum (UHV) sample-transfer system developed features short-term (less than 30 minutes) transfer of samples from atmospheric pressure into sample manipulator within UHV analysis system without significantly degrading system pressure. New system is austere approach to sample transfer, involving no automation. Total cost of system is factor of 10 less than commercially available instruments.

B85-10058
BATTERY-CHARGE-STATE MODEL

H. C. VIVIAN (CALTECH)

Jun. 1985
NPO-16158

Vol. 9, No. 1, P. 87

Charge-state model for lead/acid batteries proposed as part of effort to make equivalent of fuel gage for battery-powered vehicles. Models based on equations that approximate observable characteristics of battery electrochemistry. Uses linear equations, easier to simulate on computer, and gives smooth transitions between charge, discharge, and recuperation.

B85-10059
ENVIRONMENTAL DEGRADATION OF SOLAR REFLECTORS

F. L. BOUQUET (CALTECH)

Jun. 1985
NPO-16053

Vol. 9, No. 1, P. 88

Report presents results of study of atmospheric degradation of large solar reflectors for power generators. Three general types of reflective surfaces investigated. Report also describes computer buildup and removal (by rain and dew) of contamination from reflectors. Data used to determine effects of soil buildup and best method and frequency of washing at various geographic locations.

B85-10173
SEGMENTED TROUGH REFLECTOR

W. R. SZMYD (Lockheed Missiles & Space Co., Inc.)

Oct. 1985
NPO-15026

Vol. 9, No. 2, P. 68

Segmented troughlike reflector for solar cells approach

03 PHYSICAL SCIENCES

concentration effectiveness of true parabolic reflector yet simpler and less expensive. Walls of segmented reflector composed of reflective aluminized membrane. Lengthwise guide wire applies tension to each wall, thereby dividing each into two separate planes. Planes tend to focus Sunlight on solar cells at center of trough between walls. Segmented walls provide higher Sunlight concentration ratios than do simple walls.

B85-10174
WINDOWLESS HIGH-PRESSURE SOLAR REACTOR
K. N. R. RAMOHALLI (Caltech)
Oct. 1985

NPO-16310 Vol. 9, No. 2, P. 68
Obscuration by reaction products eliminated. Chemical reactor heated by Sunlight employs rocket technology to maintain internal pressure. Instead of keeping chamber tightly closed, pressure maintained by momentum balance between incoming and outgoing materials. Windowless solar reactor admits concentrated Sunlight through exhaust aperture. Pressure in reactor maintained dynamically.

B85-10175
MONITORING TRACE GASES IN THE ATMOSPHERE
C. R. WEBSTER (Caltech) and W. B. GRANT (Caltech)
Oct. 1985

NPO-16278 Vol. 9, No. 2, P. 69
Tunable laser spectrometer uses reflections from ordinary objects. Topographic target (ordinary feature of surroundings) returns enough energy to receiver so absorption by trace gases detected. Chopping laser beam allows return to be compared with original signal. Amplifier locks in on chopping frequency or laser modulation frequency. In laboratory simulations, spectrometer detected nitrogen dioxide in concentrations of only few parts per million.

B85-10176
MEASURING SOIL HYDRAULIC CONDUCTIVITY WITH MICROWAVES
B. J. BLANCHARD and P. E. ONEILL
Oct. 1985

GSC-12937 Vol. 9, No. 2, P. 70
Soil mapping for large or small areas done rapidly. Technique requires simple radiometric measurements of L-band (15 to 30 cm) and thermal infrared emissions from ground within 2 days after saturation of surface. Technique based on observation that correlation exists between L-band emissivity and hydraulic conductivity of soil.

B85-10177
HIGH-PERFORMANCE HEAT PIPE
J. P. ALARIO (Grumman Aerospace Corp.), R. KOSSON (Grumman Aerospace Corp.), and R. HASLETT (Grumman Aerospace Corp.)
Oct. 1985

MSC-20136 Vol. 9, No. 2, P. 70
Single vapor channel and single liquid channel joined by axial slot. New design, permits high heat-transport capacity without excessively reducing heat-transfer efficiency. Contains two large axial channels, one for vapor and one for liquid, permitting axial transport and radial heat-transfer requirements met independently. Heat pipe has capacity of approximately 10 to sixth power watt-inches (2.5 X 10 to sixth power watt-cm) orders of magnitude greater than heat capacity of existing heat pipes. Design has high radial-heat-transfer efficiency, structurally simple, and has large liquid and vapor areas.

B85-10178
AIRBORNE DIAL SYSTEM FOR REMOTE TROPOSPHERIC SENSING
E. V. BROWELL
Oct. 1985

LAR-13002 Vol. 9, No. 2, P. 71
Spatial distribution of gases and of aerosols measured. Airborne DIAL system uses two frequency-doubled Nd:YAG

lasers and mounted in NASA Wallops Electra aircraft. Multipurpose airborne differential absorption lidar (DIAL) system, developed at Langley Research Center, remotely measures profiles of various gases and aerosols in diverse atmospheric investigations. Capability to rapidly determine spatial distribution of gases such as ozone, water vapor, sulfur dioxide, and nitrogen dioxide and to measure simultaneously distribution of aerosols at several laser wavelengths provides opportunity for developing extensive data base for examining complex interaction of atmospheric dynamics and chemistry.

B85-10179
ANALYZING MICROCHIPS WITH DARK-FIELD NEGATIVE PHOTOMICROGRAPHY
S. F. SUSZKO (Caltech)
Oct. 1985

NPO-16299 Vol. 9, No. 2, P. 72
Inverse development process yields fine details. Photomicrographic technique produces images of integrated-circuit chips. Technique based on dark-field illumination: chip lit with bright central spot of light and photographed by light scattered or diffracted from spot. Reveals more about microstructure patterns related to photoresist masking than more conventional bright-field method.

B85-10180
OPTICAL MOUNTS FOR CRYOGENIC BEAM SPLITTERS
A. A. RUDMAN
Oct. 1985

GSC-12923 Vol. 9, No. 2, P. 73
Spring-loaded optical mounts maintain flatness and alignment of rigid, framed, or pellicle beam splitters over wide temperature range, despite differences in thermal expansion among materials. Mounts permit optical adjustments at ambient temperature even though optical system operated subsequently within few degrees of absolute zero. Mounts useful as holders for integrated-circuit master patterns, survey targets, vibrating membranes, noise- or pressure-sensing membranes, osmosis filters, and fuel-cell elements.

B85-10181
ESTIMATING ANTENNA SHAPE FROM FAR-FIELD MEASUREMENTS
Y. RAHMAT-SAMII (Caltech)
Oct. 1985

NPO-16425 Vol. 9, No. 2, P. 74
Amplitude and phase measurements help characterize nearly paraboloidal reflectors. Deviation of microwave reflector from ideal paraboloidal shape deduced from far-field amplitude and phase measurements with help of theoretical technique referred to as microwave holographic metrology. Technique enables estimation of antenna-surface figure from measurements taken at prescribed number of field points. After determining amount of surface deviation, performance of antenna then improved by properly adjusting surface panels.

B85-10182
IMPROVED THERMAL-DIFFUSIVITY-MEASURING APPARATUS
C. WOOD (Caltech) and A. ZOLTAN (Caltech)
Oct. 1985

NPO-16280 Vol. 9, No. 2, P. 76
Accuracy at high temperature improved. Furnace heats specimen to experimental temperature, and flash tube raises specimen temperature by small amount and for short time so diffusivity (composite property of heat capacity and conductivity) determined. Specimen mount ensures minimum heat loss during temperature-rise measurement. Measurement temperatures up to 1,000 degrees C realized with fused-quartz light pipe and up to 1,600 degrees C with sapphire light pipe.

B85-10183

MEASURING MOISTURE IN SEALED ELECTRONIC ENCLOSURES

J. KRIEG, HERMANC. (TRW, Inc.)

Oct. 1985

MSC-18886

Vol. 9, No. 2, P. 78

Instrument checks trace amounts accurately. Moisture in hermetically-sealed electronic equipment measured by instrument designed for field use. Instrument also measures pressure, volume, and contaminants of gas in sealed enclosure. Plumbing for instrument uses vacuum-tight valves so any portion of instrument cleansed by opening certain valves to vacuum source. To ensure accuracy, manifolds are of minimal volume, each comprising only volume within cross-shaped tubing fittings.

B85-10184

LENS-AND-DETECTOR ARRAY FOR SPECTROMETER

J. OBERHEUSER (Perkin-Elmer Corp.)

Oct. 1985

NPO-16388

Vol. 9, No. 2, P. 80

Supporting structure aligns lenses and serves as light baffle. Lenses and infrared detectors mounted together in cavities in electroformed plate. Plate and cavities maintain optical alignment while serving as light baffle and aperture stop.

B85-10185

ESTIMATING THE PERFORMANCE OF A CONCENTRATING SOLAR ARRAY

E. P. FRENCH (Rockwell International Corp.), M. W. MILLS (Rockwell International Corp.), and Z. BACKOVSKI (Rockwell International Corp.)

Oct. 1985

MFS-28021

Vol. 9, No. 2, P. 82

Comprehensive mathematical-analysis technique developed for array of solar-photovoltaic panels equipped with truncated-pyramid concentrators. Hollow pyramidal concentrator reflects sunlight onto panel of photovoltaic cells. Comprehensive optical, thermal, and electrical analysis performed on array of units. Technique applicable, with modifications, to analysis and design of other multiple-cell reflecting photovoltaic systems.

B85-10186

CROSSOVER CONCEPT FOR OPTICAL PRINTED CIRCUITS

R. S. JAMIESON (Caltech)

Oct. 1985

NPO-15131

Vol. 9, No. 2, P. 82

It is possible to reduce crosstalk between optical signals in intersecting optical conductors by taking two steps: Minimize amount of light diffracted into wrong conductor by selecting optimum conductor width, and place light traps in each conductor. How well techniques work depends in part on quality of optical conductors (partially surface smoothness) and on how closely optical-signal mode of propagation approaches ideal. Nature of signals also important: With digital signals, less crosstalk attenuation required than for analog signals.

B85-10187

MULTIBAND SELECTOR FOR LINEAR PHOTODETECTOR ARRAY

H. L. RICHARD

Oct. 1985

GSC-12911

Vol. 9, No. 2, P. 83

Line image observed simultaneously in two or more spectral bands. Incoming light focused through beam splitter onto two linear arrays of photodetectors to form line images. Array of band-pass filters above each detector array positioned to select spectral band of line image. These capabilities are valuable in such multispectral-imaging applications as spaceborne and airborne visible and infrared observation of Earth for geology, oil and mineral exploration, biomass distribution, forestry, agriculture, and urban and rural development.

B85-10188

INTEGRATING RESIDENTIAL PHOTOVOLTAICS WITH POWER LINES

C. S. BORDEN (Caltech)

Oct. 1985 See Also N84-16643

NPO-16331

Vol. 9, No. 2, P. 84

Report finds rooftop solar-cell arrays feed excess power to electric-utility grid for fee are potentially attractive large-scale application of photovoltaic technology. Presents assessment of breakeven costs of these arrays under variety of technological and economic assumptions.

B85-10189

TESTS OF LOW-CONCENTRATION-RATIO PHOTOVOLTAIC ELEMENTS

M. W. MILLS (Rockwell International Corp.) and Z. F. BACKOVSKI (Rockwell International Corp.)

Oct. 1985

MFS-28020

Vol. 9, No. 2, P. 84

Report describes performance measurements on elements of low-concentration-ratio solar arrays (LCRSA's) employing silicon and gallium arsenide photovoltaic cells. Measurements intended to verify predictions of performance based on mathematical models. Measured and predicted values found to agree closely for both normal and off-normal pointing of array toward Sun.

B85-10190

AUGMENTING THRUST WITH WASTE HEAT

R. H. FRISBEE (Caltech)

Oct. 1985

NPO-16218

Vol. 9, No. 2, P. 86

According to NASA report, energy rejected by nuclear reactor adds to rocket thrust. With augmentation, specific impulse increased by as much as 23 percent over that of conventional engine.

B85-10191

DUCT-FLOW ANALYSIS

T. KATSANIS

Oct. 1985

LEW-14000

Vol. 9, No. 2, P. 86

Quasi-two-dimensional velocity distribution through annular duct calculated. Computer program ANDUCT developed for calculating velocity distribution along arbitrary line between inner and outer walls of annular duct with axisymmetric swirling flow. Velocity gradient equation used with assumed variation of meridional streamline curvature. ANDUCT written in FORTRAN IV for use on IBM 370/3033 computer.

B85-10316

MOLECULAR-BEAM CHOPPER AND FOUR-CHANNEL AMPLIFIER

B. R. ADAMS (Kentron International, Inc.)

Jan. 1986

LAR-13174; LAR-13175

Vol. 9, No. 3, P. 72

Molecular-beam chopper phase controller and timing interface is subsystem of four-stage, differentially pumped, modulated molecular-beam/mass spectrometer. Subsystem maintains accurate phase control and timing for repetitive signal averaging over several hours of operation. Chopper phase controller/timing interface and four-channel programmable time-multiplexed amplifier provide substantial improvements in attainable signal-to-noise ratio, detection limit, and accuracy of molecular-beam/mass-spectrometer system.

B85-10317

FOURIER-TRANSFORM INFRARED SPECTROMETER

R. A. SCHINDLER (Caltech)

Jan. 1986

NPO-16431

Vol. 9, No. 3, P. 73

Fourier-transform spectrometer provides approximately

03 PHYSICAL SCIENCES

hundredfold increase in luminosity at detector plane over that achievable with older instruments of this type. Used to analyze such weak sources as pollutants and other low-concentration substances in atmosphere. Interferometer creates fringe patterns on two distinct arrays of light detectors, which observe different wavelength bands. Objective lens focuses scene on image plane, which contains optical chopper. To make instrument less susceptible to variations in scene under observation, field and detector lenses focus entrance aperture, rather than image, onto detector array.

B85-10318 CONTACTLESS CALORIMETRY FOR LEVITATED SAMPLES

M. C. LEE (Caltech) and W. DOKKO (Caltech)

Jan. 1986

NPO-16448

Vol. 9, No. 3, P. 74

Temperature and specific heat of hot sample measured with pyrometer in proposed experimental technique. Technique intended especially for contactless calorimetry of such materials as undercooled molten alloys, samples of which must be levitated to prevent contamination and premature crystallization. Contactless calorimetry technique enables data to be taken over entire undercooling temperature range with only one sample. Technique proves valuable in study of undercooling because difference in specific heat between undercooled-liquid and crystalline phases at same temperature provides driving force to convert metastable undercooled phase to stable crystalline phase.

B85-10319 LONG-GAIN-LENGTH, SOLAR-PUMPED BOX LASER

R. J. DE YOUNG

Jan. 1986

LAR-13256

Vol. 9, No. 3, P. 74

New laser cavity configuration efficiently couples solar radiation to laser mode volume. Lasing output powers of approximately 300 mW achieved for durations of 150 ms. New system allows lasing at substantially lower solar simulator intensities (150 Suns) and much longer laser gain lengths (60 cm).

B85-10320 OPTICAL SCANNER FOR LINEAR ARRAYS

M. W. FINKEL

Jan. 1986

GSC-12897

Vol. 9, No. 3, P. 75

Optical scanner instantaneously reads contiguous lines forming scene or target in object plane. Reading active or passive and scans, continuous or discrete. Scans essentially linear with scan angle and symmetric about axial ray. Nominal focal error, resulting from scan, well within Rayleigh limit. Scanner specifically designed to be fully compatible with general requirements of linear arrays.

B85-10321 METHANE DETECTOR WITH PLASTIC FRESNEL LENS

W. B. GRANT (Caltech)

Jan. 1986

NPO-16284

Vol. 9, No. 3, P. 76

Laser detector for natural gas leaks modified by substitution of molded plastic lens for spherical mirror. By measuring relative attenuation at two wavelengths, detector used to check for methane escaping from pipelines above or below ground and from landfill.

B85-10322 REFLECTING SLIT FOR IMAGING SPECTROMETER

N. A. PAGE (Caltech), R. E. PARKS (Caltech), and J. M. RODGERS (Caltech)

Jan. 1986

NPO-16408

Vol. 9, No. 3, P. 78

Optical slit that reflects rather than transmits performs multiple functions for imaging infrared spectrometer. Serves as field reflector, field flattener, and entrance aperture for

instrument. Reflecting slit narrow strip of spherical reflecting surface with intersecting spherical reflecting side surfaces that reject radiation originating outside slit region. Precision of slit geometry crucial in optical system.

B85-10323 LASER ALTIMETER FOR FLIGHT SIMULATOR

L. D. WEBSTER

Jan. 1986

ARC-11312

Vol. 9, No. 3, P. 79

Height of flight-simulator probe above model of terrain measured by automatic laser triangulation system. Airplane simulated by probe that moves over model of terrain. Altitude of airplane scaled from height of probe above model. Height measured by triangulation of laser beam aimed at intersection of model surface with plumb line of probe.

B85-10324 LASER PHOTOACOUSTIC TECHNIQUE DETECTS PHOTO-OXIDATION

R. H. LIANGE (Caltech), D. R. COULTER (Caltech), and A. GUPTA (Caltech)

Jan. 1986

NPO-16108

Vol. 9, No. 3, P. 80

Laser photoacoustic instrument detects small amounts of oxidation in polymers. Instrument used to evaluate resistance to oxidation in Sunlight of polymer encapsulants for solar-cell arrays. With instrument, researchers monitor samples for early stages of photooxidation and study primary mechanisms of oxidation and degradation. Effects of these mechanisms masked during later stages.

B85-10325 OPTICAL INTEGRATING SPHERE FOR VACUUM ULTRAVIOLET

C. L. BUTNER

Jan. 1986

GSC-12849

Vol. 9, No. 3, P. 80

Optical integrating sphere with integral sliding sample holder saves time by allowing radiometric measurements made on each of four samples without breaking vacuum. Designed to operate with interior evacuated so dye samples illuminated with short-wavelength ultraviolet strongly absorbed by air; need not be evacuated when using longer wavelengths. Device mounts on monochromator and evacuated through port that admits light from monochromator.

B85-10326 LASER SCHLIEREN CRYSTAL-GROWTH IMAGER

R. B. OWEN and M. H. JOHNSTON

Jan. 1986

MFS-28060

Vol. 9, No. 3, P. 81

Crystal observed as it grows from melt with aid of laser schlieren imaging. Observation method allows entire perimeter of growing crystal to be inspected. Isolated crystal facets examined, convection flows and temperature and concentration gradients revealed. Method does not require contact with, or proximity to, crystal.

B85-10327 CALCULATING ATMOSPHERIC EFFECTS IN SATELLITE IMAGERY

D. J. DINER (Caltech) and J. V. MARTONCHIK (Caltech)

Jan. 1986

NPO-16373

Vol. 9, No. 3, P. 82

Report presents detailed analysis of atmospheric blurring inherent in photographs or other observations of Earth from satellites or aircraft. Blurring result of scattering of radiation, which diffuses sharp image features by causing light from one part of scene to fall on image of adjacent part. In contrast with earlier approaches to atmospheric optics, one presented in report more accurate and versatile and designed for use on minicomputers.

B85-10328

ALGORITHMS FOR COASTAL-ZONE COLOR-SCANNER DATA

(Innovator Not Given) (Nimbus-7 Project Office) Jan. 1986

GSC-12852

Vol. 9, No. 3, P. 83

Software for Nimbus-7 Coastal-Zone Color-Scanner (CZCS) derived products consists of set of scientific algorithms for extracting information from CZCS-gathered data. Software uses CZCS-generated Calibrated Radiance-Temperature (CRT) tape as input and outputs computer-compatible tape and film product.

B85-10329

DESIGNING ECCENTRIC APERTURE OPTICAL SYSTEMS

J. R. ROGERS (University of Arizona)

Jan. 1986

NPO-16355

Vol. 9, No. 3, P. 83

Computer program aids in design of eccentric aperture optical systems by predicting vector aberration that occurs in optical system having tilted or decentered optical elements. Computer program incorporates vector theory of aberrations.

B85-10462

PLOTTING LIGHTNING-STROKE DATA

F. B. TATOM and R. A. GARST

Mar. 1986

MFS-26019

Vol. 9, No. 4, P. 80

Data on lightning-stroke locations become easier to correlate with cloudcover maps with aid of new graphical treatment. Geographic region divided by grid into array of cells. Number of lightning strokes in each cell tabulated, and value representing density of lightning strokes assigned to each cell. With contour-plotting routine, computer draws contours of lightning-stroke density for region. Shapes of contours compared directly with shapes of storm cells.

B85-10463

NEBULIZATION REFLUX CONCENTRATOR

W. R. COFER and V. G. COLLINS (College of William and Mary)

Mar. 1986

LAR-13254

Vol. 9, No. 4, P. 82

Nebulization reflux concentrator extracts and concentrates trace quantities of water-soluble gases for subsequent chemical analysis. Hydrophobic membrane and nebulizing nozzles form scrubber for removing trace quantities of soluble gases or other contaminants from atmosphere. Although hydrophobic membrane virtually blocks all transport of droplets, it offers little resistance to gas flow; hence, device permits relatively large volumes of gas scrubbed efficiently with very small volumes of liquid. This means analyzable quantities of contaminants concentrate in extracting solutions in much shorter times than with conventional techniques.

B85-10464

TRACKING SYSTEM FOR INFRARED SPECTROMETER

R. A. JOHNSON (Caltech), C. R. WEBSTER (Caltech), R. T. MENZIES (Caltech), G. B. MORRISON (Caltech), and J. H. RICCIO (Caltech)

Mar. 1986

NPO-16440

Vol. 9, No. 4, P. 83

Visible laser tracking system for infrared laser spectrometer keeps probe infrared laser beam aimed at moving reflector, thereby keeping reflector image and return laser beam within spectrometer field of view. System includes tracking mirror tilted by stepping motors under microprocessor control to deflect beams toward continually changing reflector position.

B85-10465

DETERMINING THE TEMPERATURE PROFILE IN A CYLINDRICAL SAMPLE

J. C. CLAYTON (Semtec, Inc.)

Mar. 1986

MFS-26013

Vol. 9, No. 4, P. 84

Power-series solution extrapolates from axial temperature profile. Thermal profile in homogeneous axisymmetric body determined throughout body if axial temperature profile known at any radius. New theory developed as aid in research on growth of mercury cadmium telluride for infrared detectors. In particular, applicable to Bridgman-Stockbarger growth, in which round cylindrical ampoule of molten ternary semiconductor is solidified directionally, from one end to other.

B85-10466

INTENSE SOURCE OF POLARIZED HYDROGEN ATOMS

L. MALEKI (Caltech)

Mar. 1986

NPO-16434

Vol. 9, No. 4, P. 85

Atoms produced by radio-frequency dissociation of hydrogen molecules sorted according to their hyperfine states in improved polarized hydrogen source. By use of combination of dc magnetic fields, atoms of upper hyperfine ground level selected in numbers greater than those of undesired $F = 0$ state. Source built with permanent magnets or electromagnets. Principal utility is source of polarized hydrogen for masers or experimental studies.

B85-10467

MOLECULAR THERMAL-ELECTRON DETECTORS

A. CHUTJIAN (Caltech) and S. ALAJAJIAN (Caltech)

Mar. 1986

NPO-16300

Vol. 9, No. 4, P. 85

Low-energy electrons detected with high resolution and sensitivity by their collisions with certain molecules. In thermal-electron-detection application, ambient plasma swept into collision chamber. Chamber designed to reduce stray electric fields to negligible levels and prevent inelastic and superelastic collisions with walls of collision-chamber repeller element. Instrument based on molecular detection performs high-resolution threshold photoelectron spectroscopy. Also used to detect fluorocarbons and chlorocarbons in upper atmosphere by their interaction with thermal electrons.

B85-10468

DETECTING TRACE CONTAMINANTS IN THE ATMOSPHERE

S. K. SRIVASTAVA (Caltech)

Mar. 1986

NPO-16225

Vol. 9, No. 4, P. 86

Sensitive instrument uses two low-energy electron beams to detect certain molecules. Experimental instrument identifies and measures trace contaminants in atmosphere. When fully developed, portable instrument expected to measure contaminant concentrations of certain halogen containing molecules as low as one part per trillion. Instrument employs electron beams to ionize contaminant molecules by dissociative attachment of electrons.

B85-10469

SOLID-STATE DETECTOR FOR TRACE MATERIALS

J. J. LAMBE (Caltech), S. KHANNA (Caltech), A. P. THAKOOR (Caltech), and H. G. LEDUC (Caltech)

Mar. 1986

NPO-16450

Vol. 9, No. 4, P. 88

Detector for trace chemicals senses as few as 10 to the 12th power molecules of given material on surface. Contains no moving parts, amenable to large-scale integration, and operates at room temperature. Potential applications in industrial process control and in environmental analysis. Characteristic signals indicate presence of certain chemicals.

B85-10470

TECHNIQUE FOR MEASURING GAS CONVERSION FACTORS

J. J. SINGH and D. R. SPRINKLE

03 PHYSICAL SCIENCES

Mar. 1986 See Also (N83-33127)

LAR-13220 Vol. 9, No. 4, P. 90

Technique for measuring calibration conversion factors for hydrocarbon mass flowmeters applied to widely used type of commercial thermal mass flowmeter for hydrocarbon gases. Values of conversion factors for two common hydrocarbons measured using this technique in good agreement with empirical values cited by manufacturer. Similar agreement expected for all other hydrocarbons. Technique based on Nernst theorem for matching partial pressure of oxygen in combustion product gases with that in normal air. Simple, quick, and relatively safe, particularly for toxic/poisonous hydrocarbons.

B85-10471 COMPACT IMAGING SPECTROMETER

J. B. WELLMAN (Caltech), A. F. H. GOETZ (Caltech), M. HERRING (Caltech), and G. A. VANE (Caltech)
Mar. 1986

NPO-16342 Vol. 9, No. 4, P. 91

Imaging spectrometer for use in crop and mineral resource-mapping experiments is scaled-down version. Compact imaging spectrometer uses Schmidt/Littrow optics with single spherical primary mirror. Radiation from scene strikes reflecting Schmidt corrector plate located near center of curvature of primary spherical mirror.

B85-10472 LIQUID-LEVEL SENSOR FOR CONTAINERS IN MOTION

J. J. SINGH and G. H. MALL (Computer Sciences Corp.)
Mar. 1986 See Also (N84-17560)

LAR-13327 Vol. 9, No. 4, P. 92

Nonintrusive technique monitors fluid contents of sealed vessels, regardless of fluid distribution inside vessels. Technique based on differences in cesium-137 gamma-ray attenuation coefficients in air and test liquids. Used to measure fluid content in closed containers on high-maneuvering aircraft where accelerations cause fluid to become distributed throughout container.

B85-10473 HYBRID LASER WOULD COMBINE POWER WITH EFFICIENCY

D. L. SIPES, JR. (Caltech)

Mar. 1986

NPO-16173 Vol. 9, No. 4, P. 93

Efficient laser system constructed by using two semiconductor lasers to pump neodymium yttrium aluminum garnet (Nd:YAG) device. Hybrid concept allows digital transmission at data rates of several megabits per second with reasonably sized optical aperture of 20 cm. Beams from two GaAs lasers efficiently coupled for pumping Nd:YAG crystal. Combination of lasers exploits best features of each.

B85-10474 WEDGED FIBERS SUPPRESS FEEDBACK OF LASER BEAM

I. LADANY (RCA Corp.)

Mar. 1986

LAR-13074 Vol. 9, No. 4, P. 94

When injected laser is coupled into optical fiber, emission instabilities arise because of optical feedback losses from fiber into laser. Coupling efficiencies as high as 80 percent, however, obtained by shaping end of multimode fiber into obtuse-angled wedge. Because slanted sides eliminate back reflection, such wedged fiber achieves high coupling efficiency.

B85-10475 DETERMINING CALIBRATION CONSTANTS FOR ATTITUDE MEASUREMENTS

P. TCHENG and T. D. FINLEY

Mar. 1986

LAR-13214 Vol. 9, No. 4, P. 95

Algorithm based on method of least squares determines calibration constants of seismic instruments for precise

attitude measurements. Algorithm programed and run successfully on commercially available desk-top computer. Simplifies determinations of accelerometer calibration constants, and used in field to verify accelerometer stability.

B85-10476 ACCURACY OF LIDAR MEASUREMENTS OF THE ATMOSPHERE

M. J. KAVAYA (Caltech) and R. T. MENZIES (Caltech)

Mar. 1986 See Also (N84-28067)

NPO-16493 Vol. 9, No. 4, P. 96

Report reviews sources of systematic error in laser radar (lidar) measurements of particles in atmosphere. Report applies particularly to stationary pulsed carbon dioxide lidars of type used to measure backscatter from aerosols in troposphere. Provides information for calibrating such systems accurately and consistently and interpreting their data correctly. Also useful in calibrating mobile and airborne lidars, lidars operating at wavelengths other than those of carbon dioxide lasers, and continuous-wave lidars.

B85-10477 ADSORPTION OF H₂, NE, AND N₂ ON ACTIVATED CHARCOAL

C. K. CHANG (Caltech), E. TWARD (Caltech), and K. I. BOUDAIE (Caltech)

Mar. 1986

NPO-16329 Vol. 9, No. 4, P. 97

9-page report presents measured adsorption isotherms of hydrogen, neon, and nitrogen on activated charcoal for temperatures from 77 to 400 K and pressures from 1 to 80 atmospheres (0.1 to 8.1 MPa). Heats of adsorption calculated from isotherms also presented. Report gives expressions, based on ideal-gas law, which show relationship between different definitions of volume of gas adsorbed and used in describing low-pressure isotherms.

B85-10478 MICROWAVE ATMOSPHERIC-PRESSURE SENSOR

D. A. FLOWER (Caltech), G. E. PECKHAM (Caltech), and W. J. BRADFORD (Caltech)

Mar. 1986

NPO-16496 Vol. 9, No. 4, P. 97

Report describes tests of microwave pressure sounder (MPS) for use in satellite measurements of atmospheric pressure. MPS is multifrequency radar operating between 25 and 80 GHz. Determines signal absorption over vertical path through atmosphere by measuring strength of echoes from ocean surface. MPS operates with cloud cover, and suitable for use on current meteorological satellites.

B85-10479 SOIL/STRUCTURE INTERACTIONS IN EARTHQUAKES

G. W. RAMEY (Auburn University), R. K. MOORE (Auburn University), C. H. YOO (Auburn University), T. D. BUSH, (Auburn University), and J. M. STALLINGS (Auburn University)

Mar. 1986

MFS-27078 Vol. 9, No. 4, P. 97

In effort to improve design of Earthquake-resistant structures, mathematical study undertaken to simulate interactions among soil, foundation, and superstructure during various kinds of vibrational excitation. System modeled as three lumped masses connected vertically by springs, with lowest mass connected to horizontal vibrator (representing ground) through springs and dashpot. Behavior of springs described by elastic or elastoplastic force/deformation relationships. Relationships used to approximate nonlinear system behavior and soil/foundation-interface behavior.

B85-10480 EQUIPMENT FOR MICROGRAVITY RESEARCH

J. A. FOUNTAIN

Mar. 1986

MFS-27094 Vol. 9, No. 4, P. 98

Illustrated catalog describes equipment and facilities available for experiments under low-gravity conditions. Catalog encourages scientific and commercial organizations to investigate benefits of conducting research and manufacturing activities in microgravity environment. Catalog covers equipment ranging from containers to spacecraft.

B85-10481

CALCULATION OF MACROSEGREGATION IN AN INGOT
D. R. POIRIER (General Electric Co.) and A. L. MAPLES (General Electric Co.)

Mar. 1986 See Also (N84-23752)

MFS-27068

Vol. 9, No. 4, P. 98

Report describes both two-dimensional theoretical model of macrosegregation (separating into regions of discrete composition) in solidification of binary alloy in chilled rectangular mold and interactive computer program embodying model. Model evolved from previous ones limited to calculating effects of interdendritic fluid flow on final macrosegregation for given input temperature field under assumption of no fluid in bulk melt.

B85-10482

KINEMATIC STIRLING ENGINE PERFORMANCE

J. R. C. TEW

Mar. 1986

LEW-14092

Vol. 9, No. 4, P. 99

Computer program developed for analyzing thermodynamic characteristics of kinematic Stirling engine. Computes time-varying piston positions, pressures, and gas temperatures in each of gas-control volumes into which engine working space is divided. Engine performance characterized by calculations of power and efficiency (both indicated and brake). Inputs to code are engine geometrical parameter, engine-operating conditions, and indexes that specify various options available.

B85-10483

X-RAY DIFFRACTION ANALYSIS PROGRAM

K. E. WIEDEMANN (Vigyan Research Associates, Inc.), J. UNNAM (Vigyan Research Associates, Inc.), S. V. N. NAIDU (Virginia Polytechnic Institute & State University), and C. R. HOUSKA (Virginia Polytechnic Institute & State University)

Mar. 1986

LAR-13276

Vol. 9, No. 4, P. 99

SOPAD separates overlapping peaks and analyzes derivatives of X-ray diffraction data. SOPAD helps analyst get most information out of available diffraction data. SOPAD uses Marquardt-type nonlinear regression routine to refine initial estimates of individual peak positions, intensities, shapes, and half-widths.

04 MATERIALS

B85-10060

HIGH-PURITY SILICON SEEDS FOR SILANE PYROLYSIS
G. C. HSU (CALTECH), N. K. ROHATGI (CALTECH), and A. MORRISON (CALTECH)

Jun. 1985

NPO-16287

Vol. 9, No. 1, P. 90

Seed particles for fluidized-bed production of silicon made by new contamination-free, economical method. In new method, large particles of semiconductor-grade silicon fired at each other by high-speed streams of gas and thereby break up into particles of suitable size for fluidized bed. No foreign materials introduced, and leaching unnecessary. Method used to feed fluidized-bed reactor for continuous production of high-purity silicon.

B85-10061

THERMOSETTING PHTHALOCYANINE POLYMERS

G. FOHLEN, J. PARKER, and B. ACHAR (National Research Council)

Jun. 1985

ARC-11511

Vol. 9, No. 1, P. 91

Group of phthalocyanine polymers resist thermal degradation. Polymers expected semiconducting. Principal applications probably in molded or laminated parts that have to withstand high temperatures. Polymers made from either of two classes of monomer: Bisphthalonitriles with imide linkages or Bisphthalonitriles with ester-imide linkages.

B85-10062

INCREASING FIRE SAFETY OF EPOXIES

D. A. KOURTIDES and J. A. MIKROYANNIDIS (University of Patras, Greece)

Jun. 1985

ARC-11506

Vol. 9, No. 1, P. 94

Epoxy with increased resistance to fire made by reacting any of three commercial epoxide monomers with curing agent consisting of mixture of isomers called 'DCEPD'. Curing agent incorporates phosphorus and chlorine directly into crosslinking part of polymer. DCEPD produced by nitrating precursor phosphonylmethyl benzene, then reducing resulting isomeric mixture of dinitro compounds.

B85-10063

CERAMIC COATINGS FOR ENGINE PARTS

J. E. SCHROEDER (CALTECH)

Jun. 1985

NPO-16228

Vol. 9, No. 1, P. 94

In manufacturing concept, dense, nonporous ceramic coatings applied to metal parts by plasma spraying. Coatings improve resistance of parts to corrosion and erosion in turbines and other engines. Plasma spraying faster and cheaper than previously used method, vapor deposition, and used on large parts as well as small ones.

B85-10064

HIGH-PERFORMANCE FILLETING AND CHANNEL SEALANTS

R. W. ROSSER, D. I. BASIULIS (Hughes Aircraft Co.), and D. P. SALISBURY (Hughes Aircraft Co.)

Jun. 1985

ARC-11408; ARC-11409

Vol. 9, No. 1, P. 95

Filleting and channel sealants developed for sealing cavities in wings and fuselage of aircraft. Both sealants function well at 177 degrees C, as required in current specifications for supersonic aircraft. Sealants have excellent resistance to fuel and other solvents. They stay flexible, resistant to vibrational, thermal, and mechanical stresses, and adhere well to aluminum. Prove useful in industrial applications requiring resistance to solvents at high temperatures.

B85-10065

PURIFYING ALUMINUM BY VACUUM DISTILLATION

E. R. DU FRESNE (CALTECH)

Jun. 1985

NPO-16114

Vol. 9, No. 1, P. 96

Proposed method for purifying aluminum employs one-step vacuum distillation. Raw material for process impure aluminum produced in electrolysis of aluminum ore. Impure metal melted in vacuum. Since aluminum has much higher vapor pressure than other constituents, boils off and condenses on nearby cold surfaces in proportions much greater than those of other constituents.

B85-10066

FOAM INSULATION FOR CRYOGENIC FLOWLINES

T. R. SONJU (Federal-Mogul Corp.), R. L. CARBONE (Federal-Mogul Corp.), and R. E. OVES (Federal-Mogul Corp.)

Jun. 1985

MSC-20552

Vol. 9, No. 1, P. 96

04 MATERIALS

Welded stainless-steel vacuum jackets on cryogenic ducts replaced by plastic foam-insulation jackets that weigh 12 percent less. Foam insulation has 85 percent of insulating ability of stainless-steel jacketing enclosing vacuum of 10 microns of mercury. Foam insulation easier to install than vacuum jacket. Moreover, foam less sensitive to damage and requires minimal maintenance. Resists vibration and expected to have service life of at least 10 years.

B85-10067

SHIELDING AGAINST INTENSE LASER BEAMS

J. E. SCHROEDER (CALTECH)

Jun. 1985

NPO-16186

Vol. 9, No. 1, P. 97

Multiple-layer shielding proposed to protect equipment against damage by intense infrared laser beams. New shielding concept reduces effect of destructive phase changes upon reflectance by allowing exposure of additional reflecting layers after overlaying layers vaporized.

B85-10068

SILICONE COATING ON POLYIMIDE SHEET

J. J. PARK

Jun. 1985

GSC-12913

Vol. 9, No. 1, P. 98

Silicone coatings applied to polyimide sheeting for variety of space-related applications. Coatings intended to protect flexible substrates of solar-cell blankets from degradation by oxygen atoms, electrons, plasmas, and ultraviolet light in low Earth orbit and outer space. Since coatings are flexible, generally useful in forming flexible laminates or protective layers on polyimide-sheet products.

B85-10069

MELT STIRRING BY HORIZONTAL CRUCIBLE VIBRATION

M. F. WOLF (Stanford University), D. ELWELL (Stanford University), and R. S. FEIGELSON (Stanford University)

Jun. 1985

MFS-26005

Vol. 9, No. 1, P. 98

Horizontal vibration suggested as technique for more effective stirring of melts in crystal-growth apparatus. Vibrational technique may replace accelerated crucible rotation. Potential superiority of vibrational technique shown by preliminary experiments in which ink stirred into water.

B85-10070

NONYELLOWING POLYCARBONATE FOR OUTDOOR USE

A. GUPTA (CALTECH), R. H. LIANG (CALTECH), A. YAVROUIAN (CALTECH), and A. CLAYTON (CALTECH)

Jun. 1985

NPO-15836

Vol. 9, No. 1, P. 99

Two-step photochemical process prevents yellowing of polycarbonate plastics. Use of polycarbonate plastics growing in windows, aircraft glazing, and streetlight globes. New photochemical process causes formation of stabilizers bound to polymer chains and therefore cannot be leached out.

B85-10071

REVERSING GLASS WETTABILITY

D. O. FRAZIER, J. E. SMITH JR., and W. F. KAUKLER

Jun. 1985

MFS-26006

Vol. 9, No. 1, P. 100

Treatment reverses wettability of glassware: Liquids that normally wet glass no longer do, and those that do not wet glass are made to do so. Useful in research on container effects in nucleation and growth of secondary phase from solution. Treatment consists of spreading 3 percent (by weight) solution of silicone oil in hexane isomers over glass, drying in air, and curing at 300 degrees C in vacuum for one hour.

B85-10072

RESIN CHARACTERIZATION IN CURED COMPOSITE

MATERIALS

P. R. YOUNG and A. CHANG (Kentron International, Inc.)

Jun. 1985

LAR-13172

Vol. 9, No. 1, P. 103

Molecular-level characterization of polymeric matrix resin in cured graphite-reinforced composite materials now determined through analysis of diffuse reflectance (DR) with Fourier Transform Infrared (FTIR) spectroscopy. Improved analytical method based on diffuse reflectance. DR/FTIR technique successfully applied to analysis of several different composites and adhesives impossible to analyze by conventional methods.

B85-10073

EFFICIENT PROCESS FOR MAKING POLYCRYSTALLINE SILICON

J. R. MCCORMICK (Dow Corning Corp.), F. PLAHUTNIK JR. (Dow Corning Corp.), D. H. SAWYER (Dow Corning Corp.), A. N. ARVIDSON (Dow Corning Corp.), and S. M. GOLDFARB (Dow Corning Corp.)

Jun. 1985

NPO-16121

Vol. 9, No. 1, P. 104

Solar cells made with lower capital and operating costs. Process based on chemical-vapor deposition (CVD) of dichlorosilane produces high-grade polycrystalline silicon for solar cells. Process has potential as cost-effective replacement for CVD of trichlorosilane.

B85-10074

SYNTHESIZING METAL PHTHALOCYANINE IMIDE POLYMERS

B. ACHAR, G. FOHLEN, and J. PARKER

Jun. 1985

ARC-11413

Vol. 9, No. 1, P. 105

Efficient synthesis of analytically-pure metal (II) 4,4',4'',4''' tetraaminophthalocyanine demonstrated in experiments. Typical Polymerization proceeds in two steps: First, reaction with 3,3',4,4''-benzophenonetetracarboxylic dianhydride. Second step cyclodehydration. New polymers expected useful in formulation of thermally stable varnishes, adhesives, and fibers.

B85-10075

SOLAR-ASSISTED OXIDATION OF TOXIC CYANIDE

C. E. BYVIK and A. MILES (Southern University)

Jun. 1985

LAR-13171

Vol. 9, No. 1, P. 106

In solar-assisted oxidation technique, oxygen-bearing air bubbled through cyanide solution in which platinized powdered TiO₂ is suspended. Light from either artificial source or natural Sunlight irradiates. Experiments demonstrated this technique effective in reducing concentration of cyanide to levels well below those achieved by other methods. Results suggest effective and inexpensive method for oxidizing cyanide in industrial wastewaters.

B85-10076

ETHYNYL-TERMINATED ESTER OLIGOMERS AND POLYMERS

P. M. HERGENROTHER and S. J. HAVENS (Kentron International, Inc.)

Jun. 1985

LAR-13118

Vol. 9, No. 1, P. 107

Polyesters of various molecular weights terminated with ethynyl groups. As ethynyl-terminated polyesters are exposed to elevated temperatures, thermally induced reaction of ethynyl groups occurs to provide cross-linking and chain extension. Reaction raises use temperature of polymer and greatly improves resistance to solvents. New materials produced by this process potentially useful as adhesives, composite matrices, solvent-resistant coatings, membranes, and films.

B85-10077

STATIC-SUPPRESSING OPTICAL PAINT

M. M. BIRNBAUM (CALTECH), E. C. METZLER (CALTECH),

and E. L. CLELAND (CALTECH)

Jun. 1985

NPO-15992

Vol. 9, No. 1, P. 107

Electrically conductive flat black paint adheres well to magnesium, aluminum, fiberglass, and other materials. Paint absorbs stray light in optical instruments while preventing buildup of electrostatic fields and arcing. Paint consists of primer and topcoat, both containing electrically conductive carbon-black powder. Primer two-part epoxy base, and topcoat polyurethane base.

B85-10078

IMPROVING EMITTANCE OF HIGH-TEMPERATURE INSULATING TILE

E. R. GZOWSKI (Lockheed Missiles & Space Company, Inc.)

Jun. 1985

MSC-20714

Vol. 9, No. 1, P. 108

Simple addition to ceramic insulating tiles provides backup properties that minimize transfer of heat through tiles when their surfaces become damaged. Addition of 3 percent by weight of 320 or 600-grit silicon carbide powder to ceramic during production results in impregnated tile material that resists overheating. Silicon carbide increases emittance and decreases transmittance of ceramic.

B85-10079

RUBBERIZED, BROMINATED EPOXIES

W. GILWEE, D. KOURTIDES, J. PARKER, and Z. NIR (National Research Council)

Jun. 1985

ARC-11427

Vol. 9, No. 1, P. 109

Graphite/epoxy composite materials made with resins containing bromine and rubber additives. New composites tougher and more resistant to fire. Flame resistance increased by introducing bromine via commercial brominated flame-retardant polymeric additives.

B85-10080

WATERPROOFING AGENTS FOR SILICA TILES

H. N. NAKANO (Lockheed Missiles & Space Co., Inc.), Y. D. IZU (Lockheed Missiles & Space Co., Inc.), and E. N. YOSHIOKA (Lockheed Missiles & Space Co., Inc.)

Jun. 1985

MSC-20364

Vol. 9, No. 1, P. 109

Waterproofing agent methyltrimethoxysilane applied to silica thermal insulation tiles in simple vapor-deposition process. Other waterproofing agents in same series include methylsiloxane and hexamethyldisilazane. Originally developed for insulating tiles for spacecraft, agents also find uses in roofing tiles, insulation for buildings or solar-energy systems, or solar reflectors.

B85-10081

PREPARATION AND CHARACTERIZATION OF HGXCD1-XTE

J. BROERMAN (McDonnell Douglas Corp.), B. MORRIS (McDonnell Douglas Corp.), and P. MESCHTER (McDonnell Douglas Corp.)

Jun. 1985

MFS-27037

Vol. 9, No. 1, P. 110

Experimental studies of growth of Hg_xCd_{1-x}Te important as infrared detector material. Studies part of greater effort to determine effects of processing conditions on chemical, physical, and electrical properties of this material.

B85-10082

STRENGTH OF GRAPHITE/METAL COMPOSITE LAP JOINTS

A. ELLISON (Lockheed Missiles & Space Co., Inc.) and D. KINTIS (Lockheed Missiles & Space Co., Inc.)

Jun. 1985

MFS-27030

Vol. 9, No. 1, P. 110

Report presents results of tests on fastened lap joints between strips of graphite/aluminum and graphite/magnesium composites. Goal of test program was to

establish practical load range and effect of such joint parameters as load direction relative to graphite fiber direction, edge distance, fastener diameters, and lateral spacing as function of net section efficiency.

B85-10083

PREDICTING EFFECTS OF IMPACTS ON CONFINED EXPLOSIVES

C. K. CHAN (CALTECH)

Jun. 1985

NPO-16258

Vol. 9, No. 1, P. 111

Study aimed at improving safety of explosive storage examined relationship between small-scale experiments and actual explosions. Object of study to develop scaling laws that eliminate need for full-scale explosion tests and reduce need for small-scale tests. Results of study make it possible to predict explosive behavior from small tests and numerical simulation.

B85-10084

FURTHER TESTS OF 38 BALL-BEARING GREASES

E. MCMURTREY

Jun. 1985 See Also NASA TM-82533(N83-31020/NSP)

MFS-27043

Vol. 9, No. 1, P. 111

Interim report presents recent results in program of long-term testing of ball-bearing greases in vacuum, oxidizing, and otherwise hostile environments. Class of lubricants based on perfluoroalkylpolyether (PFPE) gave best results in vacuum operation in both 1-year and 5-year tests.

B85-12192

FILAMENT GUIDES FOR SILICON-RIBBON GROWTH

A. D. MORRISON (Caltech)

Oct. 1985

NPO-16306

Vol. 9, No. 2, P. 88

Contamination reduced in modified growth system. In Silicon-ribbon growth apparatus, capillary filament guides are integral parts of crucible, extending from bottom to top of melt. Addition of guides expected to result in better thermal control of growth process and higher silicon purity.

B85-10193

LIGHTWEIGHT ELECTRICAL INSULATION

J. E. SCHROEDER (Caltech)

Oct. 1985

NPO-16165

Vol. 9, No. 2, P. 92

Hollow plastic spheres expanded and fused together. Hollow, gasfilled plastic spheres piled in mold. Heating in vacuum softens and expands spheres, forcing them together into nearly regular hexagonal close packing. Foam used as lightweight, electrically insulating material in place of solid ceramic, glass, or polymer. Padding to protect against mechanical shocks another application for such dense, regular foam.

B85-10194

DIFFUSELY REFLECTING PAINTS CONTAINING TFE

M. C. SHAI and J. B. SCHUTT

Oct. 1985

GSC-12883

Vol. 9, No. 2, P. 92

Highly reflective, diffused coatings developed by incorporating polytetrafluoroethylene (TFE) pigment with alcohol-soluble binders. Alcohol and binder mixed together in blender before adding TFE. TFE preferably outgassed in mechanical-pump vacuum for typical interval of 4 hours before adding to liquid. Like wetting agent, vacuum treatment helps to prevent clumping of TFE and eases dispersion throughout mixture. Mixture blended for 3 to 5 minutes before used. Coatings useful on reflectance-standard surfaces for calibrating radiometric instruments in both laboratory and field. Paints washable and usable as optical reference surfaces.

B85-10195

PARAMAGNETIC PRECIPITATES MAY RAISE SUPER-CURRENT

E. W. COLLINGS (Batelle Columbus)

04 MATERIALS

Oct. 1985

MFS-25925

Vol. 9, No. 2, P. 94

Addition of Mn to Ti/Nb superconducting alloy increases critical current. Adding Mn to Ti/Nb alloy has little effect on major superconducting phase, but confers strong paramagnetic susceptibility on alpha-phase particles. beta-phase particles become stronger flux pinners, resulting in increase in critical current.

B85-10196

INTERCALATED-CARBON LOW-RESISTIVITY FIBERS

A. H. YAVROUIAN (Caltech) and J. A. WOOLLAM (Caltech)

Oct. 1985

NPO-16307

Vol. 9, No. 2, P. 94

Experiments show feasibility of making lightweight, electrically conductive fibers from graphite intercalation compounds. Fibers thermally stable in air up to 100 degrees C. These materials used as ingredients in composite enclosures for electronic equipment, especially where such equipment must be both light in weight and electrically conductive for electrostatic drainage or radio-frequency suppression.

B85-10197

ION IMPLANTATION IMPROVES BEARING-SURFACE PROPERTIES

M. S. MISRA (Martin Marietta Corp.) and F. M. KUSTAS (Martin Marietta Corp.)

Oct. 1985

MFS-25995

Vol. 9, No. 2, P. 95

Selected ions fired into rolling elements to increase resistance to rolling-contact fatigue. Mask strips confine implantation to 105 degree arcs on cylindrical surfaces. Specimens kept cool by copper block through which refrigerant is circulated. Implanting nitrogen or titanium ions in metals improves resistance to fatigue, corrosion, and wear without altering bulk properties. Unlike such surface treatments as conventional nitriding, conventional carburizing, and coating, ion implantation is low-temperature process, requires no finishing operations, and produces highly-alloyed surface layer. Implantation process also helps conserve such strategic materials as chromium and cobalt by using them only where needed.

B85-10198

MICROFISSURING IN ELECTRON-BEAM-WELDED NICKEL ALLOY

J. NUNES, A.C.

Oct. 1985 See Also N83-29356

MFS-27041

Vol. 9, No. 2, P. 96

Mathematical model developed for microfissuring of commercial nickel alloy during electron-beam welding. Number of measured microfissures per unit length of weld plotted against excess power calculated by computer model. Excess power that above level likely to produce microfissures. In agreement with model, measured microfissures increase at rate of 4.5 per inch (1.8 per centimeter) per excess kilowatt.

B85-10199

MEASURING HYDROGEN CONCENTRATIONS IN METALS

M. D. DANFORD

Oct. 1985

MFS-27020

Vol. 9, No. 2, P. 96

Commercial corrosion-measurement system adapted to electrochemical determination of hydrogen concentrations in metals. New technique based on diffusion of hydrogen through foil specimen of metal. In sample holder, hydrogen produced on one side of foil, either by corrosion reaction or by cathodic current. Hydrogen diffused through foil removed on other side by constant anode potential, which leads to oxidation of hydrogen to water. Anode current is measure of concentration of hydrogen diffusing through foil. System used to study hydrogen uptake, hydrogen

elimination by baking, effect of heat treatment, and effect of electroplating on high-strength steels.

B85-10200

PRODUCTION PROCESS FOR STRONG, LIGHT CERAMIC TILES

G. R. HOLMQUIST (Lockheed Missiles & Space Co., Inc.), E. R. CORDIA (Lockheed Missiles & Space Co., Inc.), and R. S. TOMER (Lockheed Missiles & Space Co., Inc.)

Oct. 1985

MSC-20802

Vol. 9, No. 2, P. 97

Proportions of ingredients and sintering time/temperature schedule changed. Production process for lightweight, high-strength ceramic insulating tiles for Space Shuttle more than just scaled-up version of laboratory process for making small tiles. Boron in aluminum borosilicate fibers allows fusion at points where fibers contact each other during sintering, thereby greatly strengthening tiles structure.

B85-10201

IMPROVED ELECTRODES FOR LITHIUM CELLS

S. P. S. YEN (Caltech), S. SURAMPUDI (Caltech), B. J. CARTER (Caltech), and R. B. SOMOANO (Caltech)

Oct. 1985

NPO-16397

Vol. 9, No. 2, P. 98

Chlorinated elastomeric binder improves cell mechanical and electrical characteristics. Substituted for PTFE binder, chlorinated polyethylene rubber allows high cell-discharge rates and higher stored energy per unit volume. In addition, it costs about one-eighth as much as PTFE.

B85-10202

FLUIDIZED-BED PARTICLES SCAVENGE SILICON FINES

G. C. HSU (Caltech), N. ROHATGI (Caltech), R. LUTWACK (Caltech), and R. HOGLE (Caltech)

Oct. 1985

NPO-16034

Vol. 9, No. 2, P. 98

Waste reduced, and silicon production rate improved. In new process silicon formed by thermal decomposition of SiH4. Part of silicon formed on silicon seed particles as result of surface chemical reaction. However, silicon formed by homogeneous reaction in gas phase tends to form aggregates of silicon atoms, which appear as fine particles (like dust). Believed that scavenging action of seed particles enables large fraction fines to be incorporated onto seed surface. This mode of growth confirmed by electron microscopy photographs.

B85-10203

BLOWING POLYMER BUBBLES IN AN ACOUSTIC LEVITATOR

M. C. LEE (Caltech)

Oct. 1985

NPO-16212

Vol. 9, No. 2, P. 100

In new manufacturing process, small gas-filled polymer shells made by injecting gas directly into acoustically levitated prepolymer drops. New process allows sufficient time for precise control of shell geometry. Applications foreseen in fabrication of deuterium/tritium-filled fusion targets and in pharmaceutical coatings. New process also useful in glass blowing and blow molding.

B85-10204

MAGNETRON-SPUTTERED AMORPHOUS METALLIC COATINGS

A. P. THAKOOR (Caltech), M. MEHRA (Caltech), and S. K. KHANNA (Caltech)

Oct. 1985

NPO-16221

Vol. 9, No. 2, P. 100

Amorphous coatings of refractory metal/metalloid-based alloys deposited by magnetron sputtering provide extraordinary hardness and wear resistance. Sputtering target fabricated by thoroughly mixing powders of tungsten, rhenium, and boron in stated proportions and pressing at 1,200 degrees C and 3,000 lb/in. to second power (21

MPa). Substrate lightly etched by sputtering before deposition, then maintained at bias of - 500 V during initial stages of film growth while target material sputtered onto it. Argon gas at pressure used as carrier gas for sputter deposition. Coatings dense, pinhole-free, extremely smooth, and significantly resistant to chemical corrosion in acidic and neutral aqueous environments.

**B85-10205
DETERMINING FIBER ORIENTATION IN GRAPHITE-REINFORCED COMPOSITES**

J. G. DANIELS, I. LEDBETTER, FRANKE., J. M. CLEMON, B. G. PENN, and W. T. WHITE

Oct. 1985

MFS-28032

Vol. 9, No. 2, P. 101

Orientation of fibers in graphite-fiber-reinforced plastics easily determined with new method. Materials scientists thus ensure that fibers, usually not visible after graphite/plastic composite has been cured, properly oriented in test specimens and test results accurately represent the characteristics of composite. Method based on fact that continuous graphite fibers embedded in cured polymer matrix actually parallel conductors. Thus, resistance measured across laminate is at minimum when probes of ohmmeter connected to opposite ends of fibers.

**B85-10206
PREDICTING THE FATIGUE LIFE OF STRUCTURES**

P. M. BESUNER (Failure Analysis Associates), D. O. HARRIS (Failure Analysis Associates), J. M. THOMAS (Failure Analysis Associates), D. E. ALLISON (Failure Analysis Associates), J. M. BANNANTINE (Failure Analysis Associates), S. B. BROWN (Failure Analysis Associates), C. S. DAVIS (Failure Analysis Associates), G. A. DERBALIAN (Failure Analysis Associates), J. W. EISCHEN (Failure Analysis Associates), G. F. FOWLER (Failure Analysis Associates) et al

Oct. 1985

MFS-27049

Vol. 9, No. 2, P. 102

Report reviews fracture-mechanics technology for predicting life expectancy of structural components subjected to cyclic loads. Report covers analytical tools for modeling and forecasting subcritical fatigue-crack growth in structures. It emphasizes use of tools in practical, day-to-day problems of engineering design, development, and decision-making.

**B85-10207
CORROSIVE EFFECTS OF BURNING FUELS**

J. BELLAN (Caltech) and S. ELGHOBASHI (Caltech)

Oct. 1985

NPO-16345

Vol. 9, No. 2, P. 103

Literature synthesized to develop corrosion predictions for unconventional fuels. Report presents studies of probable corrosive effects of such unconventional fuels as liquefied coal. Report prepared by analyzing probable composition of fuels when they come into wide use, identifying important compounds, and searching literature for information about corrosion problems associated with compounds in environments like those in industrial and commercial boilers and furnaces.

**B85-10208
SYNTHETIC ORGANIC MATERIALS IN NUCLEAR POWERPLANTS**

F. L. BOUQUET (Caltech) and J. W. WINSLOW (Caltech)

Oct. 1985

NPO-16424

Vol. 9, No. 2, P. 103

Report aids plant designers and qualification engineers in ensuring that organic materials in nuclear powerplants will perform satisfactorily in such safety-related equipment as insulation on motor windings, pump diaphragms, motor and pump lubricants, and pump seals and gaskets. Report provides information for service that may include both mild and harsh nuclear environments.

**B85-10209
DEGRADATION OF DIELECTRICS IN SPACE**

F. L. BOUQUET (Caltech)

Oct. 1985

NPO-16003

Vol. 9, No. 2, P. 103

Effects of radiation (principally, electrons and protons) on dielectric materials summarized in report. Report based on radiation tests of optical coatings, temperature-control coatings, adhesives, radomes, thermal insulators, and light-control surfaces. Materials are primarily polymers and metal/organic coatings.

**B85-10210
PLASMA DEPOSITION OF DOPED AMORPHOUS SILICON**

H. F. CALCOTE

Oct. 1985

NPO-14955; NPO-14956

Vol. 9, No. 2, P. 104

Pair of reports present further experimental details of investigation of plasma deposition of films of phosphorous-doped amorphous silicon. Probe measurements of electrical resistance of deposited films indicated films not uniform. In general, it appeared that resistance decreased with film thickness.

**B85-10211
BONDING SOLAR-CELL MODULES**

D. R. COULTER (Caltech), E. F. CUDDIHY (Caltech), and E. F. PLUEDDEMANN (Caltech)

Oct. 1985 See Also N84-22008

NPO-16399

Vol. 9, No. 2, P. 104

Status of research program on chemical bonding for solar-cell arrays subject of 57-page report. Program aimed at identifying, developing, and validating weather-stable chemical bonding promoters. Materials key to ensuring long life in encapsulated photovoltaic modules for electric-power generation. To be cost-effective, modules must hold together for at least 20 years, reliably resisting delamination and separation of component materials

**B85-10212
MODELING A TRANSIENT CATALYTIC COMBUSTOR**

J. S. TIEN (Case Western Reserve University)

Oct. 1985

LEW-13723

Vol. 9, No. 2, P. 104

Transient model of monolith catalytic combustor presented in report done under NASA/DOE contract. Model assumes quasi-steady gas phase and thermally 'thin' solid. In gas-phase treatment, several quasi-global chemical reactions assumed capable of describing CO and unburnt hydrocarbon emissions in fuel-lean operations. In steady-state computation presented, influence of selected operating and design parameters on minimum combustor length studied. When fast transient responses required, both steady and unsteady studies made to achieve meaningful compromise in design.

**B85-10213
PLASTIC AND FAILURE ANALYSIS OF COMPOSITES**

C. A. BIGELOW and W. S. JOHNSON

Oct. 1985

LAR-13183

Vol. 9, No. 2, P. 105

Three-dimensional finite-element computer program called PAFAC (Plastic and Failure Analysis of Composites) developed for elastic/plastic analysis of fiber-reinforced composite materials and structures. PAFAC written in FORTRAN IV for batch execution. Particularly suited for analyzing laminated metal-matrix composites.

**B85-10214
EXHAUST EFFLUENT DIFFUSION MODEL**

J. R. BJORKLUND (H. E. Cramer Co., Inc.), R. K. DUMBAULD (H. E. Cramer Co., Inc.), C. S. CHENEY (H. E. Cramer Co., Inc.), and H. V. GEARY (H. E. Cramer Co., Inc.)

Oct. 1985

04 MATERIALS

MFS-25940 Vol. 9, No. 2, P. 105

Rocket Exhaust Effluent Diffusion Model (REEDM) predicts concentrations, dosages, and depositions downwind from normal and abnormal launches of rocket vehicles at NASA's Kennedy Space Center. REEDM written in FORTRAN IV for interactive execution.

B85-10330
TROUGH COATING SOLAR CELLS WITHOUT SPILL-OVER

J. D. HEAPS (Honeywell, Inc.)
Jan. 1986

NPO-15313 Vol. 9, No. 3, P. 85

Problem with trough coating of silicon on ceramic - spillover of molten silicon - overcome by combination of redesigned heaters and tiltable trough. Modifications make it possible to coat virtually any length of ceramic with film of solar-cell-grade silicon. Previously, maximum length coated before spillover occurred was 2 inches (5.1 cm).

B85-10331
REDUCING STRESS-CORROSION CRACKING IN BEARING ALLOYS

N. E. PATON (Rockwell International Corp.), D. P. DENNIES (Rockwell International Corp.), and J. B. LUMSDEN (Rockwell International Corp.)
Jan. 1986

MFS-19948 Vol. 9, No. 3, P. 86

Resistance to stress-corrosion cracking in some stainless-steel alloys increased by addition of small amounts of noble metals. 0.75 to 1.00 percent by weight of palladium or platinum added to alloy melt sufficient to improve properties of certain stainless steels so they could be used in manufacture of high-speed bearings.

B85-10332
EPOXY/FLUOROETHER COMPOSITES
R. W. ROSSER and M. S. TAYLOR (San Jose State University)
Jan. 1986

ARC-11418 Vol. 9, No. 3, P. 86

Composite materials made from unfilled and glass-fiber-reinforced epoxy toughened by copolymerization with elastomeric prepolymers of perfluoroalkyl ether diacyl fluoride (EDAF). Improved properties due to hydrogen bonding between rubber phase and epoxy matrix, plus formation of rubberlike phase domains that molecularly interpenetrate with epoxy matrix. With optimum rubber content, particle size, and particle shape, entire molecular structure reinforced and toughened. Improved composites also show increased failure strength, stiffness, glass-transition temperature, and resistance to water.

B85-10333
IMIDE CYCLOTRIPOSPHAZENE/HEXAFLUOROISOPROPYLIDENE POLYMERS

G. M. FOHLEN and J. A. PARKER
Jan. 1986

ARC-11428 Vol. 9, No. 3, P. 88

Useful physical and chemical properties observed in compounds obtained by thermally-induced melt polymerization of maleimido-phenoxy cyclotriphosphazenes linked through hexafluoroisopropylidene-dipthalimide groups. Polymers exhibit high strength, high thermal stability, and high char yields, and appear to be excellent candidates for fabricating composite materials.

B85-10334
MEASURING CARRIER LIFETIME IN GAAS BY LUMINESCENCE

O. VON ROOS (Caltech)
Jan. 1986

NPO-16337 Vol. 9, No. 3, P. 89

Luminescence proposed as nondestructive technique for measuring Shockley-Read-Hall (SRH) recombination lifetime GaAs. Sample irradiated, and luminescence escapes

through surface. Measurement requires no mechanical or electrical contact with sample. No ohmic contacts or p/n junctions needed. Sample not scrapped after tested.

B85-10335
RESIN POWDER SLURRY PROCESS FOR COMPOSITE FABRICATION

R. A. PIKE (United Technologies Corp.)
Jan. 1986

LAR-13106 Vol. 9, No. 3, P. 90

Potentially useful process for fabrication of fiber-reinforced resin-matrix composites is powder slurry technique. Applicability of technique demonstrated using powdered resin made from thermoplastic polyimide LaRC/TPI (thermoplastic polyimide). Use of process circumvents need for such high-cost organic solvents as N-methylpyrrolidinone and diglyme (diglycol methyl ether). Two basic slurries for LaRC/TPI powder investigated.

B85-10336
WATER-SOLUBLE THERMOPLASTIC POLYIMIDES

R. A. PIKE (United Technologies Corp.)
Jan. 1986

LAR-13105 Vol. 9, No. 3, P. 90

Several thermoplastic polyimide resins that show potential as matrix resins developed. Number of processes for composite fabrication evaluated, including powder processing, which involves deposition of resin powder on graphite fiber from nonresin-solvent slurry. Although powder slurry approach is viable, use of solvent system more amenable with current prepreg manufacturing methods.

B85-10337
MAGNETRON SPUTTERING DEPOSITS CORROSION-RESISTANT ALLOY

S. K. KHANNA (Caltech), A. P. THAKOOR (Caltech), and R. M. WILLIAMS (Caltech)
Jan. 1986

NPO-15928 Vol. 9, No. 3, P. 92

Dense, amorphous, metallic film resists corrosion attack by acid. Coatings thermally stable up to 800 degrees C and made corrosion resistant by proper choice of sputtering deposition conditions. Protective, corrosion-resistant coatings applied to process equipment that comes in contact with aqueous, neutral, or acidic solutions in chemical, petroleum, and paper industries, in wastewater treatment, and in heat exchangers.

B85-10338
CALCULATING CHARGE TRANSPORT IN SEMICONDUCTORS

C. E. BYVIK, A. M. BUONCRISTIANI (Christopher Newport College), and J. THOMCHICK (Pennsylvania State University)
Jan. 1986

LAR-13201 Vol. 9, No. 3, P. 92

Method, called flux method, improvement over conventional methods, easy to use, and applies in operating regime not accessible to conventional macroscopic methods. Key concept of flux method follows behavior of particle flux rather than concentration of particles. Method not subject to limitations that follow from local or infinitesimal analysis.

B85-10339
DAMPING MELT CONVECTION WITH A MAGNETIC FIELD

R. G. PIRICH (Grumman Aerospace Corp.) and J. L. DECARLO (Grumman Aerospace Corp.)
Jan. 1986

MFS-28040 Vol. 9, No. 3, P. 93

Application of 3-kG magnetic field reduces thermal and solutal convection in Bi/MnBi melt in Bridgman-Stockbarger (moving-vertical-thermal-gradient) furnace operating in normal gravitational field. Resulting Bi/MnBi alloy samples had properties similar to samples grown under nearly zero gravity. New technique proves useful in grow-

ing more uniform, defect-free semiconductor materials from such other electrically conductive melts.

B85-10340
PURIFYING WATER BY IMBIBITION
E. A. LAWTON (Caltech)

Jan. 1986

NPO-16419

Vol. 9, No. 3, P. 94

Concept for purifying water uses absorbent material to remove organic substances. Entire bulk of material employed, not just surface. Proposed purification process uses inexpensive equipment and low energy. Material is methyl acrylate polymer. Material cheap and regenerated by rinsing with methanol or by allowing absorbed compounds to evaporate from it.

B85-10341
EXTRACTING SILICON PRODUCT FROM FLUIDIZED-BED REACTORS

G. C. HSU (Caltech), N. K. ROHATGI (Caltech), and A. D. MORRISON (Caltech)

Jan. 1986

NPO-16385

Vol. 9, No. 3, P. 96

Silicon particles continuously removed from bottom of fluidizedbed reactor when grown to large size. In reactor, silane (SiH₄) flows through bed of small silicon seed particles at temperature of 650 degrees to 700 degrees C. Silane decomposes into silicon vapor and hydrogen gas, and vapor deposits as solid on seed particles. With withdrawal system, reactor operates continuously.

B85-10342
PRODUCING SILICON CARBIDE FOR SEMICONDUCTOR DEVICES

G. C. HSU (Caltech) and N. K. ROHATGI (Caltech)

Jan. 1986

NPO-16391

Vol. 9, No. 3, P. 103

Processes proposed for production of SiC crystals for use in semiconductors operating at temperatures as high as 900 degrees C. Combination of new processes produce silicon carbide chips containing epitaxial layers. Chips of SiC first grown on porous carbon matrices, then placed in fluidized bed, where additional layer of SiC grows. Processes combined to yield complete process. Liquid crystallization process used to make SiC particles or chips for fluidized-bed process.

B85-10343
SYNTHESIS OF METAL PHTHALOCYANINE SHEET POLYMERS

B. N. ACHAR, G. M. FOHLEN, and J. A. PARKER

Jan. 1986

ARC-11405

Vol. 9, No. 3, P. 104

New method for synthesizing metal phthalocyanine tetracarboxylic acids (MPTCA's) yields high purity end product. In addition, high-purity metal phthalocyanine sheet polymers synthesized from compounds. Monomer formed into sheet polymer by heating. Units of polymer linked in manner similar to phenyl-group linkages in biphenyl. Conjugation extends throughout macromolecule, thereby increasing delocalization of π -electrons. Increases conductivity and thermal stability of polymer.

B85-10344
PREDICTING THE CYCLIC RESPONSE OF HIGH-TEMPERATURE MATERIALS

V. MORENO (United Technologies Corp.)

Jan. 1986 See Also (N83-21390)

LEW-14032

Vol. 9, No. 3, P. 105

Simplified analytical procedure for estimating local stress/strain response in high-temperature structural component developed. Simplified procedure relies on assumption local inelastic response in high-temperature structure constrained by surrounding elastic material. Procedure assumes local response composed of elastic, time-independent

plastic, and creep components. Conventional yield surface concept used to determine onset of plastic action.

B85-10345
PROCESS FOR NONEQUILIBRIUM TERNARY ALLOYS
R. LUTWACK (Caltech)

Jan. 1986

NPO-16226

Vol. 9, No. 3, P. 105

Proposed metallurgical process yields amorphous ternary alloys of any range of desired compositions. Process produces homogenous alloys even when proportions of constituent metals are not those that exist in equilibrium at solidification temperature. Such alloys are well suited to use in gas turbines and advanced engines.

B85-10346
STUDYING CRYSTAL GROWTH WITH THE PELTIER EFFECT

D. J. LARSON JR. (Grumman Aerospace Corp.), B. DRES-SLER (Grumman Aerospace Corp.), R. P. SILBERSTEIN (Grumman Aerospace Corp.), and W. J. POIT (Grumman Aerospace Corp.)

Jan. 1986

MFS-28041

Vol. 9, No. 3, P. 106

Peltier interface demarcation (PID) shown useful as aid in studying heat and mass transfer during growth of crystals from molten material. In PID, two dissimilar 'metals' solid and liquid phases of same material. Current pulse passed through unidirectionally solidifying sample to create rapid Peltier thermal disturbance at liquid/solid interface. Disturbance, measured by thermocouple stationed along path of solidification at or near interface, provides information about position and shape of interface.

B85-10347
PLASMA-SPRAYED COATINGS ON POROUS SURFACES
C. H. LEIBERT

Jan. 1986

LEW-13450

Vol. 9, No. 3, P. 107

Need for combining benefits of duplex thermal-barrier coatings with film cooling on gas-turbine vanes and blades stimulated development of improved method for plasma spraying these coatings. Method reduces blocking of holes by plasma-sprayed material and at same time reduces base-metal oxidation during coating operation. Features provide potential for increased engine efficiency and power, reduced fuel consumption, use of less costly materials or construction procedures, and extended life and durability.

B85-10348
PHTHALOCYANINE TETRAAMINE EPOXY-CURING AGENTS

G. M. FOHLEN, B. N. ACHAR, and J. A. PARKER

Jan. 1986

ARC-11424

Vol. 9, No. 3, P. 107

Tough fire- and chemical-resistant epoxies produced by using metalphthalocyanine tetraamines (MPT's) of copper, cobalt, or nickel as curing agents. Synthesis of MPT's commercially realizable and gives pure compounds with almost 90-percent yield. Synthesis applicable for metals with atomic radii of about 1.35 angstroms, including Cu, Co, Ni, Zn, Fe, Pt, Al, and V. Possible to use metal phthalocyanines to cure epoxy resins in homogeneous reaction.

B85-10349
IMPROVED JET-MILL SILICON GRINDER
E. R. COLLINS (Caltech)

Jan. 1986

NPO-16336

Vol. 9, No. 3, P. 108

Proposed refinement in jet-mill grinding of silicon reduces proportion of unusable, overly ground particles. Particles serve as seeds for growth of silicon from vapor. In new grinding apparatus, particle separator distinct from collision chamber. Particle collides only once before sorted for size. If proper size, extracted; if not, returned to chamber for another collision.

04 MATERIALS

B85-10350

MEASURING THERMAL DIFFUSIVITY OF MOLTEN SEMICONDUCTORS

R. CROUCH, L. HOLLAND, and R. E. TAYLOR (Purdue University)

Jan. 1986

MFS-28047

Vol. 9, No. 3, P. 110

Thermal diffusivity of molten and solid mercury cadmium telluride measured with aid of new apparatus. Knowledge gained from such measurements help efforts to grow high-quality single crystals of this semiconductor for use in infrared detectors. Without knowledge of thermal diffusivity, difficult to control growth rate of solid from molten material.

B85-10351

MELT-PRESSED FILMS OF INSOLUBLE SEMICRYSTALLINE POLYMERS

J. R. TYERYAR, B. J. JENSEN, and R. L. FOX

Jan. 1986

LAR-13212

Vol. 9, No. 3, P. 112

Technique known as 'melt pressing' produces films from solid, insoluble, semicrystalline polymers in less than 5 minutes. Amount of crystallinity and possibly final crystal structure of film controlled in process. Induction heating, using gapped toroidal core, melts sample. Toroidal core and capacitor form tuned circuit. Below induction heating toroid, layer of insulation prevents heat transfer from insoluble film to induction heating apparatus.

B85-10352

PROTECTIVE COATINGS FOR METALS

D. J. RUGGIERI and A. P. ROWE

Jan. 1986

KSC-11308

Vol. 9, No. 3, P. 113

Report evaluates protective coatings for metal structures in seashore and acid-cloud environments. Evaluation result of study of coating application characteristics, repair techniques, and field performance. Products from variety of manufacturers included in study. Also factory-coated panels and industrial galvanized panels with and without topcoats.

B85-10353

DISCOLORATION OF POLYVINYL BUTYRAL

Q. KIM (Caltech) and A. SHUMKA (Caltech)

Jan. 1986

NPO-16411

Vol. 9, No. 3, P. 113

Report presents results of study of discoloration in polyvinyl butyral (PVB). Clear PVB gradually turns yellowish brown in simulated-aging tests and outdoor environmental tests. Discoloration severely reduces solar-cell output. Using methods of modern analytical chemistry - transmission absorption, Fourier transform infrared absorption, atomic absorption spectroscopy, and scanning-electron microscopy - study uncovered major cause of yellowing.

B85-10354

TESTS OF ZINC RICH ANTICORROSION COATINGS

J. D. MORRISON, W. J. PATON, and A. ROWE

Jan. 1986

KSC-11309

Vol. 9, No. 3, P. 114

Condition of zinc-rich anticorrosion coatings after 10 years of exposure discussed in status report, which follows up on 18-month study of anticorrosion coatings on steel started in 1971. Test panels with various coatings mounted on racks on beach and checked periodically. Of panels with inorganic zinc-rich coatings, only one slightly rusted. Panels were in such good condition they were returned to beach for more exposure.

B85-10355

CHARACTERIZING SEMICONDUCTOR ALLOYS FOR INFRARED SENSORS

B. S. L. LEHOCZKY (McDonnell Douglas Research Laboratories), F. R. SZOFRAN (McDonnell Douglas Research Laboratories), and B. G. MARTIN (McDonnell Douglas Research Laboratories)

Jan. 1986

MFS-27059

Vol. 9, No. 3, P. 115

Report presents results of continuing program aimed at characterizing mercury/cadmium/tellurium alloys and eventually developing improved methods of preparing alloys for use as infrared sensors. Work covered by report includes series of differential thermal analysis (DTA) measurements of alloy compositions with x varied from 9 to 1 in 0.1 increments.

B85-10484

MEASURING RESISTIVITIES OF SMALL FIBERS

J. DANIELS, J. M. CLEMONS, F. E. LEDBETTER, B. G. PENN, and D. J. CROUSE (Tennessee Technological University)

Mar. 1986

MFS-28077

Vol. 9, No. 4, P. 100

Technique for measuring electrical resistivities of fibers of graphite, silicon carbide/silicon nitride mixture, and other materials used in composites simple, accurate, and reproducible. Suitable for monofilament fibers with diameters of about 10 to 50 micrometers. Also adapted to two fiber strands.

B85-10485

SOLVENT-RESISTANT, THERMALLY STABLE POLY(CARBONATE-IMIDES)

T. L. ST. CLAIR, N. T. WAKELYN, S. MAUDGAL (National Research Council), and J. R. PRATT (Mississippi University for Women)

Mar. 1986

LAR-13292

Vol. 9, No. 4, P. 102

New polymers and copolymers based on polyimide backbone with carbonate moieties exhibit high temperature capability. Because of carbonate unit, many of these materials also exhibit high order or crystallinity. All of new imidecontaining polymers insensitive to acetone. New poly(carbonate-imide) exhibits significantly increased temperature resistance and shows less sensitivity to solvents than commercial polycarbonates.

B85-10486

CHROMIUM IONS IMPROVE MOISTURE RESISTANCE OF EPOXY RESINS

A. K. ST. CLAIR, T. L. ST. CLAIR, D. M. STOAKLEY, J. J. SINGH, and D. R. SPRINKLE

Mar. 1986

LAR-13226

Vol. 9, No. 4, P. 104

Broad spectrum of thermosetting epoxy resins used on commercial and military aircraft, primarily as composite matrices and adhesives. In new technique, chromium-ion containing epoxy with improved resistance to moisture produced where chromium ions believed to prevent absorption of water molecules by coordinating themselves to hydroxyl groups on epoxy chain. Anticipated that improved epoxy formulation useful as composite matrix resin, adhesive, or casting resin for applications on commercial and advanced aircraft. Improvement made without sacrifice in mechanical properties of polymer.

B85-10487

FAST-RESPONSE OXYGEN-MONITORING AND CONTROL SYSTEM

J. J. SINGH, W. T. DAVIS, and R. L. PUSTER

Mar. 1986 See Also (N84-11460)

LAR-13257

Vol. 9, No. 4, P. 105

Oxygen sensor is Y2O3-stabilized ZrO2 ceramic disk maintained at 843 degrees C. Overall system response time reduced to about 0.2 second, equal to or less than 1 percent of tunnel run time. When test gas oxygen concentration differs from normal air concentration by 25 percent or more, alarm sounds, and emergency tunnel shutdown signal operates. New ZrO2 sensors intended for hypersonic-vehicle testing.

B85-10488
MEASURING THERMOELECTRIC PROPERTIES AUTOMATICALLY

A. CHMIELEWSKI (Caltech) and C. WOOD (Caltech)

Mar. 1986

NPO-16507

Vol. 9, No. 4, P. 106

Microcomputer-controlled system speeds up measurements of Hall voltage, Seebeck coefficient, and thermal diffusivity in semiconductor compounds for thermoelectric-generator applications. With microcomputer system, large data base of these parameters gathered over wide temperature range. Microcomputer increases measurement accuracy, improves operator productivity, and reduces test time.

B85-10489
INSULATION BLANKETS FOR HIGH-TEMPERATURE USE

H. GOLDSTEIN, D. LEISER, P. M. SAWKO, H. K. LARSON, C. ESTRELLA, M. SMITH, and F. J. PITONIAK (U.S. Air Force)

Mar. 1986

ARC-11453

Vol. 9, No. 4, P. 107

Insulating blanket resists temperatures up to 1,500 degrees F (815 degrees C). Useful where high-temperature resistance, flexibility, and ease of installation are important - for example, insulation for odd-shaped furnaces and high-temperature ducts, curtains for furnace openings and fire control, and conveyor belts in hot processes. Blanket is quilted composite consisting of two face sheets: outer one of silica, inner one of silica or other glass cloth with center filling of pure silica glass felt sewn together with silica glass threads.

B85-10490
COLORLESS, TRANSPARENT, AROMATIC POLYIMIDE FILMS

A. K. ST. CLAIR, T. L. ST. CLAIR, K. S. EZZELL, and R. M. ELY

Mar. 1986

LAR-13351

Vol. 9, No. 4, P. 108

New process yields aromatic condensation polyimide films essentially colorless. Films between 90- and 100-percent transparent at visible wavelength of 500 nm. Optically transparent polyimide films made from variety of aromatic condensation polyimides. Range from very pale in color to colorless, compared to bright yellow color of conventional commercial aromatic polyimide film. Increased transparency achieved at no sacrifice in thermal stability, flexibility, toughness, or mechanical properties. These features extremely attractive as films or coating materials for aerospace applications or for any other applications where high optical transparency or thermal stability is required.

B85-10491
PHENOXY RESINS CONTAINING PENDENT ETHYNYL GROUPS

P. M. HERGENROTHER

Mar. 1986 See Also (N84-16338)

LAR-13222

Vol. 9, No. 4, P. 109

Ethynyl-containing phenoxy resins have excellent shelf life in solution or in bulk. Cured ethynyl-containing phenoxy resins offer lower moisture absorption, higher use temperatures, and better thermal stability over state-of-the-art cross-linked phenoxy resins. Depending upon cross-link density, cured ethynyl-modified phenoxy resins are solvent resistant but still thermoformable and relatively tough. Modified resins show potential for use as adhesives, composite matrices, solvent-resistant coatings, membranes, insulators, and films.

B85-10492
MICRONIZED-COAL BURNER FACILITY

F. D. CALFO and M. W. LUPTON

Mar. 1986

LEW-14131

Vol. 9, No. 4, P. 110

Micronized-coal (coal-in-oil mix) burner facility developed to fulfill need to generate erosion/corrosion data on series of superalloy specimens. In order to successfully operate gas turbine using COM, two primary conditions must be met. First, there must be adequate atomization of COM and second, minimization of coking of burner. Meeting these conditions will be achieved only by clean burning and flame stability.

B85-10493
COBALT IONS IMPROVE THE STRENGTH OF EPOXY RESINS

D. M. STOKLEY and A. K. ST. CLAIR

Mar. 1986 See Also (N84-13309)

LAR-13230

Vol. 9, No. 4, P. 111

Technique developed for improving mechanical strength of epoxy resins by adding cobalt ions in form of tris (acetylacetonato)cobalt (III) complex. Solid cast disks prepared from cobalt ion-containing epoxy resins tested for flexural strength and stiffness. Incorporation of cobalt ions into epoxies increased flexural strength of resins by 10 to 95 percent. Suitable resins for this technique include any liquid or solid TGMDA resins. Improved epoxy formulation proves useful as composite matrix resin, adhesive, or casting resin for applications on commercial and advanced aircraft.

B85-10494
ALKANE-BASED URETHANE POTTING COMPOUNDS

D. E. MORRIS

Mar. 1986 See Also (N83-34047)

MFS-27047

Vol. 9, No. 4, P. 112

New low viscosity urethanes easily mixed, molded, and outgassed. Alkane-based urethanes resist hydrolysis and oxidation and have excellent dielectric properties. Low-viscosity alkane-based urethane prepolymer prepared by one-step reaction of either isophorone diisocyanate or methyl-bis (4-cyclohexyl isocyanate) with hydrogenated, hydroxy-terminated polybutadiene (HTPBD).

B85-10495
HIGH-STRENGTH, LOW-SHRINKAGE CERAMIC TILES

W. H. WHEELER (Lockheed Missiles & Space Co., Inc.)

and J. F. CREEDON (Lockheed Missiles & Space Co., Inc.)

Mar. 1986

MSC-20654

Vol. 9, No. 4, P. 113

Addition of refractory fibers and whiskers to insulating tiles composed primarily of fibrous silica, such as those used on the skin of Space Shuttle orbiter, greatly improves properties. New composition suitable for lightweight, thermally-stable mirror blanks and as furnace and kiln insulation. Improved tiles made with current tile-fabrication processes. For given density, tiles containing silicon carbide and boron additives stronger in flexure than tiles made from silica alone. In addition, tiles with additives nearly immune to heat distortion, whereas pure-silica tiles shrink and become severely distorted.

B85-10496
RESEARCH FURNACE FOR CRYSTAL PREPARATION

R. K. CROUCH, A. L. FRIPP, JR., W. J. DEBNAM, JR., I. O. CLARK, J. M. ZWIENER (Marshall Space Flight Center), and F. M. CARLSON (Clarkson University)

Mar. 1986 See Also (N84-13211)

LAR-13302

Vol. 9, No. 4, P. 114

Three-zone furnace tested and characterized for preparation of lead-telluride (LTT) crystals. Tests show temperature in furnace controlled to obtain constant rate of movement of high-temperature isotherm down length of furnace. Temperature profiles accurately controlled by three independent heaters. Control software brings separate heaters to any desired temperature.

B85-10497
LIGHTWEIGHT PROTECTIVE GARMENTS

E. R. DU FRESNE (Caltech)

04 MATERIALS

Mar. 1986

NPO-16510

Vol. 9, No. 4, P. 115

Proposed garment material protects wearer from poisonous chemicals, bacteria, and radioactive particulates. Garment allows heat, moisture, and carbon dioxide to pass from inside to outside so wearer remains comfortable. Garment made of cotton fabric on which thin layer of polyacrylate rubber is deposited by calendaring or spraying. Lighter and cooler than existing protective garments. Polyacrylate rubber selected for garment material because it transmits water vapor and carbon dioxide at high rates.

B85-10498

ULTRASONIC MIXING OF EPOXY CURING AGENTS

W. T. HODGES (U.S. Army Structures Laboratory) and T. L. ST. CLAIR

Mar. 1986 See Also (N83-27018)

LAR-13307

Vol. 9, No. 4, P. 116

New ultrasonic mixing technique used to mix several curing agents/epoxy combinations. Major component of commercially available base epoxy resin used in tetraglycidylmethylenedianiline (TGMDA). In ultrasonic mixing system cup holds resin and curing agent during acoustic excitation. Samples placed in cup with top to ultrasonic horn forming bottom of cup. Ultrasonically treated until amber colored and transparent. Because ultrasonic agitation drives out entrapped air, degassing not necessary before cure.

B85-10499

ULTRA-HIGH-MOLECULAR-WEIGHT SI/PHENYLENE/SILOXANE POLYMERS

W. J. PATTERSON, N. H. HUNDLEY, and L. M. LUDWICK

Mar. 1986 See Also (N84-19564)

MFS-27065

Vol. 9, No. 4, P. 117

Elastomers having molecular weights above 1 million made by two-stage polymerization. Two-stage process proves far more successful than synthesis from reactive monomers. Process involves synthesis of silanoterminated prepolymer and subsequent extension of prepolymer chain with additional aminosilane monomer. Multistage method allows chain-extending monomer added in precise amounts between stages.

B85-10500

CAST IRON WITH HIGH CARBON CONTENT

P. A. CURRERI, J. C. HENDRIX (University of Alabama), and D. M. STEFANESCU (University of Alabama)

Mar. 1986

MFS-28014

Vol. 9, No. 4, P. 118

Method proposed for solidifying high-carbon cast iron without carbon particles segregating at upper surface. Solidification carried out in low gravity, for example on airplane flying free-fall parabolic trajectory. Many different microstructures obtained by proposed technique, and percentage by weight of carbon retained in melt much higher than at present.

B85-10501

BETA SILICON NITRIDE WHISKERS

R. J. HOLLIDAY (John Brown University) and P. J. SHLICHTA (Caltech)

Mar. 1986

NPO-16409

Vol. 9, No. 4, P. 118

Process for growing fibrous beta silicon nitride helps meet potentially great demand for silicon nitride ceramics. Ceramics have high tensile strength and resistance to thermal shock, which make them attractive choice for high-temperature engine parts. Process forms whiskers of strong, stable, heat-resistant material. Whiskers expected to find application as reinforcement in composite silicon nitride ceramic parts. Corklike material useful in present form for thermal barrier tiles. Process forms whiskers of strong, stable, heat-resistant material.

B85-10502

MECHANICAL DESIGN HANDBOOK FOR ELASTOMERS

M. DARLOW (Mechanical Technology, Inc.) and E. ZORZI (Mechanical Technology, Inc.)

Mar. 1986 See Also (N81-26461)

LEW-14160

Vol. 9, No. 4, P. 119

Mechanical Design Handbook for Elastomers reviews state of art in elastomer-damper technology with particular emphasis on applications of highspeed rotor dampers. Self-contained reference but includes some theoretical discussion to help reader understand how and why dampers used for rotating machines. Handbook presents step-by-step procedure for design of elastomer dampers and detailed examples of actual elastomer damper applications.

B85-10503

CONSTITUTIVE EQUATIONS OF AGING IN POLYMERS

S. T. J. PENG (Caltech)

Mar. 1986

NPO-16480

Vol. 9, No. 4, P. 120

Theoretical paper presents solutions of equations that describe polymeric aging. Solutions apply under such loading conditions as constant strain (stress relaxation), constant strain rate, and stress relaxation with sudden change of cross-link density. Theoretical models form framework for predicting chemomechanical aging behavior of elastomers and polymers.

B85-10504

SOLIDIFYING CAST IRON IN LOW GRAVITY

J. C. HENDRIX, P. A. CURRERI, and D. M. STEFANESCU

Mar. 1986

MFS-27069

Vol. 9, No. 4, P. 121

Report describes study of solidification of cast iron in low and normal gravity. Because flotation, sedimentation, and convection suppressed, alloys that solidify at nearly zero gravity have unusual and potentially useful characteristics. Study conducted in airplane that repeatedly flew along parabolic trajectories. Appears iron/carbon alloys made at low gravity have greater carbon content (as high as 5 to 10 percent) than those made of Earth gravity because carbon particles do not float to top of melt.

05 LIFE SCIENCES

B85-10085

VISION SCREENING BY COLOR PHOTOGRAPHY

R. JAYROE, J. R. RICHARDSON, J. KERR (Electro-Optics Consultants, Inc.), S. HAY (Electro-Optics Consultants, Inc.), and R. MCBRIDE (Alabama Institute for the Deaf & Blind)

Jun. 1985

MFS-25800

Vol. 9, No. 1, P. 112

Screening test developed for detecting a range of vision defects in eye, including common precursors to amblyopia. Test noninvasive, safe, and administered easily in field by operator with no medical training. Only minimal momentary cooperation of subject required. Thus, test shows promise for use with very young children. Test produces color-slide images of retinas of eyes under specially-controlled lighting conditions. Trained observer screens five children per minute.

B85-10086

COCULTURE PRODUCTION OF BUTANOL BY CLOSTRIDIUM BACTERIA

S. L. BERGSTROM (Oklahoma State University) and G. L. FOUTCH (Oklahoma State University)

Jun. 1985

NPO-16203

Vol. 9, No. 1, P. 113

Production of butanol by anaerobic fermentation of

sugars enhanced by use of two *Clostridium* species, one of which feeds on metabolic product of other. Renewed interest in fermentation process for making butanol stimulated by potential use of butanol as surfactant in enhanced oil recovery. Butanol also used as fuel or as chemical feedstock and currently produced synthetically from petroleum.

**B85-10087
EFFECT OF HYDRATION ON NITROGEN WASHOUT IN HUMANS**

J. WALIGORA, D. J. HERRIGAN JR., and J. CONKIN (Technology, Inc.)

Jun. 1985 See Also NASA TM-58254(N83-26448/NSP)
MSC-20686 Vol. 9, No. 1, P. 113

Series of experiments described in NASA technical memorandum showed drinking water before breathing nearly pure oxygen has little or no effect on rate of removal of nitrogen from body. Experiments undertaken because data from some earlier experiments suggested that, under some conditions, hydration might help prevent decompression sickness.

**B85-10215
MULTISPECTRAL ANALYSIS OF NMR IMAGERY**

R. L. BUTTERFIELD, M. W. A. A. VANNIER (Washington University School of Medicine), and D. JORDAN (University of Florida)

Oct. 1985

KSC-11301

Vol. 9, No. 2, P. 106

Conference paper discusses initial efforts to adapt multispectral satellite-image analysis to nuclear magnetic resonance (NMR) scans of human body. Flexibility of these techniques makes it possible to present NMR data in variety of formats, including pseudocolor composite images of pathological internal features. Techniques do not have to be greatly modified from form in which used to produce satellite maps of such Earth features as water, rock, or foliage.

**B85-10356
PROSTHETIC SPHINCTER CONTROLS URINATION**

J. B. TENNEY JR. (Rochester General Hospital)

Jan. 1986

MFS-25740

Vol. 9, No. 3, P. 116

People who lost muscular control of urinary canal through disease or injury aided by prosthetic sphincter. Implanted so it surrounds urethra, sphincter deflated and inflated at will by wearer to start and stop urination. Operating pressure adjusted after implantation to accommodate growth or atrophy of urinary canal and prevent tissue damage from excess pressure. Principle adapted to other organs, such as colon, ureter, or ileum.

**B85-10357
ENHANCING CENTRIFUGAL SEPARATION WITH ELECTROPHORESIS**

F. T. HERRMANN

Jan. 1986

MFS-28053

Vol. 9, No. 3, P. 119

Separation of biological cells by coil-planet centrifuge enhanced by electrophoresis. By itself, coil-planet centrifuge offers relatively gentle method of separating cells under low centrifugal force in physiological medium that keeps cells alive. With addition of voltage gradient to separation column of centrifuge, separation still gentle but faster and more complete. Since separation apparatus contains no rotary seal, probability of leakage, contamination, corrosion, and short circuits reduced.

**B85-10358
CAMERA FOR MONITORING VEGETATION**

T. Z. MARTIN (Caltech)

Jan. 1986

NPO-16349

Vol. 9, No. 3, P. 120

Video camera uses solid-state imaging devices and light

filters to bring out subtle spectral differences between healthy and stressed vegetation differences not readily detectable with infrared film cameras. Camera employs two detector arrays. Video camera made small and easily portable. Eliminates need for refrigeration of film before use, and provides instantaneous output with no delay for film development.

**B85-10359
DEVELOPMENT OF A PROSTHESIS FOR URINARY CONTROL**

J. B. TENNEY (Rochester General Hospital), R. RABINOWITZ (Rochester General Hospital), Z. TOMKIEWICZ (Rochester General Hospital), H. N. HARRISON (Rochester General Hospital), and D. W. ROGERS (Rochester General Hospital)

Jan. 1986

MFS-27062

Vol. 9, No. 3, P. 121

Report describes development and marketing of prosthetic sphincter for urinary control. With prosthetic device patients void bladder every 3 to 4 hours. Periodic voiding keeps bladder muscles exercised and healthy and avoids bladder infections and kidney damage.

**B85-10505
MASS SPECTROMETER FOR AIRBORNE MICRO-ORGANISMS**

M. P. SINHA (UCLA) and S. K. FRIEDLANDER (UCLA)

Mar. 1986

NPO-16359

Vol. 9, No. 4, P. 122

Bacteria and other micro-organisms identified continuously with aid of new technique for producing samples for mass spectrometer. Technique generates aerosol of organisms and feeds to spectrometer. Given species of organism produces characteristic set of peaks in mass spectrum and thereby identified. Technique useful for monitoring bacterial makeup in environmental studies and in places where cleanliness is essential, such as hospital operating rooms, breweries, and pharmaceutical plants.

**B85-10506
PREADAPTING TO WEIGHTLESSNESS**

M. F. RESCHKE, D. E. PARKER (Miami University), and A. P. ARROTT (Miami University)

Mar. 1986

MSC-20847

Vol. 9, No. 4, P. 124

Report discusses physiological and physical concepts of proposed training system to precondition astronauts to weightless environment. System prevents motion sickness, often experienced during early part of orbital flight. Also helps prevent seasickness and other forms of terrestrial motion sickness, often experienced during early part of orbital flight. Training affects subject's perception of inner-ear signals, visual signals, and kinesthetic motion perception. Changed perception resembles that of astronauts who spent many days in space and adapted to weightlessness.

06 MECHANICS

**B85-10088
AIRCRAFT CANOPY LOCK**

G. H. NICHOLS

Jun. 1985

FRC-11065

Vol. 9, No. 1, P. 114

Mechanism easy to open intentionally but resists accidental opening. Locking or Unlocking occurs when pull pin enters or leaves conical base. Pushing ejection pin or

06 MECHANICS

pulling knob unlocks mechanism. Unintentional release unlikely since accidental pilot motions push on knob in most cases. This safety feature, coupled with simplicity and reliability of mechanism, useful for emergency exits for land vehicles or even buildings.

B85-10089

INSPECTING HOLLOW PARTS WITH A CAT SCANNER
G. A. KUHR (Rockwell International Corp.)

Jun. 1985

MFS-19916

Vol. 9, No. 1, P. 115

Technique well known in medicine, used on manufactured objects. As it passes through a part, beam of X-rays or other radiation attenuated and scattered. Computer records variations in beam as part rotated and constructs cross section for display on video monitor. Computer-aided tomography (CAT) measures wall thickness and detecting flaws in hollow turbine blades or other curved parts.

B85-10090

CONTINUOUS LAMINAR-SMOKE GENERATOR

L. M. WEINSTEIN

Jun. 1985

LAR-13014

Vol. 9, No. 1, P. 116

Single smoke filament used to study flow in low-speed wind tunnels. Use of small-diameter single laminar smoke stream allows examination of flow structures at higher resolution, and continuous operation facilitates use.

B85-10091

INFLATABLE COLUMN STRUCTURE

J. M. HEDGEPEETH (Astro Research Corp.)

Aug. 1985

NPO-16216

Vol. 9, No. 1, P. 116

Lightweight structural member easy to store. Billowing between circumferential loops of fiber inflated column becomes series of cells. Each fiber subjected to same tension along entire length (though tension is different in different fibers). Member is called 'isotensoid' column. Serves as jack for automobiles or structures during repairs. Also used as support for temporary bleachers or swimming pools.

B85-10092

CONTACT HEAT EXCHANGER

M. L. FLEMING (Vought Corp.), D. D. STALMACH (Vought Corp.), and R. L. COX (Vought Corp.)

Aug. 1985

MSC-20419

Vol. 9, No. 1, P. 117

Fluid pressure controls contact between heat pipe and heat exchanger. Heat exchanger system in cross section provides contact interface between fluid system and heat pipe with easy assembly/disassembly of heat-pipe/ pumped-liquid system. Originally developed for use in space, new device applicable on Earth where fluid system is linked with heat pipe, where rapid assembly/disassembly required, or where high pressures or corrosive fluids used.

B85-10093

MICROPROCESSOR-CONTROLLED LASER BALANCING SYSTEM

R. S. DEMUTH (Mechanical Technology, Inc.)

Jun. 1985 See Also NASA CR-3105 (N79-17228/NSP)

LEW-13294

Vol. 9, No. 1, P. 118

Material removed by laser action as part tested for balance. Directed by microprocessor, laser fires appropriate amount of pulses in correct locations to remove necessary amount of material. Operator and microprocessor software interact through video screen and keypad; no programming skills or unprompted system-control decisions required. System provides complete and accurate balancing in single load-and-spinup cycle.

B85-10094

CALIBRATING DROPLET GENERATOR FOR PRESSURIZED TESTING VESSEL

G. J. DEFEVER (Rockwell International Corp.) and T. EXPOSITO (Rockwell International Corp.)

Jun. 1985

MFS-25992

Vol. 9, No. 1, P. 119

Device helps to align laser for droplet-sizing interferometer. Monodispersing Droplet Generator creates uniformly sized droplets. Laser source and receiver of interferometer aligned and focused on droplets. MDG mounted in high-pressure flange on tank. Line extensions pass through flange to outside. Flange allows MDG to operate at high injector back pressures used for tests.

B85-10095

WINGTIP VORTEX-AUGMENTED TURBOPUSHER PROPELLER THRUST

J. C. PATTERSON JR.

Jun. 1985 See Also NASA TN D-5729 (N70-27576/NSP)

LAR-13019

Vol. 9, No. 1, P. 121

Thrust of propeller enhanced by tip vortex. Wingtip-Mounted Nacelle provides turboprop vortex velocity recovery. Thrust of turbopusher propeller increased by flow of lift-induced vortex. As result of weaker vortex, reduction in induced drag of wing afforded by propeller-wake mass injection into core of vortex causing it to break down.

B85-10096

SUPERCONDUCTING-CAVITY ACCELEROMETER

V. S. REINHARDT and F. VON BUN

Jun. 1985

GSC-12797

Vol. 9, No. 1, P. 120

Resonant frequency of microwave superconducting cavity sensitive to gravitation and acceleration. Sensitive accelerometer assembled by combining superconducting microwave cavity and conventional microwave semiconductor oscillator circuit. Device measures accelerations as small as 10-10 cm/S² (10-13 g's). Also configured to measure small gradients in gravitational field of Earth.

B85-10097

REMOTELY-CONTROLLED DOCKING SYSTEM

J. A. CHANDLER

Jun. 1985

MSC-18969

Vol. 9, No. 1, P. 121

Spring-loaded drogue cones tolerate and correct misalignment. Attachment Mechanism equipped with spring-loaded latches, shock-absorbing springs, and self-aligning conical mating surfaces. Docking system includes three attachment mechanisms plus television camera that views set of crosshairs for alignment of vehicle and payload. Originally developed for Space Shuttle, mechanism adapted for robot manipulator arms, trailer hitches, and docking devices for in-flight refueling of airplanes.

B85-10098

SPRING-LOADED TRANSDUCER HOLDER

M. R. GARDNER

Jun. 1985

LAR-13048

Vol. 9, No. 1, P. 122

Portable ultrasonic scanner moves transducer at constant pressure. Spring-loaded holder moves ultrasonic transducer over test sample at constant pressure. Setup used to determine rate of debond taking place in glued materials subjected to fatigue loading. Holder designed as portable field unit adapted to fatigue machine that transmits data while specimen tested.

B85-10099

DIFFERENTIAL TEMPERATURE CONTROL OF ELECTRICAL HEATERS

K. N. COLE

Jun. 1985

LAR-13047

Vol. 9, No. 1, P. 123

Energy savings realized from heaters that maintain low humidity in electrical equipment. Unit applies power to electrical-equipment heater only when equipment tempera-

ture drops below preset differential above ambient. With differential controller, power consumed only 118 kWh for savings of 410 kWh/day, or 77-percent energy savings.

B85-10100

DEPLOYABLE M-BRACED TRUSS

M. M. MIKULAS JR. and M. D. RHODES

Jun. 1985

LAR-13081

Vol. 9, No. 1, P. 123

Tension/compression and shear separated structurally in deployable beam. M-Braced Sections Packaged using combination of hinges and telescoping sections. When upper sections telescope into base, diagonals hinge, telescope, and rotate along batten. Components of M-braced truss fabricated from conventional metallic materials or nonmetallic materials such as graphite/epoxy. Applications include masts for antenna feed horns and ribs for solar array blankets.

B85-10101

MULTISHAKER MODAL TESTING

R. R. GRAIG JR. (Bureau of Engineering Research)

Jun. 1985

MFS-27052

Vol. 9, No. 1, P. 124

Report prepared for Marshall Space Flight Center summarizes recent advances in mathematical analysis of structural vibrations based on experimental data. Also includes summary of research by author as well as abstracts of technical reports and papers presented at meetings or otherwise published.

B85-10102

ROCKET-BOOSTER TOWING SIMULATION

T. A. TROVILLION (Planning Research Corp.)

Jun. 1985

KSC-11289

Vol. 9, No. 1, P. 125

Report describes computer simulation of motion of solid-rocket ship. Listing of simulation program in FORTRAN. Mathematical techniques useful in such other maritime applications as buoy or ship design.

B85-10216

RETRACTABLE END PLATES FOR AIRCRAFT LIFTING SURFACES

W. D. HARVEY and S. M. MANGALAM (National Academy of Sciences)

Oct. 1985

LAR-12946; LAR-12947

Vol. 9, No. 2, P. 108

End plates and winglets improve aerodynamic characteristics of aircraft wings and other fixed lifting surfaces. Retractable end plates automatically actuated by same shaft that deflects lifting surface and require little or no extra power and absolutely no control input from cockpit. Besides being modular in construction, easily fitted to any existing aircraft design with only minor modifications.

B85-10217

AERODYNAMIC REAR CONE FOR TRUCKS

J. BULLMAN

Oct. 1985

MFS-28007

Vol. 9, No. 2, P. 109

Wind-inflated cone reduces turbulence that ordinarily occurs in air just behind square-back truck traveling at high speed. Wind around truck would enter slits in folded cone and automatically deploy it. Energy lost to air turbulence greatly reduced, and fuel consumed by truck reduced accordingly. In addition, less air turbulence means less disturbance to nearby vehicles on highway.

B85-10218

END RESTRAINTS FOR IMPACT-ENERGY-ABSORBING TUBE SPECIMENS

G. L. FARLEY (Structures Laboratory, U.S. Army Research and Technology Laboratories, AVSCOM) and J. T. MODLIN

Oct. 1985

LAR-13179

Vol. 9, No. 2, P. 109

Inexpensive device developed that eliminates tipping problem without affecting crushing process. Device consists of soft sponge-rubber insert approximately 0.5 inches (1.3 centimeters) thick, cut to same diameter as internal diameter of tube specimen. Metal washer, slightly smaller than internal diameter of tube, placed on top of rubber insert. Screw passed through washer and rubber insert and threaded into base of test machine. As screw tightened against washer, rubber insert compressed and expands radially. Radial expansion applies pressure against internal wall of tube specimen, which provides sufficient support to tube to prevent tipping.

B85-10219

ACCURATE AIRBORNE PARTICLE SAMPLER

I. M. MILLER

Oct. 1985

LAR-13080

Vol. 9, No. 2, P. 110

Air inducted isokinetically into centrifugal collector. Cloud drop collector accurately and efficiently samples droplets and rejects aerosol particles. Number of these collectors connected in series, each designed that largest size fraction of droplets captured in first one and successively smaller size fractions captured in others. By analyzing each size fraction, chemical composition of cloud droplets related to drop size.

B85-10220

TESTING MACHINE FOR BIAXIAL LOADING

R. J. DEMONET (Rockwell International Corp.) and R. D. REEVES (Rockwell International Corp.)

Oct. 1985

MSC-20477

Vol. 9, No. 2, P. 111

Standard tensile-testing machine applies bending and tension simultaneously. Biaxial-loading test machine created by adding two test fixtures to commercial tensile-testing machine. Bending moment applied by substrate-deformation fixture comprising yoke and anvil block. Pneumatic tension-load fixture pulls up on bracket attached to top surface of specimen. Tension and deflection measured with transducers. Modified test apparatus originally developed to load-test Space Shuttle surface-insulation tiles and particularly important for composite structures.

B85-10221

COMBINATION HEAT-FLUX AND TEMPERATURE GAGE

E. C. KNOX (Rockwell International Corp.)

Oct. 1985

MSC-20706

Vol. 9, No. 2, P. 112

Instrument measures both temperature and temperature gradient in confined areas. With thermopile embedded in epoxy close to thermocouple, single unit measures both temperature and heat flow. Epoxy selected for low thermal conductivity and compatibility with test environment.

B85-10222

SEQUENTIALLY-DEPLOYABLE TETRAHEDRAL BEAM

M. M. MIKULAS JR. and R. F. CRAWFORD (General Research Corp.)

Oct. 1985

LAR-13098

Vol. 9, No. 2, P. 113

Beam geometry varied three-dimensionally after beam is deployed. When tetrahedral beam completely retracted, each longeron shortened indefinitely so frames at each end of longeron folded together to lie one against other. Each tetrahedral of beam so retracted to achieve compact packaging of entire beam. Each longeron shortened by folding at midlength and ends, by telescoping, or by other means. Beam becomes crane, manipulator arm, antenna feed support, or other type of lineal structural member. Beam completely packageable, automatically deployable, and capable of having geometry varied during use.

B85-10223

HAND-HELD ELECTRONIC GAP-MEASURING TOOLS

F. E. SUGG (Rockwell International Corp.), F. W. THOMP-

06 MECHANICS

SON (Rockwell International Corp.), L. A. ARAGON (Rockwell International Corp.), and D. B. HARRINGTON (Rockwell International Corp.)
Oct. 1985

MSC-20176

Vol. 9, No. 2, P. 114

Repetitive measurements simplified by tool based on LVDT operation. With fingers in open position, Gap-measuring tool rests on digital readout instrument. With fingers inserted in gap, separation alters inductance of linear variable-differential transformer in plastic handle. Originally developed for measuring gaps between surface tiles of Space Shuttle orbiter, tool reduces measurement time from 20 minutes per tile to 2 minutes. Also reduces possibility of damage to tiles during measurement. Tool has potential applications in mass production; helps ensure proper gap dimensions in assembly of refrigerator and car doors and also used to measure dimensions of components and to verify positional accuracy of components during progressive assembly operations.

B85-10224

FIXTURE FOR LINEARLY VARIABLE DISPLACEMENT TRANSDUCERS

G. L. FARLEY (Structures Laboratory, U.S. Army Research and Technology Laboratories, AVSCOM) and D. J. BAKER (Structures Laboratory, U.S. Army Research and Technology Laboratories, AVSCOM)
Oct. 1985

LAR-12937

Vol. 9, No. 2, P. 115

Original point of interest on shear panel tracked throughout loading. Technique and fixture measure out-of-plane displacements on shear panel using linearly variable displacement transducers (LVDT's) while tracking original panel location. Technique adaptable to any size shear panel.

B85-10225

INEXPENSIVE EDDY-CURRENT STANDARD

R. F. BERRY JR.

Oct. 1985

LAR-13154

Vol. 9, No. 2, P. 116

Radial crack replicas serve as evaluation standards. Technique entails intimately joining two pieces of appropriate aluminum alloy stock and centering drilled hole through and along interface. Bore surface of hole presents two vertical stock interface lines 180 degrees apart. These lines serve as radial crack defect replicas during eddy-current technique setup and verification.

B85-10226

FORCE SENSOR FOR LARGE ROBOT ARMS

A. K. BEJCZY (Caltech), H. C. PRIMUS (Caltech), and V. D. SCHEINMAN (Caltech)

Oct. 1985

NPO-16097

Vol. 9, No. 2, P. 116

Modified Maltese-cross force sensor larger and more sensitive than earlier designs. Measures inertial forces and torques exerted on large robot arms during free movement as well as those exerted by claw on manipulated objects. Large central hole of sensor allows claw drive mounted inside arm instead of perpendicular to its axis, eliminating potentially hazardous projection. Originally developed for Space Shuttle, sensor finds applications in large industrial robots.

B85-10227

TABS REDUCE HELICOPTER-BLADE VIBRATIONS

T. G. CAMPBELL (United Technologies Corp.)

Oct. 1985

ARC-11444

Vol. 9, No. 2, P. 117

Tuned flaplike tab on trailing edge of helicopter rotor blade reduces blade vibration. Flapping tab on rotor blade produces aerodynamic loads that oppose vibrational aerodynamic loads. With proper choice of tab parameters, tab made to cancel much of blade vibration over wide range of rotor speeds and airspeeds.

B85-10228

FLOWMETER FOR CLEAR AND TRANSLUCENT FLUIDS

P. R. WHITE

Oct. 1985

MFS-28030

Vol. 9, No. 2, P. 117

Transducer with only three moving parts senses flow of clear or translucent fluid. Displacement of diaphragm by force of flow detected electrooptically and displayed by panel meter or other device. Transducer used to measure flow of gasoline to automobile engine.

B85-10229

LOW-TEMPERATURE SEAL FOR ACTUATOR ROD

R. J. LINDFORS (Consolidated Controls Corp.)

Oct. 1985

MSC-20744

Vol. 9, No. 2, P. 118

Combination bearing and seal used on Space Shuttle functions reliably at temperatures as low as - 160 degrees F and as high as + 130 degrees F. Corrosion-resistant stainless-steel spacer separates secondary and primary seals in both old and new versions of seal assembly. In new version, combination of flexible sealing lip and bridge is less susceptible to cracking at low temperatures.

B85-10230

DETECTING CRACKS IN ROUGH METAL SURFACES

N. T. ZUVER (Rockwell International Corp.), F. E. SUGG (Rockwell International Corp.), F. H. STUCKENBERG (Rockwell International Corp.), and E. T. MORRISSEY (Rockwell International Corp.)

Oct. 1985

MSC-20734

Vol. 9, No. 2, P. 119

Test based on eddy-current probe technique identifies cracks in swaged metals. Hinged collar with spring-loaded latch holds probe in place on part tested. For repeated measurements on same or similar parts, collar loosened and moved to various measuring positions. Method suitable for many kinds of metal parts, including swaged fittings, tubing, and pipes. Used for rapid crack/no-crack determinations in suspect parts already installed.

B85-10231

STATISTICAL ENERGY ANALYSIS PROGRAM

R. C. FEREBEE (McDonnell Douglas Astronautics Co.), R. W. TRUDELL (McDonnell Douglas Astronautics Co.), L. I. YANO (McDonnell Douglas Astronautics Co.), and S. I. NYGAARD (McDonnell Douglas Astronautics Co.)

Oct. 1985

MFS-27035

Vol. 9, No. 2, P. 120

Statistical Energy Analysis (SEA) is powerful tool for estimating high-frequency vibration spectra of complex structural systems and incorporated into computer program. Basic SEA analysis procedure divided into three steps: Idealization, parameter generation, and problem solution. SEA computer program written in FORTRAN V for batch execution.

B85-10232

ANALYSES OF MULTISHAFT ROTOR-BEARING RESPONSE

H. D. NELSON (Arizona State University) and W. L. MEACHAM (Arizona State University)

Oct. 1985

LEW-13925

Vol. 9, No. 2, P. 127

Method works for linear and nonlinear systems. Finite-element-based computer program developed to analyze free and forced response of multishaft rotor-bearing systems. Acronym, ARDS, denotes Analysis of Rotor Dynamic Systems. Systems with nonlinear interconnection or support bearings or both analyzed by numerically integrating reduced set of coupled system equations. Linear systems analyzed in closed form for steady excitations and treated as equivalent to nonlinear systems for transient excitation. ARDS is FORTRAN program developed on an Amdahl 470 (similar to IBM 370).

B85-10360

ADHESIVE-BONDED FIXTURE FOR FLEXURE TESTING

J. M. CLEMONS, B. G. PENN, F. E. LEDBETTER, J. G. DANIELS, and W. T. WHITE

Jan. 1986

MFS-28051

Vol. 9, No. 3, P. 122

Fixture for flexural tests of glass-fiber-reinforced epoxy rods 1/4 in. (6.4 mm) in diameter easy to fabricate. Little machining done by relatively unskilled. Flexural-test fixture allows bending stress applied to specimen rod while holding rod securely. Dowel pins, blocks, and plate that make up fixture joined by adhesive.

B85-10361

DAMAGE-FREE RELIEF-VALVE DISASSEMBLY

H. HASELMAIER (Pan Am World Services, Inc.)

Jan. 1986

MFS-28006

Vol. 9, No. 3, P. 123

Tool safely disassembles relief valves without damage to sensitive parts. Relief-valve disassembly tool used to extract valve nozzle from its housing. Holding device on tool grips nozzle. When user strikes hammer against impact disk, holding device pulls nozzle from press fit. Previously, nozzle dislodged by striking spindle above it, but practice often damaged retaining screw. New tool removes nozzle directly. With minor modifications, tool adapted to valves from different manufacturers.

B85-10362

DEPLOYABLE TRUSS MEMBER

N. T. FRINK

Jan. 1986

LAR-13219

Vol. 9, No. 3, P. 124

Compact telescoping roll extends 24 times its length. Roll telescopes into extended truss member when force is applied. Truss members deployed by various means. Truss member initially constructed in its stowed state with appropriate sheet material rolled around central core. For deployment truss extends by centrifugal force to form cone. With both ends fastened to prevent unrolling, rigid truss member formed.

B85-10363

ELEVATED-TEMPERATURE TENSILE-TESTING OF FOIL-GAGE METALS

L. B. BLACKBURN and J. R. ELLINGSWORTH

Jan. 1986

LAR-13243

Vol. 9, No. 3, P. 125

Automated system for measuring strain in metal foils at temperatures above 500 degrees F (260 degrees C) uses mechanical extensometer and displacement transducer. System includes counterbalance feature, which eliminates weight contribution of extensometer and reduces grip pressure required for attachment to specimen. Counterbalancing feature overcomes two major difficulties in using extensometers with foil-gage specimens: (1) Weight of extensometer and transducer represents significant fraction of total load applied to specimen and may actually damage it; and (2) grip pressure required for attachment of extensometer to specimens may induce bending stresses in foil-gage materials.

B85-10364

AUTOPILOT SERVOACTUATOR WITH PRESSURIZED DETENTED CENTERING

J. A. ARING (The Boeing Co.)

Jan. 1986

LAR-13185

Vol. 9, No. 3, P. 126

Centering valve allows use of mechanical override in autopilot mode. Alternate system designed incorporates centering valves into four FBW servos, providing detents for reacting mechanical system forces following FBW shutdown. Required linkage hard point incorporated directly into autopilot servoactuator by centering valve assembly shown. All components in this functional hydraulic schematic usually present in contemporary aircraft flight-control-

system autopilot servoactuators, with exception of centering valve. Centering valve, which serves as hard-point linkage for mechanical system forces, incorporated directly into flight control system.

B85-10365

MEASURING PERIMETERS OF LARGE ROUND OBJECTS

C. B. DICKINSON (Martin Marietta Corp.)

Jan. 1986

MFS-28046

Vol. 9, No. 3, P. 127

Perimeters of large objects of approximately circular cross section determined indirectly through radius measurements by any of several proposed methods. Methods reduce errors introduced by wheel moved around perimeter and counting wheel turns: Surface irregularities and variations in friction and contact pressure seriously affect accuracy and repeatability of wheel measurements. Measurement concept applicable to such other large bodies as aircraft fuselages and generator rotors.

B85-10366

LIQUID-LEVEL MONITOR FOR PRESSURIZED VESSELS

J. J. SINGH, W. T. DAVIS, and G. H. MALL (Computer Sciences Corp.)

Jan. 1986 See Also (N83-33844)

LAR-13208

Vol. 9, No. 3, P. 128

Technique for monitoring water levels in pressurized stainless-steel cylinders, based on differences in gamma-ray attenuation coefficients in water and air, developed. Full-scale laboratory prototype system constructed to test technique. Technique usable with liquids other than water, since linear attenuation coefficients for intermediate-energy gamma rays in air considerably lower than in liquids. Also adaptable for continuous monitoring of liquid levels in reservoir systems and in underground storage tanks.

B85-10367

MEASURING METAL THICKNESS WITH AN ELECTRIC PROBE

A. SHUMKA (Caltech)

Jan. 1986

NPO-16340

Vol. 9, No. 3, P. 129

Thickness of metal parts measured from one side with aid of Kelvin probe. Method developed for measuring thickness of end plate on sealed metal bellows from outside. Suitable for thicknesses of few thousandths of inch (few hundred micrometers). Method also used to determine thickness of metal coatings applied by sputtering, electroplating, and flame spraying.

B85-10368

LOW-NOISE SUPERSONIC NOZZLE

I. E. BECKWITH

Jan. 1986

LAR-13192

Vol. 9, No. 3, P. 130

Two-dimensional nozzle incorporates unusual design features of rapid expansion contour, boundary-layer bleed slots upstream of throat, and exit width-to-height ratio of 1.7 to provide noise levels in upstream regions of test rhombus substantially lower than in conventional nozzles.

B85-10369

TOGGLE HINGE FOR DEPLOYABLE STRUTS

R. T. BARBOUR (Rockwell International Corp.)

Jan. 1986

MFS-28037

Vol. 9, No. 3, P. 131

Toggle hinge allows deployable structures erected without end play encountered in conventional hinged structural members. New hinge ensures rigidity in portable bridges, masts, towers, platforms, and other deployable (and retractable) structures. Positioned halfway along length of folding strut, hinge allows halves of strut to pivot 180 degrees about center.

B85-10370

FRICTION-TESTING MACHINE

06 MECHANICS

F. J. BENZ, D. S. DIXON, and R. C. SHAW (Lockheed Corp.)

Jan. 1986

MSC-20622

Vol. 9, No. 3, P. 132

Testing machine evaluates wear and ignition characteristics of materials in rubbing contact. Offers advantages over other laboratory methods of measuring wear because it simulates operating conditions under which material will actually be used. Machine used to determine wear characteristics, rank and select materials for service with such active oxidizers as oxygen, halogens, and oxides of nitrogen, measure wear characteristics, and determine coefficients of friction.

B85-10371

NONINVASIVE FLUID LEVEL SENSOR FOR ORGANO-METALLIC SOURCES

W. GERDES

Jan. 1986

LAR-13265

Vol. 9, No. 3, P. 133

Two ultrasonic methods available for measuring level of organometallic liquid in stainless-steel (or other homogeneous solid) container. Methods require no disassembly or weighing of container. Commercially available ultrasonic flaw detectors, some of which have digital readouts and computer interfaces, used in techniques. Both methods used in crystal growth to determine level of liquids contained in sealed, opaque containers.

B85-10372

FLOWMETER FOR CLEAR FLUIDS

P. R. WHITE and W. R. MCINTOSH

Jan. 1986

MFS-28031

Vol. 9, No. 3, P. 134

Electronic flowmeter measures flow rate of clear or translucent fluids. Instrument produces electrical signal proportional to volume of fluid flowing through it per unit time. Optoelectronic instrument generates electrical signal proportional to fluid-flow rate.

B85-10373

TILTABLE-WING, TILTABLE-ROTOR AIRCRAFT

R. H. STROUB

Jan. 1986

ARC-11420

Vol. 9, No. 3, P. 135

New airplane wing tilts 90 degrees, leading edge up, to feather into rotor downwash during hovering, takeoff, or landing. After hovering or takeoff, rotors tilted forward slightly to accelerate airplane into forward flight. As airplane accelerates, wings start to tilt forward. At speeds of 20 to 40 knots (10.3 to 20.6 m/s), wings are in horizontal orientation. In this speed range, rotor power requirements decreased sufficiently to allow wings to assume normal orientation. Tilttable wings movable independently of tilttable rotors. Tilted at whatever pitch schedule yields greatest efficiency.

B85-10374

NONCONTACTING MEASUREMENT WITH A THERMO-COUPLE

W. T. WEATHERILL (Rockwell International Corp.), C. J. SCHOREDER (Rockwell International Corp.), and H. J. FREITAG (Rockwell International Corp.)

Jan. 1986

MSC-20834

Vol. 9, No. 3, P. 136

Tentlike covering brings thermocouple to within few degrees of surface temperature. Technique originally developed for measuring surface temperature of quartz fabric under radiant heating requires no direct contact with heated surface. Technique particularly useful when measuring surface temperatures of materials damaged if thermocouple or other temperature sensor attached.

B85-10375

TETHERED COMMUNICATION SATELLITES

G. VON TIESENHAUSEN

Jan. 1986

MFS-28042

Vol. 9, No. 3, P. 136

Report describes concept for placing several communication satellites in geostationary orbit without taking up more space than assigned to single satellite. Proposed scheme eases orbital crowding more economically than space platforms. Concept requires minimal redesign of existing satellites and accommodates many satellites in just one orbital slot. System much lighter in weight than geostationary platform and easier and more economical to transport.

B85-10376

PREDICTING TWO-DIMENSIONAL, UNSTEADY TURBULENT COMBUSTION

C. J. MAREK, A. F. GHONIEM (University of California), and A. K. OPPENHEIM (University of California)

Jan. 1986

LEW-14027

Vol. 9, No. 3, P. 137

MIMOC calculates flow field and flame propagation in turbulent combustion tunnel. Program employs algorithm for turbulent combustion modeling described by Ghoniem, Chorin, and Oppenheim. Program used to study flow field in model combustor, formed by rearward-facing step in channel, in terms of vorticity field, velocity field, turbulent shear stresses, flame contours, and concentration field.

B85-10377

AIRFOIL SMOOTHING AND SCALING PROGRAMS

H. L. MORGAN JR

Jan. 1986

LAR-13132

Vol. 9, No. 3, P. 137

Two programs smooth and scale arbitrary airfoil coordinates. Airfoil smoothing program (AFSMO) utilizes both least-squares polynomial and least-squares cubic-spline techniques to smooth iteratively second derivatives of y-axis airfoil coordinates with respect to transformed x-axis system that unwraps airfoil and stretches nose and trailing-edge regions.

B85-10378

THERMAL, ONE-DIMENSIONAL ANALYZER PROGRAM

D. K. PATEL (Rockwell International Corp.) and D. P. JONES (Rockwell International Corp.)

Jan. 1986

MSC-20703

Vol. 9, No. 3, P. 137

Thermal, one-dimensional analyzer program enables user to predict surface temperature of fibrous, feltlike insulation exposed to some external radiant heat source or convective heating produced by aerodynamic forces. Prediction derived from readings of thermocouple embedded in material at some depth below surface. Program useful in analysis and evaluation of insulative qualities of similar or new compositions.

B85-10379

NASTRAN/DISCOS/SAMSAN DMAP BRIDGING PROGRAM

H. P. FRISCH

Jan. 1986

GSC-12902

Vol. 9, No. 3, P. 138

Design of controller for flexible structure must incorporate flexible body data in format compatible with design and performance evaluation methods. Control designer works with several different programs to obtain all data and capabilities needed. Three programs for design and analysis of flexible structure controllers integrated.

B85-10380

INELASTIC ANALYSIS OF THERMOMECHANICALLY CYCLED STRUCTURES

A. KAUFMAN

Jan. 1986

LEW-14011

Vol. 9, No. 3, P. 138

Simplified inelastic analysis computer program (AN-SYMP) developed for predicting stress/strain history of

thermomechanically cycled structure from an elastic solution. Program uses an iterative and incremental procedure to estimate plastic strains from material stress/strain properties and simulated plasticity hardening model. Program ANSYMP developed to simplify nonlinear structural analysis using only elastic solution as input data.

**B85-10381
GEOMETRIC AND MATERIAL NONLINEAR STRUCTURAL ANALYSIS**

J. D. WHITCOMB and B. DATTA GURU
Jan. 1986

LAR-13279 Vol. 9, No. 3, P. 139

GAMNAS (Geometric and Material Nonlinear Analysis of Structures) is two-dimensional finite-element stress-analysis program supporting fracture-mechanics studies of debonding and delamination. GAMNAS options include linear, geometric-nonlinear, material-nonlinear, and combined geometric- and material-nonlinear analysis.

**B85-10382
ANALYSIS OF SCRAMJET INLETS**

A. KUMAR

Jan. 1986

LAR-13297 Vol. 9, No. 3, P. 139

NASCRIN analyzes two-dimensional flow fields in supersonic combustion ramjet (scramjet) inlets. Solves two-dimensional Euler or Navier-Stokes equations in conservative form by unsplit, explicit, two-step finite-difference method. More recent explicit/implicit, two-step scheme also incorporated for viscous flow analysis. Algebraic, two-layer eddy-viscosity model used for turbulent flow calculations.

**B85-10507
LATCH FOR TELESCOPING STRUCTURES**

E. L. AHL JR.

Mar. 1986

LAR-13189 Vol. 9, No. 4, P. 126

Latch for three-member telescoping column developed for deployment of antenna 122 meters in diameter. Deployable column along axis of antenna open lattice structure with three longerons as principal loadbearing members. Column divided into telescoping sections that deploy, one section at time. Latch automatically locks sections into position during deployment and unlocks them when antenna restowed. Latch is four-bar linkage using over-center principle for locking, with Belleville spring washers to absorb deflections.

**B85-10508
WATER-THICKNESS GAGE**

L. M. WEINSTEIN

Mar. 1986 See Also (N84-27677)

LAR-13342 Vol. 9, No. 4, P. 127

Gage for determining depth of water buildup on outside of aircraft relatively simple to operate and yields result independent of conductivity of water. Gage used to evaluate effects of water on lift and detect water weight excesses. Dual-sensor gage eliminates effects of water conductivity, providing direct correlation between resistivity and water thickness.

**B85-10509
ROTARY SPEED SENSOR FOR ANTILOCKING BRAKES**

C. M. BERDAHL (Caltech)

Mar. 1986

NPO-16479 Vol. 9, No. 4, P. 128

Sensor based on fluidic principles produces negative pressure approximately proportional to rotational speed. Sensor developed as part of antilocking brake system for motorcycles. Uses inlet pressure rather than outlet pressure as braking-control signal, eliminating pressure pulsations caused by pump vanes and ensuring low-noise signal. Sensor is centrifugal air pump turned by one of motorcycle

wheels. Air enters pump through orifice plates, and suction taken off through port in pump inlet plenum.

**B85-10510
CALCULATING BEARING FORCES FROM STRAIN-GAGE SIGNALS**

J. R. FENWICK (Rockwell International Corp.)

Mar. 1986

MFS-29000 Vol. 9, No. 4, P. 129

Technique for obtaining force components on cylindrical bearing holder uses pairs of opposing strain gages. Signals proportional to outputs of pairs of opposing gages subtracted from each other. Subtraction nearly eliminates crosstalk between orthogonal force components. Signal-processing technique equally applicable to rotating as well as stationary loads.

**B85-10511
PHOTO-OPTICAL BLADE-VIBRATION-DATA ACQUISITION SYSTEM**

L. J. KIRALY and J. L. FRAREY (Mechanical Technology, Inc.)

Mar. 1986 See Also (N80-14113)

LEW-12887 Vol. 9, No. 4, P. 130

Techniques developed for measuring blade vibrations using optical sensors fixed in casing around bladed turbine-engine stage. Measurement system coordinates and assembles inputs of many optical probes in order to monitor all of blades on spinning stage. Several points on every blade monitored in order to develop quantitative measure of overall bladed-stage response.

**B85-10512
LOCKING PULL PIN**

T. O. KILLGROVE (Caltech)

Mar. 1986

NPO-16233 Vol. 9, No. 4, P. 131

Proposed self-locking pull pin not accidentally released by shock or vibration but intentionally released by pull on lanyard. Any rotational movement of main pin traps secondary pin: prevents further rotation and disengagement of main pin.

**B85-10513
DISTRIBUTING RADIANT HEAT IN INSULATION TESTS**

H. J. FREITAG (Rockwell International Corp.), A. R. REYES (Rockwell International Corp.), and M. C. AMMERMAN (Rockwell International Corp.)

Mar. 1986

MSC-20878 Vol. 9, No. 4, P. 131

Thermally radiating blanket of stepped thickness distributes heat over insulation sample during thermal vacuum testing. Woven of silicon carbide fibers, blanket spreads heat from quartz lamps evenly over insulation sample. Because of fewer blanket layers toward periphery of sample, more heat initially penetrates there for more uniform heat distribution.

**B85-10514
SMOOTHED TWO-DIMENSIONAL EDGES FOR LAMINAR FLOW**

B. J. HOLMES, C. H. LIU, G. L. MARTIN (Kentron International, Inc.), C. S. DOMACK (Kentron International, Inc.), C. J. OBARA (Kentron International, Inc.), A. HASSAN (Arizona State University), M. D. GUNZBURGER (Carnegie-Mellon University), and R. A. NICOLAIDES (Carnegie-Mellon University)

Mar. 1986

LAR-13255 Vol. 9, No. 4, P. 132

New concept allows passive method for installing flaps, slats, ice-protection equipment, and other leading-edge devices on natural-laminar-flow (NFL) wings without causing loss of laminar flow. Two-dimensional roughness elements in laminar boundary layers strategically shaped to increase critical (allowable) height of roughness. Facilitates installa-

06 MECHANICS

tion of leading-edge devices by practical manufacturing methods.

B85-10515

FUEL GAGE FOR SLOSHING TANKS

H. D. GARNER and W. E. HOWELL

Mar. 1986

LAR-13147

Vol. 9, No. 4, P. 133

New gage accurately measures fuel remaining in moving, or sloshing, tank. Measures tank air (or other gas) pressure and time required for pressure to change from one pre-selected level to another. Time measurement directly proportional to volume of air. Data processor computes relative volumes of air and fuel in tank.

B85-10516

CALIBRATING PRESSURE TRANSDUCERS AT CRYOGENIC TEMPERATURES

B. V. GIBBENS

Mar. 1986 See Alos (N84-11458)

LAR-13242

Vol. 9, No. 4, P. 134

To calibrate transducers immersed in cryogenic environment, sealed reciprocating bellows generates sinusoidal dynamic pressure. Transducer manifold assembly and bellows immersed in cryogenic environment to minimize gradients in controllable cryogenic temperature.

B85-10517

BRaille READING SYSTEMS

H. D. GARNER

Mar. 1986

LAR-13306

Vol. 9, No. 4, P. 135

Two proposed electromechanical systems for making braille characters produced relatively inexpensively. Similar in operating principle to dotmatrix printers, two methods use electronically actuated pins to reproduce characters from information stored on magnetic tape. First, one or more pins scanned over blank page and energized at intervals to emboss text on paper, one or more dots at time. Second, handheld device containing one or more character-generator cells used by reader to scan lines of text manually.

B85-10518

HYDRAULIC CYLINDER WITH AN INTEGRAL POSITION INDICATOR

G. O. GOODWIN (Kentron International, Inc.)

Mar. 1986

LAR-13095

Vol. 9, No. 4, P. 136

Linear variable differential transformer (LVDT) incorporated within cylinder of hydraulic actuator gives precise readout of position of piston relative to cylinder. LVDT contained completely within actuator. System requires precise positioning and position readout for computer control of model motions. Minimal space available for motion cylinders, and precise, continuous position readout (with no steps or pulses) required. Device provides continuous and accurate position indication of a hydraulic cylinder by means of integral, coaxially mounted LVDT.

B85-10519

SHAFT AXIAL-DISPLACEMENT SENSOR

A. J. HILL (Rockwell International Corp.)

Mar. 1986

MFS-29048

Vol. 9, No. 4, P. 137

Shaft-speed sensor on turbopump readily adapted to indicate shaft axial displacement as well as rotational speed. Adaptation makes it unnecessary to install separate displacement sensor, which requires additional access port on pump. Combined speed/displacement sensor used for performance analysis and for pump control.

B85-10520

ACCELERATED STRESS-CORROSION TESTING

(Innovator Not Given)(Aluminum Company of America) Mar. 1986 See Also (N85-11218 and N85-11219)

LAR-13337

Vol. 9, No. 4, P. 137

Test procedures for accelerated stress-corrosion testing of high-strength aluminum alloys faster and provide more quantitative information than traditional pass/fail tests. Method uses data from tests on specimen sets exposed to corrosive environment at several levels of applied static tensile stress for selected exposure times then subsequently tensile tested to failure. Method potentially applicable to other degrading phenomena (such as fatigue, corrosion fatigue, fretting, wear, and creep) that promote development and growth of cracklike flaws within material.

B85-10521

MINIATURE MICROPHONE ADAPTER

J. C. MANNING and J. W. SIMPSON

Mar. 1986

LAR-13210

Vol. 9, No. 4, P. 138

New microphone adapter permits installation of commercially available condenser microphone 1/8 inch (3 mm) in diameter at location of sensing ports, with remotely located preamplifier. Microphone has high-impedance source and low-level electrical output signal; therefore, adapter designed with minimum capacitance to avoid degradation of microphone sensitivity. Probe insensitive to aeroacoustic disturbances in high-velocity flow.

B85-10522

ELECTRONIC/HYDRAULIC LEVEL GAGE

B. HANNINEN (Martin Marietta Corp.) and D. HARTLEY (Martin Marietta Corp.)

Mar. 1986

MFS-28066

Vol. 9, No. 4, P. 139

System for checking levelness of machines and structures requires less time and labor than conventional optical systems. Measures differences in elevation to within 0.002 in. (0.05 mm). Floats at opposite ends of structure determine positions of cores in linear variable-differential transformers. Outputs of LVDT's carried by cables to control console, where displayed to operator as difference in core levels and therefore of ends of structure.

B85-10523

ADVANCED VAPOR-SUPPLY MANIFOLD

I. O. CLARK, W. J. DEBNAM JR., A. L. FRIPP JR., and R. K. CROUCH

Mar. 1986

LAR-13259

Vol. 9, No. 4, P. 140

Advanced vapor-supply manifold solves problem of manifold purging. Design virtually eliminates dead gas volumes in manifold system. System incorporates special valve into manifold in way that leaks and contamination problems of previous systems, which use tees and three-port valves, are minimized or eliminated in both main manifold line and in supply line. Of considerable use in gas manifold systems where even small amounts of gaseous impurities constitute problem or where more than one gaseous material used in single system.

B85-10524

TITANIUM HEAT-PIPE WICKS

R. SHAUBACH (Thermacore, Inc.), G. Y. EASTMAN (Thermacore, Inc.), and D. M. ERNST (Thermacore, Inc.)

Mar. 1986

MFS-26016

Vol. 9, No. 4, P. 141

Sintered titanium offers several advantages over sintered aluminum as material for heat-pipe wicks. Titanium both strong and light. Thermal conductivity only one-seventh of aluminum, and therefore used when high thermal resistance is needed to prevent boiling of working fluid.

B85-10525

MICROPHONE BOOM FOR AIRCRAFT-ENGINE MONITORING

R. COHN, M. ECONOMU, and W. ALBRECHT

Mar. 1986

ARC-11495

Vol. 9, No. 4, P. 141

Microphone for measuring aircraft engine noise mounted on lengthwise boom supported away from fuselage and engine. This configuration minimizes boundary-layer effects and pressure doubling that is present if microphone were mounted in aircraft fuselage.

B85-10526
THERMAL-DIODE SANDWICH PANEL
A. BASIULIS (Hughes Aircraft Co.)

Mar. 1986
LAR-13121

Vol. 9, No. 4, P. 142

Thermal diode sandwich panel transfers heat in one direction, but when heat load reversed, switches off and acts as thermal insulator. Proposed to control temperature in spacecraft and in supersonic missiles to protect internal electronics. In combination with conventional heat pipes, used in solar panels and other heat-sensitive systems.

B85-10527
REDUCTION OF VANE NOISE IN WIND-TUNNEL NOZZLES

R. M. MARTIN, T. F. BROOKS, and D. R. HOAD (U.S. Army Structures Laboratory)

Mar. 1986
LAR-13333

Vol. 9, No. 4, P. 143

Vane-induced noise reduced by adhering thin layer of porous material such as foam to downwind surface of vanes, particularly near sharp trailing edges, to prevent occurrence of edge tones. Other modifications made to aerodynamically streamline vane structure were rounding leading edges and smoothly fairing trailing edges. Boundary layer trip applied to leading edge to prevent laminar tone shedding from trailing edge.

B85-10528
SQUEEZE-FILM DAMPER CONTROLS HIGH VIBRATIONS
D. P. FLEMING

Mar. 1986
LEW-13506

Vol. 9, No. 4, P. 144

Dual-clearance (two oil films) squeeze-film damper developed for controlling vibrations in aircraft turbine engines and other rotating machinery. New damper under normal conditions uses only one low-clearance film. Under high imbalance, both films active, controlling shaft vibration in nearoptimum manner and allowing continued operation until safe shutdown made.

B85-10529
NOISE-PATH MEASUREMENTS IN AIRCRAFT STRUCTURES

M. C. MCGARY and W. H. MAYES

Mar. 1986 See Also (N83-11838)
LAR-13017

Vol. 9, No. 4, P. 145

System determines amount of radiated sound power separately attributed to airborne and structure-borne paths in aircraft. Also used to evaluate vibrating plates and thin shells. Sound transducers include array of lightweight, miniature piezoelectric accelerometers and two-microphone probe. Multichannel Fast Fourier Transform (FFT) analyzer/computer used for analog-to-digital conversion and to analyze spectrum of each of input signals. Noise-path identification in aircraft performed in flight by this system.

B85-10530
STIFFNESS STUDY OF WOUND-FILAMENT PRESSURE VESSELS

V. VERDERAIME

Mar. 1986 See Also (N84-33521)
MFS-27086

Vol. 9, No. 4, P. 145

Report presents theoretical and experimental study of stiffness of lightweight, jointed pressure vessels made of wound graphite fibers and epoxy. Specimens fabricated from layers of graphite fibers, wet with epoxy, on aluminum mandrel. Segment ends thickened with interspersed layers of axially oriented fibers to reduce pinhole bearing stresses and local deformations. Segments cured at 390 degrees F

(199 degrees C). Report presents results of vibrational tests of one-quarter-scale models of wound-filament pressure vessels.

B85-10531
PREDICTING THE PERFORMANCE OF AN AXIAL-FLOW COMPRESSOR

R. J. STEINKE

Mar. 1986
LEW-14025

Vol. 9, No. 4, P. 146

Stage-stacking computer code (STGSTK) developed for predicting off-design performance of multi-stage axial-flow compressors. Code uses meanline stagestacking method. Stage and cumulative compressor performance calculated from representative meanline velocity diagrams located at rotor inlet and outlet meanline radii. Numerous options available within code. Code developed so user modify correlations to suit their needs.

B85-10532
AXIAL-FLOW COMPRESSOR PERFORMANCE WITH WATER INGESTION

T. TSUCHIYA (Purdue University) and S. B. MURTHY (Purdue University)

Mar. 1986
LEW-14026

Vol. 9, No. 4, P. 147

Stage-stacking computer code (WISGSK) developed for prediction of offdesign axial-flow compressor performance with water ingestion. Code uses meantime stage-stacking method; stage and cumulative compressor performance calculated utilizing representative triangles located at rotor inlet and outlet mean radii. Code provides options for calculation of performance with mixtures of gases such as air and water vapor and air/water droplet mixtures with different water contents. Useful for obtaining preliminary estimates of overall performance of compressors with water ingestion given design point details corresponding to airflow and nature of corrections for air/water mixture flow.

B85-10533
FLOW THROUGH GAS-TURBINE DUCTS

O. L. ANDERSON (United Technologies Corp.), G. B. HANKINS JR. (United Technologies Corp.), and D. E. EDWARDS (United Technologies Corp.)

Mar. 1986
LEW-14095

Vol. 9, No. 4, P. 147

Existing computer program, Axisymmetric Diffuser Duct code (ADD code), modified to permit calculation of flows through small gas-turbine ducts with struts, guide vanes, and large degrees of turning. Code improvements include new coordinate generator, endwall loss model, and generalized geometry capability to describe struts and guide vanes in ducts that turn more than 90 degrees. Improved output format developed to provide solution on any arbitrary plane in duct.

B85-10534
AUTOMATED DESIGN SYNTHESIS

G. N. VANDERPLAATS (Naval Postgraduate School)

Mar. 1986
LAR-13341

Vol. 9, No. 4, P. 147

Automated Design Synthesis (ADS) program is general-purpose numerical optimization program containing wide variety of algorithms. Assumed user prepares analysis problem capable of computing objective function and constraints. Program able to accept as part of input design variable quantities. Optimization process carried out by ADS coupled with user's program. ADS used for constrained and unconstrained function minimization. Solution of general problem separated into three basic levels: Strategy, Optimizer, and One-Dimensional Search. Already significant applications in area of structural synthesis (minimum-weight design).

B85-10535
RADIATION VIEW-FACTOR PROGRAM WITH INTERAC-

06 MECHANICS

TIVE GRAPHICS

A. F. EMERY (University of Washington)

Mar. 1986

LAR-13299

Vol. 9, No. 4, P. 148

VIEW is six computer programs for determining view factors, graphically displaying surfaces, and evaluating solar irradiation of assemblage of surfaces. Programs offer thermal engineer powerful system for view-factor determination. Central program of system (VIEWC) computes long-wave radiant energy exchange factors between surfaces that make up enclosure. Other VIEW programs support user working with VIEWC.

B85-10536

FOUR-CYLINDER STIRLING ENGINE CONTROL SIMULATION

C. J. DANIELE and C. F. LORENZO

Mar. 1986

LEW-14106

Vol. 9, No. 4, P. 148

Four-cylinder, Stirling-engine, transient-engine-simulation computer program developed. Program intended for control analysis. Associated engine model simplified to shorten computer calculation time. Model includes engine mechanical-drive dynamics and vehicle-load effects. Computer program also includes subroutines that allow acceleration of engine by addition of hydrogen to system and braking of engine by short circuiting of working spaces.

B85-10537

SOLUTION OF RADIATION AND CONVECTION HEAT-TRANSFER PROBLEMS

R. F. ONEILL (General Dynamics Corp.)

Mar. 1986

LEW-13978

Vol. 9, No. 4, P. 149

Computer program P5399B developed to accommodate variety of fin-type heat conduction applications involving radiative or convective boundary conditions with additionally imposed local heat flux. Program also accommodates significant variety of one-dimensional heat-transfer problems not corresponding specifically to fin-type applications. Program easily accommodates all but few specialized one-dimensional heat-transfer analyses as well as many two-dimensional analyses.

B85-10538

ORBIT TRANSFER PROGRAMS

J. V. BREAKWELL (Stanford University)

Mar. 1986

LEW-14089

Vol. 9, No. 4, P. 150

Collection of computer programs developed that solve problem of transfer between noncoplanar circular orbits for spacecraft with chemical propulsion systems. Two basic programs given. First, referred to as 'exact solution,' gives complete, exact time histories of transfers. Second, or 'approximate solution,' program gives approximate information on transfer time and fuel cost but provides no detail of trajectory.

B85-10539

BEARING THERMAL PERFORMANCE PREDICTION

R. J. PARKER

Mar. 1986 See Also (N84-18654)

LEW-14163

Vol. 9, No. 4, P. 150

Parameter called lubricant percent volume or cavity factor (XCAV) used primarily in calculation of ball or roller drag and, therefore, significantly affects calculated bearing-heat generation and temperature distribution. New equation accounts for sensitivity of XCAV to shaft speed, lubricant flow rate, and bearing size, and provides significant improvement over previous estimation methods.

B85-10540

THREE-DIMENSIONAL, SUBSONIC, TURBULENT JUNCTURE REGION FLOW

A. J. BAKER (Computational Mechanics Consultants), P. D. MANHARDT (Computational Mechanics Consultants),

and J. A. ORZECOWSKI (Computational Mechanics Consultants)

Mar. 1986

LAR-13263

Vol. 9, No. 4, P. 150

CMC3DPNS predicts three-dimensional, subsonic, turbulent aerodynamic juncture region flow. Versatile program for comprehensive flow-field analysis applies finite-element methodology to nonlinear field problems. Order-of-magnitude analysis of subsonic, three-dimensional, steady time-averaged Navier-Stokes equations for semibounded aerodynamic juncture geometries yields parabolic Navier-Stokes equations. CMC3DPNS solves these equations to predict juncture-region flow.

B85-10541

ZERO-LIFT WAVE DRAG OF COMPLEX AIRCRAFT CONFIGURATIONS

C. B. CRAIDON

Mar. 1986

LAR-13223

Vol. 9, No. 4, P. 150

WAVDRAG calculates supersonic zero-lift wave drag of complex aircraft configurations. Numerical model of aircraft used throughout design process from concept to manufacturing. Incorporates extended geometric input capabilities to permit use of more accurate mathematical model. Engineer defines aircraft components as fusiform or nonfusiform in terms of traditional parallel contours or nonintersecting contours in any direction. Laterally asymmetric configurations simulated. WAVDRAG calculates total drag and wave-drag coefficient of specified aircraft configuration.

07 MACHINERY

B85-10103

SIMULATING PRESSURE EFFECTS OF HIGH-FLOW VOLUMES

M. KAUFMAN (Rockwell International Corp.)

Jun. 1985

MFS-19909

Vol. 9, No. 1, P. 126

Dynamic test stresses realized without high-volume pumps. Assembled in Sections in gas-flow passage, contoured mandrel restricts flow rate to valve convenient for testing and spatially varies pressure on passage walls to simulate operating-pressure profile. Realistic test pressures thereby achieved without extremely high flow volumes.

B85-10104

LOW-LOSS FUEL AND OXIDIZER INJECTOR

G. L. PRAGEMAU

Jun. 1985

MFS-25989

Vol. 9, No. 1, P. 127

Pressure losses reduced without degrading combustion stability. Injection Posts form forest in cavity between oxygen manifold and secondary faceplate. Cavity is fuel manifold; fuel floods post forest and enters each post through side holes in shroud. Injector designed for improved assembly and maintenance. Posts accessible from primary combustion chamber side and changed for flow adjustment.

B85-10105

CONTINUOUSLY VARIABLE TRANSMISSION

D. C. GRANA

Jun. 1985

LAR-12844

Vol. 9, No. 1, P. 128

Chain slides along two cones, in novel transmission concept. Transmission includes chain drive between two splined shafts. Chain sprockets follow surfaces of two cones.

As one chain sprocket moves toward smaller diameter other chain sprocket moves toward larger diameter, thereby changing 'gear' ratio. Movement initiated by tension applied to chain by planetary gear mechanism. Device positive, simple, and efficient over wide range of speed ratios.

B85-10106

SPILL-DETECTOR-AND-SHUTOFF DEVICE

M. R. JARVIS (University of Illinois) and D. S. FULTON (University of Illinois)
Jun. 1985

MSC-20206

Vol. 9, No. 1, P. 129

Overflow in liquid chromatography systems rapidly detected and stopped. Spill-detector-and-shutoff device incorporated into liquid-chromatography system. When liquid from output nozzle spills on liquid sensor, device automatically shuts off pump and releases solenoid to pinch off flow in tube. Device uses common type of alarm circuit reset manually before normal operation resumes.

B85-10107

RECIPROCATING MAGNETIC REFRIGERATOR

D. L. JOHNSON (CALTECH)
Jun. 1985

NPO-16257

Vol. 9, No. 1, P. 130

Unit cools to 4 K by adiabatic demagnetization. Two porous matrices of paramagnetic material gadolinium/gallium/garnet held in long piston called displacer, machined out of Micarta (phenol formaldehyde polymer). Holes in side of displacer allow heat-exchange fluid to flow to and through matrices within. Piston seals on displacer prevent substantial mixing of fluid in two loops. Magnetic refrigerator provides continuous rather than 'one-shot' cooling.

B85-10108

FLUSHING RING FOR EDM

L. EARWOOD (Rockwell International Corp.)
Jun. 1985

MFS-19876

Vol. 9, No. 1, P. 131

Removing debris more quickly lowers cutting time. Operation, cutting oil and pressurized air supplied to ring placed around workpiece. Air forces oil through small holes and agitates oil as it flows over workpiece. High flow rate and agitation dislodge and remove debris. Electrical discharge removes material from workpiece faster.

B85-10109

BACK-PRESSURE REGULATOR FOR LARGE GAS FLOWS

E. A. THEODORE (Rockwell International Corp.) and F. CHIN (Rockwell International Corp.)
Jun. 1985

MSC-20536

Vol. 9, No. 1, P. 131

Cost reduced, and safety enhanced. Pipe exit partially obstructed by conical throat plug. When pressure in pipe falls below (or rises above) desired back pressure, plug automatically moved in (or out). Applications of system lie in environmental testing or production facilities requiring large gas flows at low pressures.

B85-10110

AIR BEARING FOR SMALL PLANAR VIBRATIONS

M. F. WOLF (Stanford University)
Jun. 1985

MFS-26003

Vol. 9, No. 1, P. 132

Air-cushion device provides vibrations along axes 90 degrees apart. Bearing includes movable slide sandwiched between two fixed support plates. Separation between plates adjusted to standard air-bearing tolerances. Pressurized air supplied to slide so it floats between plates on cushion of air. Air exhausts on top and bottom surfaces of three arms of slide. Developed for stirring crystal-growth liquids in containers.

B85-10111

QUASI-POROUS PLUG WITH VORTEX CHAMBER

J. V. WALSH (CALTECH)

Jun. 1985

NPO-16076

Vol. 9, No. 1, P. 133

Pressure-letdown valve combines quasi-porous-plug and vortex-chamber in one controllable unit. Valve useful in fossil-energy plants for reducing pressures in such erosive two-phase process streams as steam/water, coal slurries, or combustion gases with entrained particles. Quasi-Porous Plug consists of plenums separated by perforated plates. Number or size of perforations increases with each succeeding stage to compensate for expansion. In Vortex Chamber, control flow varies to control swirl and therefore difference between inlet and outlet pressures.

B85-10112

HINGED-BLADE, VERTICAL-SHAFT WINDMILL

B. SHULTZ JR.
Jun. 1985

MFS-25980

Vol. 9, No. 1, P. 134

Vertical-shaft windmill concept calls for hinged, flapping blades to increase energy-conversion efficiency by reducing wind-energy loss. Hinged Blade Halves unfold to catch wind when moving with it, then fold away from wind when moving against it.

B85-10113

FASTENING PARTS HAVING MISMATCHED THERMAL COEFFICIENTS

L. R. JACKSON, R. C. DAVIS, A. H. TAYLOR, R. R. MCWITHEY, and M. L. BLOSSER
Jun. 1985

LAR-13009

Vol. 9, No. 1, P. 137

Fastener eliminates thermal stresses and maintains snug fit. Conical-head bolt and metal washer main components of fastener that keeps constant tension on carbon/carbon parts regardless of thermal stress. Fastener used in cases where fastened parts have unmatched thermal expansion coefficients. Does not become looser or tighter as conventional bolts and nuts or rivets do at elevated temperatures.

B85-10114

PERFORMANCE IMPROVEMENT FOR NONAXISYMMETRIC NOZZLES

B. L. BERRIER
Jun. 1985

LAR-13036

Vol. 9, No. 1, P. 138

Internal flow separation eliminated during reverse thrust. Convergent and Divergent Nozzle Flaps rotate to form reverser blocker for reverse-thrust operation. During cruise operation, drums rotate in direction of external flow. During reverse-thrust operation, drums rotate in direction of internal flow. Rotating-drum thrust reverser and boundary-layer control device improves performance of nonaxisymmetric nozzles in three ways: (1) Controls thrust-reverser exhaust port area by elimination of internal flow separation in reverser exhaust port; (2) provides control of reverse-thrust flow direction (exhaust angle); and (3) eliminates external flow separation over nozzle boattail.

B85-10115

AUTOMATIC ERECTION SYSTEM FOR ANTENNA MASTS

R. D. DOTSON (Lockheed Missiles & Space Co.) and G. G. JACQUEMIN (Lockheed Missiles & Space Co.)
Jun. 1985

LAR-13115

Vol. 9, No. 1, P. 139

A telescoping mast does not require the payout of guy wires under tension. Erection system is built into stack of telescoping mast elements and is thereby protected from the weather. Concept is based on a telescoping tube mast, it is also applicable to an open truss with only minor modifications.

B85-10116

LONG-LIFE CRYOGENIC COOLER

A. SHERMAN, M. G. GASSER, P. STUDER, A. DANIELS (North American Philips Corp.), and M. GOLDOWSKY (North

07 MACHINERY

American Philips Corp.)
Jun. 1985

GSC-12697 Vol. 9, No. 1, P. 140

Magnetic bearings and noncontacting seals let cooler operate unattended at 65 K for more than 3 years. New cooler uses magnetic bearings, small piston/cylinder clearance seals, and linear motors. Cooler consists of compression and expansion sections connected end-to-end. Compression section houses reciprocating hollow piston driven by linear motor.

B85-10117

MECHANICAL MIXER FOR RUDDER/BRAKING WEDGE

D. GRIMM (Sundstrand Energy Systems)

Jun. 1985

MSC-20759 Vol. 9, No. 1, P. 141

Right and left rudder panels moved separately. Mechanical mixer enables panels of two-panel rudder to rotate in same direction for steering or in opposite directions for dynamic braking. Steering and braking inputs separate so any combination of steering and braking motions executed simultaneously. Developed for aerodynamic braking of Space Shuttle orbiter, steering/braking drive train and rudder arrangement used for similar purposes on aircraft, thereby reducing sizes of thrust reversers.

B85-10118

WIDE-GRASP LATCHING MECHANISM

M. F. NESMITH

Jun. 1985

MFS-28002 Vol. 9, No. 1, P. 141

Fingers capture and clamp without accurate positioning. Fully open position, fingers encompass large envelope. When activated by rack and pinion, fingertips move together, thereby grasping object within envelope.

B85-10119

CUTTHROUGH WARNING CIRCUIT

R. MCKOWN (Rockwell International Corp.)

Jun. 1985

MFS-19900 Vol. 9, No. 1, P. 142

Damage to underlying layer averted. Contact of cutter blade with metal shim completes circuit that warns cutting-tool operator to stop. Tool thus prevented from cutting into structural wall.

B85-10120

REMOTELY PILOTED AIRCRAFT FOR RESEARCH

T. W. REZEK

Jun. 1985 See Also NASA TM-84913 (N83-27978/NSP)

ARC-11498 Vol. 9, No. 1, P. 143

NASA Technical Memorandum presents overview of remotely-piloted research vehicle (RPRV) activities. Controlled from ground, vehicles allow new concepts tried without subjecting pilots to danger. Critical role of pilot in flight testing with RPRV's demonstrated repeatedly, and many system anomalies uncovered with no risk to human life.

B85-10121

SENSITIVITIES OF SOAP SOLUTIONS IN LEAK DETECTION

D. STUCK (Rockwell International Corp.), D. Q. LAM (Rockwell International Corp.), and C. DANIELS (Rockwell International Corp.)

Jun. 1985

MFS-19864 Vol. 9, No. 1, P. 143

Document describes method for determining minimum leak rate to which soap-solution leak detectors sensitive. Bubbles formed at smaller leak rates than previously assumed. In addition to presenting test results, document discusses effects of joint-flange configurations, properties of soap solutions, and correlation of test results with earlier data.

B85-10233

AUTOMATED COAL-MINING SYSTEM

M. D. GANGAL (Caltech), L. ISENBERG (Caltech), and E. V. LEWIS (Caltech)

Oct. 1985

NPO-16177 Vol. 9, No. 2, P. 128

Proposed system offers safety and large return on investment. System, operating by year 2000, employs machines and processes based on proven principles. According to concept, line of parallel machines, connected in groups of four to service modules, attacks face of coal seam. High-pressure water jets and central auger on each machine break face. Jaws scoop up coal chunks, and auger grinds them and forces fragments into slurry-transport system. Slurry pumped through pipeline to point of use. Concept for highly automated coal-mining system increases productivity, makes mining safer, and protects health of mine workers.

B85-10234

POINTABLE AUGER

E. V. LEWIS (Caltech)

Oct. 1985

NPO-16178 Vol. 9, No. 2, P. 129

Machine drills, crushes, and feeds coal - and seeks out extra-hard inclusions. Auger mounted on gimbal, located at its center of gravity for ease of maneuvering. Opposing hydraulic cylinders cooperate to point auger under control of microprocessor. Its diamond teeth break up coal seam, it crushes coal fed to it by mining machine jaws, and its screw action pushes crushed coal into slurry-forming chamber.

B85-10235

MODULAR PICK-AND-BUCKET MINING MACHINE

M. D. GANGAL (Caltech) and E. V. LEWIS (Caltech)

Oct. 1985

NPO-16179 Vol. 9, No. 2, P. 130

Concept for improved conventional pick-and-bucket mining machine offered as backup for hydrojet-jaw mining machine. Picks on chain dislodge coal and buckets on chain scoop it up. Depending on width cut, unit composed of only two end modules or end modules plus one, two, or three incremental modules. Folding curved shields protect sides of miner from falling coal and rock. Two side stabilizers - extendable hydraulic members anchor miner against lateral drift. Unlike conventional machines, new version tilts cutters vertically and skews them horizontally to changing floor slopes and seam heights.

B85-10236

REDUCING COAL DUST WITH WATER JETS

M. D. GANGAL (Caltech) and E. V. LEWIS (Caltech)

Oct. 1985

NPO-16180 Vol. 9, No. 2, P. 131

Jets also cool and clean cutting equipment. Modular pick-and-bucket miner suffers from disadvantage: Creates large quantities of potentially explosive coal dust. Dust clogs drive chain and other parts and must be removed by hand. Picks and bucket lips become overheated by friction and be resharpened or replaced frequently. Addition of oscillating and rotating water jets to pick-and-bucket machine keeps down dust, cools cutting edges, and flushes machine. Rotating jets wash dust away from drive chain. Oscillating jets cool cutting surfaces. Both types of jet wet airborne coal dust; it precipitates.

B85-10237

SLURRY-MIXING CHAMBER

E. V. LEWIS (Caltech)

Oct. 1985

NPO-16182 Vol. 9, No. 2, P. 132

Paddles and water jets create uniform, continuous flow. Slurry-mixing chamber on hydrojet-jaw mining machine ensures uniform, continuously flowing slurry of coal particles in water. By mixing coal and water at high speed and keeping resulting slurry in constant motion, chamber prevents slurry from becoming dry semisolid that blocks

flow. Also prevents coal particles from settling and caking in bends, corners, and other locations where flow changes in direction or speed.

**B85-10238
ALL-WATER-JET COAL EXCAVATOR**

M. D. GANGAL (Caltech)
Oct. 1985

NPO-16183

Vol. 9, No. 2, P. 133

Version of jaw miner operates without mechanical cutting and crushing. Forward-pointing jets of water dislodge and break up coal. Rearward-pointing jets further break up coal and force particles into slurry chamber. Oscillating-jet mechanism itself stays within 'jaw' structure and protected from wear and tear associated with coal handling. All-jet machine generates even less dust than anger, therefore poses lesser explosion or health hazard.

**B85-10239
COAL-SIZING AUGER**

E. V. LEWIS (Caltech)
Oct. 1985

NPO-16184

Vol. 9, No. 2, P. 134

Aft end of auger, like forward, face-piercing end, equipped with hard cutting bits such as diamonds. As auger breaks face, pulls broken coal lumps into jaws and forces them into hardened throat section. There, cutting bits chew up lumps. Clearance between throat and auger shaft sets maximum size for coal particles that pass through. Auger motion pushes coal particles into mixing chamber, where paddles combine them with water.

**B85-10240
SERVICE MODULES FOR COAL EXTRACTION**

M. D. GANGAL (Caltech) and E. V. LEWIS (Caltech)

Oct. 1985

NPO-16185

Vol. 9, No. 2, P. 134

Service train follows group of mining machines, paying out utility lines as machines progress into coal face. Service train for four mining machines removes gases and coal and provides water and electricity. Flexible, coiling armored carriers protect cables and hoses. High coal production attained by arraying row of machines across face, working side by side.

**B85-10241
SIDE SHIELD FOR WALL SUPPORT**

E. V. LEWIS (Caltech)

Oct. 1985

NPO-16188

Vol. 9, No. 2, P. 135

Method employs curved shield on each side of mining machine. In stowed position, shield folded against roof-support columns on one side. In deployed position, shield raised and braced against coal-seam wall by hydraulic cylinder. Shield supports wall until roof and wall properly secured by bolting and cement coating.

**B85-10242
ROOF SHIELD FOR ADVANCE AND RETREAT MINING**

E. V. LEWIS (Caltech)

Oct. 1985

NPO-16189

Vol. 9, No. 2, P. 136

Shield sections change their configuration to suit mining mode. Articulation cylinders raise rear shield to advance position, and locking cylinders hold it there. To change to retreat position articulation cylinders lower shield. Locking pins at edge of outermost shield plate latch shield to chock base. Shield accommodates roof heights ranging from 36 to 60 inches (0.9 to 1.52 meters).

**B85-10243
COMPACT HYDRAULIC EXCAVATOR AND SUPPORT UNIT**

E. V. LEWIS (Caltech)

Oct. 1985

NPO-16190

Vol. 9, No. 2, P. 136

Continuous-coal-mining machine maneuverable. Hydraulic coal excavator combined with chock, or roof-support structure, in self-contained unit that moves itself forward as it removes coal from seam. Unlike previous such units, new machine compact enough to be easily maneuverable; even makes small-radius right-angle turns.

B85-10244

CURTAIN WALL CREATES VENTILATION CHANNEL

E. V. LEWIS (Caltech)

Oct. 1985

NPO-16194

Vol. 9, No. 2, P. 137

Curtain-wall structure proposed for removing methane and airborne coal dust from hydrojet-jaw mining machines. Channel between curtain wall and mine wall forms closed exhaust passage. Through it, gas and dust continuously removed so high concentrations of these explosive materials not build up.

B85-10245

HOLDER FOR ULTRASONIC EVALUATION OF SMALL-DIAMETER TUBES

E. C. TAYLOR

Oct. 1985

LAR-13152

Vol. 9, No. 2, P. 138

Simple holder eliminates requirement for expensive turntable. Holder works by rotating cylindrical specimens about y-axis. Rotation synchronized with movement of transducer to permit testing without use of turntable. Holder attached to crossmember of scanning bridge with C-clamp. Permits testing of small-diameter tubes rapidly, accurately, and economically. Designed for use with commercially available electromechanical drum-type ultrasonic immersion testing device used for nondestructive evaluation of variety of materials.

B85-10246

IMPROVED HIGHWAY PADS FOR TRACKED VEHICLES

E. R. COLLINS JR. (Caltech)

Oct. 1985

NPO-16318

Vol. 9, No. 2, P. 138

New pads attach faster and hold more securely than conventional pads. Rubber pad held on tread by bent locking tab and by lip that engages recess in tread. Tab hammered in during installation and pried out during removal. New designs ease installation of rubber pads on treads of tracked vehicles to prevent damage to highways. Designs apply to bulldozers, cranes, and excavating machines.

B85-10247

LOW-FRICTION JOINT FOR ROBOT FINGERS

C. F. RUOFF (Caltech)

Oct. 1985

NPO-15914

Vol. 9, No. 2, P. 140

Mechanical linkage allows adjacent parts to move relative to each other with low friction and with no chatter, slipping, or backlash. Low-friction joint of two surfaces in rolling contact, held in alignment by taut flexible bands. No sliding friction or 'stick-slip' motion. Only rolling-contact and bending friction within bands. Proposed linkage intended for finger joints in mechanical hands for robots and manipulators.

B85-10248

BLIND-SIDE, HIGH-TEMPERATURE FASTENER LOCK

E. C. MATZ (Vought Corp.) and D. M. WHILE (Vought Corp.)

Oct. 1985

LAR-13037

Vol. 9, No. 2, P. 140

Formed-in-place staple provides positive mechanical lock. Post-supported, advanced carbon/carbon standoff panels, currently under consideration as alternate thermal protection system for Shuttle orbiter, locking feature applicable to temperatures of 1,600 degrees F (870 degrees C) and higher and employable after panel installed, resulting in blind application. Blind-side locking technique employs

07 MACHINERY

wire staple inserted into grooves in post, formed in place by ramped portion of post grooves. This splays out wire ends that move into castellated end of grommet, mechanically locking post and grommet against relative rotation. Splayed ends provide mechanical lock to prevent wire from falling out.

B85-10249

INSULATING CRYOGENIC PIPES WITH FROST

J. G. STEPHENSON (Rockwell International Corp.) and J. A. BOVA (Rockwell International Corp.)

Oct. 1985

MSC-20426

Vol. 9, No. 2, P. 141

Crystallized water vapor fills voids in pipe insulation. Small, carefully controlled amount of water vapor introduced into dry nitrogen gas before it enters aft fuselage. Vapor freezes on pipes, filling cracks in insulation. Ice prevents gaseous nitrogen from condensing on pipes and dripping on structure, in addition to helping to insulate all parts. Industrial applications include large refrigeration plants or facilities that use cryogenic liquids.

B85-10250

PRECISE ELECTROCHEMICAL DRILLING OF REPEATED DEEP HOLES

J. P. KINCHELOE (Rockwell International Corp.)

Oct. 1985

MFS-19767

Vol. 9, No. 2, P. 142

Tooling enables maintenance of close tolerances. Tooling includes guide that holds electrochemical drilling electrodes in proper relative alignment and guide-positioning fixture clamps directly on reference surfaces of strut. High precision achieved by positioning tooling anew on each strut before drilling: Tolerances of (0.008 mm) maintained in some details.

B85-10251

ADAPTER HELPS TO ALINE PLASMA TORCH

C. A. BROSEMER (Denver Aerospace)

Oct. 1985

MFS-28024

Vol. 9, No. 2, P. 143

Simple adapter allows plasma welding torch aligned accurately on weld seam. Adapter fits over nozzle of torch. Light from pilot arc inside torch passes through central orifice in cone. Light emerges from cone as beam that creates spot of light at point where torch impinges on workpiece. When torch is aligned with work, adapter is removed, plasma arc struck, and welding proceeds.

B85-10252

THERMAL SHOCK-RESISTANT COMPOSITE CRUCIBLE

H. J. GERINGER and R. W. JECK

Oct. 1985

LEW-14105

Vol. 9, No. 2, P. 143

Heating rates of 350 degrees F per minute have not caused cracking. Surrounding inner crucible is annulus of loosely packed alumina powder, which serves as compressible insulating material. Second annulus consisting of section of fused-quartz tubing surrounds and retains alumina powder. Quartz tube held in place by refractory cement helps to contain alumina powder. Small holes in upper ring of cement allow alumina powder to outgas during operation in vacuum. Originally intended for use in Chill Block Melt Spinning (CBMS) apparatus, crucible adaptable to other operations involving rapid self-induction heating of metallic charges.

B85-10253

MINIATURE ROCKET MOTOR FOR AIRCRAFT STALL/SPIN RECOVERY

M. H. LUCY

Oct. 1985

LAR-13199

Vol. 9, No. 2, P. 144

Design accommodates different thrust levels and burn times with minimum weight. Different thrust levels achieved by substituting other propellants of different diameter and

burn-rate characteristics. Different burn times achieved by simply changing length of grain/tube assembly. Grain bond material also acts as insulator for fiberglass tube. Rocket motor attached to aircraft model and ignited from radio-controlled 4.8-volt power source. Device provides more than twice energy available in previous designs at only 60 percent of weight. Rocket motor used to identify energy requirements for aircraft stall/spin recovery positive propulsion system.

B85-10254

SHAFT SEAL COMPENSATES FOR COLD FLOW

W. N. MYERS and L. A. HEIN

Oct. 1985

MFS-25678

Vol. 9, No. 2, P. 145

Seal components easy to install. Ring seal for rotating or reciprocating shafts spring-loaded to compensate for slow yielding (cold flow) of sealing material. New seal relatively easy to install because components preassembled, then installed in one piece.

B85-10255

IMPROVED EXHAUST DIFFUSER FOR JET-ENGINE TESTING

P. G. PARIKH (Caltech) and V. S. SAROHA (Caltech)

Oct. 1985

NPO-16328

Vol. 9, No. 2, P. 146

High-altitude simulator reduced power requirements. Test cell uses its exhaust-capture duct only to remove gases from engine; cooling air evacuated through separate path by auxiliary suction system. This way, capture duct cross-sectional area kept close to exhaust jet area, leading to greatly improved recovery performance.

B85-10256

GRADUALLY ACTING SHAFT STOP

D. J. LANG (Sundstrand Energy Systems)

Oct. 1985

MSC-20729

Vol. 9, No. 2, P. 147

Mechanism brakes rotation with minimal shock. Balls rising on spiral ramp generate large axial force on brake friction plates, thereby generating large braking torque. Counter triggers rise of ball. Brake used to automatically stop control mechanisms on aircraft and ships. Serves as spindle brake on machine tool. On robot, prevents overtravel of arm or holds it in fixed position.

B85-10257

HAND-HELD POWER CLAMP

J. P. CLANCY (McDonnell Douglas Corp.)

Oct. 1985

MSC-20549

Vol. 9, No. 2, P. 147

Tool furnishes large pushing or pulling forces. Device includes two clamping blocks, two clamping plates, and a motor-driven linear actuator with selflocking screw shaft. Power clamp exerts opening or closing force at push of switch. Tool approximately 1 m long. Originally designed to secure payload aboard Space Shuttle, operated with one hand to apply opening or closing force of up to 1,000 lb (4,400 N). Clamp has potential applications as end effector for industrial robots and in rescue work to push or pull wreckage with great force.

B85-10258

ANVIL FOR FLARING PCB GUIDE PINS

E. WINN (Sperry Flight Systems Corp.) and R. TURNER (Sperry Flight Systems Corp.)

Oct. 1985

MSC-20345

Vol. 9, No. 2, P. 148

Spring-loaded anvil results in fewer fractured pins. New anvil for flaring guide pins in printed-circuit boards absorbs approximately 80 percent of press force. As result fewer pins damaged, and work output of flaring press greatly increased.

B85-10259

EFFECTS OF BEARING CLEARANCE ON TURBOPUMP STABILITY

(Innovator Not Given) (Control Dynamics Co.) Oct. 1985 See Also N84-19814

MFS-27063

Vol. 9, No. 2, P. 148

Effects of bearing clearances, or 'dead bands,' on bearing loads and rotor stability in turbopumps examined in a 194-page report. Relatively simple mathematical force model for analyzing effects highlighted. Report shows nonlinear characteristics resulting from bearing dead bands have significant effect on dynamics of turbomachinery and not ignored as in the past.

B85-10260

OPTIMIZING LOAD SPECTRA FOR GEARS

S. P. P. OYOUNG (Sundstrand Energy Systems) and W. L. CARSON (University of Missouri)

Oct. 1985

MSC-20487

Vol. 9, No. 2, P. 149

Life expectancy of gear systems extended. NASA document presents algorithm for gear-load-spectrum synthesis (GLSS) as aid in choosing best load spectrum for machine containing gears. Objective of GLSS: Determine best schedule or combination of load elements-one that yields longest possible fatigue life for machine.

B85-10261

PREDICTING LEAKAGE IN LABYRINTH SEALS

G. L. MORRISON (Texas A & M University), D. L. RHODE (Texas A & M University), K. C. COGAN (Texas A & M University), D. CHI (Texas A & M University), and J. DEMKO (Texas A & M University)

Oct. 1985

MFS-27051

Vol. 9, No. 2, P. 149

Analytical and empirical methods evaluated. 264-page report presents comprehensive information on leakage in labyrinth seals. Summarizes previous analyses of leakage, reviews leakage tests conducted by authors and evaluates various analytical and experimental methods of determining leakage and discusses leakage prediction techniques.

B85-10262

EXPERIMENTS WITH A MANIPULATOR SENSOR SYSTEM

A. K. BEJCZY (Caltech), R. S. DOTSON (Caltech), J. W. BROWN (Johnson Space Center), and J. L. LEWIS (Johnson Space Center)

Oct. 1985

NPO-16094

Vol. 9, No. 2, P. 149

Force and torque data aid operator. Report describes experiments with system that displays data on forces and torques acting on end effector of remote manipulator. Demonstrated usefulness of display in manipulation tasks with narrow geometric and dynamic tolerances. Such tasks encountered in manufacturing and in operations requiring use of tools.

B85-10263

HYBRID AND ELECTRIC ADVANCED VEHICLE SYSTEMS SIMULATION

R. F. BEACH, R. A. HAMMOND (Boeing Computer Services Co.), and R. K. MCGEHEE (Boeing Computer Services Co.)

Oct. 1985

LEW-13927

Vol. 9, No. 2, P. 150

Predefined components connected to represent wide variety of propulsion systems. Hybrid and Electric Advanced Vehicle System (HEAVY) computer program is flexible tool for evaluating performance and cost of electric and hybrid vehicle propulsion systems. Allows designer to quickly, conveniently, and economically predict performance of proposed drive train.

B85-10264

AUTOMATICALLY-PROGRAMMED MACHINE TOOLS

L. PURVES and N. CLERMAN (Computer Sciences Corp.)

Oct. 1985

GSC-12758

Vol. 9, No. 2, P. 151

Software produces cutter location files for numerically-controlled machine tools. APT, acronym for Automatically Programmed Tools, is among most widely used software systems for computerized machine tools. APT developed for explicit purpose of providing effective software system for programing NC machine tools. APT system includes specification of APT programing language and language processor, which executes APT statements and generates NC machine-tool motions specified by APT statements.

B85-10265

ANALYSIS OF SPIRAL BEVEL GEARING

R. J. DRAGO (Boeing Vertol Co.) and B. R. UPPALURI (Boeing Vertol Co.)

Oct. 1985

LEW-14067

Vol. 9, No. 2, P. 151

Program generalized for automated finite-element-method model generation. Tedious task of finite-element-method (FEM) model preparation greatly reduced by development of preprocessing program for automated model generation. Utility of program, including ability to rapidly evaluate parametric changes, demonstrated for spiral, helical, and spiral bevel gearing. Postprocessing program also developed, aids in review and interpretation of calculated FEM stresses.

B85-10383

CONSTANT-PRESSURE SAWING

G. M. ORRIS (Solarex Corp.) and J. F. GERRETY (Solarex Corp.)

Jan. 1986

NPO-15233

Vol. 9, No. 3, P. 140

Attachment for reciprocating power-saw maintains nearly constant cutting pressure even though kerf length varies. Attachment developed for wire saws used to slice cylindrical silicon ingots into wafers for semiconductor devices. By maintaining constant pressure, attachment helps to ensure smooth, flat, uniform wafers. Principle adaptable to straight, toothed saws as well as to wire saws.

B85-10384

ROTATING CONNECTION FOR ELECTRICAL CABLES

D. R. MANGES

Jan. 1986

GSC-12899

Vol. 9, No. 3, P. 141

Cable reel provides electrical connections between fixed structure and rotating one. Reel carries power and signal lines while allowing rotating structure to turn up to 360 degrees with respect to fixed structure. Reel replaces sliprings. Can be used to electrically connect arm of robot with body. Reel releases cable to rotating part as it turns and takes up cable as rotating part comes back to its starting position, without tangling, twisting, or kinking.

B85-10385

MORE SECURE FASTENING FOR TRACKED-VEHICLE PADS

E. R. COLLINS JR. (Caltech)

Jan. 1986

NPO-16321

Vol. 9, No. 3, P. 142

Method of fastening road pads on tracked vehicles ensures retaining tabs properly installed and less likely to fail from shock or pad squirreling when tracked vehicle turns. No risk squirreling of pad might overcome retaining force of rubber encapsulation or teeth of split-collet fastener shred soft-iron projections on pad shell, causing inadvertent release of pad. Rod extending through track shells and tabs on pad shells includes grooved cams to secure pads.

B85-10386

COMPACT HYBRID AUTOMOTIVE PROPULSION SYSTEM

G. LUPO (Centro Ricerche Fiat S.p.A.)

Jan. 1986

07 MACHINERY

NPO-16117

Vol. 9, No. 3, P. 143

Power train proposed for experimental vehicle powered by internal combustion engine and electric motor. Intended for front-wheel drive automobile, power train mass produced using existing technology. System includes internal-combustion engine, electric motor, continuously variable transmission, torque converter, differential, and control and adjustment systems for electric motor and transmission. Continuously variable transmission integrated into hydraulic system that also handles power steering and power brakes. Batteries for electric motor mounted elsewhere in vehicle.

B85-10387

LANI5 HYDROGEN-ABSORPTION CRYOGENIC SYSTEM
J. A. JONES (Caltech)

Jan. 1986

NPO-16314

Vol. 9, No. 3, P. 144

Hydrogen-absorption refrigerating system provides about 650 mW of cooling at 20 to 29 K in continuous, closed-cycle operation. Three thermally cycled absorbers/desorbers act as compressors. System successfully tested below 29 K for over 1,000 h, while separate room-temperature hydride compressor operated continuously for 6,000 h. Due to lack of moving parts, lifetimes of 10 years or more eventually expected.

B85-10388

PULSED, HYDRAULIC COAL-MINING MACHINE
E. R. COLLINS JR (Caltech)

Jan. 1986

NPO-15859

Vol. 9, No. 3, P. 145

In proposed coal-cutting machine, piston forces water through nozzle, expelling pulsed jet that cuts into coal face. Spring-loaded piston reciprocates at end of travel to refill water chamber. Machine a onecylinder, two-cycle, internal-combustion engine, fueled by gasoline, diesel fuel, or hydrogen. Fuel converted more directly into mechanical energy of water jet.

B85-10389

SYNTHESIS AND OPTIMIZATION OF SPIRAL BEVEL GEARS

F. L. LITVIN (University of Illinois), P. RAHMAN (University of Illinois), and R. N. GOLDRICH (University of Illinois)
Jan. 1986 See Also (N82-25516)

LEW-13920

Vol. 9, No. 3, P. 146

Two mathematical models help in optimizing design of spiral bevel gears. In essence, replace actual generated tooth surface with mathematical conjugate approximation. Tooth surfaces of spiral bevel gears replaced (or approximated) by conjugate tooth surfaces. Surfaces generated by two conical surface's rigidly connected with each other and in linear tangency along common generatrix of tool cones and by conical surface and surface of revolution in linear tangency along circle. Gears have widespread applications in transmission systems of helicopters, airplanes, trucks, automobiles, tanks, and many other machines.

B85-10390

PUNCTURE-TOLERANT HEAT RADIATOR
D. G. ELLIOTT (Caltech)

Jan. 1986

NPO-16401

Vol. 9, No. 3, P. 147

Heat radiator does not lose coolant through small punctures and does not require heavy, cumbersome shielding as protection against punctures. Small holes in radiator cause no outpouring of coolant; only small amount evaporates through hole leaves system. Film of silicone oil flows along interior surface of aluminum shell, transferring much of its heat to shell and outside. Unit provides cooling for 100-kW nuclear powerplant.

B85-10391

DOLLY SWIVEL FOR FORKLIFT

J. T. JONES (Rockwell International Corp.) and P. B.

ARBINO (Rockwell International Corp.)

Jan. 1986

MFS-19866

Vol. 9, No. 3, P. 148

Adapter enables large dolly towed or pushed by forklift truck and swivel on forklift on turns. Adapter prevents dolly from slipping off forks and damaging loads. Swivel adapter rests on forklift and provides pivot for towing dolly.

B85-10392

LIGHTWEIGHT, SWITCHABLE PERISTALTIC PUMP
R. R. BELOW

Jan. 1986

MFS-28059

Vol. 9, No. 3, P. 148

Peristaltic pump moves liquids through 50 or more channels simultaneously. Special feature of pump pressure plates remotely set between idle and operating positions. In new design, unnecessary to preposition pressure plates and, unnecessary to enter pump housing to move plates into operating mode.

B85-10393

BISTABLE ARTICULATED JOINT

N. D. CRAIGHEAD (Lockheed Missiles & Space Co., Inc.), R. J. PRELIASCO (Lockheed Missiles & Space Co., Inc.), and T. D. HULT (Lockheed Missiles & Space Co., Inc.)

Jan. 1986

NPO-16038

Vol. 9, No. 3, P. 149

Joint with four-bar-linkage geometry has following attributes: Springs to fully extended fully folded positions. Automatically locks in its extended position. Joint combines zero backlash, positive locking, and centerline pivoting. Used in folding tool handles, portable antenna booms, and many other deployable structures.

B85-10394

COMPENSATING FOR SHRINKAGE IN MACHINED CERAMICS

L. AGUILAR (Lockheed Missiles & Space Co., Inc.) and B. T. FITCHETT (Lockheed Missiles & Space Co., Inc.)

Jan. 1986

MSC-20684

Vol. 9, No. 3, P. 150

Technique insures machined ceramics shrink to correct dimensions after baked in kiln. New method automatically compensates during machining for shrinkage later, when part baked. Applicable to numerically controlled machines that include provision to adjust for variations in cutting tool size, but do not provide for automatic verification of dimensions of machined parts.

B85-10395

REPLACEABLE TRANSFER TUBE FOR HIGH-PRESSURE CAVITIES

D. SORENSEN (Rockwell International Corp.) and J. RIETDYK (Rockwell International Corp.)

Jan. 1986

MFS-19775

Vol. 9, No. 3, P. 151

Set of fittings allows fluid injected into inner chamber, passing through two cavities containing fluids at different high pressures. Injection tube readily replaced, and fittings provide tight seal between cavities after replacement. Tube and fittings made from off-the-shelf parts, and familiar to workers and relatively inexpensive.

B85-10396

HEAT-POWERED PUMP FOR LIQUID METALS

R. J. CAMPANA (GA Technologies)

Jan. 1986

NPO-16457

Vol. 9, No. 3, P. 152

Proposed thermoelectromagnetic pump for liquid metal powered by waste heat; needs no battery, generator, or other external energy source. Pump turns part of heat in liquid metal into pumping energy. In combination with primary pump or on its own, thermoelectric pump circulates coolant between reactor and radiator. As long as there is decay heat to be removed, unit performs function.

**B85-10397
FORBIDDEN ZONES FOR NUMERICALLY-CONTROLLED
MACHINE TOOLS**

D. PHILPOT (Rockwell International Corp.)

Jan. 1986
MFS-19950

Vol. 9, No. 3, P. 153

Computer-controlled machine tool prevented from striking and damaging protruding members on workpiece by creating forbidden zone in control program. With aid of computer graphics, tool profile and coordinates of forbidden zone digitized and stored in computer memory as part of tool path.

**B85-10398
DRILLING HOLES IN GRAPHITE/EPOXY COMPOSITES**

J. G. DANIELS, F. E. LEDBETTER, B. G. PENN, and W. L. WHITE

Jan. 1986
MFS-28044

Vol. 9, No. 3, P. 153

Slurry of silicon carbide powder in water fed onto bit while drilling. Slurry contains about 60 percent silicon carbide by weight. Slurry recirculated by low-power pump. With slurry, dull tools cut as fast as, or faster than, sharp ones. Holes drilled rapidly and efficiently regardless of ply orientation; whether unidirectional, quasi-isotropic symmetrical, or cross-ply.

**B85-10399
MULTISTAGE PLANETARY POWER TRANSMISSIONS**

G. B. HADDEN (SKF Industries, Inc.), G. J. DYBA (SKF Industries, Inc.), M. A. RAGEN (SKF Industries), R. J. KLECKNER (SKF Industries), and L. SHEYNIN (SKF Industries)

Jan. 1986
LEW-14100

Vol. 9, No. 3, P. 154

PLANETSYS simulates thermomechanical performance of multistage planetary performance of multistage planetary power transmission. Two versions of code developed, SKF version and NASA version. Major function of program: compute performance characteristics of planet bearing for any of six kinematic inversions. PLANETSYS solves heat-balance equations for either steady-state or transient thermal conditions, and produces temperature maps for mechanical system.

**B85-10400
THREE-DIMENSIONAL TURBOMACHINE-BLADE-ROW
ANALYSIS CODE**

A. J. GLASSMAN and J. R. WOOD

Jan. 1986
LEW-14061

Vol. 9, No. 3, P. 154

Computer program (MERNEW3D) developed that prepares bulk of input data set required for Denton three-dimensional inviscid turbomachine-blade-row analysis code. Denton input generated from minimum of geometry and flow-variable information by using cubic spline curve fits for interpolation and extrapolation. Curve-fitting procedures taken from previously developed and widely used NASA computer program (MERIDL), which performs meridional streamsurface analysis.

**B85-10401
PREDICTING THE DYNAMIC BEHAVIOR OF HIGH-SPEED
ROLLER BEARINGS**

T. F. CONRY (University of Illinois)

Jan. 1986
LEW-13467

Vol. 9, No. 3, P. 155

Computer program developed for solving nonlinear differential equations of motion of high-speed, lightly loaded, cylindrical roller bearing. Program organized into three major parts: Main program, controls input and output; differential equation solver; and subroutines, used to evaluate vector function. Program has capability of performing either twodimensional or three-dimensional simulation.

**B85-10402
OFF-DESIGN PERFORMANCE OF RADIAL-INFLOW
TURBINES**

P. L. MEITNER and A. J. GLASSMAN

Jan. 1986
LEW-14060

Vol. 9, No. 3, P. 155

Computer code determines rotor exit flow from hub to tip. RTOD (Radial Turbine Off-Design), computes off-design performance of radial turbine by modeling flow with stator viscous and trailing-edge losses, and with vaneless space loss between stator and rotor, and with rotor incidence, viscous, clearance, trailing-edge, and disk friction losses.

**B85-10542
PUMPED, TWO-PHASE HEAT-TRANSFER LOOP**

F. EDELSTEIN (Grumman Aerospace Corp.)

Mar. 1986
MSC-20841

Vol. 9, No. 4, P. 152

Two-phase heat-transfer system delivers coolant to equipment as liquid and removes it as vapor. Alternatively, system heats equipment by delivering vapor and removing condensed liquid. Two-phase scheme effective for heat transfer over long distances. Heat-transfer plates remove heat from or supply heat to equipment. If temperature of plate is high, valve opens liquid-supply line to plate, and cooling results. If plate temperature is low, valve opens liquid-suction line to plate, and heating ensues.

**B85-10543
HYDROGEN REFRIGERATOR WOULD COOL BELOW 10
K**

J. A. JONES (Caltech)

Mar. 1986
NPO-16393

Vol. 9, No. 4, P. 153

Closed-cycle hydrogen refrigerator uses low-level heat energy to cool objects to temperature of 10 K. Refrigerator needs only fraction of energy of previous equipment with similar low-temperature capability. Unit compact and light in weight. With valves as only moving parts, reliable for many years. Refrigeration concept adapted to cooling superconducting magnets on magnetically levitated railcars, nuclear-particle accelerators, and variety of other cryogenic equipment.

**B85-10544
AGGLOMERATION-FREE DISTRIBUTOR FOR FLUIDIZED
BEDS**

F. OUYANG (Institute of Chemical Metallurgy), A. SINICA (Oregon State University), and O. LEVENSPIEL (Oregon State University)

Mar. 1986
NPO-16466

Vol. 9, No. 4, P. 154

New gas distributor for fluidized beds prevents hot particles from reacting on it and forming hard crust. In reduction of iron ore in fluidized bed, ore particles do not sinter on distributor and perhaps clog it or otherwise interfere with gas flow. Distributor also relatively cool. In fluidized-bed production of silicon, inflowing silane does not decompose until within bed of hot silicon particles and deposits on them. Plates of spiral distributor arranged to direct incoming gas into spiral flow. Turbulence in flow reduces frequency of contact between fluidized-bed particles and distributor.

**B85-10545
ADJUSTABLE-ANGLE DRILL BLOCK**

F. H. GALLIMORE (McDonnell Douglas Corp.)

Mar. 1986
LAR-13101

Vol. 9, No. 4, P. 154

Adjustable angular drill block accurately transfers hole patterns from mating surfaces not normal to each other. Block applicable to transfer of nonperpendicular holes in mating contoured assemblies in aircraft industry. Also useful in general manufacturing to transfer mating installation holes to irregular and angular surfaces.

07 MACHINERY

B85-10546

ROTARY JOINT FOR HEAT TRANSFER

R. SHAUBACK (Thermacore, Inc.)

Mar. 1986

MFS-26015

Vol. 9, No. 4, P. 155

Rotary joint exchanges heat between two heat pipes - one rotating and one stationary. Joint accommodates varying heat loads with little temperature drop across interface. According to concept, heat pipe enters center of disklike stationary section of joint. There, wicks in central artery of heat pipe separate into multiple strands that lead to concentric channels on rotary interface side of stationary disk. Thin layer of liquid sodium/potassium alloy carries heat from one member of rotary joint to other. Liquid conducts heat efficiently while permitting relative motion between members. Polypropylene rings contain liquid without interfering with rotation.

B85-10547

CARBON/CARBON PISTONS FOR INTERNAL COMBUSTION ENGINES

A. H. TAYLOR

Mar. 1986

LAR-13150

Vol. 9, No. 4, P. 156

Carbon/carbon piston performs same function as aluminum pistons in reciprocating internal combustion engines while reducing weight and increasing mechanical and thermal efficiencies of engine. Carbon/carbon piston concept features low piston-to-cylinder wall clearance - so low piston rings and skirts unnecessary. Advantages possible by negligible coefficient of thermal expansion of carbon/carbon.

B85-10548

CALCULATING FLOW-ANGLE DEVIATION IN ROTARY PUMPS

S. Y. MENG (Rockwell International Corp.) and R. B. FURST (Rockwell International Corp.)

Mar. 1986

MFS-29062

Vol. 9, No. 4, P. 157

New mathematical formula calculates difference between angle of impeller blade and angle of flow. Formula used for inducers of mixed-flow pumps. With formula, calculations made more quickly and accurately than previously available formulas.

B85-10549

ROUGH/SMOOTH ROTARY SEAL

W. C. CHEN (Rockwell International Corp.) and E. D. JACKSON (Rockwell International Corp.)

Mar. 1986

MFS-19947

Vol. 9, No. 4, P. 157

Rotary seal for turbopump combines low leakage of labyrinth seal with high load capacity of smooth-surface annular seal. New seal acts as strong journal bearing that provides high stiffness - about same as that of ball bearings for turbopump shaft. Seal shares load with ball bearings and prolongs their lives. At same time, seal allows minimal leakage of fluid from pump. By combining leakage control and bearing functions, seal makes multiple seals unnecessary and allows compact design.

B85-10550

PERISTALTIC PUMP WITH A STABLE OUTPUT

J. A. CHANDLER

Mar. 1986

MSC-20907

Vol. 9, No. 4, P. 158

Proposed design for peristaltic pump decreases flow-rate change that results from loss of elasticity. Instead of tubing, new pump uses special flexible liner as pumping channel. Liner molded as single piece of flexible plastic with helical internal channels. Three rollers move around inner wall of liner, compressing channels and forcing liquid before constrictions. As rollers move on, channels open elastically, drawing in liquid from inlet port and making it available when rollers return.

B85-10551

SYSTEMS ENGINEERING OF ELECTRIC AND HYBRID VEHICLES

D. W. KURTZ (Caltech) and R. R. LEVIN (Caltech)

Mar. 1986

NPO-15871

Vol. 9, No. 4, P. 159

Technical paper notes systems engineering principles applied to development of electric and hybrid vehicles such that system performance requirements support overall program goal of reduced petroleum consumption. Paper discusses iterative design approach dictated by systems analyses. In addition to obvious performance parameters of range, acceleration rate, and energy consumption, systems engineering also considers such major factors as cost, safety, reliability, comfort, necessary supporting infrastructure, and availability of materials.

B85-10552

VIBRATIONAL EFFECTS OF TURBOPUMP HOUSING FLEXIBILITY

J. R. FENWICK (Rockwell International Corp.) and R. B. TARN (Rockwell International Corp.)

Mar. 1986 See Also (N84-33811)

MFS-27083

Vol. 9, No. 4, P. 160

Methods of computer simulation of turbopump vibrations described in report. For aircraft and aerospace service, high-speed, high-performance turbomachinery should be as light in weight as possible. Certain amount of mass needed in turbomachine housing for stiffness. Report addresses question of how much extra weight is necessary. Analyses shows under certain conditions, flexible housing more stable than rigid one.

B85-10553

DYNAMIC EFFECTS OF INTERNAL SPUR-GEAR DRIVES

A. PRINTZ (Cleveland State University), R. KASUBA (Cleveland State University), J. L. FRATER (Cleveland State University), and R. AUGUST (Cleveland State University)

Mar. 1986

LEW-14167

Vol. 9, No. 4, P. 161

Set of computer programs developed for studying dynamic effects of internal spur-gear drives. New analysis procedure used for gear combinations leading up to and exceeding 'very high contact ratio' (VHCR) of three. Parametric studies with new computer programs revealed impressive list of advantages of internal spur-gear drives over external spur-gear drives.

08 FABRICATION TECHNOLOGY

B85-10122

HYBRID CONTACTLESS HEATING AND LEVITATION

M. C. LEE (CALTECH)

Jun. 1985

NPO-15657

Vol. 9, No. 1, P. 144

Acoustic and electromagnetic fields applied. In contactless processing apparatus, acoustic and electromagnetic levitating fields employed alternately or simultaneously with amplitude of each controlled to produce various combinations of heating, cooling, and levitation. Apparatus provides rapid heating and cooling or slow heating and cooling for such processes as nucleation, crystallization, incubation, deep undercooling, and heterogeneity control.

B85-10123

PHOTOVOLTAIC-PANEL LAMINATOR

R. KEENAN (Arco Solar, Inc.)

Jun. 1985

NPO-16092**Vol. 9, No. 1, P. 145**

Two-piece unit heats and presses protective layers to form laminate. Rubber diaphragm between upper and lower vacuum chambers alternates between neutral position and one that presses against solar-cell array, supplying distributed force necessary to press layers of laminate together. Encapsulation helps to protect cells from environment and to ensure long panel life while allowing efficient generation of electricity from Sunlight.

B85-10124**SERIES CONNECTION OF SOLAR CELLS**

R. KEENAN (Arco Solar, Inc.)

Jun. 1985

NPO-16091**Vol. 9, No. 1, P. 145**

Roll soldering from continuous string of cells. Automatic, continuous process attaches interconnecting strips to series string of silicon solar cells. Manufacturing process attaches each conductor from positive side of one cell to negative side of next. For reliability, 22 contacts are soldered on each side of each cell.

B85-10125**PERFORATING THIN METAL SHEETS**

M. E. DAVIDSON (Hughes Aircraft Co.)

Jun. 1985

ARC-11280**Vol. 9, No. 1, P. 146**

Sheets only few mils thick bonded together, punched, then debonded. Three-step process yields perforated sheets of metal. (1): Individual sheets bonded together to form laminate. (2): laminate perforated in desired geometric pattern. (3): After baking, laminate separates into individual sheets. Developed for fabricating conductive layer on blankets that collect and remove ions; however, perforated foils have other applications - as conductive surfaces on insulating materials; stiffeners and conductors in plastic laminates; reflectors in antenna dishes; supports for thermal blankets; lightweight grille cover materials; and material for mockup of components.

B85-10126**PRECISE FABRICATION OF ELECTROMAGNETIC-LEVITATION COILS**

E. ETHRIDGE, P. CURRERI, J. THEISS, and G. AB-BASCHIAN (University of Florida)

Jun. 1985

MFS-25986**Vol. 9, No. 1, P. 146**

Winding copper tubing on jig ensures reproducible performance. Sequence of steps insures consistent fabrication of levitation-and-melting coils. New method enables technician to produce eight coils per day, 95 percent of them acceptable. Method employs precise step-by-step procedure on specially designed wrapping and winding jig.

B85-10127**SCREW-RETAINING ALLEN WRENCH**

D. GRANETT (CALTECH)

Jun. 1985

NPO-16275**Vol. 9, No. 1, P. 148**

Steadying screws with fingers unnecessary. Crimp in uncompressed spring wire slightly protrudes from one facet of Allen wrench. Compressed spring retains Allen screw. Tool used with Allen-head screws in cramped spaces with little or no room for fingers to hold fastener while turned by wrench.

B85-10128**MAKING STRONGER TWINE WITH MATCHED STRANDS**

W. L. KIRKLAND (West Coast Netting, Inc.)

Jun. 1985

MSC-20444**Vol. 9, No. 1, P. 148**

Higher tensile strength achieved with same production equipment. Strong twine made by using spools in one of two-step manufacturing process. Three primary strands twisted together in opposite direction to form threeply twine. Technique used successfully in manufacture of safety

netting with 600- to 700-lb (2,700- to 3,100-N) tensile strength and 60-ton (54 x 10 to third power kg) tuna seine with area of 86 acres (3.5 x 10 to fifth power m²). Increase in tensile strength of completed twine found experimentally 10 to 12 percent.

B85-10129**UNIVERSAL CABLE BRACKETS**

C. VANVALKENBURGH (Essex Corporation)

Jun. 1985

MFS-26001**Vol. 9, No. 1, P. 149**

Concept allows routing easily changed. No custom hardware required in concept. Instead, standard brackets cut to length and installed at selected locations along cable route. If cable route is changed, brackets simply moved to new locations. Concept for 'universal' cable brackets make it easy to route electrical cable around and through virtually any structure.

B85-10130**BONDED AND BOLTED GRAPHITE/POLYIMIDE COMPOSITE JOINTS**

D. E. SKOUMAL (Boeing Aerospace Co.) and J. B. CUSHMAN (Boeing Aerospace Co.)

Jun. 1985 See Also NASA CR-3601 (N83-16786/NSP)

LAR-13090**Vol. 9, No. 1, P. 150**

Four types of high-temperature joints designed for control surfaces. Design, analysis, and testing performed to develop four types of graphite/polyimide bonded and bolted composite joints for lightly loaded control surfaces on advanced transportation systems that operate at temperatures up to 550 degrees F (288 degrees C).

B85-10131**SPRAY APPLICATION OF RAPIDLY SOLIDIFIED METALS**

H. P. CHU and C. L. STAUGAITIS

Jun. 1985

GSC-12880**Vol. 9, No. 1, P. 150**

Fast and economical process now available. New process applies rapidly solidified (RS) metal coatings to substrates. RS metals made directly from molten material. Have amorphous or microcrystalline structures and yield coatings having superior wear and corrosion resistance. Mixture of RS metal powder and peening particles sprayed from nozzle against surface coated. Powder and peening particles strike surface simultaneously, and impact bonds powder to surface as uniform coating. New process, which employs shot peening, is safe, fast, and inexpensive.

B85-10132**CUTTING GUIDE FOR FIBROUS SHEETS**

A. WARREN, D. (Rockwell International Corp.)

Jun. 1985

MSC-20798**Vol. 9, No. 1, P. 151**

Tool facilitates repetitive cutting of fibrous sheets. Flexible aluminum tape allows metal strips folded back on themselves, exposing fresh material for cutting. More than one strip folded back, and cutting width therefore increased in multiples of strip width. Developed for cutting strips of alumina-fiber matting, tool also used on such materials as felts, textiles, and sheet metals.

B85-10133**COPYBOARD QUICKLY MAKES CLEAN PRINTING PLATES**

W. D. BALANDIS

Jun. 1985

ARC-11365**Vol. 9, No. 1, P. 152**

Vacuum-chuck eliminates glass and sponge artwork support. Vacuum copyboard allows camera-ready original slid on top plate for proper positioning, then holds securely for photography. Bleed valve allows vacuum in copyboard box adjusted for small or large originals. With new copyboard, time-consuming and costly procedures unnecessary.

08 FABRICATION TECHNOLOGY

B85-10266

PRETINNING NICKEL-PLATED WIRE SHIELDS

J. A. IGAWA (TRW, Inc.)

Oct. 1985

MSC-20712

Vol. 9, No. 2, P. 152

Nickel-plated copper shielding for wires pretinned for subsequent soldering with help of activated rosin flux. Shield cut at point 0.25 to 0.375 in. (6 to 10 mm) from cut end of outer jacket. Loosened end of shield straightened and pulled toward cut end. Insulation of inner wires kept intact during pretinning.

B85-10267

HIGH-TEMPERATURE, HIGH-PRESSURE OPTICAL CELLS

R. P. HARRIS, L. R. HOLLAND (University of Alabama), and R. E. SMITH (University of Alabama)

Oct. 1985

MFS-26000

Vol. 9, No. 2, P. 152

Optical cell constructed for measurement of thermal diffusivity of HgCdTe semiconductor by laser pulses. Container allows radiation from laser to enter one side of alloy sample, while allowing lower-energy infrared radiation to leave opposite side of sample so temperature rise read by sensor. Composed entirely of fused silica, cell includes two optical windows joined by tube. Cell withstands 1,000 degrees C cell-operating temperature and contains molten alloy at its 100-atmosphere vapor pressure. Finally, allows alloy to solidify without bursting even though alloy expands on cooling.

B85-10268

MAKING STRUCTURAL MEMBERS FROM WIRE

T. J. DUNN

Oct. 1985

MSC-20175

Vol. 9, No. 2, P. 153

Structural members of any size, consisting of wire gridwork, fabricated onsite. Rigid beam or column formed from intersecting helices and straight members of relatively flexible wire. Wires joined at their intersections: short wire sections between joints therefore approximate sides of rigid triangular structural subunits. Although originally intended for manufacturing large structures in space, technique has potential for use on Earth.

B85-10269

SILICONE-RUBBER STITCHING SEAL

D. S. WANG (Rockwell International Corp.)

Oct. 1985

MSC-20708

Vol. 9, No. 2, P. 154

Fabric products protected from raveling by coating threads and filling stitching holes with silicone rubber. Uncured silicone rubber applied to stitching lines with air-pressurized sealant gun. Next, plastic release film placed on coated side, and blanket flipped over so release film lies underneath. Blanket then bagged and adhesive cured under partial vacuum of about 3.5 psi or under pressure. Applications include balloons, parachutes, ultralight aircraft, sails, rescue harnesses, tents, or other fabric products highly stressed in use.

B85-10270

CENTRIFUGAL GENERATOR OF FILLED SPHERICAL SHELLS

T. G. WANG (Caltech), D. GRANETT (Caltech), and W. M. AKUTAGAWA (Caltech)

Oct. 1985

NPO-16051

Vol. 9, No. 2, P. 155

Centrifugal apparatus produces filled spherical shells for wide range of industrial and scientific applications. Rotating container has radially extending nozzle in which centrifugal force draws liquid shell material from container. Liquid shell material fed from outside container and automatically maintained at fixed level. Along axis of nozzle is tube that connects through rotating seal to source of gas or other

filler material. Material-flow and rotation rates adjusted to change bubble size.

B85-10271

ALINING LARGE CYLINDERS FOR WELDING

J. H. EHL

Oct. 1985

MFS-28001

Vol. 9, No. 2, P. 156

Special tooling aligns and holds internally-stiffened large-diameter cylindrical parts for welding. Alignment brackets attached to strengthening fins on insides of cylindrical tank sections. Jackscrews on brackets raised or lowered to eliminate mismatches between adjacent sections. Tooling substantially reduces costs while allowing more precise control and improved quality.

B85-10272

PROTOTYPE FURNACE FOR AUTOMATIC PRODUCTION OF SILICON RIBBON

C. S. DUNCAN (Westinghouse Electric Corp.) and W. B. STICKEL (Westinghouse Electric Corp.)

Oct. 1985

NPO-16175

Vol. 9, No. 2, P. 156

Single-crystal material grown under precise control. New furnace permits sustained growth of single-crystal silicon ribbon by dendritic-web growth process. Furnace brings together mechanisms necessary for continuous automatic operation.

B85-10273

FABRICATION OF SLENDER STRUTS FOR DEPLOYABLE ANTENNAS

H. G. BUSH, R. M. BLUCK (Lockheed Missiles and Space Co., Inc.), and R. R. JOHNSON (Lockheed Missiles and Space Co., Inc.)

Oct. 1985

LAR-13136

Vol. 9, No. 2, P. 157

High moduli of elasticity potentially achievable. Suited for application in large diameter antennas on orbiting spacecraft. Fabrication process can accurately place dry graphite fibers and overwrap them with aluminum foil, resulting in straight, slender graphite tubes. Graphite fibers pulled out of creoled spools and fed through ceramic eyelets. Spools of aluminum foil mounted on rotating ring and capture graphite fiber as vertical winding machine carriage moves upward. Epoxy resin applied by mechanically spreading epoxy on tetrafluoroethylene mandrel by means of doctor blade attached to carriage.

B85-10274

DUPLICATING CURVED TILE SURFACES FOR PULL TESTING

R. H. SEBENICK (Rockwell International Corp.)

Oct. 1985

MSC-20795

Vol. 9, No. 2, P. 158

Strength of adhesive bonds to fragile objects with complex shapes tested easily with vacuum chucks. In bond-strength test, contact surface of chuck pressed against matching surface of bonded tile. Vacuum line extending through fine bore in chuck creates vacuum at chuck-and-tile interface. Thus, when chuck pulled away, atmospheric pressure tends to push tile away with chuck. If adhesive resists predetermined pull exerted by chuck on tile, bond acceptable. Originally developed for vacuum chucks used on silica tiles attached to outer surface of Space Shuttle orbiter, used to custom-fabricate chuck for specific tile.

B85-10275

ADJUSTABLE LID AIDS SILICON-RIBBON GROWTH

J. P. MCHUGH (Westinghouse Electric Corp.), R. G. STEIDENSTICKER (Westinghouse Electric Corp.), and C. S. DUNCAN (Westinghouse Electric Corp.)

Oct. 1985

NPO-16354

Vol. 9, No. 2, P. 159

Closely-spaced crucible cover speeds up solidification. Growth rate of dendritic-web silicon ribbon from molten

silicon increased by controlling distance between crucible susceptor lid and liquid/solid interface. Lid held in relatively high position when crucible newly filled with chunks of polycrystalline silicon. As silicon melts and forms pool of liquid at lower level, lid gradually lowered.

B85-10276

MAKING GLASS-FIBER-REINFORCED COOLANT TUBES

F. CURTIN (United Technologies Corporation)

Oct. 1985

MSC-20677

Vol. 9, No. 2, P. 159

New use found for heat-shrinkable sleeves. Smooth, noncontaminating channels for transporting cooling water in Space Shuttle Extravehicular-mobility unit made of fiber-glass tubing with aid of heat-shrinkable sleeves. Previously, glass fibers from inner walls of tubes contaminate water.

B85-10277

CONTROLLING SAMPLE ROTATION IN ACOUSTIC LEVITATION

M. B. BARMATZ (Caltech) and J. D. STONEBURNER (Caltech)

Oct. 1985

NPO-15962

Vol. 9, No. 2, P. 160

Rotation of acoustically levitated object stopped or controlled according to phase-shift monitoring and control concept. Principle applies to square-cross-section levitation chamber with two perpendicular acoustic drivers operating at same frequency. Phase difference between X and Y acoustic excitation measured at one corner by measuring variation of acoustic amplitude sensed by microphone. Phase of driver adjusted to value that produces no rotation or controlled rotation of levitated object.

B85-10278

DAMAGE AND REPAIR OF COMPOSITE STRUCTURES

J. W. DEATON

Oct. 1985

LAR-13146

Vol. 9, No. 2, P. 161

NASA technical memorandum reports on research in damage and repair of composite-material structures of types used in airplane. Research includes: Identifying defect areas, determining whether particular kind of damage weakens structure in manner that degrades performance in intended application, developing repair procedures, and testing to demonstrate given repair procedure enables component to serve during remainder of its design life.

B85-10403

HIGH-EFFICIENCY, LOW-WEIGHT POWER TRANSFORMER

J. P. WELSH (Thermal Technology, Inc.)

Jan. 1986 See Also (N83-29596)

LEW-14074

Vol. 9, No. 3, P. 156

Technology for design and fabrication of radically new type of conduction-cooled high-power (25 kVA) lightweight transformer having outstanding thermal and electrical characteristics. Fulfills longstanding need for conduction-cooled transformers and magnetics with low internal thermal resistances. Development techniques limited to conductive heat transfer, since other techniques such as liquid cooling, forced liquid cooling, and evaporative cooling of transformers impractical in zero-gravity space environment. Transformer uniquely designed: mechanical structure also serves as thermal paths for conduction cooling of magnetic core and windings.

B85-10404

COATING A SPHERE WITH EVAPORATED METAL

D. M. STRAYER (Caltech), H. W. JACKSON (Caltech), and J. R. GATEWOOD (Caltech)

Jan. 1986

NPO-16436

Vol. 9, No. 3, P. 158

In vacuum coating apparatus, metal evaporated onto sphere from small source located some distance away. Sphere held in path of metal vapor while rotated about

axis that rocks back and forth. One tilting motion particularly easy to produce is sinusoidal rocking with frequency much lower than rotational frequency. Apparatus developed for coating single-crystal sapphire spheres with niobium.

B85-10405

ECONOMICAL FABRICATION OF LARGE PARABOLIC MIRRORS

R. T. SCHNEIDER (University of Florida), U. H. KURZWEG (University of Florida), and J. D. COX (University of Florida)

Jan. 1986 See Also (N83-23588)

LAR-13139

Vol. 9, No. 3, P. 159

Long-focal-length parabolic mirrors fabricated economically by rotational casting. Technique applies to very large mirrors and incorporates new foam/fiberglass techniques ideal for producing rigid, lightweight mirrors. Process developed to produce mirrors that concentrate Sunlight for solar-pumped laser.

B85-10406

HIGH-QUALITY, THIN-FILM GERMANIUM SINGLE CRYSTALS

R. A. OUTLAW and J. HOPSON, P.

Jan. 1986

LAR-13211

Vol. 9, No. 3, P. 162

Germanium (Ge) has crystallographic characteristics similar to GaAs and compatible with heteroepitaxial growth of GaAs. Further, since efficient heteroface cells already grown on thick Ge single crystals, Ge is excellent substrate candidate for thin-film cells. Required is single-crystal Ge thin film. Method developed for epitaxially growing high-quality 10-um Ge thin films on 100. NaCl substrates by plasma-enhanced chemical-vapor deposition (PECVD) and then separating Ge films by either melt-away or differential-thermal shear stress techniques. Free-standing films used for growth of Al_xGa_{1-x}As/GaAs heteroface cells by similar techniques.

B85-10407

SUPPORTING STRUCTURES FOR FLAT SOLAR-CELL ARRAYS

A. H. WILSON (Caltech)

Jan. 1986 See Also (N81-30558)

NPO-15600

Vol. 9, No. 3, P. 163

Strong supporting structures for flat solar photovoltaic arrays built with such commonly available materials as wood and galvanized steel sheet. Structures resist expected static loads from snow and ice as well as dynamic loads from winds and even Earthquake vibrations. Supporting structure uses inexpensive materials. Parts prefabricated to minimize assembly work in field.

B85-10408

METALIZATION PATTERNS BY THERMAL DECOMPOSITION

B. D. GALLAGHER (Caltech)

Jan. 1986

NPO-16413

Vol. 9, No. 3, P. 163

Metal interconnection pattern deposited on integrated circuit or solar cell economically by thermal decomposition of metallo-organic compound. In proposed process beam from laser or quartz lamp swept over substrate in required metalization pattern; wherever beam impinges on substrate, radiant heat decomposes compound, depositing metal. Process requires less costly equipment and less time than conventional metalization. Process readily adaptable to very-large-scale integrated (VLSI) circuits.

B85-10409

IMPROVED SURFACE OF TITANIUM STRUCTURE


R. C. ECKLUND (McDonnell Douglas Corp.), M. HAYASE (McDonnell Douglas Corp.), and K. K. YASUI (McDonnell Douglas Corp.)

Jan. 1986

LAR-13148

Vol. 9, No. 3, P. 164

Potential tooling pickup not acceptable on sandwich



gates. Encoding and decoding logic implement generator polynomial that defines error-correcting code, and error correction based on algorithm also implemented by logic.

B85-10139
VECTOR LYAPUNOV FUNCTIONS FOR STOCHASTIC INTERCONNECTED SYSTEMS
D. BOUSSALIS (Caltech)

Jun. 1985
NPO-16170

Vol. 9, No. 1, P. 158

Theoretical paper presents set of sufficient conditions for asymptotic and exponential stability with probability 1 for class of stochastic interconnected systems. Theory applicable to complicated, large-scale mechanical or electrical systems, and, for several design problems, it reduces computational difficulty by relating stability criteria to fundamental structural features of system.

B85-10279
FREE-VIBRATION ANALYSIS OF STRUCTURES
K. K. GUPTA (Caltech)

Oct. 1985

NPO-15000

Vol. 9, No. 2, P. 162

Improved numerical procedure more than twice as fast as previous methods. Unified numerical algorithm efficiently solves free-vibration problems of stationary or spinning structures with or without viscous or structural damping. Algorithm used to solve static problems involving multiple loads and to solve quadratic matrix eigenvalue problems associated with finite-dynamic-element structural discretization.

B85-10280
PREDICTION OF COMBUSTION GAS DEPOSIT COMPOSITIONS
F. J. KOHL, B. J. MCBRIDE, F. J. ZELEZNIK, and S. GORDON

Oct. 1985

LEW-14091

Vol. 9, No. 2, P. 162

Demonstrated procedure used to predict accurately chemical compositions of complicated deposit mixtures. NASA Lewis Research Center's Computer Program for Calculation of Complex Chemical Equilibrium Compositions (CEC) used in conjunction with Computer Program for Calculation of Ideal Gas Thermodynamic Data (PAC) and resulting Thermodynamic Data Base (THDATA) to predict deposit compositions from metal or mineral-seeded combustion processes.

B85-10281
DESIGN LANGUAGE FOR DIGITAL SYSTEMS
S. G. SHIVA (University of Alabama)

Oct. 1985

MFS-25352

Vol. 9, No. 2, P. 163

Digital Systems Design Language (DDL) is convenient hardware description language for developing and testing digital designs and for inputting design details into design automation system. Describes digital systems at gate, register transfer, and combinational block levels. DDL-based programs written in FORTRAN IV for batch execution.

B85-10282
MANIPULATION AND DISPLAY OF PANEL-METHOD GEOMETRY
J. F. HALL (Kentron International, Inc.), D. H. NEUHART (Kentron International, Inc.), and K. B. WALKLEY (Kentron International, Inc.)

Oct. 1985

LAR-13224

Vol. 9, No. 2, P. 164

GEOM manipulates and displays any geometry data expressed in Hess format. Provides user with capability to manipulate, modify, and view such geometric configurations interactively. GEOM program and the PAGMS data-base management system written in FORTRAN IV.

B85-10283
ANALYSIS OF SATELLITE COMMUNICATION ANTENNA PATTERNS
Y. RAHMAT-SAMII (Caltech)

Oct. 1985

NPO-16400

Vol. 9, No. 2, P. 164

Computer program accurately and efficiently predicts far-field patterns of offset, or symmetric, parabolic reflector antennas. Antenna designer uses program to study effects of varying geometrical and electrical (RF) parameters of parabolic reflector and its feed system. Accurate predictions of far-field patterns help designer predict overall performance of antenna. These reflectors used extensively in modern communications satellites and in multiple-beam and low side-lobe antenna systems.

B85-10284
AN INTERACTIVE PLOTTING ROUTINE
D. W. BOWDISH (Rockwell International Corp.)

Oct. 1985

MSC-20771

Vol. 9, No. 2, P. 164

Routine called CRTRPM meets needs of applications programmer to plot data in interactive environment on Tektronix graphics terminal. CRTRPM designed specifically for applications where data is viewed and responded to at terminal. CRTRPM produces from one to four grids on terminal screen at one time, with from one to ten plots of X-Y data on each grid. CRTRPM written in FORTRAN V for interactive execution.

B85-10285
PROCESSING DIGITAL IMAGERY DATA
P. K. CONNER, B. G. JUNKIN, M. H. GRAHAM, M. T. KALCIC, and B. R. SEYFARTH

Oct. 1985

MFS-25987

Vol. 9, No. 2, P. 165

Earth Resources Laboratory Applications Software (ELAS) is geobased information system designed for analyzing and processing digital imagery data. ELAS offers user of remotely sensed data wide range of easy to use capabilities in areas of land cover analysis. ELAS system written in FORTRAN and Assembler for batch or interactive processing.

B85-10286
PERSONAL-COMPUTER VIDEO-TERMINAL EMULATOR
R. H. BUCKLEY, A. KOROMILAS (Boeing Services International), R. M. SMITH (Boeing Services International), G. E. LEE (Boeing Services International), and E. W. GIERING (Boeing Services International)

Oct. 1985

KSC-11293

Vol. 9, No. 2, P. 165

OWL-1200 video terminal emulator has been written for IBM Personal Computer. The OWL-1200 is a simple user terminal with some intelligent capabilities. These capabilities include screen formatting and block transmission of data. Emulator is written in PASCAL and Assembler for the IBM Personal Computer operating under DOS 1.1.

B85-10287
STANDARD CODES FOR TELEMETRY AND TELECOMMAND
M. L. MACMEDAN (Caltech)

Oct. 1985

NPO-16305

Vol. 9, No. 2, P. 165

Different systems communicate and development costs reduced. Report discusses efforts to standardize telemetry and telecommand codes of various space programs. Used to detect and correct bit errors in communication channels with low signal-to-noise ratios, codes proliferated in recent years. Each coding/decoding system developed to solve specific problem, but some systems are similar and exhibit similar performance.

B85-10411
CODING FOR ELECTRONIC MAIL

09 MATHEMATICS AND INFORMATION SCIENCES

R. F. RICE (Caltech) and J. J. LEE (Caltech)
Jan. 1986 See Also (N84-16429)

NPO-16350 Vol. 9, No. 3, P. 166

Scheme for coding facsimile messages promises to reduce data transmission requirements to one-tenth current level. Coding scheme paves way for true electronic mail in which handwritten, typed, or printed messages or diagrams sent virtually instantaneously - between buildings or between continents. Scheme, called Universal System for Efficient Electronic Mail (USEEM), uses unsupervised character recognition and adaptive noiseless coding of text. Image quality of resulting delivered messages improved over messages transmitted by conventional coding. Coding scheme compatible with direct-entry electronic mail as well as facsimile reproduction. Text transmitted in this scheme automatically translated to word-processor form.

B85-10412 IMPROVED NUMERICAL EVALUATION METHOD FOR ELLIPTIC INTEGRALS

V. J. ROSSOW

Jan. 1986

ARC-11467 Vol. 9, No. 3, P. 168

Two modifications to Bartky's method for numerical evaluation of complete elliptic integrals increase rate of convergence and eliminate loss of accuracy due to round-off errors. Other integrals (nonelliptic) evaluated by manipulating integrand into form $F(R)/R$ required for evaluation by this method. Improved method used to map upper half of complex plane conformally onto interior of exterior of round-nosed wedges of various angles.

B85-10413 THREE-DIMENSIONAL GRIDS FOR FLOW-FIELD CAL- CULATIONS

P. D. THOMAS (Lockheed Aircraft Co.)

Jan. 1986

ARC-11394 Vol. 9, No. 3, P. 169

New procedure generates boundary-conforming three-dimensional grids suitable for calculating flow fields around bodies with complex shapes. Extension of earlier methods limited to mapping two-dimensional flow regions onto rectangular grids in transformed planes. Technique also useful in solving thermodynamic and electrostatic fields near complex surfaces.

B85-10414 COMPUTING RELATIVE JOINT POSITIONS OF ROBOT ARMS

L. K. BARKER

Jan. 1986 See Also (N83-34661)

LAR-13264 Vol. 9, No. 3, P. 170

Vector-algebra method developed for extracting Denavit-Hartenberg parameters for any assembled robot arm. Method for extracting relative joint geometry of robot arms useful to researchers who need data for existing robot arms for either validation of mathematical models or for studies involving actual control of these devices. Method, does not require robot arm to be disassembled, also useful in recalibration of misaligned or bent robot arm and becomes useful industrial procedure. Merit of method is errors not propagated.

B85-10415 REQUIREMENTS ANALYSIS FOR INFORMATION- INTENSIVE SYSTEMS

E. D. CALLENDER (Caltech), C. HARTSOUGH (Caltech),
R. V. MORRIS (Caltech), and Y. YAMAMOTO (Caltech)

Jan. 1986

NPO-15944 Vol. 9, No. 3, P. 171

Report discusses role of requirements analysis in development of information-intensive systems. System examined from variety of human viewpoints during design, development, and implementation. Such examination, called requirements analysis, ensures system simultaneously meets

number of distinct but interacting needs. Viewpoints defined and integrated to help attain objectives.

B85-10416 CODING FOR EFFICIENT IMAGE TRANSMISSION

R. F. RICE (Caltech) and J. J. LEE (Caltech)

Jan. 1986 See Also (N83-28069)

NPO-16444 Vol. 9, No. 3, P. 171

NASA publication second in series on data-coding techniques for noiseless channels. Techniques used even in noisy channels, provided data further processed with Reed-Solomon or other error-correcting code. Techniques discussed in context of transmission of monochrome imagery from Voyager II spacecraft but applicable to other streams of data. Objective of this type coding to 'compress' data; that is, to transmit using as few bits as possible by omitting as much as possible of portion of information repeated in subsequent samples (or picture elements).

B85-10417 COMPUTATIONAL SIMPLIFICATION OF ROBOT-ARM DYNAMICS

A. K. BEJCZY (Caltech) and S. LEE (Caltech)

Jan. 1986

NPO-16377 Vol. 9, No. 3, P. 172

Report presents two general methods for reducing mathematical complexities of state equations of robot-arm dynamics. Robot arms contain both rotary and linear joints. Both methods start with homogenous coordinates and Lagrangian formulation of mechanics briefly summarized in report. First method uses matrix-analysis techniques; second, vector-analysis techniques. Vector-analysis method includes new differential-vector representation of centripetal and Coriolis forces.

B85-10418 MODAL ANALYSIS AND GAIN ESTIMATION

R. L. JONES

Jan. 1986

LAR-13334 Vol. 9, No. 3, P. 172

Interactive program yields eigenvectors, eigenvalues, and gains for feedback-control systems. Interactive Modal Analysis and Gain Estimation System (IMAGES) provides eigensystem synthesis capability to control-system engineer, IMAGES modular and flexible. Capable of both modal and spectral synthesis of multi-input control systems. IMAGES user-oriented, interactive program that frees engineer to concentrate on eigensystem synthesis. Engineer provided with scratch-pad capability that speeds control-system design.

B85-12419 TEXT EXCHANGE SYSTEM

W. V. SNYDER (Caltech) and R. J. HANSON (Sandia National Laboratories)

Jan. 1986

NPO-16357 Vol. 9, No. 3, P. 173

Text Exchange System (TES) exchanges and maintains organized textual information including source code, documentation, data, and listings. System consists of two computer programs and definition of format for information storage. Comprehensive program used to create, read, and maintain TES files. TES developed to meet three goals: First, easy and efficient exchange of programs and other textual data between similar and dissimilar computer systems via magnetic tape. Second, provide transportable management system for textual information. Third, provide common user interface, over wide variety of computing systems, for all activities associated with text exchange.

B85-10420 SUBSET REGRESSION

A. G. HOLMS

Jan. 1986 See Also (N83-28172)

LEW-14002 Vol. 9, No. 3, P. 173

Backward elimination procedure minimizes prediction

errors of equations fitted to factorial experiments. Problem of minimizing prediction error solved for two-level full- or fractional-factorial experiment with 16 factorial points and 0 to 6 center points. Such experiment provides 16 orthogonal coefficient estimates for empirical polynomial model. Each coefficient estimated with low variance error estimated from 16 observations.

B85-10421
SOLVING LARGE SYSTEMS OF NORMAL EQUATIONS
 B. PUTNEY (Geodynamics Branch)
 Jan. 1986
GSC-12858 Vol. 9, No. 3, P. 173

SOLVE II program combines any number of sets of normal equations and obtains solution vector and related statistics. Normal equations of square, nonnegative definite matrix form. Program utilizes only upper symmetric portion of matrix. Program uses partitioned Cholesky decomposition method for matrix inversion to accommodate large parameter systems.

B85-10422
TRANSPORTABLE APPLICATIONS EXECUTIVE
 M. R. SZCZUR
 Jan. 1986
GSC-12881 Vol. 9, No. 3, P. 174

Transportable Applications Executive (TAE) is collection of 'executive' programs that interact with user to manage execution of application programs. All applications running under TAE have same interface. Since TAE manages entire interactive session, user does not need to know command language of host computer. TAE utilized effectively and efficiently by both first-time user and experienced user. Provides extensive assistance to user at any stage of interactive session.

B85-10423
TEXT FILE DISPLAY PROGRAM
 J. L. VAVRUS (Caltech)
 Jan. 1986
NPO-16358 Vol. 9, No. 3, P. 174

LOOK program permits user to examine text file in pseudorandom access manner. Program provides user with way of rapidly examining contents of ASCII text file. LOOK opens text file for input only and accesses it in blockwise fashion. Handles text formatting and displays text lines on screen. User moves forward or backward in file by any number of lines or blocks. Provides ability to 'scroll' text at various speeds in forward or backward directions.

B85-10424
DATA MANIPULATION AND DISPLAY
 J. R. SZUCH
 Jan. 1986
LEW-14101 Vol. 9, No. 3, P. 174

BDMADS, BASIC Data Manipulation and Display System, is software package that runs on Apple II Plus or IIE personal computer to provide user-friendly environment in which to perform many complex operations on array of numbers.

B85-10425
FLEXIBLE AIRFRAME RESPONSE PROGRAM
 C. LIN (McDonnell Douglas Corp.)
 Jan. 1986
MSC-20762 Vol. 9, No. 3, P. 175

Generalized set of flexible vehicle equations-of-motion (EOM's) developed and incorporated into Flexible Airframe Response (FAR) program. Output from FAR program used in aircraft flight control system design.

B85-10426
UNIVERSAL NOISELESS CODING SUBROUTINES
 A. P. SCHLUTSMAYER (Caltech) and R. F. RICE (Caltech)
 Jan. 1986
NPO-15451 Vol. 9, No. 3, P. 175

Software package consists of FORTRAN subroutines

that perform universal noiseless coding and decoding of integer and binary data strings. Purpose of this type of coding to achieve data compression in sense that coded data represents original data perfectly (noiselessly) while taking fewer bits to do so. Routines universal because they apply to virtually any 'real-world' data source.

B85-10427
TRASYS FOR BEGINNERS
 K. T. SO (Rockwell International Corp.)
 Jan. 1986 See Also (N82-10754)
MSC-20855 Vol. 9, No. 3, P. 175

Self-teaching manual designed for first-time users of TRASYS (Thermal Radiation Analysis System), computer program widely used by engineers involved in thermodynamic analyses. Simpler than full TRASYS manual. Readers need no previous knowledge of program or of FORTRAN language in which it is written. Self-teaching manual gives specific instructions in operation of program and three step-by-step examples.

B85-10558
SYSTEM FOR AUTOMATED TROUBLESHOOTING
 L. FRIEDMAN (Caltech)
 Mar. 1986
NPO-16339 Vol. 9, No. 4, P. 168

New algorithms for diagnosing problems in electromechanical systems based on artificial intelligence techniques used to locate faults with minimal human intervention. After given information on system architecture, electrical connections, types of parts, and failure modes, algorithms apply 'reasoning' processes patterned after those of humans.

B85-10559
GEOMETRIC REPRESENTATIONS FOR DISCRETE FOURIER TRANSFORMS
 C. W. CAMBELL
 Mar. 1986 See Also (N84-24114)
MFS-27072 Vol. 9, No. 4, P. 167

Simple geometric representations show symmetry and periodicity of discrete Fourier transforms (DFT's). Help in visualizing requirements for storing and manipulating transform value in computations. Representations useful in any number of dimensions, but particularly in one-, two-, and three-dimensional cases often encountered in practice.

B85-10560
MAXIMUM-LIKELIHOOD PARAMETER-ESTIMATION ALGORITHM
 D. B. ELDRED (Caltech), M. HAMIDI (Caltech), and G. RODRIGUEZ (Caltech)
 Mar. 1986
NPO-16320 Vol. 9, No. 4, P. 168

Efficient version of maximum-likelihood algorithm devised for calculating normal-mode frequencies and damping parameters of vibrating system from experimental data where both process noise and measurement noise present. Method applicable in vibration analysis of such complicated structures as vehicles, aircraft, and spacecraft. New algorithm simplification of existing maximum-likelihood formulation using Kalman filter that allows for both process and measurement noise.

B85-10561
OPTIMUM CYCLIC REDUNDANCY CODES FOR NOISY CHANNELS
 E. C. POSNER (Caltech) and P. MERKEY (Caltech)
 Mar. 1986
NPO-16406 Vol. 9, No. 4, P. 168

Capabilities and limitations of cyclic redundancy codes (CRC's) for detecting transmission errors in data sent over relatively noisy channels (e.g., voice-grade telephone lines or very-high-density storage media) discussed in 16-page report. Due to prevalent use of bytes in multiples of 8 bits data transmission, report primarily concerned with cases in which both block length and number of redundant bits

09 MATHEMATICS AND INFORMATION SCIENCES

(check bits for use in error detection) included in each block are multiples of 8 bits.

B85-10562

NUMERICAL AERODYNAMIC SIMULATION FACILITY

V. L. PETERSON, W. F. BALLHAUS JR., and F. R. BAILEY
Mar. 1986

ARC-11497

Vol. 9, No. 4, P. 169

NASA numerical aerodynamic simulation (NAS) facility described in 22-page report provides advanced computational aerodynamics service by mid- to late-1980's for use by government laboratories, industry, and academia. Facility continually upgraded as computer technology advances. Facility expected to begin operating by late 1985, supports both local and remote users.

B85-10563

COMPARISON OF DECISION MODELS

A. FEINBERG (Caltech), J. R. F. MILES (Caltech), J. H. SMITH (Caltech), and E. M. SCHEUER (California State University)
Mar. 1986

NPO-16448

Vol. 9, No. 4, P. 175

Two methods of multiattribute decision analysis compared in report. One method employs linear utility model. Other utilizes multiplicative utility model. Report based on interviews with experts in automotive technology to obtain their preferences regarding 10 new types of vehicles.

B85-10564

NUMERICAL METHODS FOR CLASSICAL SAMPLED-SYSTEM ANALYSIS

H. P. FRISCH and F. H. BAUER

Mar. 1986

GSC-12827

Vol. 9, No. 4, P. 176

SAMSAN provides control-system analyst with self-consistent computer algorithms that support large-order control-system design and evaluation studies. Emphasizes sampled-system analysis. SAMSAN reduces burden on analyst by providing set of algorithms well tested and documented and readily integrated for solving control-system problems.

B85-10565

SOFTWARE COMPARISON

D. C. BLANCHARD (McDonnell Douglas Corp.)

Mar. 1986

MSC-20777

Vol. 9, No. 4, P. 176

Software Comparison Package (SCP) compares similar files. Normally, these are 90-character files produced by CDC UPDATE utility from program libraries that contain FORTRAN source code plus identifier. SCP also used to compare load maps, cross-reference outputs, and UPDATE corrections sets. Helps wherever line-by-line comparison of similarly structured files required.

B85-10566

IMAGE-PROCESSING EDUCATOR

F. J. GUNTHER (Computer Sciences Corp.)

Mar. 1986

GSC-12933

Vol. 9, No. 4, P. 177

Apple Image-Processing Educator (AIPE) explores ability of microcomputers to provide personalized computer-assisted instruction (CAI) in digital image processing of remotely sensed images. AIPE is 'proof-of-concept' system, not polished production system. User-friendly prompts provide access to explanations of common features of digital image processing and of sample programs that implement these features.

B85-10567

MANIPULATION OF NUMBERS WITH MANY DIGITS

L. W. HOWELL and M. PATRICK

Mar. 1986

MFS-28048

Vol. 9, No. 4, P. 177

PRECISION designed for manipulation of numbers with

accurate retention of up to thousands of digits per number. Use of PRECISION prevents underflow and overflow in programs that generate extreme numbers such as probability theory, statistics, and scientific applications.

B85-10568

PRINTER GRAPHICS PACKAGE

D. C. BLANCHARD (McDonnell Douglas Corp.)


Mar. 1986

MSC-20778

Vol. 9, No. 4, P. 177

Printer Graphics Package (PGP) is tool for making two-dimensional symbolic plots on line printer. PGP created to support development of Heads-Up Display (HUD) simulation. Standard symbols defined with HUD in mind. Available symbols include circle, triangle, quadrangle, window, line, numbers, and text. Additional symbols easily added or built up from available symbols.

Typical Subject Index Listing



The title of each Tech Brief is listed under several selected subject headings to provide the user with a variety of approaches in his search for specific information. The Tech Brief number, e.g., B85-10260, is located under and to the right of the title and is followed by a two-digit number, e.g., 09, which designates the subject category in which the entire entry can be found.

A

ABERRATION

Designing Eccentric Aperture Optical Systems
NPO-16355 B85-10329 03

ABRASION

Drilling Holes in Graphite/Epoxy Composites
MFS-28044 B85-10398 07

ABSORBENTS

Purifying Water by Imbibition
NPO-16419 B85-10340 04

ABSORPTION SPECTROSCOPY

Monitoring Trace Gases in the Atmosphere
NPO-16278 B85-10175 03

ACCELEROMETERS

Superconducting-Cavity, Accelerometer
GSC-12797 B85-10096 06

ACCESS CONTROL

Synchronizing Data-Bus Messages
MSC-20640 B85-10035 02

ACOUSTIC LEVITATION

Hybrid Contactless Heating and Levitation
NPO-15657 B85-10122 08

Blowing Polymer Bubbles in an Acoustic Levitator
NPO-16212 B85-10203 04

Controlling Sample Rotation in Acoustic Levitation
NPO-15962 B85-10277 08

ACOUSTIC MEASUREMENT

Frequency-Discriminating Acoustic-Event Counter
MSC-20467 B85-10160 02

Miniature Microphone Adapter
LAR-13210 B85-10521 06

ACOUSTIC SOUNDING

Noninvasive Fluid Level Sensor for Organometallic Sources
LAR-13265 B85-10371 06

ADAPTERS

Miniature Microphone Adapter
LAR-13210 B85-10521 06

ADHESION TESTS

Duplicating Curved Tile Surfaces for Pull Testing
MSC-20795 B85-10274 08

ADSORPTION

Adsorption of H₂, Ne, and N₂ on Activated Charcoal
NPO-16329 B85-10477 03

AERODYNAMIC DRAG

Zero-Lift Wave Drag of Complex Aircraft Configurations
LAR-13223 B85-10541 06

AERODYNAMIC STABILITY

Aerodynamic Rear Cone for Trucks
MFS-28007 B85-10217 06

AERODYNAMICS

Three-Dimensional Turbomachine-Blade-Row Analysis Code
LEW-14061 B85-10400 07

Three-Dimensional Grids for Flow-Field Calculations
ARC-11394 B85-10413 09

Numerical Aerodynamic Simulation Facility
ARC-11497 B85-10562 09

AEROEMBOLISM

Effect of Hydration on Nitrogen Washout in Humans
MSC-20686 B85-10087 05

AEROSOLS

Laser-Assisted Analysis of Aerosol Particles
NPO-15308 B85-10056 03

Airborne DIAL System for Remote Tropospheric Sensing
LAR-13002 B85-10178 03

AGING (MATERIALS)

Constitutive Equations of Aging in Polymers
NPO-16480 B85-10503 04

AIR POLLUTION

Detecting Trace Contaminants in the Atmosphere
NPO-16225 B85-10468 03

AIR QUALITY

Detecting Trace Contaminants in the Atmosphere
NPO-16225 B85-10468 03

AIR SAMPLING

Accurate Airborne Particle Sampler
LAR-13080 B85-10219 06

AIRCRAFT CONFIGURATIONS

Zero-Lift Wave Drag of Complex Aircraft Configurations
LAR-13223 B85-10541 06

AIRCRAFT CONTROL

Aircraft Control-Position Indicator
LAR-12984 B85-10020 01

AIRCRAFT ENGINES

Miniature Rocket Motor for Aircraft Stall/Spin Recovery
LAR-13199 B85-10253 07

Microphone Boom for Aircraft-Engine Monitoring
ARC-11495 B85-10525 06

AIRCRAFT HAZARDS

Water-Thickness Gage
LAR-13342 B85-10508 06

AIRCRAFT HYDRAULIC SYSTEMS

Autopilot Servoactuator With Pressurized Detented Centering
LAR-13185 B85-10364 06

AIRCRAFT INSTRUMENTS

Water-Thickness Gage
LAR-13342 B85-10508 06

Shaft Axial-Displacement Sensor
MFS-29048 B85-10519 06

AIRCRAFT LIGHTS

Tester for Distress Beacons
GSC-12892 B85-10442 01

AIRCRAFT MAINTENANCE

Damage and Repair of Composite Structures
LAR-13146 B85-10278 08

AIRCRAFT NOISE

Noise-Path Measurements in Aircraft Structures
LAR-13017 B85-10529 06

AIRCRAFT PERFORMANCE

Flexible Airframe Response Program
MSC-20762 B85-10425 09

AIRCRAFT STRUCTURES

Noise-Path Measurements in Aircraft Structures
LAR-13017 B85-10529 06

AIRFOIL PROFILES

Water-Thickness Gage
LAR-13342 B85-10508 06

AIRFOILS

Airfoil Smoothing and Scaling Programs
LAR-13132 B85-10377 06

ALGORITHMS

Algorithms for Software Development
NPO-16079 B85-10134 09

Compensating for Range Migration in Synthetic-Aperture Radar
NPO-15954 B85-10136 09

Determining Calibration Constants for Attitude Measurements
LAR-13214 B85-10475 03

System for Automated Troubleshooting
NPO-16339 B85-10558 09

Maximum-Likelihood Parameter-Estimation Algorithm
NPO-16320 B85-10560 09

ALIGNMENT

Out-of-Focus Alinement of Solar Concentrators
NPO-15563 B85-10044 03

ALLOWANCES

SUBJECT INDEX

- Adapter Helps To Aline Plasma Torch
MFS-28024 B85-10251 07
- ALLOWANCES**
Effects of Bearing Clearance on Turbopump Stability
MFS-27063 B85-10259 07
- ALLOYS**
Process for Nonequilibrium Ternary Alloys
NPO-16226 B85-10345 04
- ALTERNATING CURRENT**
Program Predicts Nonlinear Inverter Performance
MSC-20769 B85-10172 02
- ALTITUDE SIMULATION**
Laser Altimeter for Flight Simulator
ARC-11312 B85-10323 03
- ALUMINUM**
Purifying Aluminum by Vacuum Distillation
NPO-16114 B85-10065 04
- AMIDES**
Solvent-Resistant, Thermally Stable Poly(Carbonate-Imides)
LAR-13292 B85-10485 04
- AMINES**
Phthalocyanine Tetraamine
Epoxy-Curing Agents
ARC-11424 B85-10348 04
- AMMETERS**
Lowering Ammeter Input Impedance
NPO-16067 B85-10022 01
Power-Factor Controllers: How Safe?
MFS-27016 B85-10024 01
- AMORPHOUS SEMICONDUCTORS**
Plasma Deposition of Doped Amorphous Silicon
NPO-14955 B85-10210 04
- AMPLIFIERS**
Molecular-Beam Chopper and Four-Channel Amplifier
LAR-13174 B85-10316 03
- AMPOULES**
High-Temperature, High-Pressure Optical Cells
MFS-26000 B85-10267 08
- ANALYZERS**
Detecting Trace Contaminants in the Atmosphere
NPO-16225 B85-10468 03
Solid-State Detector for Trace Materials
NPO-16450 B85-10469 03
- ANASTIGMATISM**
Nearly Anastigmatic X-Ray Telescope
MFS-25984 B85-10047 03
- ANCHORS (FASTENERS)**
End Restraints for Impact-Energy-Absorbing Tube Specimens
LAR-13179 B85-10218 06
Blind-Side, High-Temperature Fastener Lock
LAR-13037 B85-10248 07
- ANGULAR RESOLUTION**
Obtaining One-Degree Accuracy With Shaft Encoders
LAR-13321 B85-10431 01
- ANTENNA DESIGN**
Optimizing a Linear Array of Radiating Elements
NPO-16352 B85-10298 01
- Optimization of Antenna-Structure Design
NPO-16158 B85-10299 01
- ANTENNA FEEDS**
Cassegrain-Antenna Gain Improvement
NPO-15775 B85-10433 01
- ANTENNA RADIATION PATTERNS**
Analysis of Satellite Communications Antenna Patterns
NPO-16400 B85-10283 09
- ANTENNAS**
Dual-Mode Horn Antenna for Millimeter Wavelengths
NPO-16297 B85-10006 01
Automatic Erection System for Antenna Masts
LAR-13115 B85-10115 07
Fabrication of Slender Struts for Deployable Antennas
LAR-13136 B85-10273 08
Cassegrain-Antenna Gain Improvement
NPO-15775 B85-10433 01
Measuring Antenna Signal Delays
NPO-15947 B85-10455 02
- ANVILS**
Anvil for Flaring PCB Guide Pins
MSC-20345 B85-10258 07
- APPLICATIONS (COMPUTERS)**
Transportable Applications Executive
GSC-12881 B85-10422 09
- ARC LAMPS**
Power Supply For 25-Watt Arc Lamp
LAR-13202 B85-10141 01
Orienting Arc Lamps for Longest Life
MSC-20562 B85-10155 01
- ARCHITECTURE (COMPUTERS)**
Multiplier Architecture for Coding Circuits
NPO-16363 B85-10456 02
- ARTIFICIAL SATELLITES**
Doubly-Differenced Measurements for Orbit Determinations
NPO-16111 B85-10040 02
- ATMOSPHERIC COMPOSITION**
Nebulization Reflux Concentrator
LAR-13254 B85-10463 03
- ATMOSPHERIC DIFFUSION**
Exhaust Effluent Diffusion Model
MFS-25940 B85-10214 04
- ATMOSPHERIC PRESSURE**
Microwave Atmospheric-Pressure Sensor
NPO-16496 B85-10478 03
- ATMOSPHERIC SCATTERING**
Calculating Atmospheric Effects in Satellite Imagery
NPO-16373 B85-10327 03
Accuracy of Lidar Measurements of the Atmosphere
NPO-16493 B85-10476 03
- ATOMIZERS**
Mass Spectrometer for Airborne Micro-Organisms
NPO-16359 B85-10505 05
- ATOMS**
Intense Source of Polarized Hydrogen Atoms
NPO-16434 B85-10466 03
- AUDITORY DEFECTS**
Telephone Instrument for the Deaf
KSC-11303 B85-10014 01
- AUTOMATIC CONTROL**
Back-Pressure Regulator for Large Gas Flows
MSC-20536 B85-10109 07
- AUTOMATIC GAIN CONTROL**
Wide-Brightness-Range Video Camera
MFS-25750 B85-10301 02
- AUTOMATIC TEST EQUIPMENT**
Online Tester for a Symbol Generator
MSC-20357 B85-10161 02
- AUTOMOBILES**
Compact Hybrid Automotive Propulsion System
NPO-16117 B85-10386 07
- AXIAL FLOW PUMPS**
Peristaltic Pump With a Stable Output
MSC-20907 B85-10550 07

B

- BACKUPS**
Double Light-Emitting Diode
GSC-12832 B85-10015 01
- BACTERIA**
Coculture Production of Butanol by Clostridium Bacteria
NPO-16203 B85-10086 05
- BAFFLES**
Telescope With Reflecting Baffle
ARC-11502 B85-10043 03
- BALANCING**
Microprocessor-Controlled Laser Balancing System
LEW-13294 B85-10093 06
- BALL BEARINGS**
Further Tests of 38 Ball-Bearing Greases
MFS-27043 B85-10084 04
- BATCH PROCESSING**
Manipulation of Numbers With Many Digits
MFS-28048 B85-10567 09
- BATTERY CHARGERS**
Flux Coupling for Wheelchair Battery Chargers
NPO-16269 B85-10007 01
Recharging Batteries Chemically
NPO-16024 B85-10143 01
- BCH CODES**
Fast Reed-Solomon Decoder
NPO-15867 B85-10303 02
Systolic VLSI Reed-Solomon Decoder
NPO-16383 B85-10304 02
- BEACONS**
Tester for Distress Beacons
GSC-12892 B85-10442 01
- BEAMS (SUPPORTS)**
Deployable M-Braced Truss
LAR-13081 B85-10100 06
Sequentially-Deployable Tetrahedral Beam
LAR-13098 B85-10222 06
Making Structural Members From Wire
MSC-20175 B85-10268 08
- BEARING ALLOYS**
Ion Implantation Improves Bearing-Surface Properties
MFS-25995 B85-10197 04

SUBJECT INDEX

CHARGE CARRIERS

Reducing Stress-Corrosion Cracking
in Bearing Alloys
MFS-19948 B85-10331 04

BEARINGS
Air Bearing for Small Planar
Vibrations
MFS-26003 B85-10110 07
Low-Temperature Seal for Actuator
Rod
MSC-20744 B85-10229 06
Analyses of Multishaft Rotor-Bearing
Response
LEW-13925 B85-10232 06
Effects of Bearing Clearance on
Turbopump Stability
MFS-27063 B85-10259 07
Multistage Planetary Power
Transmissions
LEW-14100 B85-10399 07
Predicting the Dynamic Behavior of
High-Speed Roller Bearings
LEW-13467 B85-10401 07
Calculating Bearing Forces From
Strain-Gage Signals
MFS-29000 B85-10510 06
Bearing Thermal Performance
Prediction
LEW-14163 B85-10539 06

BEDS (PROCESS ENGINEERING)
Agglomeration-Free Distributor for
Fluidized Beds
NPO-16456 B85-10544 07

BENDING
Testing Machine for Biaxial Loading
MSC-20477 B85-10220 06

BIOCONVERSION
Coculture Production of Butanol by
Clostridium Bacteria
NPO-16203 B85-10086 05

BIONICS
Low-Friction Joint for Robot Fingers
NPO-15914 B85-10247 07

BISTABLE CIRCUITS
Comparator With Noise Suppression
LAR-13151 B85-10147 01

BITS
Single-Event-Upset Studies: A
Compilation
NPO-16362 B85-10297 01

BODY-WING CONFIGURATIONS
Retractable End Plates for Aircraft
Lifting Surfaces
LAR-12946 B85-10216 06

BOLTS
Fastening Parts Having Mismatched
Thermal Coefficients
LAR-13009 B85-10113 07

BONDING
Bonded and Bolted
Graphite/Polyimide Composite Joints
LAR-13090 B85-10130 08
Bonding Solar-Cell Modules
NPO-16399 B85-10211 04

BOOMS (EQUIPMENT)
Microphone Boom for Aircraft-Engine
Monitoring
ARC-11495 B85-10525 06

BOOSTER RECOVERY
Rocket-Booster Towing Simulation
KSC-11289 B85-10102 06

BORON FIBERS
Measuring Resistivities of Small
Fibers
MFS-28077 B85-10484 04

BOUNDARY LAYER CONTROL
Performance Improvement for
Nonaxisymmetric Nozzles
LAR-13036 B85-10114 07

BRACKETS
Universal Cable Brackets
MFS-26001 B85-10129 08
Removing Heat From Toroidal
Inductors
NPO-16386 B85-10293 01

BRAILLE
Braille Reading Systems
LAR-13306 B85-10517 06

BRAKES (FOR ARRESTING MOTION)
Gradually Acting Shaft Stop
MSC-20729 B85-10256 07
Rotary Speed Sensor for Antilocking
Brakes
NPO-16479 B85-10509 06

BRAKING
Mechanical Mixer for Rudder/Braking
Wedge
MSC-20759 B85-10117 07

BRIGHTNESS DISCRIMINATION
Finding Bright-Spot Coordinates in
Television Images
MFS-25999 B85-10034 02

BRUSHES (ELECTRICAL CONTACTS)
Accelerating Corrosion in Solar-Cell
Tests
NPO-16096 B85-10446 01

BUBBLES
Blowing Polymer Bubbles in an
Acoustic Levitator
NPO-16212 B85-10203 04
Centrifugal Generator of Filled
Spherical Shells
NPO-16051 B85-10270 08

BUFFER STORAGE
FIFO Buffer for Asynchronous Data
Streams
MSC-20403 B85-10036 02

BURNERS
Modeling a Transient Catalytic
Combustor
LEW-13723 B85-10212 04
Micronized-Coal Burner Facility
LEW-14131 B85-10492 04

BUTYRIC ACID
Coculture Production of Butanol by
Clostridium Bacteria
NPO-16203 B85-10086 05

C

CALIBRATING
Determining Calibration Constants for
Attitude Measurements
LAR-13214 B85-10475 03
Calibrating Pressure Transducers at
Cryogenic Temperatures
LAR-13242 B85-10516 06

CANOPIES
Aircraft Canopy Lock
FRC-11065 B85-10088 06

CAPACITORS
Determining Internal Connections in
Capacitors
NPO-16499 B85-10445 01

CARBON DIOXIDE LASERS
Zone Refining by Laser
MFS-27084 B85-10555 08

CARBON FIBERS
Determining Fiber Orientation in
Graphite-Reinforced Composites
MFS-28032 B85-10205 04
Measuring Resistivities of Small
Fibers
MFS-28077 B85-10484 04
Apparatus for Sizing and Rewinding
Graphite Fibers
LAR-13323 B85-10556 08

CASES (CONTAINERS)
Conductive Container for
Semiconductor Devices
NPO-16110 B85-10439 01

CASSEGRAIN ANTENNAS
Cassegain-Antenna Gain
Improvement
NPO-15775 B85-10433 01

CAST ALLOYS
Solidifying Cast Iron in Low Gravity
MFS-27069 B85-10504 04

CASTING
Cast Iron With High Carbon Content
MFS-28014 B85-10500 04

CATALOGS (PUBLICATIONS)
Equipment for Microgravity
Research
MFS-27094 B85-10480 03

CATALYSIS
Modeling a Transient Catalytic
Combustor
LEW-13723 B85-10212 04

CAVITY RESONATORS
Superconducting-Cavity Accelerom-
eter
GSC-12797 B85-10096 06

CENTRIFUGES
Enhancing Centrifugal Separation
With Electrophoresis
MFS-28053 B85-10357 05

CERAMIC BONDING
Duplicating Curved Tile Surfaces for
Pull Testing
MSC-20795 B85-10274 08

CERAMIC COATINGS
Ceramic Coatings for Engine Parts
NPO-16228 B85-10063 04
Plasma-Sprayed Coatings on Porous
Surfaces
LEW-13450 B85-10347 04

CERAMICS
Improving Emittance of
High-Temperature Insulating Tile
MSC-20714 B85-10078 04
Production Process for Strong, Light
Ceramic Tiles
MSC-20602 B85-10200 04
High-Strength, Low-Shrinkage
Ceramic Tiles
MSC-20654 B85-10495 04
Beta Silicon Nitride Whiskers
NPO-16409 B85-10501 04

CHANNEL NOISE
Optimum Cyclic Redundancy Codes
for Noisy Channels
NPO-16406 B85-10561 09

CHANNELS (DATA TRANSMISSION)
Synchronizing Data-Bus Messages
MSC-20640 B85-10035 02

CHARCOAL
Adsorption of H₂, Ne, and N₂ on
Activated Charcoal
NPO-16329 B85-10477 03

CHARGE CARRIERS
Calculating Charge Transport in
Semiconductors
LAR-13201 B85-10338 04

CHARGE COUPLED DEVICES

SUBJECT INDEX

- CHARGE COUPLED DEVICES**
Hybrid Fiber-Optic/CCD Chip
NPO-16030 B85-10002 01
- CHARGE EFFICIENCY**
Battery-Charge-State Model
NPO-16158 B85-10058 03
- CHEMICAL REACTORS**
Windowless High-Pressure Solar Reactor
NPO-16310 B85-10174 03
Producing Silicon Carbide for Semiconductor Devices
NPO-16391 B85-10342 04
- CHIPS**
Designing Test Chips for Custom Integrated Circuits
NPO-15988 B85-10032 02
- CHIPS (ELECTRONICS)**
Single-Chip VLSI Reed-Solomon Encoder
NPO-16122 B85-10452 02
- CIRCUIT BREAKERS**
Remote Power Controllers For High-Power dc Switching
LEW-14109 B85-10148 01
- CIRCUIT PROTECTION**
Protective Cover for IC Packages
NPO-15537 B85-10011 01
Low-Voltage Protection For Volatile Computer Memories
NPO-15909 B85-10146 01
Preventing Electrostatic-Discharge Damage to Electronics
NPO-15953 B85-10296 01
Conductive Container for Semiconductor Devices
NPO-16110 B85-10439 01
- CLAMPS**
Wide-Grasp Latching Mechanism
MFS-28002 B85-10118 07
Universal Cable Brackets
MFS-26001 B85-10129 08
Optical Mounts for Cryogenic Beam Splitters
GSC-12923 B85-10180 03
Hand-Held Power Clamp
MSC-20549 B85-10257 07
- CLEANLINESS**
Copyboard Quickly Makes Clean Printing Plates
ARC-11365 B85-10133 08
- CLOCKS**
Fast Clock Recovery for Digital Communications
NPO-16083 B85-10019 01
Synchronization for Optical PPM Signals
NPO-16256 B85-10037 02
- CLOUD COVER**
Measuring Clouds With Microwaves and Infrared
NPO-16265 B85-10045 03
- CLOUDS**
Estimates of Latent Heat in Clouds
MFS-25977 B85-10055 03
Accurate Airborne Particle Sampler
LAR-13080 B85-10219 06
- CLOUDS (METEOROLOGY)**
Airborne Cloud Detector
LAR-13137 B85-10167 02
- CMOS**
Dynamic-RAM Data Storage Unit
LEW-14017 B85-10030 02
FIFO Buffer for Asynchronous Data Streams
MSC-20403 B85-10036 02
- Latchup in CMOS Integrated Circuits
NPO-16304 B85-10170 02
- COAL**
Corrosive Effects of Burning Fuels
NPO-16345 B85-10207 04
Automated Coal-Mining System
NPO-16177 B85-10233 07
Pointable Auger
NPO-16178 B85-10234 07
Modular Pick-and-Bucket Mining Machine
NPO-16179 B85-10235 07
Reducing Coal Dust With Water Jets
NPO-16180 B85-10236 07
Slurry-Mixing Chamber
NPO-16182 B85-10237 07
All-Water-Jet Coal Excavator
NPO-16183 B85-10238 07
Coal-Sizing Auger
NPO-16184 B85-10239 07
Service Modules for Coal Extraction
NPO-16185 B85-10240 07
Side Shield for Wall Support
NPO-16188 B85-10241 07
Roof Shield for Advance and Retreat Mining
NPO-16189 B85-10242 07
Compact Hydraulic Excavator and Support Unit
NPO-16190 B85-10243 07
Micronized-Coal Burner Facility
LEW-14131 B85-10492 04
- COAL UTILIZATION**
Micronized-Coal Burner Facility
LEW-14131 B85-10492 04
- COASTAL ZONE COLOR SCANNER**
Algorithms for Coastal-Zone Color-Scanner Data
GSC-12852 B85-10328 03
- COATING**
Trough Coating Solar Cells Without Spillover
NPO-15313 B85-10330 04
Plasma-Sprayed Coatings on Porous Surfaces
LEW-13450 B85-10347 04
Coating a Sphere With Evaporated Metal
NPO-16436 B85-10404 08
- COATINGS**
Protective Coatings for Metals
KSC-11308 B85-10352 04
Tests of Zinc Rich Anticorrosion Coatings
KSC-11309 B85-10354 04
- COBALT**
Cobalt Ions Improve the Strength of Epoxy Resins
LAR-13230 B85-10493 04
- CODERS**
Obtaining One-Degree Accuracy With Shaft Encoders
LAR-13321 B85-10431 01
Single-Chip VLSI Reed-Solomon Encoder
NPO-16122 B85-10452 02
- CODING**
Algorithms for Software Development
NPO-16079 B85-10134 09
Encoding Scheme Reduces Hardware Requirements
MSC-20044 B85-10138 09
Standard Codes for Telemetry and Telecommand
NPO-16305 B85-10287 09
- Coding for Electronic Mail
NPO-16350 B85-10411 09
Coding for Efficient Image Transmission
NPO-16444 B85-10416 09
Universal Noiseless Coding Subroutines
NPO-15451 B85-10426 09
- COLLIMATION**
Adapter Helps To Align Plasma Torch
MFS-28024 B85-10251 07
- COLOR PHOTOGRAPHY**
Vision Screening by Color Photography
MFS-25800 B85-10085 05
- COLUMNS**
Inflatable Column Structure
NPO-16216 B85-10091 06
- COMBUSTIBLE FLOW**
Predicting Two-Dimensional, Unsteady Turbulent Combustion
LEW-14027 B85-10376 06
- COMBUSTION CHAMBERS**
Low-Loss Fuel and Oxidizer Injector
MFS-25989 B85-10104 07
- COMBUSTION PHYSICS**
Modeling a Transient Catalytic Combustor
LEW-13723 B85-10212 04
- COMBUSTION PRODUCTS**
Prediction of Combustion Gas Deposit Compositions
LEW-14091 B85-10280 09
- COMMUNICATION EQUIPMENT**
Communications Headgear With Protective Features
LAR-13156 B85-10166 02
- COMMUNICATION SATELLITES**
Tethered Communication Satellites
MFS-28042 B85-10375 06
- COMMUTATORS**
Commutating Permanent-Magnet Motors At Low Speed
MFS-25207 B85-10150 01
- COMPARATOR CIRCUITS**
Comparator With Noise Suppression
LAR-13151 B85-10147 01
- COMPARATORS**
Picture-Element Comparator
NPO-16464 B85-10458 02
- COMPOSITE MATERIALS**
Resin Characterization in Cured Composite Materials
LAR-13172 B85-10072 04
Strength of Graphite/Metal Composite Lap Joints
MFS-27030 B85-10082 04
Determining Fiber Orientation in Graphite-Reinforced Composites
MFS-28032 B85-10205 04
Epoxy/Fluoroether Composites
ARC-11418 B85-10332 04
Resin Powder Slurry Process for Composite Fabrication
LAR-13106 B85-10335 04
Water-Soluble Thermoplastic Polyimides
LAR-13105 B85-10336 04
- COMPOSITE STRUCTURES**
Plastic and Failure Analysis of Composites
LAR-13183 B85-10213 04
Thermal Shock-Resistant Composite Crucible
LEW-14105 B85-10252 07

SUBJECT INDEX

Damage and Repair of Composite Structures
LAR-13146 B85-10278 08

COMPRESSORS
Predicting the Performance of an Axial-Flow Compressor
LEW-14025 B85-10531 06
Axial-Flow Compressor Performance With Water Ingestion
LEW-14026 B85-10532 06

COMPUTATION
Data Manipulation and Display
LEW-14101 B85-10424 09

COMPUTER DESIGN
Automatically-Programed Machine Tools
GSC-12758 B85-10264 07

COMPUTER GRAPHICS
Manipulation and Display of Panel-Method Geometry
LAR-13224 B85-10282 09
An Interactive Plotting Routine
MSC-20771 B85-10284 09
Radiation View-Factor Program With Interactive Graphics
LAR-13299 B85-10535 06
Printer Graphics Package
MSC-20778 B85-10568 09

COMPUTER PROGRAMS
Algorithms for Software Development
NPO-16079 B85-10134 09
Computer-Aided Reliability Estimation
LAR-13349 B85-10315 02
Airfoil Smoothing and Scaling Programs
LAR-13132 B85-10377 06
Design of Linear Quadratic Regulators and Kalman Filters
LEW-14128 B85-10461 02
X-Ray Diffraction Analysis Program
LAR-13276 B85-10483 03
Automated Design Synthesis
LAR-13341 B85-10534 06
Radiation View-Factor Program With Interactive Graphics
LAR-13299 B85-10535 06
Orbit Transfer Programs
LEW-14089 B85-10538 06
Bearing Thermal Performance Prediction
LEW-14163 B85-10539 06
Three-Dimensional, Subsonic, Turbulent Juncture Region Flow
LAR-13263 B85-10540 06
Zero-Lift Wave Drag of Complex Aircraft Configurations
LAR-13223 B85-10541 06
Software Comparison
MSC-20777 B85-10565 09
Image-Processing Educator
GSC-12933 B85-10566 09
Manipulation of Numbers With Many Digits
MFS-28048 B85-10567 09
Printer Graphics Package
MSC-20778 B85-10568 09

COMPUTER STORAGE DEVICES
Low-Voltage Protection For Volatile Computer Memories
NPO-15909 B85-10146 01

COMPUTER SYSTEMS PROGRAMS
Transportable Applications Executive
GSC-12881 B85-10422 09

COMPUTER SYSTEMS SIMULATION
Personal-Computer Video-Terminal Emulator
KSC-11293 B85-10286 09

COMPUTERIZED SIMULATION
Soil/Structure Interactions in Earthquakes
MFS-27078 B85-10479 03
Vibrational Effects of Turbopump Housing Flexibility
MFS-27083 B85-10552 07
Numerical Aerodynamic Simulation Facility
ARC-11497 B85-10562 09

COMPUTERS
Experimental Parallel-Processing Computer
NPO-16043 B85-10302 02
Image Interpolation With Dedicated Digital Hardware
GSC-12882 B85-10312 02

CONCENTRATORS
Out-of-Focus Alinement of Solar Concentrators
NPO-15563 B85-10044 03
Nebulization Reflux Concentrator
LAR-13254 B85-10463 03

CONDUCTIVITY METERS
Measuring Soil Hydraulic Conductivity With Microwaves
GSC-12937 B85-10176 03

CONFORMAL MAPPING
Improved Numerical Evaluation Method for Elliptic Integrals
ARC-11467 B85-10412 09
Three-Dimensional Grids for Flow-Field Calculations
ARC-11394 B85-10413 09

CONNECTORS
Attaching an Electrical Ground to an Aluminum Structure
MSC-20668 B85-10294 01
Connectors and Wiring for Cryogenic Temperatures
LAR-13193 B85-10300 01

CONSTITUTIVE EQUATIONS
Constitutive Equations of Aging in Polymers
NPO-16480 B85-10503 04

CONSTRICTORS
Prosthetic Sphincter Controls Urination
MFS-25740 B85-10356 05
Development of a Prosthesis for Urinary Control
MFS-27062 B85-10359 05

CONSTRUCTION
Automatic Erection System for Antenna Masts
LAR-13115 B85-10115 07

CONTACT RESISTANCE
Attaching an Electrical Ground to an Aluminum Structure
MSC-20668 B85-10294 01

CONTAINERLESS MELTS
Hybrid Contactless Heating and Levitation
NPO-15657 B85-10122 08

CONTROL
Numerical Methods for Classical Sampled-System Analysis
GSC-12827 B85-10564 09

CONTROL EQUIPMENT
Experiments With a Manipulator Sensor System
NPO-16094 B85-10262 07

COST ANALYSIS

CONTROL SIMULATION
Personal-Computer Video-Terminal Emulator
KSC-11293 B85-10286 09
NASTRAN-DISCOS/SAMSAN DMAP Bridging Program
GSC-12902 B85-10379 06
Modal Analysis and Gain Estimation
LAR-13334 B85-10418 09
Numerical Methods for Classical Sampled-System Analysis
GSC-12827 B85-10564 09

CONTROLLERS
Portable Temperature Set-Point Controller
MSC-20056 B85-10142 01

CONVECTIVE FLOW
Damping Melt Convection With A Magnetic Field
MFS-28040 B85-10339 04

CONVECTIVE HEAT TRANSFER
Solution of Radiation and Convection Heat-Transfer Problems
LEW-13978 B85-10537 06

COOLERS
Long-Life Cryogenic Cooler
GSC-12697 B85-10116 07

COOLING
Removing Heat From Toroidal Inductors
NPO-16386 B85-10293 01
High-Efficiency, Low-Weight Power Transformer
LEW-14074 B85-10403 08

COOLING SYSTEMS
Making Glass-Fiber-Reinforced Coolant Tubes
MSC-20677 B85-10276 08
Puncture-Tolerant Heat Radiator
NPO-16401 B85-10390 07

COORDINATE TRANSFORMATIONS
Three-Dimensional Grids for Flow-Field Calculations
ARC-11394 B85-10413 09

COORDINATES
Finding Bright-Spot Coordinates in Television Images
MFS-25999 B85-10034 02

CORROSION
Corrosive Effects of Burning Fuels
NPO-16345 B85-10207 04
Accelerated Stress-Corrosion Testing
LAR-13337 B85-10520 06

CORROSION PREVENTION
Magnetron Sputtering Deposits Corrosion-Resistant Alloy
NPO-15928 B85-10337 04
Protective Coatings for Metals
KSC-11308 B85-10352 04
Tests of Zinc Rich Anticorrosion Coatings
KSC-11309 B85-10354 04

CORROSION TESTS
Accelerating Corrosion in Solar-Cell Tests
NPO-16096 B85-10446 01
Accelerated Stress-Corrosion Testing
LAR-13337 B85-10520 06

COST ANALYSIS
Cost and Performance Model for Photovoltaic Systems
NPO-16404 B85-10314 02

COUPLINGS

COUPLINGS

- Flux Coupling for Wheelchair Battery Chargers
 - NPO-16269 B85-10007 01
 - Rotating Connection for Electrical Cables
 - GSC-12899 B85-10384 07
- CRACK INITIATION**
 - Accelerated Stress-Corrosion Testing
 - LAR-13337 B85-10520 06
- CRACKS**
 - Detecting Cracks in Rough Metal Surfaces
 - MSC-20734 B85-10230 06
- CRAWLER TRACTORS**
 - Improved Highway Pads for Tracked Vehicles
 - NPO-16318 B85-10246 07
- CREEP ANALYSIS**
 - Predicting the Cyclic Response of High-Temperature Materials
 - LEW-14032 B85-10344 04
- CROP IDENTIFICATION**
 - Compact Imaging Spectrometer
 - NPO-16342 B85-10471 03
- CROSSOVERS**
 - Crossover Concept for Optical Printed Circuits
 - NPO-15131 B85-10186 03
- CRUCIBLES**
 - Filament Guides for Silicon-Ribbon Growth
 - MSC-20798 B85-10132 08
 - Thermal Shock-Resistant Composite Crucible
 - LEW-14105 B85-10252 07
 - Adjustable Lid Aids Silicon-Ribbon Growth
 - NPO-16354 B85-10275 08
 - Research Furnace for Crystal Preparation
 - LAR-13302 B85-10496 04
- CRUSHERS**
 - Coal-Sizing Auger
 - NPO-16184 B85-10239 07
- CRYOGENIC COOLING**
 - Long-Life Cryogenic Cooler
 - GSC-12697 B85-10116 07
 - Hydrogen Refrigerator Would Cool Below 10 K
 - NPO-16393 B85-10543 07
- CRYOGENIC EQUIPMENT**
 - Foam Insulation for Cryogenic Flowlines
 - MSC-20552 B85-10066 04
 - Insulating Cryogenic Pipes With Frost
 - MSC-20426 B85-10249 07
 - LaNi₅ Hydrogen-Absorption Cryogenic System
 - NPO-16314 B85-10387 07
 - Hydrogen Refrigerator Would Cool Below 10 K
 - NPO-16393 B85-10543 07
- CRYOGENIC WIND TUNNELS**
 - Calibrating Pressure Transducers at Cryogenic Temperatures
 - LAR-13242 B85-10516 06
- CRYOGENICS**
 - Connectors and Wiring for Cryogenic Temperatures
 - LAR-13193 B85-10300 01
- CRYSTAL GROWTH**
 - Efficient Process for Making Polycrystalline Silicon
 - NPO-16121 B85-10073 04

- Preparation and Characterization of HgxCd_{1-x}Te
 - MFS-27037 B85-10081 04
- Filament Guides for Silicon-Ribbon Growth
 - NPO-16175 B85-10272 08
- Prototype Furnace for Automatic Production of Silicon Ribbon
 - NPO-16175 B85-10272 08
- Adjustable Lid Aids Silicon-Ribbon Growth
 - NPO-16354 B85-10275 08
- Laser Schlieren Crystal-Growth Imager
 - MFS-28060 B85-10326 03
- Studying Crystal Growth With the Peltier Effect
 - MFS-28041 B85-10346 04
- Research Furnace for Crystal Preparation
 - LAR-13302 B85-10496 04
- CRYSTALLIZATION**
 - Variable-Temperature-Gradient Device for Solidification Research
 - MFS-26008 B85-10042 03
- CUSHIONS**
 - Air Bearing for Small Planar Vibrations
 - MFS-26003 B85-10110 07
- CUTTERS**
 - Cutthrough Warning Circuit
 - MFS-19900 B85-10119 07
- CUTTING**
 - Cutting Guide for Fibrous Sheets
 - MSC-20798 B85-10132 08
- CYANIDES**
 - Solar-Assisted Oxidation of Toxic Cyanide
 - LAR-13171 B85-10075 04
- CYLINDERS**
 - Hydraulic Cylinder With an Integral Position Indicator
 - LAR-13095 B85-10518 06

D

DAMAGE ASSESSMENT

- Damage and Repair of Composite Structures
 - LAR-13146 B85-10278 08

DAMPERS (VALVES)

- Quasi-Porous Plug With Vortex Chamber
 - NPO-16076 B85-10111 07

DAMPING

- Damping Melt Convection With A Magnetic Field
 - MFS-28040 B85-10339 04

DATA COMPRESSION

- Coding for Electronic Mail
 - NPO-16350 B85-10411 09
- Coding for Efficient Image Transmission
 - NPO-16444 B85-10416 09
- Universal Noiseless Coding Subroutines
 - NPO-15451 B85-10426 09

DATA PROCESSING

- Data Manipulation and Display
 - LEW-14101 B85-10424 09

DATA PROCESSING TERMINALS

- 'Speaking' Microcomputer
 - MFS-25976 B85-10307 02

DATA SAMPLING

- Molecular-Beam Chopper and Four-Channel Amplifier
 - LAR-13174 B85-10316 03

DATA STORAGE

- Dynamic-RAM Data Storage Unit
 - LEW-14017 B85-10030 02

DECISION THEORY

- Comparison of Decision Models
 - NPO-16446 B85-10563 09

DECISIONS

- Comparison of Decision Models
 - NPO-16446 B85-10563 09

DECODERS

- Fast Reed-Solomon Decoder
 - NPO-15867 B85-10303 02
- Systolic VLSI Reed-Solomon Decoder
 - NPO-16383 B85-10304 02
- Modular VLSI Reed-Solomon Decoder
 - NPO-15837 B85-10306 02
- Fast VLSI Viterbi Decoder
 - NPO-16365 B85-10311 02

DECODING

- Telephone Instrument for the Deaf
 - KSC-11303 B85-10014 01
- Universal Noiseless Coding Subroutines
 - NPO-15451 B85-10426 09

DECOMPRESSION SICKNESS

- Effect of Hydration on Nitrogen Washout in Humans
 - MSC-20886 B85-10087 05

DEFLECTION

- Electro-optical System Measures Aircraft Deflections
 - ARC-11454 B85-10305 02

DEGRADATION

- Environmental Degradation of Solar Reflectors
 - NPO-16053 B85-10059 03

DEMODULATORS

- Pulse-Width-to-Analog-Voltage Converter
 - MSC-20006 B85-10157 01

DEPOSITION

- Plasma Deposition of Doped Amorphous Silicon
 - NPO-14955 B85-10210 04
- Inexpensive Masks for Film Deposition
 - NPO-16416 B85-10557 08

DEPTH MEASUREMENT

- Liquid-Level Monitor for Pressurized Vessels
 - LAR-13208 B85-10366 06
- Noninvasive Fluid Level Sensor for Organometallic Sources
 - LAR-13265 B85-10371 06

DESIGN ANALYSIS

- Synthesis and Optimization of Spiral Bevel Gears
 - LEW-13920 B85-10389 07
- Automated Design Synthesis
 - LAR-13341 B85-10534 06
- Dynamic Effects of Internal Spur-Gear Drives
 - LEW-14167 B85-10553 07

DETECTION

- Sensitivities of Soap Solutions in Leak Detection
 - MFS-19864 B85-10121 07
- Molecular Thermal-Electron Detectors
 - NPO-16300 B85-10467 03

SUBJECT INDEX

DEVICES

High-Visibility Data Display
MFS-19925 B85-10026 02

DIELECTRICS

Degradation of Dielectrics in Space
NPO-16003 B85-10209 04

DIES

Controlled-Shape, Ultrasonic-Angle-
Beam Standard Reflector
LAR-13153 B85-10410 08

DIFFUSION WELDING

Improved Surface of Titanium
Structure
LAR-13148 B85-10409 08

DIGITAL DATA

Storing Data and Video on One
Tape
MSC-20705 B85-10027 02

FIFO Buffer for Asynchronous Data
Streams
MSC-20403 B85-10036 02

DIGITAL FILTERS

Convolver for Pipelined-Image
Processor
NPO-16462 B85-10451 02

DIGITAL SIMULATION

Design of Linear Quadratic
Regulators and Kalman Filters
LEW-14128 B85-10461 02

Calculation of Macroseggregation in an
Ingot
MFS-27068 B85-10481 03

Flow Through Gas-Turbine Ducts
LEW-14095 B85-10533 06

Four-Cylinder Stirling Engine Control
Simulation
LEW-14106 B85-10536 06

Solution of Radiation and Convection
Heat-Transfer Problems
LEW-13978 B85-10537 06

Dynamic Effects of Internal
Spur-Gear Drives
LEW-14167 B85-10553 07

DIGITAL SYSTEMS

Design Language for Digital
Systems
MFS-25352 B85-10281 09

Testing Electronic Devices for
Single-Event Upset
NPO-16468 B85-10454 02

DIGITAL TECHNIQUES

Modular, Fast, Two-Dimensional
Cyclic Convolver
NPO-16379 B85-10448 02

DIMENSIONAL MEASUREMENT

Hand-Held Electronic Gap-Measuring
Tools
MSC-20176 B85-10223 06

DIODES

Damping Relaxation Oscillations in
Laser Diodes
NPO-15980 B85-10010 01

Fast-Recovery, High-Voltage Power
Diode
LEW-14036 B85-10016 01

DIRECTIONAL

(CRYSTALS)

Damping Melt Convection With A
Magnetic Field
MFS-28040 B85-10339 04

DISCOLORATION

Discoloration of Polyvinyl Butyral
NPO-16411 B85-10353 04

DISCRIMINATORS

Segmented Detector for Cosmic
Gamma Rays
NPO-16245 B85-10053 03

DISPLACEMENT MEASUREMENT

Fixture for Linearly Variable
Displacement Transducers
LAR-12937 B85-10224 06

Electro-optical System Measures
Aircraft Deflections
ARC-11454 B85-10305 02

Elevated-Temperature Tensile-
Testing of Foil-Gage Metals
LAR-13243 B85-10363 06

DISPLAY DEVICES

Digital High-Current Monitor
LAR-13072 B85-10003 01

High-Visibility Data Display
MFS-19925 B85-10026 02

A Quick Visual Power-Supply
Monitor
MFS-26014 B85-10436 01

DISTILLATION

Purifying Aluminum by Vacuum
Distillation
NPO-16114 B85-10065 04

DOLLIES

Dolly Swivel for Forklift
MFS-19866 B85-10391 07

DRILLING

Precise Electrochemical Drilling of
Repeated Deep Holes
MFS-19767 B85-10250 07

Drilling Holes in Graphite/Epoxy
Composites
MFS-28044 B85-10398 07

Adjustable-Angle Drill Block
LAR-13101 B85-10545 07

DRILLS

Pointable Auger
NPO-16178 B85-10234 07

Adjustable-Angle Drill Block
LAR-13101 B85-10545 07

DROPS (LIQUIDS)

Calibrating Droplet Generator for
Pressurized Testing Vessel
MFS-25992 B85-10094 06

DUCTED FAN ENGINES

Duct-Flow Analysis
LEW-14000 B85-10191 03

DUCTED FLOW

Flow Through Gas-Turbine Ducts
LEW-14095 B85-10533 06

DUCTS

Foam Insulation for Cryogenic
Flowlines
MSC-20552 B85-10066 04

DYNAMIC MODELS

Residue-Measure Model-Reduction
Technique
MSC-20369 B85-10137 09

DYNAMIC RESPONSE

NASTRAN/DISCOS/SAMSAN DMAP
Bridging Program
GSC-12902 B85-10379 06

Computational Simplification of
Robot-Arm Dynamics
NPO-16377 B85-10417 09

Flexible Airframe Response Program
MSC-20762 B85-10425 09

E

EARTH ATMOSPHERE

Accuracy of Lidar Measurements of
the Atmosphere
NPO-16493 B85-10476 03

ELECTRIC FIELD STRENGTH

EARTHQUAKES

Soil/Structure Interactions in
Earthquakes
MFS-27078 B85-10479 03

EDDY CURRENTS

Inexpensive Eddy-Current Standard
LAR-13154 B85-10225 06

EDITING ROUTINES (COMPUTERS)

Text Exchange System
NPO-16357 B85-10419 09

Data Manipulation and Display
LEW-14101 B85-10424 09

EIGENVECTORS

Modal Analysis and Gain Estimation
LAR-13334 B85-10418 09

ELASTOMERS

Ultra-High-Molecular-Weight Silphen-
ylene/Siloxane Polymers
MFS-27065 B85-10499 04

Mechanical Design Handbook for
Elastomers
LEW-14160 B85-10502 04

ELASTOPLASTICITY

Predicting the Cyclic Response of
High-Temperature Materials
LEW-14032 B85-10344 04

Inelastic Analysis of
Thermomechanically Cycled Structures
LEW-14011 B85-10380 06

Geometric and Material Nonlinear
Structural Analysis
LAR-13279 B85-10381 06

ELECTRIC BATTERIES

Recharging Batteries Chemically
NPO-16024 B85-10143 01

Improved Electrodes for Lithium
Cells
NPO-16397 B85-10201 04

ELECTRIC BRIDGES

Tiltmeter Indicates Sense of Slope
NPO-16153 B85-10005 01

ELECTRIC COILS

Recovering Energy From Relays
NPO-16268 B85-10012 01

ELECTRIC CONNECTORS

Electrically Connecting to Pressure
Vessels
MSC-20709 B85-10154 01

Connectors and Wiring for Cryogenic
Temperatures
LAR-13193 B85-10300 01

Rotating Connection for Electrical
Cables
GSC-12899 B85-10384 07

ELECTRIC CONTACTS

Rolling-Contact Rheostat
NPO-15567 B85-10144 01

Study of Contact Resistances in
Integrated Circuits
NPO-16248 B85-10159 01

Determining Internal Connections in
Capacitors
NPO-16499 B85-10445 01

ELECTRIC CURRENT

Digital High-Current Monitor
LAR-13072 B85-10003 01

ELECTRIC DISCHARGES

Flushing Ring for EDM
MFS-19876 B85-10108 07

ELECTRIC FIELD STRENGTH

Fiber-Optic Electric-Field Meter
NPO-16435 B85-10290 01

Rotating Capacitor Measures Steady
Electric Fields
NPO-16550 B85-10449 02

ELECTRIC FIELDS

SUBJECT INDEX

ELECTRIC FIELDS

Rotating Capacitor Measures Steady
Electric Fields
NPO-16550 B85-10449 02

ELECTRIC HYBRID VEHICLES

Hybrid and Electric Advanced Vehicle
Systems Simulation
LEW-13927 B85-10263 07
Compact Hybrid Automotive
Propulsion System
NPO-16117 B85-10386 07
Systems Engineering of Electric and
Hybrid Vehicles
NPO-15871 B85-10551 07

ELECTRIC MOTORS

Commutating Permanent-Magnet
Motors At Low Speed
MFS-25207 B85-10150 01

ELECTRIC POWER PLANTS

Photovoltaics in Japan
NPO-16330 B85-10025 01

ELECTRIC POWER SUPPLIES

Power Supply For 25-Watt Arc
Lamp
LAR-13202 B85-10141 01
Incrementally Variable High-Voltage
Supply
MFS-28018 B85-10145 01
A Quick Visual Power-Supply
Monitor
MFS-26014 B85-10436 01

ELECTRIC POWER TRANSMISSION

Integrating Residential Photovoltaics
With Power Lines
NPO-16331 B85-10188 03
High-Efficiency, Low-Weight Power
Transformer
LEW-14074 B85-10403 08

ELECTRIC PULSES

Generating Independent Preionizing
Pulses for Lasers
NPO-16402 B85-10429 01

ELECTRIC RELAYS

Recovering Energy From Relays
NPO-16268 B85-10012 01

ELECTRIC SWITCHES

Reed-Switch Position Indicator
KSC-11215 B85-10152 01
Plug-In RF Selector Switch
MSC-20572 B85-10292 01

ELECTRIC TERMINALS

Determining Internal Connections In
Capacitors
NPO-16499 B85-10445 01

ELECTRICAL FAULTS

System for Automated
Troubleshooting
NPO-16339 B85-10558 09

ELECTRICAL GROUNDING

Attaching an Electrical Ground to an
Aluminum Structure
MSC-20668 B85-10294 01
Preventing Electrostatic-Discharge
Damage to Electronics
NPO-15953 B85-10296 01

ELECTRICAL INSULATION

Lightweight Electrical Insulation
NPO-16165 B85-10193 04

ELECTRICAL MEASUREMENT

Measuring Thermoelectric Properties
Automatically
NPO-16507 B85-10488 04

ELECTRICAL RESISTANCE

Study of Contact Resistances in
Integrated Circuits
NPO-16248 B85-10159 01

Measuring Metal Thickness With an
Electric Probe
NPO-16340 B85-10367 06

ELECTRICAL RESISTIVITY

Measuring Resistivities of Small
Fibers
MFS-28077 B85-10484 04

ELECTROCHEMICAL CELLS

Thermally-Rechargeable Elec-
trochemical Cell
NPO-16273 B85-10048 03
Recharging Batteries Chemically
NPO-16024 B85-10143 01

ELECTROCHEMICAL MACHINING

Precise Electrochemical Drilling of
Repeated Deep Holes
MFS-19767 B85-10250 07

ELECTRODES

Improved Electrodes for Lithium
Cells
NPO-16397 B85-10201 04

ELECTROMAGNETIC PUMPS

Heat-Powered Pump for Liquid
Metals
NPO-16457 B85-10396 07

ELECTROMECHANICAL DEVICES

Braille Reading Systems
LAR-13306 B85-10517 06
System for Automated
Troubleshooting
NPO-16339 B85-10558 09

ELECTRON BEAM WELDING

Microfissuring in
Electron-Beam-Welded Nickel Alloy
MFS-27041 B85-10198 04

ELECTRON MICROSCOPES

Measuring Recombination Velocities
in Solar Cells
NPO-16243 B85-10001 01

ELECTRONIC EQUIPMENT TESTS

Online Tester for a Symbol
Generator
MSC-20357 B85-10161 02
Analyzing Microchips With Dark-Field
Negative Photomicrography
NPO-16299 B85-10179 03
Measuring Moisture in Sealed
Electronic Enclosures
MSC-18866 B85-10183 03
Smoothly Adjustable dc Load
MSC-20853 B85-10289 01
Testing Electronic Devices for
Single-Event Upset
NPO-16468 B85-10454 02

ELECTRONIC PACKAGING

Protective Cover for IC Packages
NPO-15537 B85-10011 01
Measuring Moisture in Sealed
Electronic Enclosures
MSC-18866 B85-10183 03
Intercalated-Carbon Low-Resistivity
Fibers
NPO-16307 B85-10196 04

ELECTRONS

Molecular Thermal-Electron
Detectors
NPO-16300 B85-10467 03

ELECTROPHORESIS

Enhancing Centrifugal Separation
With Electrophoresis
MFS-28053 B85-10357 05

ELECTROSTATIC PRECIPITATORS

Improved Electronic Control for
Electrostatic Precipitators
LAR-13273 B85-10457 02

ELECTROSTATIC SHIELDING

High-Voltage Isolation Transformer
GSC-12817 B85-10018 01

ELLIPTIC FUNCTIONS

Improved Numerical Evaluation
Method for Elliptic Integrals
ARC-11467 B85-10412 09

EMISSIVITY

Contactless Calorimetry for Levitated
Samples
NPO-16448 B85-10318 03

EMITTANCE

Improving Emittance of
High-Temperature Insulating Tile
MSC-20714 B85-10078 04

ENCAPSULATED MICROCIRCUITS

Analyzing Microchips With Dark-Field
Negative Photomicrography
NPO-16299 B85-10179 03

ENERGY CONVERSION EFFICIENCY

Solar Cells With Multiple Small
Junctions
NPO-16126 B85-10021 01
Hinged-Blade, Vertical-Shaft
Windmill
MFS-25980 B85-10112 07

Estimating the Performance of a
Concentrating Solar Array
MFS-28021 B85-10185 03
Augmenting Thrust With Waste Heat
NPO-16218 B85-10190 03

ENGINE CONTROL

Four-Cylinder Stirling Engine Control
Simulation
LEW-14106 B85-10536 06

ENGINE PARTS

Ceramic Coatings for Engine Parts
NPO-16228 B85-10063 04

ENGINES

Kinematic Stirling Engine
Performance
LEW-14092 B85-10482 03

ENVIRONMENTAL CONTROL

Portable Temperature Set-Point
Controller
MSC-20056 B85-10142 01

EPOXY COMPOUNDS

Epoxy/Fluoroether Composites
ARC-11418 B85-10332 04
Phthalocyanine Tetraamine
Epoxy-Curing Agents
ARC-11424 B85-10348 04
Ultrasonic Mixing of Epoxy Curing
Agents
LAR-13307 B85-10498 04

EPOXY RESINS

Increasing Fire Safety of Epoxies
ARC-11506 B85-10062 04
Chromium Ions Improve Moisture
Resistance of Epoxy Resins
LAR-13226 B85-10486 04
Cobalt Ions Improve the Strength of
Epoxy Resins
LAR-13230 B85-10493 04

ERROR ANALYSIS

Complementary-Logic Fault Detector
NPO-15410 B85-10017 01
System for Automated
Troubleshooting
NPO-16339 B85-10558 09

ERROR CORRECTING CODES

Encoding Scheme Reduces
Hardware Requirements
MSC-20044 B85-10138 09

ERROR CORRECTING DEVICES

Fast Reed-Solomon Decoder
NPO-15867 B85-10303 02

SUBJECT INDEX

FLIGHT INSTRUMENTS

Systolic VLSI Reed-Solomon
Decoder NPO-16383 B85-10304 02
Modular VLSI Reed-Solomon
Decoder NPO-15837 B85-10306 02
Fast VLSI Viterbi Decoder
NPO-16365 B85-10311 02

ERROR DETECTION CODES
Optimum Cyclic Redundancy Codes
for Noisy Channels
NPO-16406 B85-10561 09

ERRORS
Single-Event-Upset Studies: A
Compilation NPO-16362 B85-10297 01

ESTERS
Ethynyl-Terminated Ester Oligomers
and Polymers LAR-13118 B85-10076 04

EVAPORATORS
High-Performance Heat Pipe
MSC-20136 B85-10177 03

EXCAVATION
Modular Pick-and-Bucket Mining
Machine NPO-16179 B85-10235 07

EXCIMER LASERS
Pulse Coupling for Laser Excitation
NPO-16403 B85-10428 01
Magnetically-Switched, Long-Pulse
XeCl Laser NPO-16410 B85-10430 01

EXHAUST DIFFUSERS
Improved Exhaust Diffuser for
Jet-Engine Testing NPO-16328 B85-10255 07

EXHAUST GASES
Corrosive Effects of Burning Fuels
NPO-16345 B85-10207 04

EXPLOSIVES
Predicting Effects of Impacts on
Confined Explosives NPO-16258 B85-10083 04

EXTENSOMETERS
Elevated-Temperature Tensile-
Testing of Foil-Gage Metals
LAR-13243 B85-10363 06

EXTRACTION
Extracting Silicon Product From
Fluidized-Bed Reactors NPO-16385 B85-10341 04

EYE EXAMINATIONS
Vision Screening by Color
Photography MFS-25800 B85-10085 05

F

FABRICATION
Precise Fabrication of
Electromagnetic-Levitation Coils
MFS-25986 B85-10126 08
Controlling Transistor Temperature
During Burn-In MFS-28076 B85-10437 01
Colorless, Transparent, Aromatic
Polyimide Films LAR-13351 B85-10490 04

FACSIMILE COMMUNICATION
Coding for Electronic Mail
NPO-16350 B85-10411 09

FACTORIAL DESIGN
Subset Regression
LEW-14002 B85-10420 09

FAILURE ANALYSIS
Predicting the Fatigue life of
Structures MFS-27049 B85-10206 04
Plastic and Failure Analysis of
Composites LAR-13183 B85-10213 04

FAR FIELDS
Analysis of Satellite Communications
Antenna Patterns NPO-16400 B85-10283 09

FASTENERS
Aircraft Canopy Lock
FRC-11065 B85-10088 06
Fastening Parts Having Mismatched
Thermal Coefficients LAR-13009 B85-10113 07
Blind-Side, High-Temperature
Fastener Lock LAR-13037 B85-10248 07
Hand-Held Power Clamp
MSC-20549 B85-10257 07
More Secure Fastening for
Tracked-Vehicle Pads NPO-16321 B85-10385 07
Locking Pull Pin NPO-16233 B85-10512 06

FATIGUE (MATERIALS)
Predicting the Fatigue life of
Structures MFS-27049 B85-10206 04

FATIGUE LIFE
Predicting the Fatigue life of
Structures MFS-27049 B85-10206 04
Optimizing Load Spectra for Gears
MSC-20487 B85-10260 07

FAULT TOLERANCE
Complementary-Logic Fault Detector
NPO-15410 B85-10017 01
Computer-Aided Reliability
Estimation LAR-13349 B85-10315 02

FEEDBACK CONTROL
Modal Analysis and Gain Estimation
LAR-13334 B85-10418 09
Wedge Fibers Suppress Feedback
of Laser Beam LAR-13074 B85-10474 03

FERMENTATION
Coculture Production of Butanol by
Clostridium Bacteria NPO-16203 B85-10086 05

FIBER COMPOSITES
Intercalated-Carbon Low-Resistivity
Fibers NPO-16307 B85-10196 04
Fabrication of Slender Struts for
Deployable Antennas LAR-13136 B85-10273 08
Measuring Resistivities of Small
Fibers MFS-28077 B85-10484 04
Apparatus for Sizing and Rewinding
Graphite Fibers LAR-13323 B85-10556 08

FIBER OPTICS
Hybrid Fiber-Optic/CCD Chip
NPO-16030 B85-10002 01
Fiber-Optic Electric-Field Meter
NPO-16435 B85-10290 01
Wedge Fibers Suppress Feedback
of Laser Beam LAR-13074 B85-10474 03

FIBER ORIENTATION
Determining Fiber Orientation in
Graphite-Reinforced Composites
MFS-28032 B85-10205 04

FIBERS
Making Stronger Twine With Matched
Strands MSC-20444 B85-10128 08
Cutting Guide for Fibrous Sheets
MSC-20798 B85-10132 08

FILAMENT WINDING
Stiffness Study of Wound-Filament
Pressure Vessels MFS-27086 B85-10530 06

FILE MAINTENANCE (COMPUTERS)
Text File Display Program
NPO-16358 B85-10423 09
Software Comparison
MSC-20777 B85-10565 09

FILLETS
High-Performance Filleting and
Channel Sealants ARC-11408 B85-10064 04

FILM THICKNESS
Measuring Metal Thickness With an
Electric Probe NPO-16340 B85-10367 06

FINGERS
Wide-Grasp Latching Mechanism
MFS-28002 B85-10118 07

FINITE ELEMENT METHOD
Automatically-Programed Machine
Tools GSC-12758 B85-10264 07
Three-Dimensional, Subsonic,
Turbulent Junction Region Flow
LAR-13263 B85-10540 06

FIREPROOFING
Increasing Fire Safety of Epoxies
ARC-11506 B85-10062 04

FITTINGS
Replaceable Transfer Tube for
High-Pressure Cavities MFS-19775 B85-10395 07

FIXTURES
Adhesive-Bonded Fixture for Flexure
Testing MFS-28051 B85-10360 06

FLAME PROPAGATION
Predicting Two-Dimensional,
Unsteady Turbulent Combustion
LEW-14027 B85-10376 06

FLAME RETARDANTS
Rubberized, Brominated Epoxies
ARC-11427 B85-10079 04

FLASH LAMPS
Altering Flashlamp Output for
Realistic Solar Simulation
NPO-16167 B85-10054 03

FLEXING
Adhesive-Bonded Fixture for Flexure
Testing MFS-28051 B85-10360 06

FLIGHT CHARACTERISTICS
Flexible Airframe Response Program
MSC-20762 B85-10425 09

FLIGHT CONDITIONS
Remotely Piloted Aircraft for
Research ARC-11498 B85-10120 07
Airborne Cloud Detector
LAR-13137 B85-10167 02

FLIGHT INSTRUMENTS
Aircraft Control-Position Indicator
LAR-12984 B85-10020 01

FLIGHT SIMULATORS

SUBJECT INDEX

FLIGHT SIMULATORS

Laser Altimeter for Flight Simulator
ARC-11312 B85-10323 03

FLOATING POINT ARITHMETIC

Manipulation of Numbers With Many
Digits
MFS-28048 B85-10567 09

FLOW DISTRIBUTION

Duct-Flow Analysis
LEW-14000 B85-10191 03

FLOW GEOMETRY

Calculating Flow-Angle Deviation in
Rotary Pumps
MFS-29062 B85-10548 07

FLOW MEASUREMENT

Controllers for Flow-Field Survey
Apparatus
LAR-13180 B85-10310 02

FLOW VELOCITY

Vibration-Free Raman Doppler
Velocimeter
LAR-13268 B85-10447 02

FLOW VISUALIZATION

Continuous Laminar-Smoke
Generator
LAR-13014 B85-10090 06

FLOWMETERS

Flowmeter for Clear and Translucent
Fluids
MFS-28030 B85-10228 06

Flowmeter for Clear Fluids
MFS-28031 B85-10372 06

Technique for Measuring Gas
Conversion Factors
LAR-13220 B85-10470 03

FLUID BOUNDARIES

Spill-Detector-and-Shutoff Device
MSC-20206 B85-10106 07

FLUID FILLED SHELLS

Centrifugal Generator of Filled
Spherical Shells
NPO-16051 B85-10270 08

FLUID FLOW

Flowmeter for Clear and Translucent
Fluids
MFS-28030 B85-10228 06

Flowmeter for Clear Fluids
MFS-28031 B85-10372 06

FLUID PRESSURE

Contact Heat Exchanger
MSC-20419 B85-10092 06

FLUIDIZED BED PROCESSORS

High-Purity Silicon Seeds for Silane
Pyrolysis
NPO-16287 B85-10060 04

Fluidized-Bed Particles Scavenge
Silicon Fines
NPO-16034 B85-10202 04

Extracting Silicon Product From
Fluidized-Bed Reactors
NPO-16385 B85-10341 04

Agglomeration-Free Distributor for
Fluidized Beds
NPO-16466 B85-10544 07

FLUOROPOLYMERS

Epoxy/Fluoroether Composites
ARC-11418 B85-10332 04

Imide Cyclotriphosphazene/Hexa-
fluoroisopropylidene Polymers
ARC-11428 B85-10333 04

FLUSHING

Flushing Ring for EDM
MFS-19876 B85-10108 07

FLUX PINNING

Paramagnetic Precipitates May Raise
Supercurrent
MFS-25925 B85-10195 04

FLY BY WIRE CONTROL

Autopilot Servoactuator With
Pressurized Detented Centering
LAR-13185 B85-10364 06

FLYWHEELS

Control Electronics for
Solar/Flywheel Power Supply
MFS-25978 B85-10443 01

FOLDING STRUCTURES

Hinged-Blade, Vertical-Shaft
Windmill
MFS-25980 B85-10112 07

Sequentially-Deployable Tetrahedral
Beam
LAR-13098 B85-10222 06

Making Structural Members From
Wire
MSC-20175 B85-10268 08

Toggle Hinge for Deployable Struts
MFS-28037 B85-10369 06

Bistable Articulated Joint
NPO-16038 B85-10393 07

Latch for Telescoping Structures
LAR-13169 B85-10507 06

FORMING TECHNIQUES

Improved Surface of Titanium
Structure
LAR-13148 B85-10409 08

FORMULAS (MATHEMATICS)

Determining the Temperature Profile
in a Cylindrical Sample
MFS-26013 B85-10465 03

Calculating Flow-Angle Deviation in
Rotary Pumps
MFS-29062 B85-10548 07

FOSSIL FUELS

Prediction of Combustion Gas
Deposit Compositions
LEW-14091 B85-10280 09

FOURIER TRANSFORMATION

Geometric Representations for
Discrete Fourier Transforms
MFS-27072 B85-10559 09

FRAMES

Deployable M-Braced Truss
LAR-13081 B85-10100 06

Supporting Structures for Flat
Solar-Cell Arrays
NPO-15600 B85-10407 08

FREQUENCY DISCRIMINATORS

Frequency-Discriminating Acoustic-
Event Counter
MSC-20467 B85-10160 02

FREQUENCY MODULATION

Damping Relaxation Oscillations in
Laser Diodes
NPO-15980 B85-10010 01

Programmable Driver for
Voltage-Controlled Oscillators
NPO-16364 B85-10162 02

FREQUENCY SYNCHRONIZATION

Satellite Time- and
Frequency-Transfer System
MFS-25991 B85-10169 02

FRESNEL LENSES

Methane Detector With Plastic
Fresnel Lens
NPO-16284 B85-10321 03

FRICTION MEASUREMENT

Friction-Testing Machine
MSC-20622 B85-10370 06

FUEL CELLS

Methanol Fuel Cell
NPO-15823 B85-10050 03

FUEL CONSUMPTION

Retractable End Plates for Aircraft
Lifting Surfaces
LAR-12948 B85-10216 06

Aerodynamic Rear Cone for Trucks
MFS-28007 B85-10217 06

FUEL GAGES

Liquid-Level Sensor for Containers in
Motion
LAR-13327 B85-10472 03

Fuel Gage for Sloshing Tanks
LAR-13147 B85-10515 06

FUEL INJECTION

Low-Loss Fuel and Oxidizer Injector
MFS-25989 B85-10104 07

FUEL TANKS

Fuel Gage for Sloshing Tanks
LAR-13147 B85-10515 06

FUNCTION GENERATORS

Function Generator for Image
Processor
NPO-16461 B85-10460 02

FURNACES

High-Temperature Hall-Effect
Apparatus
NPO-16279 B85-10038 02

Prototype Furnace for Automatic
Production of Silicon Ribbon
NPO-16175 B85-10272 08

Research Furnace for Crystal
Preparation
LAR-13302 B85-10496 04

G

GALLIUM ARSENIDES

Measuring Carrier Lifetime in GaAs
by Luminescence
NPO-16337 B85-10334 04

GAMMA RAY ABSORPTIOMETRY

Liquid-Level Monitor for Pressurized
Vessels
LAR-13208 B85-10366 06

GAMMA RAYS

Protective Package for a Gamma-Ray
Detector
NPO-16019 B85-10041 03

Segmented Detector for Cosmic
Gamma Rays
NPO-16245 B85-10053 03

GAPS

Hand-Held Electronic Gap-Measuring
Tools
MSC-20176 B85-10223 06

GARMENTS

Lightweight Protective Garments
NPO-16510 B85-10497 04

GAS ANALYSIS

Technique for Measuring Gas
Conversion Factors
LAR-13220 B85-10470 03

GAS DETECTORS

Monitoring Trace Gases in the
Atmosphere
NPO-16278 B85-10175 03

Methane Detector With Plastic
Fresnel Lens
NPO-16284 B85-10321 03

GAS EXPLOSIONS

Curtain Wall Creates Ventilation
Channel
NPO-16194 B85-10244 07

SUBJECT INDEX

GAS FLOW
 Simulating Pressure Effects of
 High-Flow Volumes
 MFS-19909 B85-10103 07
 Back-Pressure Regulator for Large
 Gas Flows
 MSC-20536 B85-10109 07

GAS LASERS
 Long-Gain-Length, Solar-Pumped
 Box Laser
 LAR-13256 B85-10319 03
 Magnetically-Switched, Long-Pulse
 XeCl Laser
 NPO-16410 B85-10430 01

GAS TURBINE ENGINES
 Squeeze-Film Damper Controls High
 Vibrations
 LEW-13506 B85-10528 06

GAS TURBINES
 Flow Through Gas-Turbine Ducts
 LEW-14095 B85-10533 06

GAS-METAL INTERACTIONS
 Measuring Hydrogen Concentrations
 in Metals
 MFS-27020 B85-10199 04

GEARS
 Optimizing Load Spectra for Gears
 MSC-20487 B85-10260 07
 Automatically-Programed Machine
 Tools
 GSC-12758 B85-10264 07
 Synthesis and Optimization of Spiral
 Bevel Gears
 LEW-13920 B85-10389 07
 Dynamic Effects of Internal
 Spur-Gear Drives
 LEW-14167 B85-10553 07

GENERATORS
 Calibrating Droplet Generator for
 Pressurized Testing Vessel
 MFS-25992 B85-10094 06

GEODESY
 Solving Large Systems of Normal
 Equations
 GSC-12858 B85-10421 09

GEOMETRY
 Geometric Representations for
 Discrete Fourier Transforms
 MFS-27072 B85-10559 09

GERMANIUM
 High-Quality, Thin-Film Germanium
 Single Crystals
 LAR-13211 B85-10406 08

GLANDS (SEALS)
 Low-Temperature Seal for Actuator
 Rod
 MSC-20744 B85-10229 06
 Replaceable Transfer Tube for
 High-Pressure Cavities
 MFS-19775 B85-10395 07

GLASS
 Reversing Glass Wettability
 MFS-26006 B85-10071 04

GLASS FIBER REINFORCED
PLASTICS
 Making Glass-Fiber-Reinforced
 Coolant Tubes
 MSC-20677 B85-10276 08

GLASSWARE
 Reversing Glass Wettability
 MFS-26006 B85-10071 04

GLOBAL POSITIONING SYSTEM
 Doubly-Differenced Measurements
 for Orbit Determinations
 NPO-16111 B85-10040 02

GRAPHITE
 Apparatus for Sizing and Rewinding
 Graphite Fibers
 LAR-13323 B85-10556 08

GRAPHITE-EPOXY COMPOSITES
 Rubberized, Brominated Epoxies
 ARC-11427 B85-10079 04
 Drilling Holes in Graphite/Epoxy
 Composites
 MFS-28044 B85-10398 07

GRAPHITE-POLYIMIDE COMPOSITES
 Bonded and Bolted
 Graphite/Polyimide Composite Joints
 LAR-13090 B85-10130 08

GRAVITY GRADIENT SATELLITES
 Tethered Communication Satellites
 MFS-28042 B85-10375 06

GRAZING INCIDENCE
 Nearly Anastigmatic X-Ray
 Telescope
 MFS-25984 B85-10047 03

GREASES
 Further Tests of 38 Ball-Bearing
 Greases
 MFS-27043 B85-10084 04

GRINDING MILLS
 Improved Jet-Mill Silicon Grinder
 NPO-16336 B85-10349 04

GUIDANCE SENSORS
 Automatic Guidance for Remote
 Manipulator
 NPO-13386 B85-10453 02

H

HALL EFFECT
 High-Temperature Hall-Effect
 Apparatus
 NPO-16279 B85-10038 02

HAMMERS
 Damage-Free Relief-Valve
 Disassembly
 MFS-28006 B85-10361 06
 Dent-Removing Tool
 MFS-29044 B85-10554 08

HANDBOOKS
 Mechanical Design Handbook for
 Elastomers
 LEW-14160 B85-10502 04

HEAT
 Estimates of Latent Heat in Clouds
 MFS-25977 B85-10055 03

HEAT EXCHANGERS
 Contact Heat Exchanger
 MSC-20419 B85-10092 06
 Reciprocating Magnetic Refrigerator
 NPO-16257 B85-10107 07
 Pumped, Two-Phase Heat-Transfer
 Loop
 MSC-20841 B85-10542 07

HEAT MEASUREMENT
 Combination Heat-Flux and
 Temperature Gage
 MSC-20706 B85-10221 06
 Contactless Calorimetry for Levitated
 Samples
 NPO-16448 B85-10318 03

HEAT PIPES
 High-Performance Heat Pipe
 MSC-20136 B85-10177 03
 Titanium Heat-Pipe Wicks
 MFS-26016 B85-10524 06
 Rotary Joint for Heat Transfer
 MFS-26015 B85-10546 07

HUMIDITY MEASUREMENT

HEAT RADIATORS
 Puncture-Tolerant Heat Radiator
 NPO-16401 B85-10390 07

HEAT TRANSFER
 Solution of Radiation and Convection
 Heat-Transfer Problems
 LEW-13978 B85-10537 06
 Pumped, Two-Phase Heat-Transfer
 Loop
 MSC-20841 B85-10542 07
 Rotary Joint for Heat Transfer
 MFS-26015 B85-10546 07

HEATING EQUIPMENT
 Differential Temperature Control of
 Electrical Heaters
 LAR-13047 B85-10099 06
 Pumped, Two-Phase Heat-Transfer
 Loop
 MSC-20841 B85-10542 07

HELICOPTER PERFORMANCE
 Tabs Reduce Helicopter-Blade
 Vibrations
 ARC-11444 B85-10227 06

HELMETS
 Communications Headgear With
 Protective Features
 LAR-13156 B85-10166 02

HIGH TEMPERATURE
 High-Temperature Hall-Effect
 Apparatus
 NPO-16279 B85-10038 02

HIGH VOLTAGES
 Fast-Recovery, High-Voltage Power
 Diode
 LEW-14036 B85-10016 01
 Incrementally Variable High-Voltage
 Supply
 MFS-28018 B85-10145 01
 Remotely-Adjustable Solid-State
 High-Voltage Supply
 NPO-15719 B85-10151 01

HINGES
 Toggle Hinge for Deployable Struts
 MFS-28037 B85-10369 06

HOLDERS
 Manipulator for Heating and Cooling
 in Ultrahigh Vacuum
 LAR-13040 B85-10051 03
 Ultrahigh-Vacuum Sample-Transfer
 System
 LAR-12993 B85-10057 03
 Spring-Loaded Transducer Holder
 LAR-13048 B85-10098 06
 Cutting Guide for Fibrous Sheets
 MSC-20798 B85-10132 08
 Optical Mounts for Cryogenic Beam
 Splitters
 GSC-12923 B85-10180 03

HORN ANTENNAS
 Dual-Mode Horn Antenna for
 Millimeter Wavelengths
 NPO-16297 B85-10006 01

HOT ELECTRONICS
 Molecular Thermal-Electron
 Detectors
 NPO-16300 B85-10467 03

HOT PRESSING
 Melt-Pressed Films of Insoluble
 Semicrystalline Polymers
 LAR-13212 B85-10351 04

HUMIDITY
 Low-Cost Humidity Sensor
 NPO-16544 B85-10440 01

HUMIDITY MEASUREMENT
 Low-Cost Humidity Sensor
 NPO-16544 B85-10440 01

HYBRID CIRCUITS

HYBRID CIRCUITS

Hybrid Fiber-Optic/CCD Chip
NPO-16030 B85-10002 01

HYBRID PROPULSION

Compact Hybrid Automotive
Propulsion System
NPO-16117 B85-10386 07

HYDRATION

Effect of Hydration on Nitrogen
Washout in Humans
MSC-20686 B85-10087 05

HYDRAULIC EQUIPMENT

Hydraulic Cylinder With an Integral
Position Indicator
LAR-13095 B85-10518 06

HYDRAULIC JETS

Reducing Coal Dust With Water Jets
NPO-16180 B85-10236 07
All-Water-Jet Coal Excavator
NPO-16183 B85-10238 07
Pulsed, Hydraulic Coal-Mining
Machine
NPO-15859 B85-10388 07

HYDROCARBON COMBUSTION

Technique for Measuring Gas
Conversion Factors
LAR-13220 B85-10470 03

HYDROGEN ATOMS

Intense Source of Polarized
Hydrogen Atoms
NPO-16434 B85-10466 03

HYDROGEN EMBRITTLEMENT

Measuring Hydrogen Concentrations
in Metals
MFS-27020 B85-10199 04

HYDROGEN PRODUCTION

Methanol Fuel Cell
NPO-15823 B85-10050 03

HYPERSONIC WIND TUNNELS

Fast-Response Oxygen-Monitoring
and Control System
LAR-13257 B85-10487 04

I

IMAGE PROCESSING

Processing of Image Data by
Integrated Circuits
NPO-15059 B85-10164 02
Image Interpolation With Dedicated
Digital Hardware
GSC-12882 B85-10312 02
Algorithms for Coastal-Zone
Color-Scanner Data
GSC-12852 B85-10328 03
Coding for Efficient Image
Transmission
NPO-16444 B85-10416 09
Convolver for Pipelined-Image
Processor
NPO-16462 B85-10451 02
Picture-Element Comparator
NPO-16464 B85-10458 02
Programmable Pipelined-Image
Processor
NPO-16463 B85-10459 02
Function Generator for Image
Processor
NPO-16461 B85-10460 02
Image-Processing Educator
GSC-12933 B85-10566 09

IMAGE RESOLUTION

Calculating Atmospheric Effects in
Satellite Imagery
NPO-16373 B85-10327 03

IMAGERY

SAW-Modulated Image Device
LAR-12633 B85-10009 01
Imaging Spectrometer for
Geophysical Surveys
NPO-16072 B85-10046 03

IMAGING TECHNIQUES

Finding Bright-Spot Coordinates in
Television Images
MFS-25999 B85-10034 02
Wide-Angle, Wide-Band Camera for
Remote Imaging
NPO-15799 B85-10052 03
Multispectral Analysis of NMR
Imagery
KSC-11301 B85-10215 05
Optical Scanner for Linear Arrays
GSC-12897 B85-10320 03
Convolver for Pipelined-Image
Processor
NPO-16462 B85-10451 02
Compact Imaging Spectrometer
NPO-16342 B85-10471 03

IMIDES

Synthesizing Metal Phthalocyanine
Imide Polymers
ARC-11413 B85-10074 04
Solvent-Resistant, Thermally Stable
Poly(Carbonate-Imides)
LAR-13292 B85-10485 04

IMPACT LOADS

Predicting Effects of Impacts on
Confined Explosives
NPO-16258 B85-10083 04

IMPACT RESISTANCE

Rubberized, Brominated Epoxies
ARC-11427 B85-10079 04

IMPEDANCE

Lowering Ammeter Input Impedance
NPO-16067 B85-10022 01
Power-Factor Controllers: How
Safe?
MFS-27016 B85-10024 01

INDICATING INSTRUMENTS

Reed-Switch Position Indicator
KSC-11215 B85-10152 01
Airborne Cloud Detector
LAR-13137 B85-10167 02

INDUCTORS

Precise Fabrication of
Electromagnetic-Levitation Coils
MFS-25986 B85-10126 08
Removing Heat From Toroidal
Inductors
NPO-16386 B85-10293 01
Multiple-Winding Output Inductors for
Power Converters
NPO-16176 B85-10434 01

INDUSTRIAL WASTES

Solar-Assisted Oxidation of Toxic
Cyanide
LAR-13171 B85-10075 04

INFORMATION MANAGEMENT

Requirements Analysis for
Information-Intensive Systems
NPO-15944 B85-10415 09
Text Exchange System
NPO-16357 B85-10419 09

INFORMATION RETRIEVAL

Text File Display Program
NPO-16358 B85-10423 09

INFRARED DETECTORS

Preparation and Characterization of
HgxCd1-xTe
MFS-27037 B85-10081 04

SUBJECT INDEX

Characterizing Semiconductor Alloys
for Infrared Sensors
MFS-27059 B85-10355 04

INFRARED IMAGERY

Infrared Linear Imaging Array
NPO-15805 B85-10023 01

INFRARED LASERS

Long-Gain-Length, Solar-Pumped
Box Laser
LAR-13256 B85-10319 03
Generating Tunable Far-Infrared
Laser Sidebands
NPO-16497 B85-10450 02

INFRARED RADIATION

Measuring Clouds With Microwaves
and Infrared
NPO-16265 B85-10045 03

INFRARED SPECTROMETERS

Lens-and-Detector Array for
Spectrometer
NPO-16388 B85-10184 03
Fourier-Transform Infrared
Spectrometer
NPO-16431 B85-10317 03
Reflecting Slit for Imaging
Spectrometer
NPO-16408 B85-10322 03
Tracking System for Infrared
Spectrometer
NPO-16440 B85-10464 03
Compact Imaging Spectrometer
NPO-16342 B85-10471 03

INFRARED TRACKING

Tracking System for Infrared
Spectrometer
NPO-16440 B85-10464 03

INFRARED WINDOWS

High-Temperature, High-Pressure
Optical Cells
MFS-26000 B85-10267 08

INGOTS

Calculation of Macrosegregation in an
Ingot
MFS-27068 B85-10481 03

INJECTION LASERS

High-Output Injection Laser
LAR-13213 B85-10149 01

INJECTORS

Replaceable Transfer Tube for
High-Pressure Cavities
MFS-19775 B85-10395 07

INPUT/OUTPUT ROUTINES

Personal-Computer Video-Terminal
Emulator
KSC-11293 B85-10286 09
Three-Dimensional Turbomachine-
Blade-Row Analysis Code
LEW-14061 B85-10400 07
Text Exchange System
NPO-16357 B85-10419 09
Text File Display Program
NPO-16358 B85-10423 09

INSPECTION

Detecting Cracks in Rough Metal
Surfaces
MSC-20734 B85-10230 06
Controlled-Shape, Ultrasonic-Angle-
Beam Standard Reflector
LAR-13153 B85-10410 08

INSULATION

Lightweight Electrical Insulation
NPO-16165 B85-10193 04
Insulating Cryogenic Pipes With
Frost
MSC-20426 B85-10249 07

L

Insulation Blankets for
High-Temperature Use
ARC-11453 B85-10489 04

ION IMPLANTATION
Ion Implantation Improves
Bearing-Surface Properties
MFS-25995 B85-10197 04

ION IRRADIATION
Modeling 'Soft' Errors in Bipolar
Integrated Circuits
NPO-16375 B85-10158 01

IONIC DIFFUSION
Discoloration of Polyvinyl Butyral
NPO-16411 B85-10353 04

IONIZING RADIATION
Degradation of Dielectrics in Space
NPO-16003 B85-10209 04
Testing Electronic Devices for
Single-Event Upset
NPO-16468 B85-10454 02

IRON
Cast Iron With High Carbon Content
MFS-28014 B85-10500 04

ISOLATORS
High-Voltage Isolation Transformer
GSC-12817 B85-10018 01

J

JACKETS
Insulation Blankets for
High-Temperature Use
ARC-11453 B85-10489 04

JET ENGINES
Improved Exhaust Diffuser for
Jet-Engine Testing
NPO-16328 B85-10255 07
Analysis of Scramjet Inlets
LAR-13297 B85-10382 06

JIGS
End Restraints for
Impact-Energy-Absorbing Tube
Specimens
LAR-13179 B85-10218 06
Holder for Ultrasonic Evaluation of
Small-Diameter Tubes
LAR-13152 B85-10245 07
Precise Electrochemical Drilling of
Repeated Deep Holes
MFS-19767 B85-10250 07
Aligning Large Cylinders for Welding
MFS-28001 B85-10271 08
Adhesive-Bonded Fixture for Flexure
Testing
MFS-28051 B85-10360 06

JOINTS (JUNCTIONS)
Bonded and Bolted
Graphite/Polyimide Composite Joints
LAR-13090 B85-10130 08
Bistable Articulated Joint
NPO-16038 B85-10393 07

JOULE-THOMSON EFFECT
LaNi₅ Hydrogen-Absorption
Cryogenic System
NPO-16314 B85-10387 07

K

KALMAN FILTERS
Design of Linear Quadratic
Regulators and Kalman Filters
LEW-14128 B85-10461 02

KAPTON (TRADEMARK)
Silicone Coating on Polyimide Sheet
GSC-12913 B85-10068 04

Insulation Blankets for
High-Temperature Use
ARC-11453 B85-10489 04

INTEGRATED CIRCUITS
Protective Cover for IC Packages
NPO-15537 B85-10011 01
Designing Test Chips for Custom
Integrated Circuits
NPO-15988 B85-10032 02
Modeling 'Soft' Errors in Bipolar
Integrated Circuits
NPO-16375 B85-10158 01
Study of Contact Resistances in
Integrated Circuits
NPO-16248 B85-10159 01
Processing of Image Data by
Integrated Circuits
NPO-15059 B85-10164 02
Latchup in CMOS Integrated Circuits
NPO-16304 B85-10170 02
Analyzing Microchips With Dark-Field
Negative Photomicrography
NPO-16299 B85-10179 03
Modular VLSI Reed-Solomon
Decoder
NPO-15837 B85-10306 02
Fast VLSI Viterbi Decoder
NPO-16365 B85-10311 02
Metalization Patterns by Thermal
Decomposition
NPO-16413 B85-10408 08

INTEGRATED ENERGY SYSTEMS
Cost and Performance Model for
Photovoltaic Systems
NPO-16404 B85-10314 02

INTEGRATED OPTICS
Crossover Concept for Optical
Printed Circuits
NPO-15131 B85-10186 03
Polarizing Filter for Integrated Optics
NPO-16429 B85-10288 01

INTERCALATION
Intercalated-Carbon Low-Resistivity
Fibers
NPO-16307 B85-10196 04

INTERFEROMETRY
Interferometry Measures Elliptical
Satellite Orbits
NPO-16313 B85-10171 02

INTERNAL COMBUSTION ENGINES
Carbon/Carbon Pistons for Internal
Combustion Engines
LAR-13150 B85-10547 07

INTERPHONES
Communications Headgear With
Protective Features
LAR-13156 B85-10166 02

INTERPOLATION
Image Interpolation With Dedicated
Digital Hardware
GSC-12882 B85-10312 02

INTERPROCESSOR COMMUNICATION
Synchronizing Data-Bus Messages
MSC-20640 B85-10035 02

INTERROGATION
Self-Identifying Reflecting Targets
NPO-16106 B85-10033 02

INVERTERS
Remotely-Adjustable Solid-State
High-Voltage Supply
NPO-15719 B85-10151 01
Rotary Power Transformer and
Inverter Circuit
NPO-16270 B85-10156 01
Program Predicts Nonlinear Inverter
Performance
MSC-20769 B85-10172 02

LABORATORY EQUIPMENT

Laser Schlieren Crystal-Growth
Imager
MFS-28060 B85-10326 03

LABYRINTH SEALS
Predicting Leakage in Labyrinth
Seals
MFS-27051 B85-10261 07

LAMINAR FLOW
Continuous Laminar-Smoke
Generator
LAR-13014 B85-10090 06
Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06

LAMINATES
Photovoltaic-Panel Laminator
NPO-16092 B85-10123 08
Perforating Thin Metal Sheets
ARC-11280 B85-10125 08
Plastic and Failure Analysis of
Composites
LAR-13183 B85-10213 04

LANDFORMS
Processing Digital Imagery Data
MFS-25987 B85-10285 09

LAP JOINTS
Strength of Graphite/Metal
Composite Lap Joints
MFS-27030 B85-10082 04

LASER DAMAGE
Shielding Against Intense Laser
Beams
NPO-16166 B85-10067 04

LASER DOPPLER VELOCIMETERS
Vibration-Free Raman Doppler
Velocimeter
LAR-13268 B85-10447 02

LASER PUMPING
Hybrid Laser Would Combine Power
With Efficiency
NPO-16173 B85-10473 03

LASER SPECTROMETERS
Laser-Assisted Analysis of Aerosol
Particles
NPO-15308 B85-10056 03
Monitoring Trace Gases in the
Atmosphere
NPO-16278 B85-10175 03

LASERS
Shielding Against Intense Laser
Beams
NPO-16166 B85-10067 04
Microprocessor-Controlled Laser
Balancing System
LEW-13294 B85-10093 06
Calibrating Droplet Generator for
Pressurized Testing Vessel
MFS-25992 B85-10094 06
Laser Links for Instrumentation
Systems
MSC-20863 B85-10313 02
Long-Gain-Length, Solar-Pumped
Box Laser
LAR-13256 B85-10319 03
Pulse Coupling for Laser Excitation
NPO-16403 B85-10428 01
Generating Independent Preionizing
Pulses for Lasers
NPO-16402 B85-10429 01
Magnetically-Switched, Long-Pulse
XeCl Laser
NPO-16410 B85-10430 01

LATCH-UP

SUBJECT INDEX

- Improved Waveguide Laser Array
NPO-16500 B85-10435 01
Generating Tunable Far-Infrared
Laser Sidebands
NPO-16497 B85-10450 02
Hybrid Laser Would Combine Power
With Efficiency
NPO-16173 B85-10473 03
Wedge Fibers Suppress Feedback
of Laser Beam
LAR-13074 B85-10474 03
Zone Refining by Laser
MFS-27084 B85-10555 08
- LATCH-UP**
Latchup in CMOS Integrated Circuits
NPO-16304 B85-10170 02
- LATCHES**
Aircraft Canopy Lock
FRC-11065 B85-10088 06
Wide-Grasp Latching Mechanism
MFS-28002 B85-10118 07
Latch for Telescoping Structures
LAR-13169 B85-10507 06
Locking Pull Pin
NPO-16233 B85-10512 06
- LATENT HEAT**
Estimates of Latent Heat in Clouds
MFS-25977 B85-10055 03
- LEAD ACID BATTERIES**
Battery-Charge-State Model
NPO-16158 B85-10058 03
- LEADING EDGE FLAPS**
Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06
- LEAKAGE**
Sensitivities of Soap Solutions in
Leak Detection
MFS-19864 B85-10121 07
Predicting Leakage in Labyrinth
Seals
MFS-27051 B85-10261 07
- LENGTH**
Measuring Perimeters of Large
Round Objects
MFS-28046 B85-10365 06
- LEVEL (HORIZONTAL)**
Electronic/Hydraulic Level Gage
MFS-28066 B85-10522 06
- LEVEL (QUANTITY)**
Liquid-Level Monitor for Pressurized
Vessels
LAR-13208 B85-10366 06
Noninvasive Fluid Level Sensor for
Organometallic Sources
LAR-13265 B85-10371 06
- LEVITATION**
Hybrid Contactless Heating and
Levitation
NPO-15657 B85-10122 08
Precise Fabrication of
Electromagnetic-Levitation Coils
MFS-25986 B85-10126 08
Blowing Polymer Bubbles in an
Acoustic Levitator
NPO-16212 B85-10203 04
Controlling Sample Rotation in
Acoustic Levitation
NPO-15962 B85-10277 08
- LIAPUNOV FUNCTIONS**
Vector Lyapunov Functions for
Stochastic Interconnected Systems
NPO-16170 B85-10139 09
- LIFE (DURABILITY)**
Orienting Arc Lamps for Longest
Life
MSC-20562 B85-10155 01
- LIGHT EMITTING DIODES**
Double Light-Emitting Diode
GSC-12832 B85-10015 01
- LIGHT SOURCES**
Double Light-Emitting Diode
GSC-12832 B85-10015 01
- LIGHTNING**
Plotting Lightning-Stroke Data
MFS-26019 B85-10462 03
- LINEAR ARRAYS**
Optimizing a Linear Array of Radiating
Elements
NPO-16352 B85-10298 01
- LINEAR EQUATIONS**
Residue-Measure Model-Reduction
Technique
MSC-20369 B85-10137 09
- LINKAGES**
Continuously Variable Transmission
LAR-12844 B85-10105 07
Bistable Articulated Joint
NPO-16038 B85-10393 07
Latch for Telescoping Structures
LAR-13169 B85-10507 06
- LIQUID CHROMATOGRAPHY**
Spill-Detector-and-Shutoff Device
MSC-20206 B85-10106 07
- LIQUID HYDROGEN**
LaNi₅ Hydrogen-Absorption
Cryogenic System
NPO-16314 B85-10387 07
- LIQUID LEVELS**
Liquid-Level Sensor for Containers in
Motion
LAR-13327 B85-10472 03
- LIQUID METALS**
Heat-Powered Pump for Liquid
Metals
NPO-16457 B85-10396 07
- LITHIUM**
Improved Electrodes for Lithium
Cells
NPO-16397 B85-10201 04
- LOAD TESTING MACHINES**
Testing Machine for Biaxial Loading
MSC-20477 B85-10220 06
Friction-Testing Machine
MSC-20622 B85-10370 06
- LOAD TESTS**
Smoothly Adjustable dc Load
MSC-20853 B85-10289 01
- LOADS (FORCES)**
Calculating Bearing Forces From
Strain-Gage Signals
MFS-29000 B85-10510 06
- LOCKS (FASTENERS)**
Blind-Side, High-Temperature
Fastener Lock
LAR-13037 B85-10248 07
Toggle Hinge for Deployable Struts
MFS-28037 B85-10369 06
- LOGIC CIRCUITS**
Complementary-Logic Fault Detector
NPO-15410 B85-10017 01
Single-Event-Upset Studies: A
Compilation
NPO-16362 B85-10297 01
Interface Circuits for Self-Checking
Microprocessors
NPO-15700 B85-10309 02
Multiplier Architecture for Coding
Circuits
NPO-16363 B85-10456 02
Picture-Element Comparator
NPO-16464 B85-10458 02
- LOGIC DESIGN**
Design Language for Digital
Systems
MFS-25352 B85-10281 09
- LOW GRAVITY MANUFACTURING**
Cast Iron With High Carbon Content
MFS-28014 B85-10500 04
Solidifying Cast Iron in Low Gravity
MFS-27069 B85-10504 04
- LOW VOLTAGE**
Low-Voltage Protection For Volatile
Computer Memories
NPO-15909 B85-10146 01
- LUGS**
Electrically Connecting to Pressure
Vessels
MSC-20709 B85-10154 01

M

- MACHINE TOOLS**
Flushing Ring for EDM
MFS-19876 B85-10108 07
Analysis of Spiral Bevel Gearing
LEW-14067 B85-10265 07
Constant-Pressure Sawing
NPO-15233 B85-10383 07
Forbidden Zones for
Numerically-Controlled Machine Tools
MFS-19950 B85-10397 07
Adjustable-Angle Drill Block
LAR-13101 B85-10545 07
- MACHINING**
Compensating for Shrinkage in
Machined Ceramics
MSC-20684 B85-10394 07
- MAGNETIC STORAGE**
Recovering Energy From Relays
NPO-16268 B85-10012 01
- MAGNETIC TAPES**
Encoding Scheme Reduces
Hardware Requirements
MSC-20044 B85-10138 09
- MAGNETRON SPUTTERING**
Magnetron-Sputtered Amorphous
Metallic Coatings
NPO-16221 B85-10204 04
Magnetron Sputtering Deposits
Corrosion-Resistant Alloy
NPO-15928 B85-10337 04
- MAINTENANCE**
Dent-Removing Tool
MFS-29044 B85-10554 08
- MANAGEMENT INFORMATION SYSTEMS**
Requirements Analysis for
Information-Intensive Systems
NPO-15944 B85-10415 09
- MANIFOLDS**
Advanced Vapor-Supply Manifold
LAR-13259 B85-10523 06
- MANIPULATORS**
Manipulator for Heating and Cooling
in Ultrahigh Vacuum
LAR-13040 B85-10051 03
Ultrahigh-Vacuum Sample-Transfer
System
LAR-12993 B85-10057 03
Experiments With a Manipulator
Sensor System
NPO-16094 B85-10262 07
Automatic Guidance for Remote
Manipulator
NPO-13386 B85-10453 02

SUBJECT INDEX

MINING

MASS FLOW
Off-Design Performance of
Radial-Inflow Turbines
LEW-14060 B85-10402 07

MASS SPECTROMETERS
Mass Spectrometer for Airborne
Micro-Organisms
NPO-16359 B85-10505 05

MASS SPECTROSCOPY
Laser-Assisted Analysis of Aerosol
Particles
NPO-15308 B85-10056 03
Molecular-Beam Chopper and
Four-Channel Amplifier
LAR-13174 B85-10316 03

MATHEMATICAL MODELS
Battery-Charge-State Model
NPO-16158 B85-10058 03
Synthesis and Optimization of Spiral
Bevel Gears
LEW-13920 B85-10389 07
Computing Relative Joint Positions of
Robot Arms
LAR-13264 B85-10414 09
Computational Simplification of
Robot-Arm Dynamics
NPO-16377 B85-10417 09

MATRICES (MATHEMATICS)
Solving Large Systems of Normal
Equations
GSC-12858 B85-10421 09

MEASURING INSTRUMENTS
Measuring Perimeters of Large
Round Objects
MFS-28046 B85-10365 06
Rotating Capacitor Measures Steady
Electric Fields
NPO-16550 B85-10449 02
Electronic/Hydraulic Level Gage
MFS-28066 B85-10522 06

MECHANICAL DEVICES
Mechanical Mixer for Rudder/Braking
Wedge
MSC-20759 B85-10117 07

MECHANICAL DRIVES
Continuously Variable Transmission
LAR-12844 B85-10105 07
Multistage Planetary Power
Transmissions
LEW-14100 B85-10399 07
Dynamic Effects of Internal
Spur-Gear Drives
LEW-14167 B85-10553 07

MECHANICAL MEASUREMENT
Hand-Held Electronic Gap-Measuring
Tools
MSC-20176 B85-10223 06

MECHANICAL PROPERTIES
Resin Characterization in Cured
Composite Materials
LAR-13172 B85-10072 04
Strength of Graphite/Metal
Composite Lap Joints
MFS-27030 B85-10082 04

MEDICAL ELECTRONICS
Multispectral Analysis of NMR
Imagery
KSC-11301 B85-10215 05

MELTS (CRYSTAL GROWTH)
Melt Stirring by Horizontal Crucible
Vibration
MFS-26005 B85-10069 04

MERCURY CADMIUM TELLURIDES
Preparation and Characterization of
HgxCd_{1-x}Te
MFS-27037 B85-10081 04

Measuring Thermal Diffusivity of
Molten Semiconductors
MFS-28047 B85-10350 04
Characterizing Semiconductor Alloys
for Infrared Sensors
MFS-27059 B85-10355 04

METAL COATINGS
Spray Application of Rapidly Solidified
Metals
GSC-12880 B85-10131 08
Magnetron-Sputtered Amorphous
Metallic Coatings
NPO-16221 B85-10204 04
Coating a Sphere With Evaporated
Metal
NPO-16436 B85-10404 08

METAL CUTTING
Cutthrough Warning Circuit
MFS-19900 B85-10119 07

METAL SHEETS
Perforating Thin Metal Sheets
ARC-11280 B85-10125 08

METALLIZING
Metalization Patterns by Thermal
Decomposition
NPO-16413 B85-10408 08

METHANE
Methane Detector With Plastic
Fresnel Lens
NPO-16284 B85-10321 03

METHYL ALCOHOL
Methanol Fuel Cell
NPO-15823 B85-10050 03

MICHELSON INTERFEROMETERS
Fourier-Transform Infrared
Spectrometer
NPO-16431 B85-10317 03

MICROCOMPUTERS
'Speaking' Microcomputer
MFS-25976 B85-10307 02
Interface Circuits for Self-Checking
Microprocessors
NPO-15700 B85-10309 02
Measuring Thermoelectric Properties
Automatically
NPO-16507 B85-10488 04
Image-Processing Educator
GSC-12933 B85-10566 09

MICROCRACKS
Microfracturing in
Electron-Beam-Welded Nickel Alloy
MFS-27041 B85-10198 04

MICROELECTRONICS
Infrared Linear Imaging Array
NPO-15805 B85-10023 01
Designing Test Chips for Custom
Integrated Circuits
NPO-15988 B85-10032 02

MICROMODULES
Conductive Container for
Semiconductor Devices
NPO-16110 B85-10439 01

MICROORGANISMS
Mass Spectrometer for Airborne
Micro-Organisms
NPO-16359 B85-10505 05

MICROPHONES
Miniature Microphone Adapter
LAR-13210 B85-10521 06
Microphone Boom for Aircraft-Engine
Monitoring
ARC-11495 B85-10525 06

MICROPROCESSORS
Storing Data and Video on One
Tape
MSC-20705 B85-10027 02

Redundant Asynchronous
Microprocessor System
ARC-11348 B85-10031 02
Microprocessor-Controlled Laser
Balancing System
LEW-13294 B85-10093 06

MICROWAVE ANTENNAS
Improved Thick Dichroic Reflector for
Microwave Feeds
NPO-13506 B85-10004 01

MICROWAVE OSCILLATORS
Programmable Driver for
Voltage-Controlled Oscillators
NPO-16364 B85-10162 02

MICROWAVE RADIOMETERS
Measuring Soil Hydraulic Conductivity
With Microwaves
GSC-12937 B85-10176 03

MICROWAVE SENSORS
Microwave Atmospheric-Pressure
Sensor
NPO-16496 B85-10478 03

MICROWAVE SWITCHING
Microwave Power Combiner With
Switching Diodes
NPO-15775 B85-10432 01

MICROWAVES
Measuring Clouds With Microwaves
and Infrared
NPO-16265 B85-10045 03
Recovering Microwave
Cross-Polarization Losses
NPO-15353 B85-10168 02

MILLIMETER WAVES
Dual-Mode Horn Antenna for
Millimeter Wavelengths
NPO-16297 B85-10006 01

MINES (EXCAVATIONS)
Curtain Wall Creates Ventilation
Channel
NPO-16194 B85-10244 07

MINIATURE ELECTRONIC EQUIPMENT
Solid-State Detector for Trace
Materials
NPO-16450 B85-10469 03

MINING
Automated Coal-Mining System
NPO-16177 B85-10233 07
Pointable Auger
NPO-16178 B85-10234 07
Modular Pick-and-Bucket Mining
Machine
NPO-16179 B85-10235 07
Reducing Coal Dust With Water Jets
NPO-16180 B85-10236 07
Slurry-Mixing Chamber
NPO-16182 B85-10237 07
All-Water-Jet Coal Excavator
NPO-16183 B85-10238 07
Coal-Sizing Auger
NPO-16184 B85-10239 07
Service Modules for Coal Extraction
NPO-16185 B85-10240 07
Side Shield for Wall Support
NPO-16188 B85-10241 07
Roof Shield for Advance and Retreat
Mining
NPO-16189 B85-10242 07
Compact Hydraulic Excavator and
Support Unit
NPO-16190 B85-10243 07
Pulsed, Hydraulic Coal-Mining
Machine
NPO-15859 B85-10388 07

MINORITY CARRIERS

SUBJECT INDEX

MINORITY CARRIERS

Measuring Carrier Lifetime in GaAs
by Luminescence
NPO-16337 B85-10334 04

MIRRORS

Telescope With Reflecting Baffle
ARC-11502 B85-10043 03
Economical Fabrication of Large
Parabolic Mirrors
LAR-13139 B85-10405 08

MIXERS

Slurry-Mixing Chamber
NPO-16182 B85-10237 07

MIXING

Melt Stirring by Horizontal Crucible
Vibration
MFS-26005 B85-10069 04
Ultrasonic Mixing of Epoxy Curing
Agents
LAR-13307 B85-10498 04

MOISTURE METERS

Measuring Moisture in Sealed
Electronic Enclosures
MSC-18866 B85-10183 03
Low-Cost Humidity Sensor
NPO-16544 B85-10440 01

MOISTURE RESISTANCE

Chromium Ions Improve Moisture
Resistance of Epoxy Resins
LAR-13226 B85-10486 04

MONITORS

Digital High-Current Monitor
LAR-13072 B85-10003 01
High-Visibility Data Display
MFS-19925 B85-10026 02
A Quick Visual Power-Supply
Monitor
MFS-26014 B85-10436 01
Tester for Distress Beacons
GSC-12892 B85-10442 01

MONTE CARLO METHOD

Simplified Worst-Case Analysis of
Complex Systems
MSC-20232 B85-10135 09

MOTION SIMULATORS

Rocket-Booster Towing Simulation
KSC-11289 B85-10102 06

MOTOR VEHICLES

Rotary Speed Sensor for Antilocking
Brakes
NPO-16479 B85-10509 06

MOTORS

Efficient Power Amplifier for Motor
Control
GSC-12807 B85-10291 01

MOUNTING

Reduced-Stress Mounting for
Thermocouples
NPO-16513 B85-10444 01

MULTIPLEXING

Single-Frequency Multitransmitter
Telemetry
LAR-13006 B85-10039 02

MULTISPECTRAL BAND SCANNERS

Processing Digital Imagery Data
MFS-25987 B85-10285 09

MULTIVARIATE

STATISTICAL
Subset Regression
LEW-14002 B85-10420 09

N

NAVIGATION AIDS

Tester for Distress Beacons
GSC-12892 B85-10442 01

NEODYMIUM LASERS

Hybrid Laser Would Combine Power
With Efficiency
NPO-16173 B85-10473 03

NICKEL ALLOYS

Microfissuring in
Electron-Beam-Welded Nickel Alloy
MFS-27041 B85-10198 04

NITROGEN

Effect of Hydration on Nitrogen
Washout in Humans
MSC-20686 B85-10087 05

NITROGEN POLYMERS

Synthesizing Metal Phthalocyanine
Imide Polymers
ARC-11413 B85-10074 04

NOISE MEASUREMENT

Noise-Path Measurements in Aircraft
Structures
LAR-13017 B85-10529 06

NOISE REDUCTION

Comparator With Noise Suppression
LAR-13151 B85-10147 01
Low-Noise Supersonic Nozzle
LAR-13192 B85-10368 06
Reduction of Vane Noise in
Wind-Tunnel Nozzles
LAR-13333 B85-10527 06

NONDESTRUCTIVE TESTS

Inexpensive Eddy-Current Standard
LAR-13154 B85-10225 06
Detecting Cracks in Rough Metal
Surfaces
MSC-20734 B85-10230 06

NONEQUILIBRIUM CONDITIONS

Process for Nonequilibrium Ternary
Alloys
NPO-16226 B85-10345 04

NONLINEAR OPTICS

Retrodirective-Optical-Transponder
Concept
NPO-16315 B85-10153 01

NOZZLE EFFICIENCY

Performance Improvement for
Nonaxisymmetric Nozzles
LAR-13036 B85-10114 07

NOZZLE FLOW

Low-Noise Supersonic Nozzle
LAR-13192 B85-10368 06

NUCLEAR MAGNETIC RESONANCE

Multispectral Analysis of NMR
Imagery
KSC-11301 B85-10215 05

NUCLEAR POWER PLANTS

Synthetic Organic Materials in
Nuclear Powerplants
NPO-16424 B85-10208 04

NUMERICAL ANALYSIS

Free-Vibration Analysis of Structures
NPO-15000 B85-10279 09
Numerical Aerodynamic Simulation
Facility
ARC-11497 B85-10562 09
Numerical Methods for Classical
Sampled-System Analysis
GSC-12827 B85-10564 09

NUMERICAL CONTROL

High-Speed Computer-Controlled
Switch-Matrix System
LEW-14050 B85-10028 02

Redundant Asynchronous

Microprocessor System
ARC-11348 B85-10031 02

Analysis of Spiral Bevel Gearing
LEW-14067 B85-10265 07

Compensating for Shrinkage in
Machined Ceramics
MSC-20684 B85-10394 07

Forbidden Zones for
Numerically-Controlled Machine Tools
MFS-19950 B85-10397 07

NUMERICAL INTEGRATION

Improved Numerical Evaluation
Method for Elliptic Integrals
ARC-11467 B85-10412 09

O

ONE DIMENSIONAL FLOW

Predicting the Performance of an
Axial-Flow Compressor
LEW-14025 B85-10531 06

OPERATING SYSTEMS (COMPUTERS)

Transportable Applications Executive
GSC-12881 B85-10422 09

OPERATIONAL AMPLIFIERS

Lowering Ammeter Input Impedance
NPO-16067 B85-10022 01
Power-Factor Controllers: How
Safe?
MFS-27016 B85-10024 01

OPTICAL COMMUNICATION

Retrodirective-Optical-Transponder
Concept
NPO-16315 B85-10153 01
Laser Links for Instrumentation
Systems
MSC-20863 B85-10313 02

OPTICAL DATA PROCESSING

Processing of Image Data by
Integrated Circuits
NPO-15059 B85-10164 02
Processing Digital Imagery Data
MFS-25987 B85-10285 09

OPTICAL EQUIPMENT

Wide-Angle, Wide-Band Camera for
Remote Imaging
NPO-15799 B85-10052 03
Designing Eccentric Aperture Optical
Systems
NPO-16355 B85-10329 03

OPTICAL FILTERS

Altering Flashlamp Output for
Realistic Solar Simulation
NPO-16167 B85-10054 03

OPTICAL MEASURING INSTRUMENTS

Optical Integrating Sphere for
Vacuum Ultraviolet
GSC-12849 B85-10325 03

OPTICAL RADAR

Accuracy of Lidar Measurements of
the Atmosphere
NPO-16493 B85-10476 03

OPTICAL SCANNERS

Optical Scanner for Linear Arrays
GSC-12897 B85-10320 03

OPTICAL TRACKING

Sensor Tracks the Sun From Any
Angle
NPO-16211 B85-10308 02

OPTICAL WAVEGUIDES

Hybrid Fiber-Optic/CCD Chip
NPO-16030 B85-10002 01

SUBJECT INDEX

PIPES (TUBES)

Crossover Concept for Optical
Printed Circuits
NPO-15131 B85-10186 03

Polarizing Filter for Integrated Optics
NPO-16429 B85-10288 01

OPTIMIZATION
Optimizing a Linear Array of Radiating
Elements
NPO-16352 B85-10298 01

Optimization of Antenna-Structure
Design
NPO-16158 B85-10299 01

Automated Design Synthesis
LAR-13341 B85-10534 06

ORBIT CALCULATION
Doubly-Differenced Measurements
for Orbit Determinations
NPO-16111 B85-10040 02

ORBITS
Interferometry Measures Elliptical
Satellite Orbits
NPO-16313 B85-10171 02

Orbit Transfer Programs
LEW-14089 B85-10538 06

ORGANIC MATERIALS
Synthetic Organic Materials in
Nuclear Powerplants
NPO-16424 B85-10208 04

ORGANOMETALLIC POLYMERS
Synthesis of Metal Phthalocyanine
Sheet Polymers
ARC-11405 B85-10343 04

OSCILLATION DAMPERS
Squeeze-Film Damper Controls High
Vibrations
LEW-13506 B85-10528 06

OSCILLATIONS
Damping Relaxation Oscillations in
Laser Diodes
NPO-15980 B85-10010 01

OXIDIZERS
Low-Loss Fuel and Oxidizer Injector
MFS-25989 B85-10104 07

OXYGEN
Fast-Response Oxygen-Monitoring
and Control System
LAR-13257 B85-10487 04

OXYGEN ANALYZERS
Fast-Response Oxygen-Monitoring
and Control System
LAR-13257 B85-10487 04

P

PACKINGS (SEALS)
Shaft Seal Compensates for Cold
Flow
MFS-25678 B85-10254 07

PAINTS
Static-Suppressing Optical Paint
NPO-15992 B85-10077 04

Diffusely Reflecting Paints Containing
TFE
GSC-12883 B85-10194 04

PANEL METHOD (FLUID DYNAMICS)
Manipulation and Display of
Panel-Method Geometry
LAR-13224 B85-10282 09

PANELS
Fixture for Linearly Variable
Displacement Transducers
LAR-12937 B85-10224 06

PARABOLIC ANTENNAS
Estimating Antenna Shape From
Far-Field Measurements
NPO-16425 B85-10181 03

Analysis of Satellite Communications
Antenna Patterns
NPO-16400 B85-10283 09

PARABOLIC REFLECTORS
Economical Fabrication of Large
Parabolic Mirrors
LAR-13139 B85-10405 08

**PARALLEL
(COMPUTERS)**
Experimental Parallel-Processing
Computer
NPO-16043 B85-10302 02

PARAMAGNETISM
Paramagnetic Precipitates May Raise
Supercurrent
MFS-25925 B85-10195 04

PARAMETERIZATION
Maximum-Likelihood Parameter-Est-
imation Algorithm
NPO-16320 B85-10560 09

PARTICLE SIZE DISTRIBUTION
Improved Jet-Mill Silicon Grinder
NPO-16336 B85-10349 04

PARTICLES
Laser-Assisted Analysis of Aerosol
Particles
NPO-15308 B85-10056 03

Accurate Airborne Particle Sampler
LAR-13080 B85-10219 06

PELTIER EFFECTS
Studying Crystal Growth With the
Peltier Effect
MFS-28041 B85-10346 04

PERFLUORO COMPOUNDS
Further Tests of 38 Ball-Bearing
Greases
MFS-27043 B85-10084 04

PERFORATING
Perforating Thin Metal Sheets
ARC-11280 B85-10125 08

PERFORMANCE PREDICTION
Kinematic Stirling Engine
Performance
LEW-14092 B85-10482 03

Bearing Thermal Performance
Prediction
LEW-14163 B85-10539 06

PERFORMANCE TESTS
Remotely Piloted Aircraft for
Research
ARC-11498 B85-10120 07

PHASE CONTROL
Controlling Sample Rotation in
Acoustic Levitation
NPO-15962 B85-10277 08

PHASE SHIFT CIRCUITS
Signal Processor for Multirate PSK
Signals
MSC-20195 B85-10008 01

PHASE SHIFT KEYING
Signal Processor for Multirate PSK
Signals
MSC-20195 B85-10008 01

PHENOLIC EPOXY RESINS
Phenoxy Resins Containing Pendant
Ethyne Groups
LAR-13222 B85-10491 04

PHENOLIC RESINS
Phenoxy Resins Containing Pendant
Ethyne Groups
LAR-13222 B85-10491 04

PHOSPHORUS POLYMERS
Imide Cyclotriphosphazene/Hexa-
fluoroisopropylidene Polymers
ARC-11428 B85-10333 04

PHOTOACOUSTIC SPECTROSCOPY
Laser Photoacoustic Technique
Detects Photo-Oxidation
NPO-16108 B85-10324 03

PHOTOCHEMICAL REACTIONS
Nonyellowing Polycarbonate for
Outdoor Use
NPO-15836 B85-10070 04

PHOTOMETERS
Lens-and-Detector Array for
Spectrometer
NPO-16388 B85-10184 03

Multiband Selector for Linear
Photodetector Array
GSC-12911 B85-10187 03

PHOTOOXIDATION
Laser Photoacoustic Technique
Detects Photo-Oxidation
NPO-16108 B85-10324 03

PHOTOVOLTAIC CELLS
Photovoltaics in Japan
NPO-16330 B85-10025 01

Spectrophotovoltaic Power
Generation
MFS-27027 B85-10049 03

Photovoltaic-Panel Laminator
NPO-16092 B85-10123 08

Segmented Trough Reflector
NPO-15026 B85-10173 03

Estimating the Performance of a
Concentrating Solar Array
MFS-28021 B85-10185 03

Integrating Residential Photovoltaics
With Power Lines
NPO-16331 B85-10188 03

Tests of Low-Concentration-Ratio
Photovoltaic Elements
MFS-28020 B85-10189 03

Floating-Emitter Solar-Cell Transistor
NPO-16467 B85-10441 01

PHthalOCYANIN
Thermosetting Phthalocyanine
Polymers
ARC-11511 B85-10061 04

Synthesizing Metal Phthalocyanine
Imide Polymers
ARC-11413 B85-10074 04

Synthesis of Metal Phthalocyanine
Sheet Polymers
ARC-11405 B85-10343 04

Phthalocyanine Tetraamine
Epoxy-Curing Agents
ARC-11424 B85-10348 04

PIGMENTS
Diffusely Reflecting Paints Containing
TFE
GSC-12883 B85-10194 04

PINS
Locking Pull Pin
NPO-16233 B85-10512 06

PIPELINING (COMPUTERS)
Fast Control Sequencer
NPO-16116 B85-10163 02

Programmable Pipelined-Image
Processor
NPO-16463 B85-10459 02

PIPES (TUBES)
Foam Insulation for Cryogenic
Flowlines
MSC-20552 B85-10066 04

Contact Heat Exchanger
MSC-20419 B85-10092 06

PISTONS

SUBJECT INDEX

- Insulating Cryogenic Pipes With Frost
MSC-20426 B85-10249 07
Making Glass-Fiber-Reinforced
Coolant Tubes B85-10276 08
MSC-20677
Titanium Heat-Pipe Wicks
MFS-26016 B85-10524 06
- PISTONS**
Carbon/Carbon Pistons for Internal Combustion Engines
LAR-13150 B85-10547 07
- PIVOTS**
Dolly Swivel for Forklift
MFS-19866 B85-10391 07
- PLANT STRESS**
Camera for Monitoring Vegetation
NPO-16349 B85-10358 05
- PLASMA SPRAYING**
Plasma-Sprayed Coatings on Porous Surfaces
LEW-13450 B85-10347 04
- PLASMA TORCHES**
Adapter Helps To Align Plasma Torch
MFS-28024 B85-10251 07
- PLASTIC DEFORMATION**
Inelastic Analysis of Thermomechanically Cycled Structures
LEW-14011 B85-10380 06
- PLASTICS**
Nonyellowing Polycarbonate for Outdoor Use
NPO-15836 B85-10070 04
- PLOTTERS**
Plotting Lightning-Stroke Data
MFS-26019 B85-10462 03
- PLOTTING**
An Interactive Plotting Routine
MSC-20771 B85-10284 09
- PLUGS**
Quasi-Porous Plug With Vortex Chamber
NPO-16076 B85-10111 07
- POLARIZERS**
Polarizing Filter for Integrated Optics
NPO-16429 B85-10288 01
- POLYCARBONATES**
Nonyellowing Polycarbonate for Outdoor Use
NPO-15836 B85-10070 04
Solvent-Resistant, Thermally Stable Poly(Carbonate-Imides)
LAR-13292 B85-10485 04
- POLYCRYSTALS**
Efficient Process for Making Polycrystalline Silicon
NPO-16121 B85-10073 04
- POLYESTERS**
Ethynyl-Terminated Ester Oligomers and Polymers
LAR-13118 B85-10076 04
- POLYIMIDE RESINS**
Resin Powder Slurry Process for Composite Fabrication
LAR-13106 B85-10335 04
Water-Soluble Thermoplastic Polyimides
LAR-13105 B85-10336 04
- POLYIMIDES**
Colorless, Transparent, Aromatic Polyimide Films
LAR-13351 B85-10490 04
- POLYMER CHEMISTRY**
Laser Photoacoustic Technique Detects Photo-Oxidation
NPO-16108 B85-10324 03
- POLYMER PHYSICS**
Constitutive Equations of Aging in Polymers
NPO-16480 B85-10503 04
- POLYMERIC FILMS**
Silicone Coating on Polyimide Sheet
GSC-12913 B85-10068 04
Melt-Pressed Films of Insoluble Semicrystalline Polymers
LAR-13212 B85-10351 04
Colorless, Transparent, Aromatic Polyimide Films
LAR-13351 B85-10490 04
- POLYMERIZATION**
Thermosetting Phthalocyanine Polymers
ARC-11511 B85-10061 04
Ultra-High-Molecular-Weight Silphenylene/Siloxane Polymers
MFS-27065 B85-10499 04
- POLYMERS**
Imide Cyclotriphosphazene/Hexafluoroisopropylidene Polymers
ARC-11428 B85-10333 04
Synthesis of Metal Phthalocyanine Sheet Polymers
ARC-11405 B85-10343 04
- POSITION INDICATORS**
Aircraft Control-Position Indicator
LAR-12984 B85-10020 01
Electro-optical System Measures Aircraft Deflections
ARC-11454 B85-10305 02
Hydraulic Cylinder With an Integral Position Indicator
LAR-13095 B85-10518 06
- POSITIONING**
Manipulator for Heating and Cooling in Ultrahigh Vacuum
LAR-13040 B85-10051 03
- POSITIONING DEVICES (MACHINERY)**
Holder for Ultrasonic Evaluation of Small-Diameter Tubes
LAR-13152 B85-10245 07
Controllers for Flow-Field Survey Apparatus
LAR-13180 B85-10310 02
Computing Relative Joint Positions of Robot Arms
LAR-13264 B85-10414 09
- POTENTIOMETERS**
Rolling-Contact Rheostat
NPO-15567 B85-10144 01
- POTTING COMPOUNDS**
Alkane-Based Urethane Potting Compounds
MFS-27047 B85-10494 04
- POWER AMPLIFIERS**
Smoothly Adjustable dc Load
MSC-20853 B85-10289 01
Efficient Power Amplifier for Motor Control
GSC-12807 B85-10291 01
- POWER CONDITIONING**
Incrementally Variable High-Voltage Supply
MFS-28018 B85-10145 01
- POWER CONVERTERS**
Multiple-Winding Output Inductors for Power Converters
NPO-16176 B85-10434 01
- POWER LINES**
Universal Cable Brackets
MFS-26001 B85-10129 08
Program Predicts Nonlinear Inverter Performance
MSC-20769 B85-10172 02
- POWER SUPPLY CIRCUITS**
Remotely-Adjustable Solid-State High-Voltage Supply
NPO-15719 B85-10151 01
Rotary Power Transformer and Inverter Circuit
NPO-16270 B85-10156 01
Microwave Power Combiner With Switching Diodes
NPO-15775 B85-10432 01
Control Electronics for Solar/Flywheel Power Supply
MFS-25978 B85-10443 01
- PRECIPITATORS**
Improved Electronic Control for Electrostatic Precipitators
LAR-13273 B85-10457 02
- PREDICTION ANALYSIS TECHNIQUES**
Prediction of Combustion Gas Deposit Compositions
LEW-14091 B85-10280 09
- PRESSING (FORMING)**
Anvil for Flaring PCB Guide Pins
MSC-20345 B85-10258 07
- PRESSURE**
Simulating Pressure Effects of High-Flow Volumes
MFS-19909 B85-10103 07
- PRESSURE SENSORS**
Touch Sensor for Robots
NPO-16230 B85-10295 01
Microwave Atmospheric-Pressure Sensor
NPO-16496 B85-10478 03
Calibrating Pressure Transducers at Cryogenic Temperatures
LAR-13242 B85-10516 06
- PRESSURE VESSELS**
Electrically Connecting to Pressure Vessels
MSC-20709 B85-10154 01
High-Temperature, High-Pressure Optical Cells
MFS-26000 B85-10267 08
Stiffness Study of Wound-Filament Pressure Vessels
MFS-27086 B85-10530 06
- PRINTERS (DATA PROCESSING)**
Printer Graphics Package
MSC-20778 B85-10568 09
- PRINTING**
Copyboard Quickly Makes Clean Printing Plates
ARC-11365 B85-10133 08
- PRODUCTION ENGINEERING**
Forbidden Zones for Numerically-Controlled Machine Tools
MFS-19950 B85-10397 07
- PROGRAMMING LANGUAGES**
Design Language for Digital Systems
MFS-25352 B85-10281 09
- PROPELLERS**
Wingtip Vortex-Augmented Turbopusher Propeller Thrust
LAR-13019 B85-10095 06
- PROPULSION SYSTEM PERFORMANCE**
Hybrid and Electric Advanced Vehicle Systems Simulation
LEW-13927 B85-10263 07
- PROSTHETIC DEVICES**
Prosthetic Sphincter Controls Urination
MFS-25740 B85-10356 05

SUBJECT INDEX

Development of a Prosthesis for Urinary Control
MFS-27062 B85-10359 05

PROTECTIVE CLOTHING
Lightweight Protective Garments
NPO-16510 B85-10497 04

PROTECTIVE COATINGS
Ceramic Coatings for Engine Parts
NPO-16228 B85-10063 04
Silicone Coating on Polyimide Sheet
GSC-12913 B85-10068 04
Diffusely Reflecting Paints Containing TFE
GSC-12883 B85-10194 04
Magnetron-Sputtered Amorphous Metallic Coatings
NPO-16221 B85-10204 04
Protective Coatings for Metals
KSC-11308 B85-10352 04
Tests of Zinc Rich Anticorrosion Coatings
KSC-11309 B85-10354 04

PULSE COMMUNICATION
Fast Clock Recovery for Digital Communications
NPO-16083 B85-10019 01

PULSE DURATION
Pulse-Width-to-Analog-Voltage Converter
MSC-20006 B85-10157 01

PULSE DURATION MODULATION
Efficient Power Amplifier for Motor Control
GSC-12807 B85-10291 01

PULSE GENERATORS
Pulse Coupling for Laser Excitation
NPO-16403 B85-10428 01
Generating Independent Preionizing Pulses for Lasers
NPO-16402 B85-10429 01

PULSE HEATING
Measuring Thermal Diffusivity of Molten Semiconductors
MFS-28047 B85-10350 04

PULSE POSITION MODULATION
Synchronization for Optical PPM Signals
NPO-16256 B85-10037 02

PULSE WIDTH AMPLITUDE CONVERTERS
Pulse-Width-to-Analog-Voltage Converter
MSC-20006 B85-10157 01

PUMPS
Simulating Pressure Effects of High-Flow Volumes
MFS-19909 B85-10103 07
Pulsed, Hydraulic Coal-Mining Machine
NPO-15859 B85-10388 07
Lightweight, Switchable Peristaltic Pump
MFS-28059 B85-10392 07
Heat-Powered Pump for Liquid Metals
NPO-16457 B85-10396 07
Calculating Flow-Angle Deviation in Rotary Pumps
MFS-29062 B85-10548 07
Rough/Smooth Rotary Seal
MFS-19947 B85-10549 07
Peristaltic Pump With a Stable Output
MSC-20907 B85-10550 07

PURGING
Advanced Vapor-Supply Manifold
LAR-13259 B85-10523 06

PURIFICATION

Purifying Aluminum by Vacuum Distillation
NPO-16114 B85-10065 04
Purifying Water by Imbibition
NPO-16419 B85-10340 04

R

RADAR

Point Simulator for Synthetic-Aperture Radar
NPO-16296 B85-10165 02

RADIAL FLOW

Off-Design Performance of Radial-Inflow Turbines
LEW-14060 B85-10402 07

RADIANT HEATING

Noncontacting Measurement With a Thermocouple
MSC-20834 B85-10374 06

RADIATION ABSORPTION

Single-Event-Upset Studies: A Compilation
NPO-16362 B85-10297 01

RADIATION DAMAGE

Synthetic Organic Materials in Nuclear Powerplants
NPO-16424 B85-10208 04
Degradation of Dielectrics in Space
NPO-16003 B85-10209 04
Testing Electronic Devices for Single-Event Upset
NPO-16468 B85-10454 02

RADIATION DETECTORS

Protective Package for a Gamma-Ray Detector
NPO-16019 B85-10041 03
Segmented Detector for Cosmic Gamma Rays
NPO-16245 B85-10053 03

RADIATION PROTECTION

Protective Package for a Gamma-Ray Detector
NPO-16019 B85-10041 03

RADIATIVE HEAT TRANSFER

TRASYS for Beginners
MSC-20855 B85-10427 09
Solution of Radiation and Convection Heat-Transfer Problems
LEW-13978 B85-10537 06

RADIATIVE RECOMBINATION

Measuring Carrier Lifetime in GaAs by Luminescence
NPO-16337 B85-10334 04

RADIATIVE TRANSFER

Calculating Atmospheric Effects in Satellite Imagery
NPO-16373 B85-10327 03

RAMJET ENGINES

Analysis of Scramjet Inlets
LAR-13297 B85-10382 06

RANDOM ACCESS MEMORY

Dynamic-RAM Data Storage Unit
LEW-14017 B85-10030 02
Modeling 'Soft' Errors in Bipolar Integrated Circuits
NPO-16375 B85-10158 01

RANDOM ERRORS

Single-Event-Upset Studies: A Compilation
NPO-16362 B85-10297 01

REMOTE MANIPULATOR SYSTEM

RANGE ERRORS

Compensating for Range Migration in Synthetic-Aperture Radar
NPO-15954 B85-10136 09

RATINGS

Comparison of Decision Models
NPO-16446 B85-10563 09

RAWINSONDES

Estimates of Latent Heat in Clouds
MFS-25977 B85-10055 03

RECHARGING

Thermally-Rechargeable Electrochemical Cell
NPO-16273 B85-10048 03

RECIPROCATING

Reciprocating Magnetic Refrigerator
NPO-16257 B85-10107 07

RECOVERABLE LAUNCH VEHICLES

Rocket-Booster Towing Simulation
KSC-11289 B85-10102 06

RECRYSTALLIZATION

Melt-Pressed Films of Insoluble Semicrystalline Polymers
LAR-13212 B85-10351 04

REDUNDANCY

Interface Circuits for Self-Checking Microprocessors
NPO-15700 B85-10309 02

REDUNDANT COMPONENTS

Redundant Asynchronous Microprocessor System
ARC-11348 B85-10031 02

REFLECTORS

Improved Thick Dichroic Reflector for Microwave Feeds
NPO-13506 B85-10004 01
Self-Identifying Reflecting Targets
NPO-16106 B85-10033 02
Designing Eccentric Aperture Optical Systems
NPO-16355 B85-10329 03

REFRIGERATING MACHINERY

Hydrogen Refrigerator Would Cool Below 10 K
NPO-16393 B85-10543 07

REFRIGERATORS

Reciprocating Magnetic Refrigerator
NPO-16257 B85-10107 07

REGRESSION ANALYSIS

Subset Regression
LEW-14002 B85-10420 09

REGULATORS

Back-Pressure Regulator for Large Gas Flows
MSC-20536 B85-10109 07

RELIABILITY ANALYSIS

Computer-Aided Reliability Estimation
LAR-13349 B85-10315 02

RELIEF VALVES

Damage-Free Relief-Valve Disassembly
MFS-28006 B85-10361 06

REMOTE CONSOLES

'Speaking' Microcomputer
MFS-25976 B85-10307 02

REMOTE CONTROL

Remotely-Controlled Docking System
MSC-18969 B85-10097 06
Remote Power Controllers For High-Power dc Switching
LEW-14109 B85-10148 01

REMOTE MANIPULATOR SYSTEM

Automatic Guidance for Remote Manipulator
NPO-13386 B85-10453 02

REMOTE SENSORS

SUBJECT INDEX

REMOTE SENSORS

Airborne DIAL System for Remote
Tropospheric Sensing
LAR-13002 B85-10178 03

REMOTELY PILOTED VEHICLES

Remotely Piloted Aircraft for
Research
ARC-11498 B85-10120 07

REQUIREMENTS

Requirements Analysis for
Information-Intensive Systems
NPO-15944 B85-10415 09

RESEARCH FACILITIES

Numerical Aerodynamic Simulation
Facility
ARC-11497 B85-10562 09

RESIDUES

Residue-Measure Model-Reduction
Technique
MSC-20369 B85-10137 09

RESIN MATRIX COMPOSITES

Resin Characterization in Cured
Composite Materials
LAR-13172 B85-10072 04

RESISTORS

Rolling-Contact Rheostat
NPO-15567 B85-10144 01

RESOLUTION

SAW-Modulated Image Device
LAR-12633 B85-10009 01

RESONANCE

Ferroresonant Circuit With Increased
Efficiency
NPO-16326 B85-10140 01

RESONANT FREQUENCIES

Resistive Fine Tuning of Resonant
Circuit
NPO-16276 B85-10013 01

RETAINING

Screw-Retaining Allen Wrench
NPO-16275 B85-10127 08

RLC CIRCUITS

Resistive Fine Tuning of Resonant
Circuit
NPO-16276 B85-10013 01

ROBOTS

Force Sensor for Large Robot Arms
NPO-16097 B85-10226 06
Low-Friction Joint for Robot Fingers
NPO-15914 B85-10247 07
Computing Relative Joint Positions of
Robot Arms
LAR-13264 B85-10414 09
Computational Simplification of
Robot-Arm Dynamics
NPO-16377 B85-10417 09

ROCKET ENGINES

Miniature Rocket Motor for Aircraft
Stall/Spin Recovery
LAR-13199 B85-10253 07

ROCKET EXHAUST

Exhaust Effluent Diffusion Model
MFS-25940 B85-10214 04

ROLLER BEARINGS

Predicting the Dynamic Behavior of
High-Speed Roller Bearings
LEW-13467 B85-10401 07

ROTARY WINGS

Tabs Reduce Helicopter-Blade
Vibrations
ARC-11444 B85-10227 06

ROTATING SHAFTS

Obtaining One-Degree Accuracy With
Shaft Encoders
LAR-13321 B85-10431 01
Shaft Axial-Displacement Sensor
MFS-29048 B85-10519 06

ROTORS

Analyses of Multishaft Rotor-Bearing
Response
LEW-13925 B85-10232 06
Rotating Connection for Electrical
Cables
GSC-12899 B85-10384 07

RUDDERS

Mechanical Mixer for Rudder/Braking
Wedge
MSC-20759 B85-10117 07

S

SAFETY

Predicting Effects of Impacts on
Confined Explosives
NPO-16258 B85-10083 04
Curtain Wall Creates Ventilation
Channel
NPO-16194 B85-10244 07

SAMPLES

Ultrahigh-Vacuum Sample-Transfer
System
LAR-12993 B85-10057 03

SAMPLING

Accurate Airborne Particle Sampler
LAR-13080 B85-10219 06

SANDWICH STRUCTURES

Thermal-Diode Sandwich Panel
LAR-13121 B85-10526 06

SAWS

Constant-Pressure Sawing
NPO-15233 B85-10383 07

SCANNERS

Inspecting Hollow Parts With a CAT
Scanner
MFS-19916 B85-10089 06
Optical Scanner for Linear Arrays
GSC-12897 B85-10320 03

SCAVENGING

Fluidized-Bed Particles Scavenge
Silicon Fines
NPO-16034 B85-10202 04

SCENE ANALYSIS

Algorithms for Coastal-Zone
Color-Scanner Data
GSC-12852 B85-10328 03

SCHLIEREN PHOTOGRAPHY

Laser Schlieren Crystal-Growth
Imager
MFS-28060 B85-10326 03

SCHMIDT CAMERAS

Wide-Angle, Wide-Band Camera for
Remote Imaging
NPO-15799 B85-10052 03

SCREWS

Screw-Retaining Allen Wrench
NPO-16275 B85-10127 08

SEALERS

High-Performance Filleting and
Channel Sealants
ARC-11408 B85-10064 04

SEALS (STOPPERS)

Low-Temperature Seal for Actuator
Rod
MSC-20744 B85-10229 06
Shaft Seal Compensates for Cold
Flow
MFS-25678 B85-10254 07
Predicting Leakage in Labyrinth
Seals
MFS-27051 B85-10261 07
Silicone-Rubber Stitching Seal
MSC-20708 B85-10269 08

Rough/Smooth Rotary Seal
MFS-19947 B85-10549 07

SEAMS (JOINTS)

High-Performance Filleting and
Channel Sealants
ARC-11408 B85-10064 04
Silicone-Rubber Stitching Seal
MSC-20708 B85-10269 08

SEISMOGRAPHS

Determining Calibration Constants for
Attitude Measurements
LAR-13214 B85-10475 03

SELF ALIGNMENT

Remotely-Controlled Docking
System
MSC-18969 B85-10097 06

SEMICONDUCTOR DEVICES

Conductive Container for
Semiconductor Devices
NPO-16110 B85-10439 01

SEMICONDUCTOR JUNCTIONS

Solar Cells With Multiple Small
Junctions
NPO-16126 B85-10021 01

SEMICONDUCTOR LASERS

High-Output Injection Laser
LAR-13213 B85-10149 01

SEMICONDUCTORS (MATERIALS)

High-Purity Silicon Seeds for Silane
Pyrolysis
NPO-16287 B85-10060 04
Calculating Charge Transport in
Semiconductors
LAR-13201 B85-10338 04
Producing Silicon Carbide for
Semiconductor Devices
NPO-16391 B85-10342 04
Characterizing Semiconductor Alloys
for Infrared Sensors
MFS-27059 B85-10355 04

SEPARATORS

Enhancing Centrifugal Separation
With Electrophoresis
MFS-28053 B85-10357 05

SEQUENTIAL CONTROL

Fast Control Sequencer
NPO-16116 B85-10163 02

SERVICE MODULES

Service Modules for Coal Extraction
NPO-16185 B85-10240 07

SERVOMECHANISMS

Force Sensor for Large Robot Arms
NPO-16097 B85-10226 06
Low-Friction Joint for Robot Fingers
NPO-15914 B85-10247 07
Controllers for Flow-Field Survey
Apparatus
LAR-13180 B85-10310 02
Autopilot Servoactuator With
Pressurized Detented Centering
LAR-13185 B85-10364 06

SETUPS

Aligning Large Cylinders for Welding
MFS-28001 B85-10271 08

SHAFTS (MACHINE ELEMENTS)

Analyses of Multishaft Rotor-Bearing
Response
LEW-13925 B85-10232 06
Shaft Seal Compensates for Cold
Flow
MFS-25678 B85-10254 07
Gradually Acting Shaft Stop
MSC-20729 B85-10256 07

SHAKING

Multishaker Modal Testing
MFS-27052 B85-10101 06

SUBJECT INDEX

SHEAR STRENGTH

Fixture for Linearly Variable
Displacement Transducers
LAR-12937 B85-10224 06

SHIELDING

Shielding Against Intense Laser
Beams
NPO-16166 B85-10067 04

SHOCK RESISTANCE

Thermal Shock-Resistant Composite
Crucible
LEW-14105 B85-10252 07

SHRINKAGE

Compensating for Shrinkage in
Machined Ceramics
MSC-20684 B85-10394 07

SHUTDOWNS

Spill-Detector-and-Shutoff Device
MSC-20206 B85-10106 07

SIGNAL ENCODING

Standard Codes for Telemetry and
Telecommand
NPO-16305 B85-10287 09

SIGNAL MEASUREMENT

Measuring Antenna Signal Delays
NPO-15947 B85-10455 02

SIGNAL PROCESSING

Signal Processor for Multirate PSK
Signals
MSC-20195 B85-10008 01
Modular, Fast, Two-Dimensional
Cyclic Convolver
NPO-16379 B85-10448 02

SIGNAL TRANSMISSION

Recovering Microwave
Cross-Polarization Losses
NPO-15353 B85-10168 02
Optimum Cyclic Redundancy Codes
for Noisy Channels
NPO-16406 B85-10561 09

SILICON

High-Purity Silicon Seeds for Silane
Pyrolysis
NPO-16287 B85-10060 04
Efficient Process for Making
Polycrystalline Silicon
NPO-16121 B85-10073 04
Filament Guides for Silicon-Ribbon
Growth
Fluidized-Bed Particles Scavenge
Silicon Fines
NPO-16034 B85-10202 04
Plasma Deposition of Doped
Amorphous Silicon
NPO-14955 B85-10210 04
Prototype Furnace for Automatic
Production of Silicon Ribbon
NPO-16175 B85-10272 08
Adjustable Lid Aids Silicon-Ribbon
Growth
NPO-16354 B85-10275 08
Extracting Silicon Product From
Fluidized-Bed Reactors
NPO-16385 B85-10341 04
Improved Jet-Mill Silicon Grinder
NPO-16336 B85-10349 04

SILICON CARBIDES

Producing Silicon Carbide for
Semiconductor Devices
NPO-16391 B85-10342 04

SILICON DIOXIDE

Waterproofing Agents for Silica Tiles
MSC-20364 B85-10080 04

SILICON FILMS

Trough Coating Solar Cells Without
Spillover
NPO-15313 B85-10330 04

SILICON NITRIDES

Beta Silicon Nitride Whiskers
NPO-16409 B85-10501 04

SILICONE RUBBER

Silicone-Rubber Stitching Seal
MSC-20708 B85-10269 08

SIMULATION

Point Simulator for Synthetic-Aperture
Radar
NPO-16296 B85-10165 02

SIMULTANEOUS EQUATIONS

Solving Large Systems of Normal
Equations
GSC-12858 B85-10421 09

SINTERING

Production Process for Strong, Light
Ceramic Tiles
MSC-20602 B85-10200 04

SIZE DETERMINATION

Measuring Perimeters of Large
Round Objects
MFS-28046 B85-10365 06

SIZING (SURFACE TREATMENT)

Apparatus for Sizing and Rewinding
Graphite Fibers
LAR-13323 B85-10556 08

SLICING

Constant-Pressure Sawing
NPO-15233 B85-10383 07

SLITS

Reflecting Slit for Imaging
Spectrometer
NPO-16408 B85-10322 03

SLOPES

Tiltmeter Indicates Sense of Slope
NPO-16153 B85-10005 01

SLURRIES

Resin Powder Slurry Process for
Composite Fabrication
LAR-13106 B85-10335 04

SMOKE

Continuous Laminar-Smoke
Generator
LAR-13014 B85-10090 06

SOAPS

Sensitivities of Soap Solutions in
Leak Detection
MFS-19864 B85-10121 07

SODIUM SULFUR BATTERIES

Thermally-Rechargeable Electro-
Chemical Cell
NPO-16273 B85-10048 03

SOILS

Measuring Soil Hydraulic Conductivity
With Microwaves
GSC-12937 B85-10176 03

SOLAR ARRAYS

Photovoltaic-Panel Laminator
NPO-16092 B85-10123 08
Estimating the Performance of a
Concentrating Solar Array
MFS-28021 B85-10185 03
Multiband Selector for Linear
Photodetector Array
GSC-12911 B85-10187 03
Tests of Low-Concentration-Ratio
Photovoltaic Elements
MFS-28020 B85-10189 03
Bonding Solar-Cell Modules
NPO-16399 B85-10211 04
Supporting Structures for Flat
Solar-Cell Arrays
NPO-15600 B85-10407 08

SOLAR CELLS

Measuring Recombination Velocities
in Solar Cells
NPO-16243 B85-10001 01

Solar Cells With Multiple Small
Junctions
NPO-16126 B85-10021 01

Photovoltaics in Japan
NPO-16330 B85-10025 01

Efficient Process for Making
Polycrystalline Silicon
NPO-16121 B85-10073 04

Series Connection of Solar Cells
NPO-16091 B85-10124 08

Segmented Trough Reflector
NPO-15026 B85-10173 03

Integrating Residential Photovoltaics
With Power Lines
NPO-16331 B85-10188 03

Tests of Low-Concentration-Ratio
Photovoltaic Elements
MFS-28020 B85-10189 03

Bonding Solar-Cell Modules
NPO-16399 B85-10211 04

Trough Coating Solar Cells Without
Spillover
NPO-15313 B85-10330 04

Floating-Emitter Solar-Cell Transistor
NPO-16467 B85-10441 01

Accelerating Corrosion in Solar-Cell
Tests
NPO-16096 B85-10446 01

SOLAR COLLECTORS

Out-of-Focus Alinement of Solar
Concentrators
NPO-15563 B85-10044 03

SOLAR GENERATORS

Cost and Performance Model for
Photovoltaic Systems
NPO-16404 B85-10314 02

Control Electronics for
Solar/Flywheel Power Supply
MFS-25978 B85-10443 01

SOLAR HEATING

Windowless High-Pressure Solar
Reactor
NPO-16310 B85-10174 03

SOLAR INSTRUMENTS

Sensor Tracks the Sun From Any
Angle
NPO-16211 B85-10308 02

SOLAR REFLECTORS

Environmental Degradation of Solar
Reflectors
NPO-16053 B85-10059 03

Segmented Trough Reflector
NPO-15026 B85-10173 03

Windowless High-Pressure Solar
Reactor
NPO-16310 B85-10174 03

Economical Fabrication of Large
Parabolic Mirrors
LAR-13139 B85-10405 08

SOLAR SIMULATORS

Altering Flashlamp Output for
Realistic Solar Simulation
NPO-16167 B85-10054 03

SOLDERED JOINTS

Series Connection of Solar Cells
NPO-16091 B85-10124 08

SOLDERING

Series Connection of Solar Cells
NPO-16091 B85-10124 08

Pretinning Nickel-Plated Wire
Shields
MSC-20712 B85-10266 08

SOLIDIFICATION

Variable-Temperature-Gradient De-
vice for Solidification Research
MFS-26008 B85-10042 03

- Calculation of Macroseggregation in an Ingot
MFS-27068 B85-10481 03
Solidifying Cast Iron in Low Gravity
MFS-27069 B85-10504 04
- SOLOMON COMPUTERS**
Single-Chip VLSI Reed-Solomon Encoder
NPO-16122 B85-10452 02
- SPACE COMMERCIALIZATION**
Variable-Temperature-Gradient Device for Solidification Research
MFS-26008 B85-10042 03
Reversing Glass Wettability
MFS-26006 B85-10071 04
Cast Iron With High Carbon Content
MFS-28014 B85-10500 04
Solidifying Cast Iron in Low Gravity
MFS-27069 B85-10504 04
- SPACE ERECTABLE STRUCTURES**
Deployable Truss Member
LAR-13219 B85-10362 06
- SPACE TOOLS**
Equipment for Microgravity Research
MFS-27094 B85-10480 03
- SPACECRAFT DOCKING**
Remotely-Controlled Docking System
MSC-18969 B85-10097 06
- SPACECRAFT RADIATORS**
Puncture-Tolerant Heat Radiator
NPO-16401 B85-10390 07
- SPECTRAL BANDS**
Spectrophotovoltaic Power Generation
MFS-27027 B85-10049 03
- SPECTRAL ENERGY DISTRIBUTION**
Spectrophotovoltaic Power Generation
MFS-27027 B85-10049 03
- SPECTRAL REFLECTANCE**
Camera for Monitoring Vegetation
NPO-16349 B85-10358 05
- SPECTROMETERS**
Imaging Spectrometer for Geophysical Surveys
NPO-16072 B85-10046 03
Lens-and-Detector Array for Spectrometer
NPO-16388 B85-10184 03
Fourier-Transform Infrared Spectrometer
NPO-16431 B85-10317 03
Reflecting Slit for Imaging Spectrometer
NPO-16408 B85-10322 03
Compact Imaging Spectrometer
NPO-16342 B85-10471 03
- SPECTROSCOPIC ANALYSIS**
Resin Characterization in Cured Composite Materials
LAR-13172 B85-10072 04
- SPECTRUM ANALYSIS**
Frequency-Discriminating Acoustic-Event Counter
MSC-20467 B85-10160 02
Multiband Selector for Linear Photodetector Array
GSC-12911 B85-10187 03
- SPEED CONTROL**
Gradually Acting Shaft Stop
MSC-20729 B85-10256 07
- SPEED INDICATORS**
Shaft Axial-Displacement Sensor
MFS-29048 B85-10519 06
- SPHERES**
Optical Integrating Sphere for Vacuum Ultraviolet
GSC-12849 B85-10325 03
- SPHERICAL SHELLS**
Centrifugal Generator of Filled Spherical Shells
NPO-16051 B85-10270 08
- SPRAYED COATINGS**
Ceramic Coatings for Engine Parts
NPO-16228 B85-10063 04
Spray Application of Rapidly Solidified Metals
GSC-12880 B85-10131 08
- SPUTTERING**
Magnetron Sputtering Deposits
Corrosion-Resistant Alloy
NPO-15928 B85-10337 04
- STAINLESS STEELS**
Reducing Stress-Corrosion Cracking in Bearing Alloys
MFS-19948 B85-10331 04
- STANDARDS**
Inexpensive Eddy-Current Standard
LAR-13154 B85-10225 06
- STARTERS**
Power Supply For 25-Watt Arc Lamp
LAR-13202 B85-10141 01
- STATIC ELECTRICITY**
Static-Suppressing Optical Paint
NPO-15992 B85-10077 04
Preventing Electrostatic-Discharge Damage to Electronics
NPO-15953 B85-10296 01
- STATIC STABILITY**
Free-Vibration Analysis of Structures
NPO-15000 B85-10279 09
- STATISTICAL ANALYSIS**
Simplified Worst-Case Analysis of Complex Systems
MSC-20232 B85-10135 09
Statistical Energy Analysis Program
MFS-27035 B85-10231 06
- STEELS**
Measuring Hydrogen Concentrations in Metals
MFS-27020 B85-10199 04
- STIFFNESS**
Stiffness Study of Wound-Filament Pressure Vessels
MFS-27086 B85-10530 06
- STIRLING CYCLE**
Long-Life Cryogenic Cooler
GSC-12697 B85-10116 07
Kinematic Stirling Engine Performance
LEW-14092 B85-10482 03
Four-Cylinder Stirling Engine Control Simulation
LEW-14106 B85-10536 06
- STIRLING ENGINES**
Kinematic Stirling Engine Performance
LEW-14092 B85-10482 03
Four-Cylinder Stirling Engine Control Simulation
LEW-14106 B85-10536 06
- STOCHASTIC PROCESSES**
Vector Lyapunov Functions for Stochastic Interconnected Systems
NPO-16170 B85-10139 09
- STORAGE BATTERIES**
Battery-Charge-State Model
NPO-16158 B85-10058 03
- STRAIN GAGES**
Calculating Bearing Forces From Strain-Gage Signals
MFS-29000 B85-10510 06
- STRANDS**
Making Stronger Twine With Matched Strands
MSC-20444 B85-10128 08
- STRESS ANALYSIS**
Geometric and Material Nonlinear Structural Analysis
LAR-13279 B85-10381 06
- STRESS CORROSION**
Reducing Stress-Corrosion Cracking in Bearing Alloys
MFS-19948 B85-10331 04
- STRESS CYCLES**
Predicting the Cyclic Response of High-Temperature Materials
LEW-14032 B85-10344 04
Inelastic Analysis of Thermomechanically Cycled Structures
LEW-14011 B85-10380 06
- STRUCTURAL ANALYSIS**
Geometric and Material Nonlinear Structural Analysis
LAR-13279 B85-10381 06
- STRUCTURAL DESIGN**
Optimization of Antenna-Structure Design
NPO-16158 B85-10299 01
- STRUCTURAL MEMBERS**
Inflatable Column Structure
NPO-16216 B85-10091 08
- STRUCTURAL STABILITY**
Vector Lyapunov Functions for Stochastic Interconnected Systems
NPO-16170 B85-10139 09
- STRUCTURAL VIBRATION**
Multishaker Modal Testing
MFS-27052 B85-10101 06
Statistical Energy Analysis Program
MFS-27035 B85-10231 06
Free-Vibration Analysis of Structures
NPO-15000 B85-10279 09
NASTRAN/DISCOS/SAMSAN DMAP Bridging Program
GSC-12902 B85-10379 06
- STYROFOAM (TRADEMARK)**
Lightweight Electrical Insulation
NPO-16165 B85-10193 04
- SUBSONIC FLOW**
Three-Dimensional, Subsonic, Turbulent Junction Region Flow
LAR-13263 B85-10540 06
- SUBSTRATES**
Infrared Linear Imaging Array
NPO-15805 B85-10023 01
Spray Application of Rapidly Solidified Metals
GSC-12880 B85-10131 08
- SUPERCONDUCTIVITY**
Superconducting-Cavity Accelerometer
GSC-12797 B85-10096 06
- SUPERCONDUCTORS**
Paramagnetic Precipitates May Raise Supercurrent
MFS-25925 B85-10195 04
- SUPERSONIC FLOW**
Analysis of Scramjet Inlets
LAR-13297 B85-10382 06
- SUPERSONIC NOZZLES**
Low-Noise Supersonic Nozzle
LAR-13192 B85-10368 06

SUPPORTS

Inflatable Column Structure
NPO-16216 B85-10091 06

Automatic Erection System for
Antenna Masts
LAR-13115 B85-10115 07

Optical Mounts for Cryogenic Beam
Splitters
GSC-12923 B85-10180 03

End Restraints for
Impact-Energy-Absorbing Tube
Specimens
LAR-13179 B85-10218 06

Side Shield for Wall Support
NPO-16188 B85-10241 07

Roof Shield for Advance and Retreat
Mining
NPO-16189 B85-10242 07

Supporting Structures for Flat
Solar-Cell Arrays
NPO-15600 B85-10407 08

SURFACE ACOUSTIC WAVE DEVICES

SAW-Modulated Image Device
LAR-12633 B85-10009 01

SURFACE DISTORTION

Estimating Antenna Shape From
Far-Field Measurements
NPO-16425 B85-10181 03

SURFACE PROPERTIES

Reversing Glass Wettability
MFS-26006 B85-10071 04

SURFACE TEMPERATURE

Thermal, One-Dimensional Analyzer
Program
MSC-20703 B85-10378 06

SURVEYS

Imaging Spectrometer for
Geophysical Surveys
NPO-16072 B85-10046 03

Electronic/Hydraulic Level Gage
MFS-28066 B85-10522 06

SWITCHES

Reed-Switch Position Indicator
KSC-11215 B85-10152 01

Plug-In RF Selector Switch
MSC-20572 B85-10292 01

SWITCHING CIRCUITS

High-Speed Computer-Controlled
Switch-Matrix System
LEW-14050 B85-10028 02

Remote Power Controllers For
High-Power dc Switching
LEW-14109 B85-10148 01

Commutating Permanent-Magnet
Motors At Low Speed
MFS-25207 B85-10150 01

Microwave Power Combiner With
Switching Diodes
NPO-15775 B85-10432 01

SWIVELS

Dolly Swivel for Forklift
MFS-19866 B85-10391 07

SYNCHRONISM

Fast Clock Recovery for Digital
Communications
NPO-16083 B85-10019 01

Synchronization for Optical PPM
Signals
NPO-16256 B85-10037 02

Satellite Time-
Frequency-Transfer System
MFS-25991 B85-10169 02

SYNTHESIS (CHEMISTRY)

Synthesizing Metal Phthalocyanine
Imide Polymers
ARC-11413 B85-10074 04

SYNTHESIZERS

Keyboard With Voice Output
MSC-20869 B85-10438 01

SYNTHETIC APERTURE RADAR

Compensating for Range Migration in
Synthetic-Aperture Radar
NPO-15954 B85-10136 09

Point Simulator for Synthetic-Aperture
Radar
NPO-16296 B85-10165 02

Modular, Fast, Two-Dimensional
Cyclic Convolver
NPO-16379 B85-10448 02

SYNTHETIC RUBBERS

Ultra-High-Molecular-Weight Silphen-
ylene/Siloxane Polymers
MFS-27065 B85-10499 04

SYSTEMS ANALYSIS

Simplified Worst-Case Analysis of
Complex Systems
MSC-20232 B85-10135 09

SYSTEMS ENGINEERING

Systems Engineering of Electric and
Hybrid Vehicles
NPO-15871 B85-10551 07

T

TACTILE DISCRIMINATION

Touch Sensor for Robots
NPO-16230 B85-10295 01

TANKS (CONTAINERS)

Liquid-Level Sensor for Containers in
Motion
LAR-13327 B85-10472 03

TAPERED COLUMNS

Deployable Truss Member
LAR-13219 B85-10362 06

TARGET RECOGNITION

Self-Identifying Reflecting Targets
NPO-16106 B85-10033 02

TELECOMMUNICATION

Low-Cost Teleconference System
NPO-16057 B85-10029 02

TELECONFERENCING

Low-Cost Teleconference System
NPO-16057 B85-10029 02

TELEMETRY

Single-Frequency Multitransmitter
Telemetry
LAR-13006 B85-10039 02

Standard Codes for Telemetry and
Telecommand
NPO-16305 B85-10287 09

Laser Links for Instrumentation
Systems
MSC-20863 B85-10313 02

TELEPHONES

Telephone Instrument for the Deaf
KSC-11303 B85-10014 01

TELESCOPES

Telescope With Reflecting Baffle
ARC-11502 B85-10043 03

TELEVISION EQUIPMENT

Wide-Brightness-Range Video
Camera
MFS-25750 B85-10301 02

TEMPERATURE CONTROL

Differential Temperature Control of
Electrical Heaters
LAR-13047 B85-10099 06

Portable Temperature Set-Point
Controller
MSC-20056 B85-10142 01

TEMPERATURE DISTRIBUTION

Orienting Arc Lamps for Longest
Life
MSC-20562 B85-10155 01

Thermal, One-Dimensional Analyzer
Program
MSC-20703 B85-10378 06

TEMPERATURE GRADIENTS

Variable-Temperature-Gradient De-
vice for Solidification Research
MFS-26008 B85-10042 03

TEMPERATURE MEASUREMENT

Improved
ng Apparatus
NPO-16280 B85-10182 03

Contactless Calorimetry for Levitated
Samples
NPO-16448 B85-10318 03

Determining the Temperature Profile
in a Cylindrical Sample
MFS-26013 B85-10465 03

TEMPERATURE MEASURING

Combination Heat-Flux and
Temperature Gage
MSC-20706 B85-10221 06

TEMPERATURE PROBES

Noncontacting Measurement With a
Thermocouple
MSC-20834 B85-10374 06

TEMPERATURE PROFILES

Determining the Temperature Profile
in a Cylindrical Sample
MFS-26013 B85-10465 03

TENSILE TESTS

Testing Machine for Biaxial Loading
MSC-20477 B85-10220 06

Elevated-Temperature Tensile-Test-
ing of Foil-Gage Metals
LAR-13243 B85-10363 06

TERNARY ALLOYS

Process for Nonequilibrium Ternary
Alloys
NPO-16226 B85-10345 04

TEST CHAMBERS

Improved Exhaust Diffuser for
Jet-Engine Testing
NPO-16328 B85-10255 07

TEST PATTERN GENERATORS

Online Tester for a Symbol
Generator
MSC-20357 B85-10161 02

TESTS

Distributing Radiant Heat in Insulation
Tests
MSC-20878 B85-10513 06

TETHERED SATELLITES

Tethered Communication Satellites
MFS-28042 B85-10375 06

TETRAHEDRONS

Sequentially-Deployable Tetrahedral
Beam
LAR-13098 B85-10222 06

THERMAL ANALYSIS

Preparation and Characterization of
HgxCd1-xTe
MFS-27037 B85-10081 04

THERMAL DECOMPOSITION

Metalization Patterns by Thermal
Decomposition
NPO-16413 B85-10408 08

THERMAL DIFFUSIVITY

Improved Thermal-Diffusivity-
Measuring Apparatus
NPO-16280 B85-10182 03

THERMAL EXPANSION

SUBJECT INDEX

- Measuring Thermal Diffusivity of Molten Semiconductors
MFS-28047 B85-10350 04
- THERMAL EXPANSION**
Fastening Parts Having Mismatched Thermal Coefficients
LAR-13009 B85-10113 07
- THERMAL INSULATION**
Foam Insulation for Cryogenic Flowlines
MSC-20552 B85-10066 04
Improving Emittance of High-Temperature Insulating Tile
MSC-20714 B85-10078 04
Thermal, One-Dimensional Analyzer Program
MSC-20703 B85-10378 06
Insulation Blankets for High-Temperature Use
ARC-11453 B85-10489 04
High-Strength, Low-Shrinkage Ceramic Tiles
MSC-20654 B85-10495 04
Distributing Radiant Heat in Insulation Tests
MSC-20878 B85-10513 06
Thermal-Diode Sandwich Panel
LAR-13121 B85-10526 06
- THERMAL PROTECTION**
Thermal-Diode Sandwich Panel
LAR-13121 B85-10526 06
- THERMAL RADIATION**
Radiation View-Factor Program With Interactive Graphics
LAR-13299 B85-10535 06
- THERMAL STABILITY**
Ethynyl-Terminated Ester Oligomers and Polymers
LAR-13118 B85-10076 04
- THERMAL VACUUM TESTS**
Distributing Radiant Heat in Insulation Tests
MSC-20878 B85-10513 06
- THERMOCOUPLES**
Differential Temperature Control of Electrical Heaters
LAR-13047 B85-10099 06
Combination Heat-Flux and Temperature Gage
MSC-20706 B85-10221 06
Noncontacting Measurement With a Thermocouple
MSC-20834 B85-10374 06
Reduced-Stress Mounting for Thermocouples
NPO-16513 B85-10444 01
- THERMODYNAMICS**
TRASYS for Beginners
MSC-20855 B85-10427 09
- THERMOELECTRICITY**
Studying Crystal Growth With the Peltier Effect
MFS-28041 B85-10346 04
Measuring Thermoelectric Properties Automatically
NPO-16507 B85-10488 04
- THERMOPLASTIC RESINS**
Water-Soluble Thermoplastic Polyimides
LAR-13105 B85-10336 04
- THERMOSETTING RESINS**
Thermosetting Phthalocyanine Polymers
ARC-11511 B85-10061 04
- THICKNESS**
Measuring Metal Thickness With an Electric Probe
NPO-16340 B85-10367 06
- THIN FILMS**
High-Quality, Thin-Film Germanium Single Crystals
LAR-13211 B85-10406 08
Inexpensive Masks for Film Deposition
NPO-16416 B85-10557 08
- THRUST**
Wingtip Vortex-Augmented Turbopusher Propeller Thrust
LAR-13019 B85-10095 06
- THRUST REVERSAL**
Performance Improvement for Nonaxisymmetric Nozzles
LAR-13036 B85-10114 07
- TILES**
Improving Emittance of High-Temperature Insulating Tile
MSC-20714 B85-10078 04
Waterproofing Agents for Silica Tiles
MSC-20364 B85-10080 04
Production Process for Strong, Light Ceramic Tiles
MSC-20602 B85-10200 04
Duplicating Curved Tile Surfaces for Pull Testing
MSC-20795 B85-10274 08
High-Strength, Low-Shrinkage Ceramic Tiles
MSC-20654 B85-10495 04
- TILT ROTOR AIRCRAFT**
Tilttable-Wing, Tilttable-Rotor Aircraft
ARC-11420 B85-10373 06
- TILT WING AIRCRAFT**
Tilttable-Wing, Tilttable-Rotor Aircraft
ARC-11420 B85-10373 06
- TILTMETERS**
Tiltmeter Indicates Sense of Slope
NPO-16153 B85-10005 01
- TIME DIVISION MULTIPLE ACCESS**
High-Speed Computer-Controlled Switch-Matrix System
LEW-14050 B85-10028 02
- TIME SIGNALS**
Satellite Time- and Frequency-Transfer System
MFS-25991 B85-10169 02
- TITANIUM**
Improved Surface of Titanium Structure
LAR-13148 B85-10409 08
- TOMOGRAPHY**
Inspecting Hollow Parts With a CAT Scanner
MFS-19916 B85-10089 06
- TOOLS**
Hand-Held Power Clamp
MSC-20549 B85-10257 07
Anvil for Flaring PCB Guide Pins
MSC-20345 B85-10258 07
Damage-Free Relief-Valve Disassembly
MFS-28006 B85-10361 06
Dent-Removing Tool
MFS-29044 B85-10554 08
- TORQUE**
Experiments With a Manipulator Sensor System
NPO-16094 B85-10262 07
- TOUCH**
Touch Sensor for Robots
NPO-16230 B85-10295 01
- TOWED BODIES**
Rocket-Booster Towing Simulation
KSC-11289 B85-10102 06
- TOXIC HAZARDS**
Solar-Assisted Oxidation of Toxic Cyanide
LAR-13171 B85-10075 04
- TRACE ELEMENTS**
Solid-State Detector for Trace Materials
NPO-16450 B85-10469 03
- TRACKED VEHICLES**
Improved Highway Pads for Tracked Vehicles
NPO-16318 B85-10246 07
- TRACKING (POSITION)**
Sensor Tracks the Sun From Any Angle
NPO-16211 B85-10308 02
Tracking System for Infrared Spectrometer
NPO-16440 B85-10464 03
- TRANSDUCERS**
Spring-Loaded Transducer Holder
LAR-13048 B85-10098 06
Force Sensor for Large Robot Arms
NPO-16097 B85-10226 06
Flowmeter for Clear and Translucent Fluids
MFS-28030 B85-10228 06
Fiber-Optic Electric-Field Meter
NPO-16435 B85-10290 01
Flowmeter for Clear Fluids
MFS-28031 B85-10372 06
- TRANSFER ORBITS**
Orbit Transfer Programs
LEW-14089 B85-10538 06
- TRANSFORMERS**
High-Voltage Isolation Transformer
GSC-12817 B85-10018 01
Rotary Power Transformer and Inverter Circuit
NPO-16270 B85-10156 01
High-Efficiency, Low-Weight Power Transformer
LEW-14074 B85-10403 08
- TRANSIENT RESPONSE**
Predicting the Dynamic Behavior of High-Speed Roller Bearings
LEW-13467 B85-10401 07
- TRANSISTORS**
Controlling Transistor Temperature During Burn-In
MFS-28076 B85-10437 01
Floating-Emitter Solar-Cell Transistor
NPO-16467 B85-10441 01
- TRANSMISSION**
Continuously Variable Transmission
LAR-12844 B85-10105 07
- TRANSMISSION LOSS**
Recovering Microwave Cross-Polarization Losses
NPO-15353 B85-10168 02
- TRANSMISSIONS (MACHINE ELEMENTS)**
Hybrid and Electric Advanced Vehicle Systems Simulation
LEW-13927 B85-10263 07
Multistage Planetary Power Transmissions
LEW-14100 B85-10399 07
- TRANSMITTERS**
Single-Frequency Multitransmitter Telemetry
LAR-13006 B85-10039 02

SUBJECT INDEX

VIBRATIONAL SPECTRA

TRANSPONDERS

Retrodirective-Optical-Transponder
Concept
NPO-16315 B85-10153 01

TRANSPORT PROPERTIES

Calculating Charge Transport in
Semiconductors
LAR-13201 B85-10338 04

TREADS

More Secure Fastening for
Tracked-Vehicle Pads
NPO-16321 B85-10385 07

TRIANGULATION

Laser Altimeter for Flight Simulator
ARC-11312 B85-10323 03

TROPOSPHERE

Airborne DIAL System for Remote
Tropospheric Sensing
LAR-13002 B85-10178 03

TRUCKS

Aerodynamic Rear Cone for Trucks
MFS-28007 B85-10217 06

TRUSSES

Deployable M-Braced Truss
LAR-13081 B85-10100 06
Making Structural Members From
Wire
MSC-20175 B85-10268 08
Fabrication of Slender Struts for
Deployable Antennas
LAR-13136 B85-10273 08
Deployable Truss Member
LAR-13219 B85-10362 06

TUNABLE LASERS

Generating Tunable Far-Infrared
Laser Sidebands
NPO-16497 B85-10450 02

TUNING

Resistive Fine Tuning of Resonant
Circuit
NPO-16276 B85-10013 01

TUNNELING (EXCAVATION)

Automated Coal-Mining System
NPO-16177 B85-10233 07
Compact Hydraulic Excavator and
Support Unit
NPO-16190 B85-10243 07

TURBINE BLADES

Inspecting Hollow Parts With a CAT
Scanner
MFS-19916 B85-10089 06

TURBINE ENGINES

Photo-Optical Blade-Vibration-Data
Acquisition System
LEW-12887 B85-10511 06

TURBINE PUMPS

Effects of Bearing Clearance on
Turbopump Stability
MFS-27063 B85-10259 07
Rough/Smooth Rotary Seal
MFS-19947 B85-10549 07
Vibrational Effects of Turbopump
Housing Flexibility
MFS-27083 B85-10552 07

TURBINES

Off-Design Performance of
Radial-Inflow Turbines
LEW-14060 B85-10402 07

TURBOCOMPRESSORS

Predicting the Performance of an
Axial-Flow Compressor
LEW-14025 B85-10531 06
Axial-Flow Compressor Performance
With Water Ingestion
LEW-14026 B85-10532 06

TURBOMACHINE BLADES

Three-Dimensional Turbomachine-
Blade-Flow Analysis Code
LEW-14061 B85-10400 07

Photo-Optical Blade-Vibration-Data
Acquisition System
LEW-12887 B85-10511 06

TURBOMACHINERY

Duct-Flow Analysis
LEW-14000 B85-10191 03

TURBOSHAFTS

Shaft Axial-Displacement Sensor
MFS-29048 B85-10519 06

TURBULENT FLOW

Predicting Two-Dimensional,
Unsteady Turbulent Combustion
LEW-14027 B85-10376 06
Three-Dimensional, Subsonic,
Turbulent Junction Region Flow
LAR-13263 B85-10540 06

TWISTING

Making Stronger Twine With Matched
Strands
MSC-20444 B85-10128 08

TYPEWRITERS

Keyboard With Voice Output
MSC-20869 B85-10438 01

U

ULTRAPURE METALS

Purifying Aluminum by Vacuum
Distillation
NPO-16114 B85-10065 04

ULTRASONIC AGITATION

Ultrasonic Mixing of Epoxy Curing
Agents
LAR-13307 B85-10498 04

ULTRASONIC SCANNERS

Spring-Loaded Transducer Holder
LAR-13048 B85-10098 06

ULTRASONIC TESTS

Holder for Ultrasonic Evaluation of
Small-Diameter Tubes
LAR-13152 B85-10245 07
Controlled-Shape,
Beam Standard Reflector
LAR-13153 B85-10410 08

ULTRAVIOLET REFLECTION

Optical Integrating Sphere for
Vacuum Ultraviolet
GSC-12849 B85-10325 03

URETHANES

Alkane-Based Urethane Potting
Compounds
MFS-27047 B85-10494 04

URINATION

Prosthetic Sphincter Controls
Urination
MFS-25740 B85-10356 05
Development of a Prosthesis for
Urinary Control
MFS-27062 B85-10359 05

USER MANUALS (COMPUTER PROGRAMS)

TRASYS for Beginners
MSC-20855 B85-10427 09

V

VACUUM FURNACES

Improved Thermal-Diffusivity-
Measuring Apparatus
NPO-16280 B85-10182 03

VACUUM PUMPS

Copyboard Quickly Makes Clean
Printing Plates
ARC-11365 B85-10133 08

VALVES

Quasi-Porous Plug With Vortex
Chamber
NPO-16076 B85-10111 07
Advanced Vapor-Supply Manifold
LAR-13259 B85-10523 06

VAPOR DEPOSITION

Coating a Sphere With Evaporated
Metal
NPO-16436 B85-10404 08

VAPOR PHASE EPITAXY

High-Quality, Thin-Film Germanium
Single Crystals
LAR-13211 B85-10406 08

VECTOR ANALYSIS

Vector Lyapunov Functions for
Stochastic Interconnected Systems
NPO-16170 B85-10139 09

VEHICULAR TRACKS

Improved Highway Pads for Tracked
Vehicles
NPO-16318 B85-10246 07
More Secure Fastening for
Tracked-Vehicle Pads
NPO-16321 B85-10385 07

VELOCITY

Measuring Recombination Velocities
in Solar Cells
NPO-16243 B85-10001 01

VELOCITY MEASUREMENT

Vibration-Free Raman Doppler
Velocimeter
LAR-13268 B85-10447 02

VERTICAL TAKEOFF AIRCRAFT

Tiltable-Wing, Tiltable-Rotor Aircraft
ARC-11420 B85-10373 06

VERY LONG BASE INTERFEROMETRY

Interferometry Measures Elliptical
Satellite Orbits
NPO-16313 B85-10171 02

VIBRATION

Melt Stirring by Horizontal Crucible
Vibration
MFS-26005 B85-10069 04

VIBRATION DAMPING

Air Bearing for Small Planar
Vibrations
MFS-26003 B85-10110 07
Tabs Reduce Helicopter-Blade
Vibrations
ARC-11444 B85-10227 06

Squeeze-Film Damper Controls High
Vibrations
LEW-13506 B85-10528 06

VIBRATION EFFECTS

Vibrational Effects of Turbopump
Housing Flexibility
MFS-27083 B85-10552 07

VIBRATION MEASUREMENT

Photo-Optical Blade-Vibration-Data
Acquisition System
LEW-12887 B85-10511 06

VIBRATION TESTS

Multishaker Modal Testing
MFS-27052 B85-10101 06

VIBRATIONAL SPECTRA

Statistical Energy Analysis Program
MFS-27035 B85-10231 06
Maximum-Likelihood Parameter-Esti-
mation Algorithm
NPO-16320 B85-10560 09

VIDEO DATA

VIDEO DATA

Low-Cost Teleconference System
NPO-16057 B85-10029 02
Programmable Pipelined-Image
Processor NPO-16463 B85-10459 02

VIDEO EQUIPMENT

Storing Data and Video on One
Tape
MSC-20705 B85-10027 02
Wide-Brightness-Range Video
Camera
MFS-25750 B85-10301 02
Camera for Monitoring Vegetation
NPO-16349 B85-10358 05

VINYL POLYMERS

Discoloration of Polyvinyl Butyral
NPO-16411 B85-10353 04

VISION

Vision Screening by Color
Photography
MFS-25800 B85-10085 05

VITERBI DECODERS

Fast VLSI Viterbi Decoder
NPO-16365 B85-10311 02

VOICE

Keyboard With Voice Output
MSC-20869 B85-10438 01

VOLT-AMPERE CHARACTERISTICS

Fast-Recovery, High-Voltage Power
Diode
LEW-14036 B85-10016 01

VOLTAGE CONVERTERS (DC TO DC)

Multiple-Winding Output Inductors for
Power Converters
NPO-16176 B85-10434 01

VOLTAGE REGULATORS

Ferroresonant Circuit With Increased
Efficiency
NPO-16326 B85-10140 01
Programmable Driver for
Voltage-Controlled Oscillators
NPO-16364 B85-10162 02

VORTICES

Wingtip Vortex-Augmented
Turbopusher Propeller Thrust
LAR-13019 B85-10095 06

W

WARNING SYSTEMS

Cutthrough Warning Circuit
MFS-19900 B85-10119 07

WASTE ENERGY UTILIZATION

Augmenting Thrust With Waste Heat
NPO-16218 B85-10190 03

WATER DEPTH

Water-Thickness Gage
LAR-13342 B85-10508 06

WATER INJECTION

Axial-Flow Compressor Performance
With Water Ingestion
LEW-14026 B85-10532 06

WATER TREATMENT

Purifying Water by Imbibition
NPO-16419 B85-10340 04

WATERPROOFING

Waterproofing Agents for Silica Tiles
MSC-20364 B85-10080 04
Chromium Ions Improve Moisture
Resistance of Epoxy Resins
LAR-13226 B85-10486 04

WAVEGUIDE LASERS

Improved Waveguide Laser Array
NPO-16500 B85-10435 01

WAVEGUIDES

Improved Thick Dichroic Reflector for
Microwave Feeds
NPO-13506 B85-10004 01

WEAR

Ion Implantation Improves
Bearing-Surface Properties
MFS-25995 B85-10197 04

WEAR TESTS

Optimizing Load Spectra for Gears
MSC-20487 B85-10260 07
Friction-Testing Machine
MSC-20622 B85-10370 06

WEATHERING

Environmental Degradation of Solar
Reflectors
NPO-16053 B85-10059 03

WEIGHTLESSNESS

Preadapting to Weightlessness
MSC-20847 B85-10506 05

WEIGHTLESSNESS SIMULATION

Preadapting to Weightlessness
MSC-20847 B85-10506 05

WELDING

Alining Large Cylinders for Welding
MFS-28001 B85-10271 08

WETTABILITY

Reversing Glass Wettability
MFS-26006 B85-10071 04

WHEELCHAIRS

Flux Coupling for Wheelchair Battery
Chargers
NPO-16269 B85-10007 01

WIND TUNNEL NOZZLES

Reduction of Vane Noise in
Wind-Tunnel Nozzles
LAR-13333 B85-10527 06

WIND TUNNEL TESTS

Continuous Laminar-Smoke
Generator
LAR-13014 B85-10090 06

WIND TUNNELS

Reduction of Vane Noise in
Wind-Tunnel Nozzles
LAR-13333 B85-10527 06

WINDMILLS

(WINDPOWERED)
Hinged-Blade, Vertical-Shaft
Windmill
MFS-25980 B85-10112 07

WING TANKS

Fuel Gage for Sloshing Tanks
LAR-13147 B85-10515 06

WINGLETS

Retractable End Plates for Aircraft
Lifting Surfaces
LAR-12946 B85-10216 06

WINGS

Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06

WIRING

Pretinning Nickel-Plated Wire
Shields
MSC-20712 B85-10266 08
Connectors and Wiring for Cryogenic
Temperatures
LAR-13193 B85-10300 01

WRENCHES

Screw-Retaining Allen Wrench
NPO-16275 B85-10127 08

SUBJECT INDEX

X

X RAY DIFFRACTION

X-Ray Diffraction Analysis Program
LAR-13276 B85-10483 03

X RAY TELESCOPES

Nearly Anastigmatic X-Ray
Telescope
MFS-25984 B85-10047 03

Z


ZIRCONIUM OXIDES

Fast-Response Oxygen-Monitoring
and Control System
LAR-13257 B85-10487 04

ZONE MELTING

Zone Refining by Laser
MFS-27084 B85-10555 08

Typical Personal Author Index Listing



This index is arranged alphabetically by author. The Tech Brief title is listed followed by the originating Center number, e.g., MFS-25986. The Tech Brief number, e.g., B85-10126, is followed by a two-digit number, e.g., 08, which designates the subject category.

A

ABBASCHIAN, G.
Precise Electromagnetic-Levitation Coils of
MFS-25986 B85-10126 08

ACHAR, B.
Thermosetting Phthalocyanine
Polymers B85-10061 04
ARC-11511
Synthesizing Metal Phthalocyanine
Imide Polymers B85-10074 04
ARC-11413

ACHAR, B. N.
Synthesis of Metal Phthalocyanine
Sheet Polymers B85-10343 04
ARC-11405
Phthalocyanine Tetraamine
Epoxy-Curing Agents B85-10348 04
ARC-11424

ADAMS, B. R.
Molecular-Beam Chopper and
Four-Channel Amplifier B85-10316 03
LAR-13174

AGUILAR, L.
Compensating for Shrinkage in
Machined Ceramics B85-10394 07
MSC-20684

AHL JR., E. L.
Latch for Telescoping Structures B85-10507 06
LAR-13169

AKUTAGAWA, W. M.
Centrifugal Generator of Filled
Spherical Shells B85-10270 08
NPO-16051

AL-AYOUBI, R. R.
Program Predicts Nonlinear Inverter
Performance B85-10172 02
MSC-20769

ALAJAJIAN, S.
Molecular Thermal-Electron
Detectors B85-10467 03
NPO-16300

ALARIO, J. P.
High-Performance Heat Pipe B85-10177 03
MSC-20136

ALBRECHT, W.
Microphone Boom for Aircraft-Engine
Monitoring B85-10525 06
ARC-11495

ALLISON, D. E.
Predicting the Fatigue life of
Structures B85-10206 04
MFS-27049

AMMERMAN, M. C.
Distributing Radiant Heat in Insulation
Tests B85-10513 06
MSC-20878

ANDERSON, H. R.
Incrementally Variable High-Voltage
Supply B85-10145 01
MFS-28018

ANDERSON, O. L.
Flow Through Gas-Turbine Ducts B85-10533 06
LEW-14095

ANNERTON, J.
'Speaking' Microcomputer B85-10307 02
MFS-25976

ARAGON, L. A.
Hand-Held Electronic Gap-Measuring
Tools B85-10223 06
MSC-20176

ARBINO, P. B.
Dolly Swivel for Forklift B85-10391 07
MFS-19866

ARGOUD, M. J.
Out-of-Focus Alinement of Solar
Concentrators B85-10044 03
NPO-15563

ARING, J. A.
Autopilot Servoactuator With
Pressurized Detented Centering B85-10364 06
LAR-13185

ARMSTRONG, R. W.
Processing of Image Data by
Integrated Circuits B85-10164 02
NPO-15059

ARROTT, A. P.
Preadapting to Weightlessness B85-10506 05
MSC-20847

ARVIDSON, A. N.
Efficient Process for Making
Polycrystalline Silicon B85-10073 04
NPO-16121

ASHBY JR., G. C.
Controllers for Flow-Field Survey
Apparatus B85-10310 02
LAR-13180

ATCHESON, P. D.
Wide-Angle, Wide-Band Camera for
Remote Imaging B85-10052 03
NPO-15799

AUGUST, R.
Dynamic Effects of Internal
Spur-Gear Drives B85-10553 07
LEW-14167

B

BACKOVSKY, Z.
Estimating the Performance of a
Concentrating Solar Array B85-10185 03
MFS-28021

BACKOVSKY, Z. F.
Tests of Low-Concentration-Ratio
Photovoltaic Elements B85-10189 03
MFS-28020

BAILEY, F. R.
Numerical Aerodynamic Simulation
Facility B85-10562 09
ARC-11497

BAILEY, G. C.
Infrared Linear Imaging Array B85-10023 01
NPO-15805

BAILEY, P. S.
Laser Links for Instrumentation
Systems B85-10313 02
MSC-20863

BAKER, A. J.
Three-Dimensional, Subsonic,
Turbulent Junction Region Flow B85-10540 06
LAR-13263

BAKER, D. J.
Fixture for Linearly Variable
Displacement Transducers B85-10224 06
LAR-12937

BALANDIS, W. D.
Copyboard Quickly Makes Clean
Printing Plates B85-10133 08
ARC-11365

BALLHAUS JR., W. F.
Numerical Aerodynamic Simulation
Facility B85-10562 09
ARC-11497

BALODIS, V.
Fast-Recovery, High-Voltage Power
Diode B85-10016 01
LEW-14036

BANNANTINE, J. M.
Predicting the Fatigue life of
Structures B85-10206 04
MFS-27049

BARBOUR, R. T.
Toggle Hinge for Deployable Struts B85-10369 06
MFS-28037

BARKER, L. K.
Computing Relative Joint Positions of
Robot Arms B85-10414 09
LAR-13264

BARMATZ, M. B.
Controlling Sample Rotation in
Acoustic Levitation B85-10277 08
NPO-15962

BASCLE, K. P.
FIFO Buffer for Asynchronous Data
Streams B85-10036 02
MSC-20403

BASIULIS, A.
Thermal-Diode Sandwich Panel B85-10526 06
LAR-13121

BASIULIS, D. I.

PERSONAL AUTHOR INDEX

- BASIULIS, D. I.**
High-Performance Filleting and Channel Sealants
ARC-11408 B85-10064 04
- BATTS, C. N.**
Comparator With Noise Suppression
LAR-13151 B85-10147 01
- BAUER, F. H.**
Numerical Methods for Classical Sampled-System Analysis
GSC-12827 B85-10564 09
- BAUGH, B. T.**
Manipulator for Heating and Cooling in Ultrahigh Vacuum
LAR-13040 B85-10051 03
Ultrahigh-Vacuum Sample-Transfer System
LAR-12993 B85-10057 03
- BAVUSO, S. J.**
Computer-Aided Reliability Estimation
LAR-13349 B85-10315 02
- BEACH, R. F.**
Hybrid and Electric Advanced Vehicle Systems Simulation
LEW-13927 B85-10263 07
- BECKWITH, I. E.**
Low-Noise Supersonic Nozzle
LAR-13192 B85-10368 06
- BEJCZY, A. K.**
Force Sensor for Large Robot Arms
NPO-16097 B85-10226 06
Experiments With a Manipulator Sensor System
NPO-16094 B85-10262 07
Computational Simplification of Robot-Arm Dynamics
NPO-16377 B85-10417 09
- BELLAN, J.**
Corrosive Effects of Burning Fuels
NPO-16345 B85-10207 04
- BELOW, R. R.**
Lightweight, Switchable Peristaltic Pump
MFS-28059 B85-10392 07
- BENUMOF, R.**
Modeling 'Soft' Errors in Bipolar Integrated Circuits
NPO-16375 B85-10158 01
- BENZ, F. J.**
Friction-Testing Machine
MSC-20622 B85-10370 06
- BENZ, H. F.**
SAW-Modulated Image Device
LAR-12633 B85-10009 01
- BERDAHL, C. M.**
Rotary Speed Sensor for Antilocking Brakes
NPO-16479 B85-10509 06
- BERGSTROM, S. L.**
Coculture Production of Butanol by Clostridium Bacteria
NPO-16203 B85-10086 05
- BERMAN, A.**
Fast-Recovery, High-Voltage Power Diode
LEW-14036 B85-10016 01
- BERRIER, B. L.**
Performance Improvement for Nonaxisymmetric Nozzles
LAR-13036 B85-10114 07
- BERRY, JR., R. F.**
Inexpensive Eddy-Current Standard
LAR-13154 B85-10225 06
Controlled-Shape, Ultrasonic-Angle-Beam Standard Reflector
LAR-13153 B85-10410 08
- BESUNER, P. M.**
Predicting the Fatigue life of Structures
MFS-27049 B85-10206 04
- BIGELOW, C. A.**
Plastic and Failure Analysis of Composites
LAR-13183 B85-10213 04
- BILLINGTON, K. L.**
Attaching an Electrical Ground to an Aluminum Structure
MSC-20668 B85-10294 01
- BIRNBAUM, M. M.**
Static-Suppressing Optical Paint
NPO-15992 B85-10077 04
Sensor Tracks the Sun From Any Angle
NPO-16211 B85-10308 02
- BJORKLUND, J. R.**
Exhaust Effluent Diffusion Model
MFS-25940 B85-10214 04
- BLACKBURN, L. B.**
Elevated-Temperature Tensile-Testing of Foil-Gage Metals
LAR-13243 B85-10363 06
- BLANCHARD, B. J.**
Measuring Soil Hydraulic Conductivity With Microwaves
GSC-12937 B85-10176 03
- BLANCHARD, D. C.**
Software Comparison
MSC-20777 B85-10565 09
Printer Graphics Package
MSC-20778 B85-10568 09
- BLANK, S. J.**
Optimizing a Linear Array of Radiating Elements
NPO-16352 B85-10298 01
- BLOSSER, M. L.**
Fastening Parts Having Mismatched Thermal Coefficients
LAR-13009 B85-10113 07
- BLUCK, R. M.**
Fabrication of Slender Struts for Deployable Antennas
LAR-13136 B85-10273 08
- BORDEN, C. S.**
Integrating Residential Photovoltaics With Power Lines
NPO-16331 B85-10188 03
Cost and Performance Model for Photovoltaic Systems
NPO-16404 B85-10314 02
- BORDEN, T. J.**
Protective Cover for IC Packages
NPO-15537 B85-10011 01
- BOREHAM, J. F.**
Microwave Power Combiner With Switching Diodes
NPO-15775 B85-10432 01
- BOTEZ, D.**
High-Output Injection Laser
LAR-13213 B85-10149 01
- BOUDAIE, K. I.**
Adsorption of H₂, Ne, and N₂ on Activated Charcoal
NPO-16329 B85-10477 03
- BOUQUET, F. L.**
Environmental Degradation of Solar Reflectors
NPO-16053 B85-10059 03
Synthetic Organic Materials in Nuclear Powerplants
NPO-16424 B85-10208 04
Degradation of Dielectrics in Space
NPO-16003 B85-10209 04
- BOUSSALIS, D.**
Vector Lyapunov Functions for Stochastic Interconnected Systems
NPO-16170 B85-10139 09
- BOVA, J. A.**
Insulating Cryogenic Pipes With Frost
MSC-20426 B85-10249 07
- BOWDISH, D. W.**
An Interactive Plotting Routine
MSC-20771 B85-10284 09
- BRADFORD, W. J.**
Microwave Atmospheric-Pressure Sensor
NPO-16496 B85-10478 03
- BREAKWELL, J. V.**
Orbit Transfer Programs
LEW-14089 B85-10538 06
- BRIDGEFORTH, A. O.**
Rotary Power Transformer and Inverter Circuit
NPO-16270 B85-10156 01
- BROERMAN, J.**
Preparation and Characterization of HgxCd_{1-x}Te
MFS-27037 B85-10081 04
- BROOKS, T. F.**
Reduction of Vane Noise in Wind-Tunnel Nozzles
LAR-13333 B85-10527 06
- BROSEMER, C. A.**
Adapter Helps To Align Plasma Torch
MFS-28024 B85-10251 07
- BROWELL, E. V.**
Airborne DIAL System for Remote Tropospheric Sensing
LAR-13002 B85-10178 03
- BROWN, J. W.**
Experiments With a Manipulator Sensor System
NPO-16094 B85-10262 07
- BROWN, R. J.**
Efficient Power Amplifier for Motor Control
GSC-12807 B85-10291 01
- BROWN, S. B.**
Predicting the Fatigue life of Structures
MFS-27049 B85-10206 04
- BROWN, W. H.**
Telephone Instrument for the Deaf
KSC-11303 B85-10014 01
- BRYANT, L. A.**
Computer-Aided Reliability Estimation
LAR-13349 B85-10315 02
- BUCKLEY, R. H.**
Personal-Computer Video-Terminal Emulator
KSC-11293 B85-10286 09
- BUEHLER, M. G.**
Designing Test Chips for Custom Integrated Circuits
NPO-15988 B85-10032 02
Study of Contact Resistances in Integrated Circuits
NPO-16248 B85-10159 01
- BULLMAN, J.**
Aerodynamic Rear Cone for Trucks
MFS-28007 B85-10217 06
- BUNKER, R. L.**
Sensor Tracks the Sun From Any Angle
NPO-16211 B85-10308 02

- BUONCRISTIANI, A. M.**
Calculating Charge Transport in
Semiconductors
LAR-13201 B85-10338 04
- BUSH, H. G.**
Fabrication of Slender Struts for
Deployable Antennas
LAR-13136 B85-10273 08
- BUSH JR., T. D.**
Soil/Structure Interactions in
Earthquakes
MFS-27078 B85-10479 03
- BUTNER, C. L.**
Optical Integrating Sphere for
Vacuum Ultraviolet
GSC-12849 B85-10325 03
- BUTTERFIELD, R. L.**
Multispectral Analysis of NMR
Imagery
KSC-11301 B85-10215 05
- BYVIK, C. E.**
Solar-Assisted Oxidation of Toxic
Cyanide
LAR-13171 B85-10075 04
Calculating Charge Transport in
Semiconductors
LAR-13201 B85-10338 04
- C**
- CALCOTE, H. F.**
Plasma Deposition of Doped
Amorphous Silicon
NPO-14955 B85-10210 04
- CALFO, F. D.**
Micronized-Coal Burner Facility
LEW-14131 B85-10492 04
- CALLENDER, E. D.**
Requirements Analysis for
Information-Intensive Systems
NPO-15944 B85-10415 09
- CAMBELL, C. W.**
Geometric Representations for
Discrete Fourier Transforms
MFS-27072 B85-10559 09
- CAMPANA, R. J.**
Heat-Powered Pump for Liquid
Metals
NPO-16457 B85-10396 07
- CAMPBELL, R. E.**
Airborne Cloud Detector
LAR-13137 B85-10167 02
- CAMPBELL, T. G.**
Tabs Reduce Helicopter-Blade
Vibrations
ARC-11444 B85-10227 06
- CARBONE, R. L.**
Foam Insulation for Cryogenic
Flowlines
MSC-20552 B85-10066 04
- CARLSON, F. M.**
Research Furnace for Crystal
Preparation
LAR-13302 B85-10496 04
- CARRENO, V. A.**
Single-Frequency Multitransmitter
Telemetry
LAR-13006 B85-10039 02
- CARROLL, J.**
Spectrophotovoltaic Power
Generation
MFS-27027 B85-10049 03
- CARSON, W. L.**
Optimizing Load Spectra for Gears
MSC-20487 B85-10260 07
- CARTER, B. J.**
Improved Electrodes for Lithium
Cells
NPO-16397 B85-10201 04
- CASH, B.**
Digital High-Current Monitor
LAR-13072 B85-10003 01
- CATER, J. P.**
Storing Data and Video on One
Tape
MSC-20705 B85-10027 02
- CHA, A. G.**
Cassegrain-Antenna Gain
Improvement
NPO-15775 B85-10433 01
- CHAN, C. K.**
Predicting Effects of Impacts on
Confined Explosives
NPO-16258 B85-10083 04
- CHANDLER, J. A.**
Remotely-Controlled Docking
System
MSC-18969 B85-10097 06
Peristaltic Pump With a Stable
Output
MSC-20907 B85-10550 07
- CHANDRAMOULI, R.**
Interface Circuits for Self-Checking
Microprocessors
NPO-15700 B85-10309 02
- CHANG, A.**
Resin Characterization in Cured
Composite Materials
LAR-13172 B85-10072 04
- CHANG, C. K.**
Adsorption of H₂, Ne, and N₂ on
Activated Charcoal
NPO-16329 B85-10477 03
- CHEMIELEWSKI, A. B.**
High-Temperature Hall-Effect
Apparatus
NPO-16279 B85-10038 02
- CHEN, W. C.**
Rough/Smooth Rotary Seal
MFS-19947 B85-10549 07
- CHENEY, C. S.**
Exhaust Effluent Diffusion Model
MFS-25940 B85-10214 04
- CHENG, L. J.**
Floating-Emitter Solar-Cell Transistor
NPO-16467 B85-10441 01
- CHI, D.**
Predicting Leakage in Labyrinth
Seals
MFS-27051 B85-10261 07
- CHIN, F.**
Back-Pressure Regulator for Large
Gas Flows
MSC-20536 B85-10109 07
- CHIN, J.**
Incrementally Variable High-Voltage
Supply
MFS-28018 B85-10145 01
- CHMIELEWSKI, A.**
Measuring Thermoelectric Properties
Automatically
NPO-16507 B85-10488 04
- CHRISTIAN, W.**
Power-Factor Controllers: How
Safe?
MFS-27016 B85-10024 01
- CHU, H. P.**
Spray Application of Rapidly Solidified
Metals
GSC-12880 B85-10131 08
- CHUTJIAN, A.**
Molecular Thermal-Electron
Detectors
NPO-16300 B85-10467 03
- CLANCY, J. P.**
Hand-Held Power Clamp
MSC-20549 B85-10257 07
- CLARK, I. O.**
Research Furnace for Crystal
Preparation
LAR-13302 B85-10496 04
Advanced Vapor-Supply Manifold
LAR-13259 B85-10523 06
- CLATTERBUCK, C. H.**
High-Voltage Isolation Transformer
GSC-12817 B85-10018 01
- CLAYTON, A.**
Nonyellowing Polycarbonate for
Outdoor Use
NPO-15836 B85-10070 04
- CLAYTON, J. C.**
Determining the Temperature Profile
in a Cylindrical Sample
MFS-26013 B85-10465 03
- CLELAND, E. L.**
Static-Suppressing Optical Paint
NPO-15992 B85-10077 04
- CLEMMONS JR., J. I.**
Obtaining One-Degree Accuracy With
Shaft Encoders
LAR-13321 B85-10431 01
- CLEMON, J. M.**
Determining Fiber Orientation in
Graphite-Reinforced Composites
MFS-28032 B85-10205 04
- CLEMONS, J. M.**
Adhesive-Bonded Fixture for Flexure
Testing
MFS-28051 B85-10360 06
Measuring Resistivities of Small
Fibers
MFS-28077 B85-10484 04
- CLERMAN, N.**
Automatically-Programed Machine
Tools
GSC-12758 B85-10264 07
- COFER III, W. R.**
Nebulization Reflux Concentrator
LAR-13254 B85-10463 03
- COGAN, K. C.**
Predicting Leakage in Labyrinth
Seals
MFS-27051 B85-10261 07
- COHN, R.**
Microphone Boom for Aircraft-Engine
Monitoring
ARC-11495 B85-10525 06
- COLE, K. N.**
Differential Temperature Control of
Electrical Heaters
LAR-13047 B85-10099 06
- COLLINGS, E. W.**
Paramagnetic Precipitates May Raise
Supercurrent
MFS-25925 B85-10195 04
- COLLINS JR., E. R.**
Improved Highway Pads for Tracked
Vehicles
NPO-16318 B85-10246 07
Improved Jet-Mill Silicon Grinder
NPO-16336 B85-10349 04
More Secure Fastening for
Tracked-Vehicle Pads
NPO-16321 B85-10385 07
Pulsed, Hydraulic Coal-Mining
Machine
NPO-15859 B85-10388 07

COLLINS, V. G.

- COLLINS, V. G.**
Nebulization Reflux Concentrator
LAR-13254 B85-10463 03
- CONKIN, J.**
Effect of Hydration on Nitrogen Washout in Humans
MSC-20686 B85-10087 05
- CONLEY, W. R.**
Inexpensive Masks for Film Deposition
NPO-16416 B85-10557 08
- CONNER, P. K.**
Processing Digital Imagery Data
MFS-25987 B85-10285 09
- CONNOLLY, J. C.**
High-Output Injection Laser
LAR-13213 B85-10149 01
- CONROY, B. L.**
Microwave Power Combiner With Switching Diodes
NPO-15775 B85-10432 01
- CONRY, T. F.**
Predicting the Dynamic Behavior of High-Speed Roller Bearings
LEW-13467 B85-10401 07
- CORDIA, E. R.**
Production Process for Strong, Light Ceramic Tiles
MSC-20602 B85-10200 04
- CORY, B.**
High-Speed Computer-Controlled Switch-Matrix System
LEW-14050 B85-10028 02
- COULSON, J.**
Image Interpolation With Dedicated Digital Hardware
GSC-12882 B85-10312 02
- COULTER, D. R.**
Bonding Solar-Cell Modules
NPO-16399 B85-10211 04
- Laser Photoacoustic Technique Detects Photo-Oxidation
NPO-16108 B85-10324 03
- COX, J. D.**
Economical Fabrication of Large Parabolic Mirrors
LAR-13139 B85-10405 08
- COX, R. L.**
Contact Heat Exchanger
MSC-20419 B85-10092 06
- CRAIDON, C., B.**
Zero-Lift Wave Drag of Complex Aircraft Configurations
LAR-13223 B85-10541 06
- CRAIG, G. D.**
Wide-Brightness-Range Video Camera
MFS-25750 B85-10301 02
- CRAIGHEAD III, N. D.**
Bistable Articulated Joint
NPO-16038 B85-10393 07
- CRAWFORD, R. F.**
Sequentially-Deployable Tetrahedral Beam
LAR-13098 B85-10222 06
- CREEDON, J. F.**
High-Strength, Low-Shrinkage Ceramic Tiles
MSC-20654 B85-10495 04
- CROUCH, R.**
Measuring Thermal Diffusivity of Molten Semiconductors
MFS-28047 B85-10350 04
- CROUCH, R. K.**
Research Furnace for Crystal Preparation
LAR-13302 B85-10496 04

- Advanced Vapor-Supply Manifold
LAR-13259 B85-10523 06
- CROUSE, D. J.**
Measuring Resistivities of Small Fibers
MFS-28077 B85-10484 04
- CUDDIHY, E. F.**
Bonding Solar-Cell Modules
NPO-16399 B85-10211 04
- CURRERI, P.**
Precise Fabrication of Electromagnetic-Levitation Coils
MFS-25986 B85-10126 08
- CURRERI, P. A.**
Cast Iron With High Carbon Content
MFS-28014 B85-10500 04
- Solidifying Cast Iron in Low Gravity
MFS-27069 B85-10504 04
- CURTIN, F.**
Making Glass-Fiber-Reinforced Coolant Tubes
MSC-20677 B85-10276 08
- CUSHMAN, J. B.**
Bonded and Bolted Graphite/Polyimide Composite Joints
LAR-13090 B85-10130 08

D

- DANFORD, M. D.**
Measuring Hydrogen Concentrations in Metals
MFS-27020 B85-10199 04
- DANIELE, C. J.**
Four-Cylinder Stirling Engine Control Simulation
LEW-14106 B85-10536 06
- DANIELS, A.**
Long-Life Cryogenic Cooler
GSC-12697 B85-10116 07
- DANIELS, C.**
Sensitivities of Soap Solutions in Leak Detection
MFS-19864 B85-10121 07
- DANIELS, J.**
Measuring Resistivities of Small Fibers
MFS-28077 B85-10484 04
- DANIELS, J. G.**
Determining Fiber Orientation in Graphite-Reinforced Composites
MFS-28032 B85-10205 04
- Adhesive-Bonded Fixture for Flexure Testing
MFS-28051 B85-10360 06
- Drilling Holes in Graphite/Epoxy Composites
MFS-28044 B85-10398 07
- DARLOW, M.**
Mechanical Design Handbook for Elastomers
LEW-14160 B85-10502 04
- DATTAGURU, B.**
Geometric and Material Nonlinear Structural Analysis
LAR-13279 B85-10381 06
- DAUD, T.**
Solar Cells With Multiple Small Junctions
NPO-16126 B85-10021 01
- DAVIDSON, M. E.**
Perforating Thin Metal Sheets
ARC-11280 B85-10125 08

PERSONAL AUTHOR INDEX

- DAVIS, C. S.**
Predicting the Fatigue life of Structures
MFS-27049 B85-10206 04
- DAVIS, R. C.**
Fastening Parts Having Mismatched Thermal Coefficients
LAR-13009 B85-10113 07
- DAVIS, W. T.**
Liquid-Level Monitor for Pressurized Vessels
LAR-13208 B85-10366 06
- Fast-Response Oxygen-Monitoring and Control System
LAR-13257 B85-10487 04
- DAVISSON, M. C.**
Cost and Performance Model for Photovoltaic Systems
NPO-16404 B85-10314 02
- DE YOUNG, R. J.**
Long-Gain-Length, Solar-Pumped Box Laser
LAR-13256 B85-10319 03
- DEANGELIS, V. M.**
Electro-optical System Measures Aircraft Deflections
ARC-11454 B85-10305 02
- DEATON, J. W.**
Damage and Repair of Composite Structures
LAR-13148 B85-10278 08
- DEBNAM JR., W. J.**
Research Furnace for Crystal Preparation
LAR-13302 B85-10496 04
- Advanced Vapor-Supply Manifold
LAR-13259 B85-10523 06
- DECARLO, J. L.**
Damping Melt Convection With A Magnetic Field
MFS-28040 B85-10339 04
- DEFEVER, G. J.**
Calibrating Droplet Generator for Pressurized Testing Vessel
MFS-25992 B85-10094 06
- DEMKO, J.**
Predicting Leakage in Labyrinth Seals
MFS-27051 B85-10261 07
- DEMONET, R. J.**
Testing Machine for Biaxial Loading
MSC-20477 B85-10220 06
- DEMUTH, R. S.**
Microprocessor-Controlled Laser Balancing System
LEW-13294 B85-10093 06
- DENNIS, D. P.**
Reducing Stress-Corrosion Cracking in Bearing Alloys
MFS-19948 B85-10331 04
- DENNIS, D. V.**
Aircraft Control-Position Indicator
LAR-12984 B85-10020 01
- DENNISON, E. W.**
Out-of-Focus Alinement of Solar Concentrators
NPO-15563 B85-10044 03
- DERBALIAN, G. A.**
Predicting the Fatigue life of Structures
MFS-27049 B85-10206 04
- DETWILER, R. C.**
Low-Voltage Protection For Volatile Computer Memories
NPO-15909 B85-10148 01

PERSONAL AUTHOR INDEX

FITCHETT, B. T.

DEUTSCH, L. J.
Systolic VLSI Reed-Solomon
Decoder NPO-16383 B85-10304 02
Single-Chip VLSI Reed-Solomon
Encoder NPO-16122 B85-10452 02
Multiplier Architecture for Coding
Circuits NPO-16363 B85-10456 02
DICKINSON, C. B.
Measuring Perimeters of Large
Round Objects MFS-28046 B85-10365 06
DICKINSON, R. M.
Retrodirective-Optical-Transponder
Concept NPO-16315 B85-10153 01
DINER, D. J.
Calculating Atmospheric Effects in
Satellite Imagery NPO-16373 B85-10327 03
DIXON, D. S.
Friction-Testing Machine
MSC-20622 B85-10370 06
DOKKO, W.
Contactless Calorimetry for Levitated
Samples NPO-16448 B85-10318 03
DOLLAND, C.
Commutating Permanent-Magnet
Motors At Low Speed MFS-25207 B85-10150 01
DOMACK, C. S.
Smoothed Two-Dimensional Edges
for Laminar Flow LAR-13255 B85-10514 06
DOTSON, R. D.
Automatic Erection System for
Antenna Masts LAR-13115 B85-10115 07
DOTSON, R. S.
Experiments With a Manipulator
Sensor System NPO-16094 B85-10262 07
DOZOIS, P. C.
Preventing Electrostatic-Discharge
Damage to Electronics NPO-15953 B85-10296 01
DRAGO, R. J.
Analysis of Spiral Bevel Gearing
LEW-14067 B85-10265 07
DRESSLER, B.
Studying Crystal Growth With the
Peltier Effect MFS-28041 B85-10346 04
DU FRESNE, E. R.
Purifying Aluminum by Vacuum
Distillation NPO-16114 B85-10065 04
Lightweight Protective Garments
NPO-16510 B85-10497 04
DUFFIN, J.
Fast-Recovery, High-Voltage Power
Diode LEW-14036 B85-10016 01
DUMBAULD, R. K.
Exhaust Effluent Diffusion Model
MFS-25940 B85-10214 04
DUNCAN, C. S.
Prototype Furnace for Automatic
Production of Silicon Ribbon
NPO-16175 B85-10272 08
Adjustable Lid Aids Silicon-Ribbon
Growth NPO-16354 B85-10275 08

DUNN, T. J.
Making Structural Members From
Wire MSC-20175 B85-10268 08
DUNN, W. R.
Redundant Asynchronous
Microprocessor System ARC-11348 B85-10031 02
DYBA, G. J.
Multistage Planetary Power
Transmissions LEW-14100 B85-10399 07

E

EARWOOD, L.
Flushing Ring for EDM
MFS-19876 B85-10108 07
EASTMAN, G. Y.
Titanium Heat-Pipe Wicks
MFS-26016 B85-10524 06
ECKLUND, R. C.
Improved Surface of Titanium
Structure LAR-13148 B85-10409 08
ECONOMU, M.
Microphone Boom for Aircraft-Engine
Monitoring ARC-11495 B85-10525 06
EDELSTEIN, F.
Pumped, Two-Phase Heat-Transfer
Loop MSC-20841 B85-10542 07
EDWARDS, D. E.
Flow Through Gas-Turbine Ducts
LEW-14095 B85-10533 06
EHL, J. H.
Aligning Large Cylinders for Welding
MFS-28001 B85-10271 08
EISCHEN, J. W.
Predicting the Fatigue life of
Structures MFS-27049 B85-10206 04
ELDRED, D. B.
Maximum-Likelihood Parameter-Esti-
mation Algorithm NPO-16320 B85-10560 09
ELGHOBASHI, S.
Corrosive Effects of Burning Fuels
NPO-16345 B85-10207 04
ELLINGSWORTH, J. R.
Elevated-Temperature Tensile-Test-
ing of Foil-Gage Metals LAR-13243 B85-10363 06
ELLIOTT, D. G.
Puncture-Tolerant Heat Radiator
NPO-16401 B85-10390 07
ELLIS, J.
Interferometry Measures Elliptical
Satellite Orbits NPO-16313 B85-10171 02
ELLISON, A.
Strength of Graphite/Metal
Composite Lap Joints MFS-27030 B85-10082 04
ELWELL, D.
Melt Stirring by Horizontal Crucible
Vibration MFS-26005 B85-10069 04
ELY, R. M.
Colorless, Transparent, Aromatic
Polyimide Films LAR-13351 B85-10490 04

EMERY, A. F.
Radiation View-Factor Program With
Interactive Graphics LAR-13299 B85-10535 06
ENG, B.
Rotating Capacitor Measures Steady
Electric Fields NPO-16550 B85-10449 02
ERNST, D. M.
Titanium Heat-Pipe Wicks
MFS-26016 B85-10524 06
ESTRELLA, C.
Insulation Blankets for
High-Temperature Use ARC-11453 B85-10489 04
ETHRIDGE, E.
Precise Fabrication of
Electromagnetic-Levitation Coils
MFS-25986 B85-10126 08
EXPOSITO, T.
Calibrating Droplet Generator for
Pressurized Testing Vessel MFS-25992 B85-10094 06
EXTON, R. J.
Vibration-Free Raman Doppler
Velocimeter LAR-13268 B85-10447 02
EZZELL, K. S.
Colorless, Transparent, Aromatic
Polyimide Films LAR-13351 B85-10490 04

F

FARHOOMAND, J.
Generating Tunable Far-Infrared
Laser Sidebands NPO-16497 B85-10450 02
FARLEY, G. L.
End Restraints for
Impact-Energy-Absorbing Tube
Specimens LAR-13179 B85-10218 06
Fixture for Linearly Variable
Displacement Transducers LAR-12937 B85-10224 06
FEIGELSON, R. S.
Melt Stirring by Horizontal Crucible
Vibration MFS-26005 B85-10069 04
FEINBERG, A.
Comparison of Decision Models
NPO-16446 B85-10563 09
FENWICK, J. R.
Calculating Bearing Forces From
Strain-Gage Signals MFS-29000 B85-10510 06
Vibrational Effects of Turbopump
Housing Flexibility MFS-27083 B85-10552 07
FEREBEE, R. C.
Statistical Energy Analysis Program
MFS-27035 B85-10231 06
FINKEL, M. W.
Optical Scanner for Linear Arrays
GSC-12897 B85-10320 03
FINLEY, T. D.
Determining Calibration Constants for
Attitude Measurements LAR-13214 B85-10475 03
FITCHETT, B. T.
Compensating for Shrinkage in
Machined Ceramics MSC-20684 B85-10394 07

FLEMING, D. P.

FLEMING, D. P.
Squeeze-Film Damper Controls High
Vibrations
LEW-13506 B85-10528 06

FLEMING, M. L.
Contact Heat Exchanger
MSC-20419 B85-10092 06

FLOWER, D. A.
Microwave Atmospheric-Pressure
Sensor
NPO-16496 B85-10478 03

FODALE, B.
Electro-optical System Measures
Aircraft Deflections
ARC-11454 B85-10305 02

FOHLEN, G.
Thermosetting Phthalocyanine
Polymers
ARC-11511 B85-10061 04
Synthesizing Metal Phthalocyanine
Imide Polymers
ARC-11413 B85-10074 04

FOHLEN, G. M.
Imide Cyclotriphosphazene/Hexa-
fluoroisopropylidene Polymers
ARC-11428 B85-10333 04
Synthesis of Metal Phthalocyanine
Sheet Polymers
ARC-11405 B85-10343 04
Phthalocyanine Tetraamine
Epoxy-Curing Agents
ARC-11424 B85-10348 04

FONG, M.
Protective Package for a Gamma-Ray
Detector
NPO-16019 B85-10041 03

FOUNTAIN, J. A.
Equipment for Microgravity
Research
MFS-27094 B85-10480 03

FOUTCH, G. L.
Coculture Production of Butanol by
Clostridium Bacteria
NPO-16203 B85-10086 05

FOWLER, G. F.
Predicting the Fatigue life of
Structures
MFS-27049 B85-10206 04

FOWLER, L. E.
Programmable Driver for
Voltage-Controlled Oscillators
NPO-16364 B85-10162 02

FOX, R. L.
Melt-Pressed Films of Insoluble
Semicrystalline Polymers
LAR-13212 B85-10351 04

FRANKE, J. M.
Obtaining One-Degree Accuracy With
Shaft Encoders
LAR-13321 B85-10431 01

FRALEY, J. L.
Photo-Optical Blade-Vibration-Data
Acquisition System
LEW-12887 B85-10511 06

FRATER, J. L.
Dynamic Effects of Internal
Spur-Gear Drives
LEW-14167 B85-10553 07

FRAUENHOLZ, R. B.
Interferometry Measures Elliptical
Satellite Orbits
NPO-16313 B85-10171 02

FRAZER, R. E.
Self-Identifying Reflecting Targets
NPO-16106 B85-10033 02

FRAZIER, D. O.
Reversing Glass Wettability
MFS-26006 B85-10071 04

FREITAG, H. J.
Noncontacting Measurement With a
Thermocouple
MSC-20834 B85-10374 06

Distributing Radiant Heat in Insulation
Tests
MSC-20878 B85-10513 06

FRENCH, E. P.
Estimating the Performance of a
Concentrating Solar Array
MFS-28021 B85-10185 03

FRIEDLANDER, S. K.
Laser-Assisted Analysis of Aerosol
Particles
NPO-15308 B85-10056 03
Mass Spectrometer for Airborne
Micro-Organisms
NPO-16359 B85-10505 05

FRIEDMAN, L.
System for Automated
Troubleshooting
NPO-16339 B85-10558 09

FRINK, N. T.
Deployable Truss Member
LAR-13219 B85-10362 06

FRIPP JR., A. L.
Research Furnace for Crystal
Preparation
LAR-13302 B85-10496 04
Advanced Vapor-Supply Manifold
LAR-13259 B85-10523 06

FRISBEE, R. H.
Augmenting Thrust With Waste Heat
NPO-16218 B85-10190 03

FRISCH, H. P.
NASTRAN/DISCOS/SAMSAN DMAP
Bridging Program
GSC-12902 B85-10379 06
Numerical Methods for Classical
Sampled-System Analysis
GSC-12827 B85-10564 09

FULTON, D. S.
Spill-Detector-and-Shutoff Device
MSC-20206 B85-10106 07

FURST, R. B.
Calculating Flow-Angle Deviation in
Rotary Pumps
MFS-29062 B85-10548 07

G

GALINDO, V.
Cassegrain-Antenna Gain
Improvement
NPO-15775 B85-10433 01

GALLAGHER, B. D.
Metalization Patterns by Thermal
Decomposition
NPO-16413 B85-10408 08

GALLIMORE, F. H.
Adjustable-Angle Drill Block
LAR-13101 B85-10545 07

GANGAL, M. D.
Automated Coal-Mining System
NPO-16177 B85-10233 07

Modular Pick-and-Bucket Mining
Machine
NPO-16179 B85-10235 07

Reducing Coal Dust With Water Jets
NPO-16180 B85-10236 07

All-Water-Jet Coal Excavator
NPO-16183 B85-10238 07

PERSONAL AUTHOR INDEX

Service Modules for Coal Extraction
NPO-16185 B85-10240 07

GARDNER, M. R.
Spring-Loaded Transducer Holder
LAR-13048 B85-10098 06

GARNER, H. D.
Fuel Gage for Sloshing Tanks
LAR-13147 B85-10515 06
Braille Reading Systems
LAR-13306 B85-10517 06

GARST, R. A.
Plotting Lightning-Stroke Data
MFS-26019 B85-10462 03

GASSER, M. G.
Long-Life Cryogenic Cooler
GSC-12697 B85-10116 07

GATEWOOD, J. R.
Coating a Sphere With Evaporated
Metal
NPO-16436 B85-10404 08

GAUGH, C.
Fast-Recovery, High-Voltage Power
Diode
LEW-14036 B85-10016 01

GEARY, H. V.
Exhaust Effluent Diffusion Model
MFS-25940 B85-10214 04

GENNERY, D. B.
Picture-Element Comparator
NPO-16464 B85-10458 02
Programmable Pipelined-Image
Processor
NPO-16463 B85-10459 02

Function Generator for Image
Processor
NPO-16461 B85-10460 02

GERDES, W.
Noninvasive Fluid Level Sensor for
Organometallic Sources
LAR-13265 B85-10371 06

GERINGER, H. J.
Thermal Shock-Resistant Composite
Crucible
LEW-14105 B85-10252 07

GERRETY, J. F.
Constant-Pressure Sawing
NPO-15233 B85-10383 07

GEYSER, L.
Design of Linear Quadratic
Regulators and Kalman Filters
LEW-14128 B85-10461 02

GHONIEM, A. F.
Predicting Two-Dimensional,
Unsteady Turbulent Combustion
LEW-14027 B85-10376 06

GIBBENS, B. V.
Calibrating Pressure Transducers at
Cryogenic Temperatures
LAR-13242 B85-10516 06

GIERING, E. W.
Personal-Computer Video-Terminal
Emulator
KSC-11293 B85-10286 09

GIFFIN, C. E.
Laser-Assisted Analysis of Aerosol
Particles
NPO-15308 B85-10056 03

GILWEE, W.
Rubberized, Brominated Epoxies
ARC-11427 B85-10079 04

GLASSMAN, A. J.
Three-Dimensional
ade-Row Analysis Code
LEW-14061 B85-10400 07

Off-Design Performance of
Radial-Inflow Turbines
LEW-14060 B85-10402 07

PERSONAL AUTHOR INDEX

GLUCH, D. P.
Residue-Measure Model-Reduction
Technique
MSC-20369 B85-10137 09

GOETZ, A. F. H.
Compact Imaging Spectrometer
NPO-16342 B85-10471 03

GOLDFARB, S. M.
Efficient Process for Making
Polycrystalline Silicon
NPO-16121 B85-10073 04

GOLDOWSKY, M.
Long-Life Cryogenic Cooler
GSC-12697 B85-10116 07

GOLDRICH, R. N.
Synthesis and Optimization of Spiral
Bevel Gears
LEW-13920 B85-10389 07

GOLDSTEIN, H.
Insulation Blankets for
High-Temperature Use
ARC-11453 B85-10489 04

GOLDSTEIN, R.
Polarizing Filter for Integrated Optics
NPO-16429 B85-10288 01

GOODWIN, G. O.
Hydraulic Cylinder With an Integral
Position Indicator
LAR-13095 B85-10518 06

GORDON, S.
Prediction of Combustion Gas
Deposit Compositions
LEW-14091 B85-10280 09

GOSS, W. C.
Hybrid Fiber-Optic/CCD Chip
NPO-16030 B85-10002 01
Polarizing Filter for Integrated Optics
NPO-16429 B85-10288 01

GRAF, J.
Recharging Batteries Chemically
NPO-16024 B85-10143 01

GRAHAM, L. J.
Frequency-Discriminating Acoustic-
Event Counter
MSC-20467 B85-10160 02

GRAHAM, M. H.
Processing Digital Imagery Data
MFS-25987 B85-10285 09

GRAIG JR., R. R.
Multishaker Modal Testing
MFS-27052 B85-10101 06

GRANA, D. C.
Continuously Variable Transmission
LAR-12844 B85-10105 07

GRANETT, D.
Screw-Retaining Allen Wrench
NPO-16275 B85-10127 08
Centrifugal Generator of Filled
Spherical Shells
NPO-16051 B85-10270 08

GRANT, W. B.
Monitoring Trace Gases in the
Atmosphere
NPO-16278 B85-10175 03
Methane Detector With Plastic
Fresnel Lens
NPO-16284 B85-10321 03

GRAZYK, T.
Power-Factor Controllers: How
Safe?
MFS-27016 B85-10024 01

GRIMM, D.
Mechanical Mixer for Rudder/Braking
Wedge
MSC-20759 B85-10117 07

GRINER, D. B.
Zone Refining by Laser
MFS-27084 B85-10555 08

GRISWOLD, T. W.
Designing Test Chips for Custom
Integrated Circuits
NPO-15988 B85-10032 02

GUNTHER, F. J.
Image-Processing Educator
GSC-12933 B85-10566 09

GUNZBURGER, M. D.
Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06

GUPTA, A.
Nonyellowing Polycarbonate for
Outdoor Use
NPO-15836 B85-10070 04
Laser Photoacoustic Technique
Detects Photo-Oxidation
NPO-16108 B85-10324 03

GUPTA, K. K.
Free-Vibration Analysis of Structures
NPO-15000 B85-10279 09

GZOWSKI, E. R.
Improving Emittance of
High-Temperature Insulating Tile
MSC-20714 B85-10078 04

H

HADDEN, G. B.
Multistage Planetary Power
Transmissions
LEW-14100 B85-10399 07

HALL, J. F.
Manipulation and Display of
Panel-Method Geometry
LAR-13224 B85-10282 09

HALL, T. C.
Double Light-Emitting Diode
GSC-12832 B85-10015 01

HAMIDI, M.
Maximum-Likelihood Parameter-Esti-
mation Algorithm
NPO-16320 B85-10560 09

HAMMOND, R. A.
Hybrid and Electric Advanced Vehicle
Systems Simulation
LEW-13927 B85-10263 07

HAMPTON, H. R.
Electro-optical System Measures
Aircraft Deflections
ARC-11454 B85-10305 02

HANEY, M. W.
Point Simulator for Synthetic-Aperture
Radar
NPO-16296 B85-10165 02

HANKINS JR., G. B.
Flow Through Gas-Turbine Ducts
LEW-14095 B85-10533 06

HANNA, M. F.
Determining Internal Connections in
Capacitors
NPO-16499 B85-10445 01

HANNINEN, B.
Electronic/Hydraulic Level Gage
MFS-28066 B85-10522 06

HANSON, R. J.
Text Exchange System
NPO-16357 B85-10419 09

HARRINGTON, D. B.
Hand-Held Electronic Gap-Measuring
Tools
MSC-20176 B85-10223 06

HARRIS, D. O.
Predicting the Fatigue life of
Structures
MFS-27049 B85-10206 04

HARRIS, L. H.
Synchronizing Data-Bus Messages
MSC-20640 B85-10035 02

HARRIS, R. P.
High-Temperature, High-Pressure
Optical Cells
MFS-26000 B85-10267 08

HARRISON, H. N.
Development of a Prosthesis for
Urinary Control
MFS-27062 B85-10359 05

HARTENSTEIN, R.
Image Interpolation With Dedicated
Digital Hardware
GSC-12882 B85-10312 02

HARTLEY, D.
Electronic/Hydraulic Level Gage
MFS-28066 B85-10522 06

HARTSOUGH, C.
Requirements Analysis for
Information-Intensive Systems
NPO-15944 B85-10415 09

HARVEY, W. D.
Retractable End Plates for Aircraft
Lifting Surfaces
LAR-12946 B85-10216 06

HASELMAIER, H.
Damage-Free Relief-Valve
Disassembly
MFS-28006 B85-10361 06

HASLETT, R.
High-Performance Heat Pipe
MSC-20136 B85-10177 03

HASSAN, A.
Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06

HAVENS, S. J.
Ethynyl-Terminated Ester Oligomers
and Polymers
LAR-13118 B85-10076 04

HAY, S.
Vision Screening by Color
Photography
MFS-25800 B85-10085 05

HAYASE, M.
Improved Surface of Titanium
Structure
LAR-13148 B85-10409 08

HEAPS, J. D.
Trough Coating Solar Cells Without
Spillover
NPO-15313 B85-10330 04

HEDGEPEETH, J. M.
Inflatable Column Structure
NPO-16216 B85-10091 06

HEIN, L. A.
Shaft Seal Compensates for Cold
Flow
MFS-25678 B85-10254 07

HELGESEN, R. J.
Signal Processor for Multirate PSK
Signals
MSC-20195 B85-10008 01

HENDRIX, J. C.
Cast Iron With High Carbon Content
MFS-28014 B85-10500 04
Solidifying Cast Iron in Low Gravity
MFS-27069 B85-10504 04

HERGENROTHER, P. M.
Ethynyl-Terminated Ester Oligomers
and Polymers
LAR-13118 B85-10076 04

HERRING, M.

Phenoxy Resins Containing Pendent
Ethynyl Groups
LAR-13222 B85-10491 04

HERRING, M.
Compact Imaging Spectrometer
NPO-16342 B85-10471 03

HERRMANN, F. T.
Enhancing Centrifugal Separation
With Electrophoresis
MFS-28053 B85-10357 05

HILL, A. J.
Shaft Axial-Displacement Sensor
MFS-29048 B85-10519 06

HO, P.
High-Speed Computer-Controlled
Switch-Matrix System
LEW-14050 B85-10028 02

HOAD, D. R.
Reduction of Vane Noise in
Wind-Tunnel Nozzles
LAR-13333 B85-10527 06

HODGES, W. T.
Ultrasonic Mixing of Epoxy Curing
Agents
LAR-13307 B85-10498 04

HOFFMAN, M.
High-Speed Computer-Controlled
Switch-Matrix System
LEW-14050 B85-10028 02

HOGLE, R.
Fluidized-Bed Particles Scavenge
Silicon Fines
NPO-16034 B85-10202 04

HOLLAND, L.
Measuring Thermal Diffusivity of
Molten Semiconductors
MFS-28047 B85-10350 04

HOLLAND, L. R.
High-Temperature, High-Pressure
Optical Cells
MFS-26000 B85-10267 08

HOLLIDAY, R. J.
Beta Silicon Nitride Whiskers
NPO-16409 B85-10501 04

HOLMES, B. J.
Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06

HOLMQUIST, G. R.
Production Process for Strong, Light
Ceramic Tiles
MSC-20602 B85-10200 04

HOLMS, A. G.
Subset Regression
LEW-14002 B85-10420 09

HOPSON, J., P.
High-Quality, Thin-Film Germanium
Single Crystals
LAR-13211 B85-10406 08

HORRIGAN JR., D. J.
Effect of Hydration on Nitrogen
Washout in Humans
MSC-20686 B85-10087 05

HOUSKA, C. R.
X-Ray Diffraction Analysis Program
LAR-13276 B85-10483 03

HOWELL, L. W.
Manipulation of Numbers With Many
Digits
MFS-28048 B85-10567 09

HOWELL, W. E.
Fuel Gage for Sloshing Tanks
LAR-13147 B85-10515 06

HOWLAND, A. R.
Measuring Antenna Signal Delays
NPO-15947 B85-10455 02

HSU, G. C.
High-Purity Silicon Seeds for Silane
Pyrolysis
NPO-16287 B85-10060 04

Fluidized-Bed Particles Scavenge
Silicon Fines
NPO-16034 B85-10202 04

Extracting Silicon Product From
Fluidized-Bed Reactors
NPO-16385 B85-10341 04

Producing Silicon Carbide for
Semiconductor Devices
NPO-16391 B85-10342 04

HUBER, W. C.
Keyboard With Voice Output
MSC-20869 B85-10438 01

HULT, T. D.
Bistable Articulated Joint
NPO-16038 B85-10393 07

HUNDLEY, N. H.
Ultra-High-Molecular-Weight Silphen-
ylene/Siloxane Polymers
MFS-27065 B85-10499 04

HWON, A. H.
Plug-In RF Selector Switch
MSC-20572 B85-10292 01

I

IGAWA, J. A.
Pretinning Nickel-Plated Wire
Shields
MSC-20712 B85-10266 08

ISENBERG, L.
Automated Coal-Mining System
NPO-16177 B85-10233 07

IZU, Y. D.
Waterproofing Agents for Silica Tiles
MSC-20364 B85-10080 04

J

JACKSON, E. D.
Rough/Smooth Rotary Seal
MFS-19947 B85-10549 07

JACKSON, H. W.
Coating a Sphere With Evaporated
Metal
NPO-16436 B85-10404 08

JACKSON, L. R.
Fastening Parts Having Mismatched
Thermal Coefficients
LAR-13009 B85-10113 07

JACQUEMIN, G. G.
Automatic Erection System for
Antenna Masts
LAR-13115 B85-10115 07

JAMIESON, R. S.
Crossover Concept for Optical
Printed Circuits
NPO-15131 B85-10186 03

JANESICK, J. R.
Hybrid Fiber-Optic/CCD Chip
NPO-16030 B85-10002 01

JARVIS, M. R.
Spill-Detector-and-Shutoff Device
MSC-20206 B85-10106 07

JAYROE, R.
Vision Screening by Color
Photography
MFS-25800 B85-10085 05

PERSONAL AUTHOR INDEX

JECK, R. W.
Thermal Shock-Resistant Composite
Crucible
LEW-14105 B85-10252 07

JENSEN, B. J.
Melt-Pressed Films of Insoluble
Semicrystalline Polymers
LAR-13212 B85-10351 04

JIN, M. Y.
Compensating for Range Migration in
Synthetic-Aperture Radar
NPO-15954 B85-10136 09

JOHNSON, D. L.
Reciprocating Magnetic Refrigerator
NPO-16257 B85-10107 07

JOHNSON, R. A.
Tracking System for Infrared
Spectrometer
NPO-16440 B85-10464 03

JOHNSON, R. L.
Double Light-Emitting Diode
GSC-12832 B85-10015 01

JOHNSON, R. R.
Fabrication of Slender Struts for
Deployable Antennas
LAR-13136 B85-10273 08

JOHNSON, W. S.
Plastic and Failure Analysis of
Composites
LAR-13183 B85-10213 04

JOHNSTON, A. R.
Fiber-Optic Electric-Field Meter
NPO-16435 B85-10290 01

Rotating Capacitor Measures Steady
Electric Fields
NPO-16550 B85-10449 02

Automatic Guidance for Remote
Manipulator
NPO-13386 B85-10453 02

JOHNSTON, D. F.
Improved Electronic Control for
Electrostatic Precipitators
LAR-13273 B85-10457 02

JOHNSTON, J. O.
Redundant Asynchronous
Microprocessor System
ARC-11348 B85-10031 02

JOHNSTON, M. H.
Laser Schlieren Crystal-Growth
Imager
MFS-28060 B85-10326 03

JONES, D. P.
Thermal, One-Dimensional Analyzer
Program
MSC-20703 B85-10378 06

JONES, J. A.
LaNi5 Hydrogen-Absorption
Cryogenic System
NPO-16314 B85-10387 07

Hydrogen Refrigerator Would Cool
Below 10 K
NPO-16393 B85-10543 07

JONES, J. T.
Dolly Swivel for Forklift
MFS-19866 B85-10391 07

JONES, R. L.
Modal Analysis and Gain Estimation
LAR-13334 B85-10418 09

JONES, S. B.
Obtaining One-Degree Accuracy With
Shaft Encoders
LAR-13321 B85-10431 01

JORDAN, D.
Multispectral Analysis of NMR
Imagery
KSC-11301 B85-10215 05

JUDAY, D.
Online Tester for a Symbol
Generator
MSC-20357 B85-10161 02

JUNKIN, B. G.
Processing Digital Imagery Data
MFS-25987 B85-10285 09

K

KALCIC, M. T.
Processing Digital Imagery Data
MFS-25987 B85-10285 09

KAPON, E.
Improved Waveguide Laser Array
NPO-16500 B85-10435 01

KARATNICKI, H.
Fast-Recovery, High-Voltage Power
Diode
LEW-14036 B85-10016 01

KASUBA, R.
Dynamic Effects of Internal
Spur-Gear Drives
LEW-14167 B85-10553 07

KATSANIS, T.
Duct-Flow Analysis
LEW-14000 B85-10191 03

KATZ, J.
Damping Relaxation Oscillations in
Laser Diodes
NPO-15980 B85-10010 01

Improved Waveguide Laser Array
NPO-16500 B85-10435 01

KAUFMAN, A.
Inelastic Analysis of
Thermomechanically Cycled Structures
LEW-14011 B85-10380 06

KAUFMAN, M.
Simulating Pressure Effects of
High-Flow Volumes
MFS-19909 B85-10103 07

KAUKLER, W. F.
Variable-Temperature-Gradient De-
vice for Solidification Research
MFS-26008 B85-10042 03

Reversing Glass Wettability
MFS-26006 B85-10071 04

KAVAYA, M. J.
Accuracy of Lidar Measurements of
the Atmosphere
NPO-16493 B85-10476 03

KEENAN, R.
Photovoltaic-Panel Laminator
NPO-16092 B85-10123 08

Series Connection of Solar Cells
NPO-16091 B85-10124 08

KERR, J.
Vision Screening by Color
Photography
MFS-25800 B85-10085 05

KHANNA, S.
Solid-State Detector for Trace
Materials
NPO-16450 B85-10469 03

KHANNA, S. K.
Magnetron-Sputtered Amorphous
Metallic Coatings
NPO-16221 B85-10204 04

Magnetron Sputtering Deposits
Corrosion-Resistant Alloy
NPO-15928 B85-10337 04

KILLGROVE, T. O.
Locking Pull Pin
NPO-16233 B85-10512 06

KIM, Q.
Discoloration of Polyvinyl Butyral
NPO-16411 B85-10353 04

KINCHELOE, J. P.
Precise Electrochemical Drilling of
Repeated Deep Holes
MFS-19767 B85-10250 07

KINTIS, D.
Strength of Graphite/Metal
Composite Lap Joints
MFS-27030 B85-10082 04

KIRALY, L. J.
Photo-Optical Blade-Vibration-Data
Acquisition System
LEW-12887 B85-10511 06

KIRKHAM, H.
Rotating Capacitor Measures Steady
Electric Fields
NPO-16550 B85-10449 02

KIRKLAND, W. L.
Making Stronger Twine With Matched
Strands
MSC-20444 B85-10128 08

KISS, J.
Orienting Arc Lamps for Longest
Life
MSC-20562 B85-10155 01

KLECKNER, R. J.
Multistage Planetary Power
Transmissions
LEW-14100 B85-10399 07

KNOWLES, G.
Spectrophotovoltaic Power
Generation
MFS-27027 B85-10049 03

KNOX, E. C.
Combination Heat-Flux and
Temperature Gage
MSC-20706 B85-10221 06

KOHL, F. J.
Prediction of Combustion Gas
Deposit Compositions
LEW-14091 B85-10280 09

KOLIWAD, K. M.
Solar Cells With Multiple Small
Junctions
NPO-16126 B85-10021 01

KOROMILAS, A.
Personal-Computer Video-Terminal
Emulator
KSC-11293 B85-10286 09

KORSCH, D.
Nearly Anastigmatic X-Ray
Telescope
MFS-25984 B85-10047 03

KOSSON, R.
High-Performance Heat Pipe
MSC-20136 B85-10177 03

KOURTIDES, D.
Rubberized, Brominated Epoxies
ARC-11427 B85-10079 04

KOURTIDES, D. A.
Increasing Fire Safety of Epoxies
ARC-11506 B85-10062 04

KOVACIK, J.
Power-Factor Controllers: How
Safe?
MFS-27016 B85-10024 01

KRIEG JR., H. C.
Measuring Moisture in Sealed
Electronic Enclosures
MSC-18866 B85-10183 03

KUHR, G. A.
Inspecting Hollow Parts With a CAT
Scanner
MFS-19916 B85-10089 06

KUMAR, A.
Analysis of Scramjet Inlets
LAR-13297 B85-10382 06

KURTZ, D. W.
Systems Engineering of Electric and
Hybrid Vehicles
NPO-15871 B85-10551 07

KURZWEG, U. H.
Economical Fabrication of Large
Parabolic Mirrors
LAR-13139 B85-10405 08

KUSTAS, F. M.
Ion Implantation Improves
Bearing-Surface Properties
MFS-25995 B85-10197 04

L

LABAW, C. C.
Imaging Spectrometer for
Geophysical Surveys
NPO-16072 B85-10046 03

LADANY, I.
Wedge Fibers Suppress Feedback
of Laser Beam
LAR-13074 B85-10474 03

LAHMEYER, C. R.
Fast Control Sequencer
NPO-16116 B85-10163 02

LAM, D. Q.
Sensitivities of Soap Solutions in
Leak Detection
MFS-19864 B85-10121 07

LAMBE, J.
Study of Contact Resistances in
Integrated Circuits
NPO-16248 B85-10159 01

LAMBE, J. J.
Solid-State Detector for Trace
Materials
NPO-16450 B85-10469 03

LANG, D. J.
Gradually Acting Shaft Stop
MSC-20729 B85-10256 07

LARSON, E.
Fast-Recovery, High-Voltage Power
Diode
LEW-14036 B85-10016 01

LARSON, H. K.
Insulation Blankets for
High-Temperature Use
ARC-11453 B85-10489 04

LARSON JR., D. J.
Studying Crystal Growth With the
Peltier Effect
MFS-28041 B85-10346 04

LAUDENSLAGER, J. B.
Magnetically-Switched, Long-Pulse
XeCl Laser
NPO-16410 B85-10430 01

LAUE, E. G.
Low-Cost Humidity Sensor
NPO-16544 B85-10440 01

LAWTON, E. A.
Purifying Water by Imbibition
NPO-16419 B85-10340 04

LEDBETTER, F. E.
Determining Fiber Orientation in
Graphite-Reinforced Composites
MFS-28032 B85-10205 04

Adhesive-Bonded Fixture for Flexure
Testing
MFS-28051 B85-10360 06

- Drilling Holes in Graphite/Epoxy Composites
MFS-28044 B85-10398 07
- Measuring Resistivities of Small Fibers
MFS-28077 B85-10484 04
- LEDUC, H. G.**
Solid-State Detector for Trace Materials
NPO-16450 B85-10469 03
- LEE, G. E.**
Personal-Computer Video-Terminal Emulator
KSC-11293 B85-10286 09
- LEE, J. J.**
Coding for Electronic Mail
NPO-16350 B85-10411 09
Coding for Efficient Image Transmission
NPO-16444 B85-10416 09
- LEE, M. C.**
Hybrid Contactless Heating and Levitation
NPO-15657 B85-10122 08
Blowing Polymer Bubbles in an Acoustic Levitator
NPO-16212 B85-10203 04
Contactless Calorimetry for Levitated Samples
NPO-16448 B85-10318 03
- LEE, S.**
Computational Simplification of Robot-Arm Dynamics
NPO-16377 B85-10417 09
- LEHOCZKY, B. S. L.**
Characterizing Semiconductor Alloys for Infrared Sensors
MFS-27059 B85-10355 04
- LEHTINEN, B.**
Design of Linear Quadratic Regulators and Kalman Filters
LEW-14128 B85-10461 02
- LEIBERT, C. H.**
Plasma-Sprayed Coatings on Porous Surfaces
LEW-13450 B85-10347 04
- LEIGHTY, B. D.**
Power Supply For 25-Watt Arc Lamp
LAR-13202 B85-10141 01
- LEIPHAM, T.**
Dent-Removing Tool
MFS-29044 B85-10554 08
- LEISER, D.**
Insulation Blankets for High-Temperature Use
ARC-11453 B85-10489 04
- LEVENSPIEL, O.**
Agglomeration-Free Distributor for Fluidized Beds
NPO-16466 B85-10544 07
- LEVIN, R. R.**
Systems Engineering of Electric and Hybrid Vehicles
NPO-15871 B85-10551 07
- LEVY, R.**
Optimization of Antenna-Structure Design
NPO-16158 B85-10299 01
- LEWIS, E. V.**
Automated Coal-Mining System
NPO-16177 B85-10233 07
Pointable Auger
NPO-16178 B85-10234 07
- Modular Pick-and-Bucket Mining Machine
NPO-16179 B85-10235 07
Reducing Coal Dust With Water Jets
NPO-16180 B85-10236 07
Slurry-Mixing Chamber
NPO-16182 B85-10237 07
Coal-Sizing Auger
NPO-16184 B85-10239 07
Service Modules for Coal Extraction
NPO-16185 B85-10240 07
Side Shield for Wall Support
NPO-16188 B85-10241 07
Roof Shield for Advance and Retreat Mining
NPO-16189 B85-10242 07
Compact Hydraulic Excavator and Support Unit
NPO-16190 B85-10243 07
Curtain Wall Creates Ventilation Channel
NPO-16194 B85-10244 07
- LEWIS, J. L.**
Experiments With a Manipulator Sensor System
NPO-16084 B85-10262 07
- LIANG, R. H.**
Nonyellowing Polycarbonate for Outdoor Use
NPO-15836 B85-10070 04
- LIANGE, R. H.**
Laser Photoacoustic Technique Detects Photo-Oxidation
NPO-16108 B85-10324 03
- LIN, C.**
Flexible Airframe Response Program
MSC-20762 B85-10425 09
- LINDFORS, R. J.**
Low-Temperature Seal for Actuator Rod
MSC-20744 B85-10229 06
- LINDSEY, C. P.**
Improved Waveguide Laser Array
NPO-16500 B85-10435 01
- LINLOR, W. I.**
Telescope With Reflecting Baffle
ARC-11502 B85-10043 03
- LITVIN, F. L.**
Synthesis and Optimization of Spiral Bevel Gears
LEW-13920 B85-10389 07
- LIU, C. H.**
Smoothed Two-Dimensional Edges for Laminar Flow
LAR-13255 B85-10514 06
- LIU, K. Y.**
Fast Reed-Solomon Decoder
NPO-15867 B85-10303 02
Modular VLSI Reed-Solomon Decoder
NPO-15837 B85-10306 02
Modular, Fast, Two-Dimensional Cyclic Convolver
NPO-16379 B85-10448 02
- LOCKWOOD, R. A.**
High-Temperature Hall-Effect Apparatus
NPO-16279 B85-10038 02
- LONBORG, J. O.**
Tiltmeter Indicates Sense of Slope
NPO-16153 B85-10005 01
Preventing Electrostatic-Discharge Damage to Electronics
NPO-15953 B85-10296 01
- LONG, K.**
Power-Factor Controllers: How Safe?
MFS-27016 B85-10024 01
- LORENZO, C. F.**
Four-Cylinder Stirling Engine Control Simulation
LEW-14106 B85-10536 06
- LOVELESS, R. L.**
Incrementally Variable High-Voltage Supply
MFS-28018 B85-10145 01
- LUCAS, C.**
Protective Package for a Gamma-Ray Detector
NPO-16019 B85-10041 03
- LUCY, M. H.**
Miniature Rocket Motor for Aircraft Stall/Spin Recovery
LAR-13199 B85-10253 07
- LUDWICK, L. M.**
Ultra-High-Molecular-Weight Silphenylene/Siloxane Polymers
MFS-27065 B85-10499 04
- LUKE, K. L.**
Measuring Recombination Velocities in Solar Cells
NPO-16243 B85-10001 01
- LUMSDEN III, J. B.**
Reducing Stress-Corrosion Cracking in Bearing Alloys
MFS-19948 B85-10331 04
- LUPO, G.**
Compact Hybrid Automotive Propulsion System
NPO-16117 B85-10386 07
- LUPTON, M. W.**
Micronized-Coal Burner Facility
LEW-14131 B85-10492 04
- LUTWACK, R.**
Fluidized-Bed Particles Scavenge Silicon Fines
NPO-16034 B85-10202 04
Process for Nonequilibrium Ternary Alloys
NPO-16226 B85-10345 04

M

- MACMEDAN, M. L.**
Standard Codes for Telemetry and Telecommand
NPO-16305 B85-10287 09
- MALEKI, L.**
Intense Source of Polarized Hydrogen Atoms
NPO-16434 B85-10466 03
- MALL, G. H.**
Liquid-Level Monitor for Pressurized Vessels
LAR-13208 B85-10366 06
Liquid-Level Sensor for Containers in Motion
LAR-13327 B85-10472 03
- MALONE, C. J.**
Single-Event-Upset Studies: A Compilation
NPO-16362 B85-10297 01
Testing Electronic Devices for Single-Event Upset
NPO-16468 B85-10454 02
- MANDY, C.**
'Speaking' Microcomputer
MFS-25976 B85-10307 02

- MANGALAM, S. M.**
Retractable End Plates for Aircraft
Lifting Surfaces
LAR-12946 B85-10216 06
- MANGES, D. R.**
Rotating Connection for Electrical
Cables
GSC-12899 B85-10384 07
- MANHARDT, P. D.**
Three-Dimensional, Subsonic,
Turbulent Junction Region Flow
LAR-13263 B85-10540 06
- MANNING, J. C.**
Miniature Microphone Adapter
LAR-13210 B85-10521 06
- MAPLES, A. L.**
Calculation of Macroseggregation in an
Ingot
MFS-27068 B85-10481 03
- MAREK, C. J.**
Predicting Two-Dimensional,
Unsteady Turbulent Combustion
LEW-14027 B85-10376 06
- MARGAIT, S.**
Damping Relaxation Oscillations in
Laser Diodes
NPO-15980 B85-10010 01
- MARGALIT, S.**
Improved Waveguide Laser Array
NPO-16500 B85-10435 01
- MARTIN, B. G.**
Characterizing Semiconductor Alloys
for Infrared Sensors
MFS-27059 B85-10355 04
- MARTIN, G. L.**
Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06
- MARTIN, R. M.**
Reduction of Vane Noise in
Wind-Tunnel Nozzles
LAR-13333 B85-10527 06
- MARTIN, T. Z.**
Camera for Monitoring Vegetation
NPO-16349 B85-10358 05
- MARTONCHIK, J. V.**
Calculating Atmospheric Effects in
Satellite Imagery
NPO-16373 B85-10327 03
- MATTISON, E.**
Satellite Time- and
Frequency-Transfer System
MFS-25991 B85-10169 02
- MATZA, E. C.**
Blind-Side, High-Temperature
Fastener Lock
LAR-13037 B85-10248 07
- MAUDGAL, S.**
Solvent-Resistant, Thermally Stable
Poly(Carbonate-Imides)
LAR-13292 B85-10485 04
- MAYES, W. H.**
Noise-Path Measurements in Aircraft
Structures
LAR-13017 B85-10529 06
- MCBRIDE, B. J.**
Prediction of Combustion Gas
Deposit Compositions
LEW-14091 B85-10280 09
- MCBRIDE, R.**
Vision Screening by Color
Photography
MFS-25800 B85-10085 05
- MCCARROLL, J. E.**
Dent-Removing Tool
MFS-29044 B85-10554 08
- MCCONAUGY, K.**
Online Tester for a Symbol
Generator
MSC-20357 B85-10161 02
- MCCORMICK, J. R.**
Efficient Process for Making
Polycrystalline Silicon
NPO-16121 B85-10073 04
- MCDERMID, I. S.**
Magnetically-Switched, Long-Pulse
XeCl Laser
NPO-16410 B85-10430 01
- MCGARY, M. C.**
Noise-Path Measurements in Aircraft
Structures
LAR-13017 B85-10529 06
- MCGEHEE, R. K.**
Hybrid and Electric Advanced Vehicle
Systems Simulation
LEW-13927 B85-10263 07
- MCGREGOR, J. W.**
Experimental Parallel-Processing
Computer
NPO-16043 B85-10302 02
- MCHUGH, J. P.**
Adjustable Lid Aids Silicon-Ribbon
Growth
NPO-16354 B85-10275 08
- MCINTOSH, W. R.**
Flowmeter for Clear Fluids
MFS-28031 B85-10372 06
- MCKOWN, R.**
Cutthrough Warning Circuit
MFS-19900 B85-10119 07
- MCLYMAN, C. W.**
Flux Coupling for Wheelchair Battery
Chargers
NPO-16269 B85-10007 01
- MCLYMAN, C. W. T.**
Recovering Energy From Relays
NPO-16268 B85-10012 01
- MCKOWN, R.**
Resistive Fine Tuning of Resonant
Circuit
NPO-16276 B85-10013 01
- MCKOWN, R.**
Efficiency
NPO-16326 B85-10140 01
- MCKOWN, R.**
Rotary Power Transformer and
Inverter Circuit
NPO-16270 B85-10156 01
- MCKOWN, R.**
Removing Heat From Toroidal
Inductors
NPO-16386 B85-10293 01
- MCKOWN, R.**
Multiple-Winding Output Inductors for
Power Converters
NPO-16176 B85-10434 01
- MCMURTREY, E.**
Further Tests of 38 Ball-Bearing
Greases
MFS-27043 B85-10084 04
- MCNEIL, J. A.**
Programmable Driver for
Voltage-Controlled Oscillators
NPO-16364 B85-10162 02
- MCPHERSON, J. P.**
Airborne Cloud Detector
LAR-13137 B85-10167 02
- MCWITHEY, R. R.**
Fastening Parts Having Mismatched
Thermal Coefficients
LAR-13009 B85-10113 07
- MEACHAM, W. L.**
Analyses of Multishaft Rotor-Bearing
Response
LEW-13925 B85-10232 06
- MEHRA, M.**
Magnetron-Sputtered Amorphous
Metallic Coatings
NPO-16221 B85-10204 04
- MEITNER, P. L.**
Off-Design Performance of
Radial-Inflow Turbines
LEW-14060 B85-10402 07
- MENG, S. Y.**
Calculating Flow-Angle Deviation in
Rotary Pumps
MFS-29062 B85-10548 07
- MENZIES, R. T.**
Tracking System for Infrared
Spectrometer
NPO-16440 B85-10464 03
- MENZIES, R. T.**
Accuracy of Lidar Measurements of
the Atmosphere
NPO-16493 B85-10476 03
- MERKEY, P.**
Optimum Cyclic Redundancy Codes
for Noisy Channels
NPO-16406 B85-10561 09
- MESCHTER, P.**
Preparation and Characterization of
HgxCd1-xTe
MFS-27037 B85-10081 04
- METZGER, A.**
Protective Package for a Gamma-Ray
Detector
NPO-16019 B85-10041 03
- METZLER, E. C.**
Static-Suppressing Optical Paint
NPO-15992 B85-10077 04
- MEYER, G.**
Redundant Asynchronous
Microprocessor System
ARC-11348 B85-10031 02
- MIKE, R. A.**
Resin Powder Slurry Process for
Composite Fabrication
LAR-13106 B85-10335 04
- MIKROYANNIDIS, J. A.**
Increasing Fire Safety of Epoxies
ARC-11506 B85-10062 04
- MIKULAS JR., M. M.**
Deployable M-Braced Truss
LAR-13081 B85-10100 06
- MILNER, J. F.**
Sequentially-Deployable Tetrahedral
Beam
LAR-13098 B85-10222 06
- MILES, A.**
Solar-Assisted Oxidation of Toxic
Cyanide
LAR-13171 B85-10075 04
- MILES, J. R. F.**
Comparison of Decision Models
NPO-16446 B85-10563 09
- MILLER, I. M.**
Accurate Airborne Particle Sampler
LAR-13080 B85-10219 06
- MILLS, M. W.**
Estimating the Performance of a
Concentrating Solar Array
MFS-28021 B85-10185 03
- MILLS, M. W.**
Tests of Low-Concentration-Ratio
Photovoltaic Elements
MFS-28020 B85-10189 03
- MILNER, J. F.**
Portable Temperature Set-Point
Controller
MSC-20056 B85-10142 01
- MISRA, M. S.**
Ion Implantation Improves
Bearing-Surface Properties
MFS-25995 B85-10197 04

MITTRA, R.

MITTRA, R.
Cassegrain-Antenna Gain
Improvement
NPO-15775 B85-10433 01

MODLIN, J. T.
End Restraints for
Impact-Energy-Absorbing Tube
Specimens
LAR-13179 B85-10218 06

MOORE, D. M.
Protective Package for a Gamma-Ray
Detector
NPO-16019 B85-10041 03

MOORE, R. K.
Soil/Structure Interactions in
Earthquakes
MFS-27078 B85-10479 03

MORENO, V.
Predicting the Cyclic Response of
High-Temperature Materials
LEW-14032 B85-10344 04

MORGAN JR., H. L.
Airfoil Smoothing and Scaling
Programs
LAR-13132 B85-10377 06

MORRIS, B.
Preparation and Characterization of
HgxCd1-xTe
MFS-27037 B85-10081 04

MORRIS, D. E.
Alkane-Based Urethane Potting
Compounds
MFS-27047 B85-10494 04

MORRIS, R. V.
Requirements Analysis for
Information-Intensive Systems
NPO-15944 B85-10415 09

MORRISON, A.
High-Purity Silicon Seeds for Silane
Pyrolysis
NPO-16287 B85-10060 04

MORRISON, A. D.
Filament Guides for Silicon-Ribbon
Growth
Extracting Silicon Product From
Fluidized-Bed Reactors
NPO-16385 B85-10341 04

MORRISON, G. B.
Tracking System for Infrared
Spectrometer
NPO-16440 B85-10464 03

MORRISON, G. L.
Predicting Leakage in Labyrinth
Seals
MFS-27051 B85-10261 07

MORRISON, J. D.
Tests of Zinc Rich Anticorrosion
Coatings
KSC-11309 B85-10354 04

MORRISSEY, E. T.
Detecting Cracks in Rough Metal
Surfaces
MSC-20734 B85-10230 06

MUELLER, R. L.
Altering Flashlamp Output for
Realistic Solar Simulation
NPO-16167 B85-10054 03

MUKAI, S.
Improved Waveguide Laser Array
NPO-16500 B85-10435 01

MURTHY, S. B.
Axial-Flow Compressor Performance
With Water Ingestion
LEW-14026 B85-10532 06

MYERS, W. N.
Shaft Seal Compensates for Cold
Flow
MFS-25678 B85-10254 07

N

NAIDU, S. V. N.
X-Ray Diffraction Analysis Program
LAR-13276 B85-10483 03

NAKANO, H. N.
Waterproofing Agents for Silica Tiles
MSC-20364 B85-10080 04

NELSON, H. D.
Analyses of Multishaft Rotor-Bearing
Response
LEW-13925 B85-10232 06

NESMITH, M. F.
Wide-Grasp Latching Mechanism
MFS-28002 B85-10118 07

NEUHART, D. H.
Manipulation and Display of
Panel-Method Geometry
LAR-13224 B85-10282 09

NICHOLS, D. K.
Latchup in CMOS Integrated Circuits
NPO-16304 B85-10170 02

Single-Event-Upset Studies: A
Compilation
NPO-16362 B85-10297 01

Testing Electronic Devices for
Single-Event Upset
NPO-16468 B85-10454 02

NICHOLS, G. H.
Aircraft Canopy Lock
FRC-11065 B85-10088 06

NICOLAIDES, R. A.
Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06

NIR, Z.
Rubberized, Brominated Epoxies
ARC-11427 B85-10079 04

NIXON, J. H.
Storing Data and Video on One
Tape
MSC-20705 B85-10027 02

NJOKU, E. G.
Measuring Clouds With Microwaves
and Infrared
NPO-16265 B85-10045 03

NOLA, F. J.
Control Electronics for
Solar/Flywheel Power Supply
MFS-25978 B85-10443 01

NORRIS, D. D.
Laser-Assisted Analysis of Aerosol
Particles
NPO-15308 B85-10056 03

NUNES JR., A. C.
Microfissuring in
Electron-Beam-Welded Nickel Alloy
MFS-27041 B85-10198 04

NYGAARD, S. I.
Statistical Energy Analysis Program
MFS-27035 B85-10231 06

O

OBARA, C. J.
Smoothed Two-Dimensional Edges
for Laminar Flow
LAR-13255 B85-10514 06

PERSONAL AUTHOR INDEX

OBERHEUSER, J.
Lens-and-Detector Array for
Spectrometer
NPO-16388 B85-10184 03

OEPOMO, T. S.
Program Predicts Nonlinear Inverter
Performance
MSC-20769 B85-10172 02

OHLSON, J. E.
Recovering Microwave
Cross-Polarization Losses
NPO-15353 B85-10168 02

OLIVER, R.
Protective Package for a Gamma-Ray
Detector
NPO-16019 B85-10041 03

ONDRASKI, V. J.
Doubly-Differenced Measurements
for Orbit Determinations
NPO-16111 B85-10040 02

ONEILL, P. E.
Measuring Soil Hydraulic Conductivity
With Microwaves
GSC-12937 B85-10176 03

ONEILL, R. F.
Solution of Radiation and Convection
Heat-Transfer Problems
LEW-13978 B85-10537 06

OPPENHEIM, A. K.
Predicting Two-Dimensional,
Unsteady Turbulent Combustion
LEW-14027 B85-10376 06

ORRIS, G. M.
Constant-Pressure Sawing
NPO-15233 B85-10383 07

ORZECOWSKI, J. A.
Three-Dimensional, Subsonic,
Turbulent Junction Region Flow
LAR-13263 B85-10540 06

OSTERAAS, J. D.
Predicting the Fatigue life of
Structures
MFS-27049 B85-10206 04

OTOSHI, T. Y.
Measuring Antenna Signal Delays
NPO-15947 B85-10455 02

OTT, F. M.
Determining Internal Connections in
Capacitors
NPO-16499 B85-10445 01

OUTLAW, R.
Manipulator for Heating and Cooling
in Ultrahigh Vacuum
LAR-13040 B85-10051 03

Ultrahigh-Vacuum Sample-Transfer
System
LAR-12993 B85-10057 03

OUTLAW, R. A.
High-Quality, Thin-Film Germanium
Single Crystals
LAR-13211 B85-10406 08

OUYANG, F.
Agglomeration-Free Distributor for
Fluidized Beds
NPO-16466 B85-10544 07

OVES, R. E.
Foam Insulation for Cryogenic
Flowlines
MSC-20552 B85-10066 04

OWEN, R. B.
Laser Schlieren Crystal-Growth
Imager
MFS-28060 B85-10326 03

OYOUNG, S. P. P.
Optimizing Load Spectra for Gears
MSC-20487 B85-10260 07

P

- PACALA, T. J.**
Pulse Coupling for Laser Excitation
NPO-16403 B85-10428 01
Generating Independent Preionizing
Pulses for Lasers
NPO-16402 B85-10429 01
Magnetically-Switched, Long-Pulse
XeCl Laser
NPO-16410 B85-10430 01
- PAGE, N. A.**
Reflecting Slit for Imaging
Spectrometer
NPO-16408 B85-10322 03
- PANDEY, P. C.**
Measuring Clouds With Microwaves
and Infrared
NPO-16265 B85-10045 03
- PARIKH, P. G.**
Improved Exhaust Diffuser for
Jet-Engine Testing
NPO-16328 B85-10255 07
- PARK, J. J.**
Silicone Coating on Polyimide Sheet
GSC-12913 B85-10068 04
- PARKER, D. E.**
Preadapting to Weightlessness
MSC-20847 B85-10506 05
- PARKER, J.**
Thermosetting Phthalocyanine
Polymers
ARC-11511 B85-10061 04
Synthesizing Metal Phthalocyanine
Imide Polymers
ARC-11413 B85-10074 04
Rubberized, Brominated Epoxies
ARC-11427 B85-10079 04
- PARKER, J. A.**
Imide Cyclotriphosphazene/Hexa-
fluoroisopropylidene Polymers
ARC-11428 B85-10333 04
Synthesis of Metal Phthalocyanine
Sheet Polymers
ARC-11405 B85-10343 04
Phthalocyanine Tetraamine
Epoxy-Curing Agents
ARC-11424 B85-10348 04
- PARKER, J. B.**
High-Temperature Hall-Effect
Apparatus
NPO-16279 B85-10038 02
- PARKER, R. J.**
Bearing Thermal Performance
Prediction
LEW-14163 B85-10539 06
- PARKS, R. E.**
Reflecting Slit for Imaging
Spectrometer
NPO-16408 B85-10322 03
- PATEL, D. K.**
Thermal, One-Dimensional Analyzer
Program
MSC-20703 B85-10378 06
- PATOCKA, C. G.**
Smoothly Adjustable dc Load
MSC-20853 B85-10289 01
- PATON, N. E.**
Reducing Stress-Corrosion Cracking
in Bearing Alloys
MFS-19948 B85-10331 04
- PATON, W. J.**
Tests of Zinc Rich Anticorrosion
Coatings
KSC-11309 B85-10354 04
- PATRICK, M.**
Manipulation of Numbers With Many
Digits
MFS-28048 B85-10567 09
- PATTERSON JR., J. C.**
Wingtip Vortex-Augmented
Turbopusher Propeller Thrust
LAR-13019 B85-10095 06
- PATTERSON, W. J.**
Ultra-High-Molecular-Weight Silphen-
ylene/Siloxane Polymers
MFS-27065 B85-10499 04
- PECKHAM, G. E.**
Microwave Atmospheric-Pressure
Sensor
NPO-16496 B85-10478 03
- PENFIELD, H.**
Satellite Time- and
Frequency-Transfer System
MFS-25991 B85-10169 02
- PENG, S. T. J.**
Constitutive Equations of Aging in
Polymers
NPO-16480 B85-10503 04
- PENN, B. G.**
Determining Fiber Orientation in
Graphite-Reinforced Composites
MFS-28032 B85-10205 04
Adhesive-Bonded Fixture for Flexure
Testing
MFS-28051 B85-10360 06
Drilling Holes in Graphite/Epoxy
Composites
MFS-28044 B85-10398 07
Measuring Resistivities of Small
Fibers
MFS-28077 B85-10484 04
- PETERSEN, P. L.**
Computer-Aided Reliability
Estimation
LAR-13349 B85-10315 02
- PETERSON, V. L.**
Numerical Aerodynamic Simulation
Facility
ARC-11497 B85-10562 09
- PETRICK, W.**
Protective Package for a Gamma-Ray
Detector
NPO-16019 B85-10041 03
- PHILPOT, D.**
Forbidden Zones for
Numerically-Controlled Machine Tools
MFS-19950 B85-10397 07
- PICKETT, H. M.**
Dual-Mode Horn Antenna for
Millimeter Wavelengths
NPO-16297 B85-10006 01
Generating Tunable Far-Infrared
Laser Sidebands
NPO-16497 B85-10450 02
- PIKE, R. A.**
Water-Soluble Thermoplastic
Polyimides
LAR-13105 B85-10336 04
- PINA, C. A.**
Designing Test Chips for Custom
Integrated Circuits
NPO-15988 B85-10032 02
- PIRICH, R. G.**
Damping Melt Convection With A
Magnetic Field
MFS-28040 B85-10339 04
- PITONIAK, F. J.**
Insulation Blankets for
High-Temperature Use
ARC-11453 B85-10489 04
- PLAHUTNIK JR., F.**
Efficient Process for Making
Polycrystalline Silicon
NPO-16121 B85-10073 04
- PLUEDDEMANN, E. F.**
Bonding Solar-Cell Modules
NPO-16399 B85-10211 04
- POIRIER, D. R.**
Calculation of Macroseggregation in an
Ingot
MFS-27068 B85-10481 03
- POIT, W. J.**
Studying Crystal Growth With the
Peltier Effect
MFS-28041 B85-10346 04
- POND, C. L.**
Simplified Worst-Case Analysis of
Complex Systems
MSC-20232 B85-10135 09
- POSNER, E. C.**
Optimum Cyclic Redundancy Codes
for Noisy Channels
NPO-16406 B85-10561 09
- POSTAL, R. B.**
Microwave Power Combiner With
Switching Diodes
NPO-15775 B85-10432 01
- POTTER, D. W.**
Incrementally Variable High-Voltage
Supply
MFS-28018 B85-10145 01
- POTTER, P. D.**
Improved Thick Dichroic Reflector for
Microwave Feeds
NPO-13506 B85-10004 01
- PRAGEMAU, G. L.**
Low-Loss Fuel and Oxidizer Injector
MFS-25989 B85-10104 07
- PRATT, J. R.**
Solvent-Resistant, Thermally Stable
Poly(Carbonate-Imides)
LAR-13292 B85-10485 04
- PRELIASCO, R. J.**
Bistable Articulated Joint
NPO-16038 B85-10393 07
- PRICE, W. E.**
Single-Event-Upset Studies: A
Compilation
NPO-16362 B85-10297 01
Testing Electronic Devices for
Single-Event Upset
NPO-16468 B85-10454 02
- PRIMUS, H. C.**
Force Sensor for Large Robot Arms
NPO-16097 B85-10226 06
Touch Sensor for Robots
NPO-16230 B85-10295 01
- PRINTZ, A.**
Dynamic Effects of Internal
Spur-Gear Drives
LEW-14167 B85-10553 07
- PSALTIS, D.**
Point Simulator for Synthetic-Aperture
Radar
NPO-16296 B85-10165 02
- PURVES, L.**
Automatically-Programed Machine
Tools
GSC-12758 B85-10264 07
- PUSTER, R. L.**
Fast-Response Oxygen-Monitoring
and Control System
LAR-13257 B85-10487 04
- PUTNEY, B.**
Solving Large Systems of Normal
Equations
GSC-12858 B85-10421 09

RABINOWITZ, R.

R

- RABINOWITZ, R.**
Development of a Prosthesis for Urinary Control
MFS-27062 B85-10359 05
- RAGEN, M. A.**
Multistage Planetary Power Transmissions
LEW-14100 B85-10399 07
- RAHMAN, P.**
Synthesis and Optimization of Spiral Bevel Gears
LEW-13920 B85-10389 07
- RAHMAT-SAMII, Y.**
Estimating Antenna Shape From Far-Field Measurements
NPO-16425 B85-10181 03
- Analysis of Satellite Communications Antenna Patterns
NPO-16400 B85-10283 09
- RAMER, O. G.**
Polarizing Filter for Integrated Optics
NPO-16429 B85-10288 01
- RAMEY, G. W.**
Soil/Structure Interactions in Earthquakes
MFS-27078 B85-10479 03
- RAMOHALLI, K. N. R.**
Windowless High-Pressure Solar Reactor
NPO-16310 B85-10174 03
- READ, W. S.**
Preventing Electrostatic-Discharge Damage to Electronics
NPO-15953 B85-10296 01
- REED, I. S.**
Single-Chip VLSI Reed-Solomon Encoder
NPO-16122 B85-10452 02
- REEVES, R. D.**
Testing Machine for Biaxial Loading
MSC-20477 B85-10220 06
- REINHARDT, V. S.**
Superconducting-Cavity Accelerometer
GSC-12797 B85-10096 06
- REITER, L. J.**
Cost and Performance Model for Photovoltaic Systems
NPO-16404 B85-10314 02
- RENNELS, D. A.**
Interface Circuits for Self-Checking Microprocessors
NPO-15700 B85-10309 02
- RESCHKE, M. F.**
Preadapting to Weightlessness
MSC-20847 B85-10506 05
- REYES, A. R.**
Distributing Radiant Heat in Insulation Tests
MSC-20878 B85-10513 06
- REZEK, T. W.**
Remotely Piloted Aircraft for Research
ARC-11498 B85-10120 07
- RHODE, D. L.**
Predicting Leakage in Labyrinth Seals
MFS-27051 B85-10261 07
- RHODES, M. D.**
Deployable M-Braced Truss
LAR-13081 B85-10100 06

- RICCIO, J. H.**
Tracking System for Infrared Spectrometer
NPO-16440 B85-10464 03
- RICE, J. T.**
Conductive Container for Semiconductor Devices
NPO-16110 B85-10439 01
- RICE, R. F.**
Low-Cost Teleconference System
NPO-16057 B85-10029 02
- Coding for Electronic Mail
NPO-16350 B85-10411 09
- Coding for Efficient Image Transmission
NPO-16444 B85-10416 09
- Universal Noiseless Coding Subroutines
NPO-15451 B85-10426 09
- RICHARD, H. L.**
Multiband Selector for Linear Photodetector Array
GSC-12911 B85-10187 03
- RICHARDSON, J. R.**
Vision Screening by Color Photography
MFS-25800 B85-10085 05
- RICHARDSON, T. E.**
Finding Bright-Spot Coordinates in Television Images
MFS-25999 B85-10034 02
- RICHTER, R.**
Thermally-Rechargeable Electrochemical Cell
NPO-16273 B85-10048 03
- RIETDYK, J.**
Replaceable Transfer Tube for High-Pressure Cavities
MFS-19775 B85-10395 07
- ROBINSON, J. N.**
Predicting the Fatigue life of Structures
MFS-27049 B85-10206 04
- RODGERS, J. M.**
Reflecting Slit for Imaging Spectrometer
NPO-16408 B85-10322 03
- RODRIGUEZ, G.**
Maximum-Likelihood Parameter-Estimation Algorithm
NPO-16320 B85-10560 09
- ROGERS, D. W.**
Development of a Prosthesis for Urinary Control
MFS-27062 B85-10359 05
- ROGERS, J. R.**
Designing Eccentric Aperture Optical Systems
NPO-16355 B85-10329 03
- ROHATGI, N.**
Fluidized-Bed Particles Scavenge Silicon Fines
NPO-16034 B85-10202 04
- ROHATGI, N. K.**
High-Purity Silicon Seeds for Silane Pyrolysis
NPO-16287 B85-10060 04
- Extracting Silicon Product From Fluidized-Bed Reactors
NPO-16385 B85-10341 04
- Producing Silicon Carbide for Semiconductor Devices
NPO-16391 B85-10342 04
- ROSSER, R. W.**
High-Performance Filleting and Channel Sealants
ARC-11408 B85-10064 04

PERSONAL AUTHOR INDEX

- Epoxy/Fluoroether Composites
ARC-11418 B85-10332 04
- ROSSI, P. J.**
Electrically Connecting to Pressure Vessels
MSC-20709 B85-10154 01
- ROSSOW, V. J.**
Improved Numerical Evaluation Method for Elliptic Integrals
ARC-11467 B85-10412 09
- ROWE, A.**
Tests of Zinc Rich Anticorrosion Coatings
KSC-11309 B85-10354 04
- ROWE, A. P.**
Protective Coatings for Metals
KSC-11308 B85-10352 04
- ROWLETTE, J.**
Recharging Batteries Chemically
NPO-16024 B85-10143 01
- RUDMAN, A. A.**
Optical Mounts for Cryogenic Beam Splitters
GSC-12923 B85-10180 03
- RUGGIERI, D. J.**
Protective Coatings for Metals
KSC-11308 B85-10352 04
- RUITBERG, A. P.**
High-Voltage Isolation Transformer
GSC-12817 B85-10018 01
- RUOFF, C. F.**
Rolling-Contact Rheostat
NPO-15567 B85-10144 01
- Low-Friction Joint for Robot Fingers
NPO-15914 B85-10247 07
- ## S
- SAH, C. T.**
Floating-Emitter Solar-Cell Transistor
NPO-16467 B85-10441 01
- SALAMA, M. A.**
Experimental Parallel-Processing Computer
NPO-16043 B85-10302 02
- SALISBURY, D. P.**
High-Performance Filleting and Channel Sealants
ARC-11408 B85-10064 04
- SAROHIA, V. S.**
Improved Exhaust Diffuser for Jet-Engine Testing
NPO-16328 B85-10255 07
- SASNOWITZ, H.**
Encoding Scheme Reduces Hardware Requirements
MSC-20044 B85-10138 09
- SAWKO, P. M.**
Insulation Blankets for High-Temperature Use
ARC-11453 B85-10489 04
- SAWYER, D. H.**
Efficient Process for Making Polycrystalline Silicon
NPO-16121 B85-10073 04
- SCHEINMAN, V. D.**
Force Sensor for Large Robot Arms
NPO-16097 B85-10226 06
- SCHEUER, E. M.**
Comparison of Decision Models
NPO-16446 B85-10563 09
- SCHINDLER, R. A.**
Fourier-Transform Infrared Spectrometer
NPO-16431 B85-10317 03

- SCHLUTSMAYER, A. P.**
Low-Cost Teleconference System
NPO-16057 B85-10029 02
Universal Noiseless Coding
Subroutines
NPO-15451 B85-10426 09
- SCHNEIDER, R. T.**
Economical Fabrication of Large
Parabolic Mirrors
LAR-13139 B85-10405 08
- SCHOREDER, C. J.**
Noncontacting Measurement With a
Thermocouple
MSC-20834 B85-10374 06
- SCHROEDER, J. E.**
Ceramic Coatings for Engine Parts
NPO-16228 B85-10063 04
Shielding Against Intense Laser
Beams
NPO-16166 B85-10067 04
Lightweight Electrical Insulation
NPO-16165 B85-10193 04
- SCHUTT, J. B.**
Diffusely Reflecting Paints Containing
TFE
GSC-12883 B85-10194 04
- SCOTT, B. C.**
Controlling Transistor Temperature
During Burn-In
MFS-28076 B85-10437 01
- SEAMAN, C. H.**
Altering Flashlamp Output for
Realistic Solar Simulation
NPO-16167 B85-10054 03
- SEBENICK, R. H.**
Duplicating Curved Tile Surfaces for
Pull Testing
MSC-20795 B85-10274 08
- SEIDEL, B. L.**
Recovering Microwave
Cross-Polarization Losses
NPO-15353 B85-10168 02
- SEYFARTH, B. R.**
Processing Digital Imagery Data
MFS-25987 B85-10285 09
- SEYMOUR, H. R.**
Electro-optical System Measures
Aircraft Deflections
ARC-11454 B85-10305 02
- SHAI, M. C.**
Diffusely Reflecting Paints Containing
TFE
GSC-12883 B85-10194 04
- SHALABY, H. M.**
Accelerating Corrosion in Solar-Cell
Tests
NPO-16096 B85-10446 01
- SHAO, H. M.**
Systolic VLSI Reed-Solomon
Decoder
NPO-16383 B85-10304 02
Multiplier Architecture for Coding
Circuits
NPO-16363 B85-10456 02
- SHAUBACH, R.**
Titanium Heat-Pipe Wicks
MFS-26016 B85-10524 06
- SHAUBACK, R.**
Rotary Joint for Heat Transfer
MFS-26015 B85-10546 07
- SHAW, R. C.**
Friction-Testing Machine
MSC-20622 B85-10370 06
- SHERMAN, A.**
Long-Life Cryogenic Cooler
GSC-12697 B85-10116 07
- SHEYNIN, L.**
Multistage Planetary Power
Transmissions
LEW-14100 B85-10399 07
- SHIMADA, K.**
Photovoltaics in Japan
NPO-16330 B85-10025 01
- SHIVA, S. G.**
Design Language for Digital
Systems
MFS-25352 B85-10281 09
- SHLICHTA, P. J.**
Beta Silicon Nitride Whiskers
NPO-16409 B85-10501 04
- SHULTZ JR., B.**
Hinged-Blade, Vertical-Shaft
Windmill
MFS-25980 B85-10112 07
- SHUMKA, A.**
Discoloration of Polyvinyl Butyral
NPO-16411 B85-10353 04
Measuring Metal Thickness With an
Electric Probe
NPO-16340 B85-10367 06
- SIEGEL, C. M.**
Lowering Ammeter Input Impedance
NPO-16067 B85-10022 01
- SILBERSTEIN, R. P.**
Studying Crystal Growth With the
Peltier Effect
MFS-28041 B85-10346 04
- SIMMONS, N. E.**
Pulse-Width-to-Analog-Voltage Con-
verter
MSC-20006 B85-10157 01
- SIMMS, W. T.**
Remotely-Adjustable Solid-State
High-Voltage Supply
NPO-15719 B85-10151 01
- SIMONS, D.**
Image Interpolation With Dedicated
Digital Hardware
GSC-12882 B85-10312 02
- SIMPSON, J. W.**
Miniature Microphone Adapter
LAR-13210 B85-10521 06
- SINGH, J. J.**
Liquid-Level Monitor for Pressurized
Vessels
LAR-13208 B85-10366 06
Technique for Measuring Gas
Conversion Factors
LAR-13220 B85-10470 03
Liquid-Level Sensor for Containers in
Motion
LAR-13327 B85-10472 03
Chromium Ions Improve Moisture
Resistance of Epoxy Resins
LAR-13226 B85-10486 04
Fast-Response Oxygen-Monitoring
and Control System
LAR-13257 B85-10487 04
- SINHA, M. P.**
Laser-Assisted Analysis of Aerosol
Particles
NPO-15308 B85-10056 03
Mass Spectrometer for Airborne
Micro-Organisms
NPO-16359 B85-10505 05
- SINICA, A.**
Agglomeration-Free Distributor for
Fluidized Beds
NPO-16466 B85-10544 07
- SIPES JR., D. L.**
Hybrid Laser Would Combine Power
With Efficiency
NPO-16173 B85-10473 03
- SIRE, R. A.**
Predicting the Fatigue life of
Structures
MFS-27049 B85-10206 04
- SKOUMAL, D. E.**
Bonded and Bolted
Graphite/Polyimide Composite Joints
LAR-13090 B85-10130 08
- SLUSSER, K.**
High-Visibility Data Display
MFS-19925 B85-10026 02
- SMITH JR., J. E.**
Reversing Glass Wettability
MFS-26006 B85-10071 04
- SMITH, J. H.**
Cost and Performance Model for
Photovoltaic Systems
NPO-16404 B85-10314 02
Comparison of Decision Models
NPO-16446 B85-10563 09
- SMITH, L. S.**
Single-Event-Upset Studies: A
Compilation
NPO-16362 B85-10297 01
- SMITH, M.**
Insulation Blankets for
High-Temperature Use
ARC-11453 B85-10489 04
- SMITH, P. J.**
Estimates of Latent Heat in Clouds
MFS-25977 B85-10055 03
- SMITH, R. E.**
High-Temperature, High-Pressure
Optical Cells
MFS-26000 B85-10267 08
- SMITH, R. M.**
Personal-Computer Video-Terminal
Emulator
KSC-11293 B85-10286 09
- SNYDER, W. V.**
Text Exchange System
NPO-16357 B85-10419 09
- SO, K. T.**
TRASYS for Beginners
MSC-20855 B85-10427 09
- SOLIMAN, K. A.**
Latchup in CMOS Integrated Circuits
NPO-16304 B85-10170 02
- SOMOANO, R. B.**
Improved Electrodes for Lithium
Cells
NPO-16397 B85-10201 04
- SONJU, T. R.**
Foam Insulation for Cryogenic
Flowlines
MSC-20552 B85-10066 04
- SORENSEN, D.**
Replaceable Transfer Tube for
High-Pressure Cavities
MFS-19775 B85-10395 07
- SOSACK, G. S.**
Pulse-Width-to-Analog-Voltage Con-
verter
MSC-20006 B85-10157 01
- SPISZ, E.**
High-Speed Computer-Controlled
Switch-Matrix System
LEW-14050 B85-10028 02
- SPRINKLE, D. R.**
Technique for Measuring Gas
Conversion Factors
LAR-13220 B85-10470 03
Chromium Ions Improve Moisture
Resistance of Epoxy Resins
LAR-13226 B85-10486 04

SRIVASTAVA, S. K.

- SRIVASTAVA, S. K.**
 Detecting Trace Contaminants in the Atmosphere
 NPO-16225 B85-10468 03
- ST. CLAIR, A. K.**
 Chromium Ions Improve Moisture Resistance of Epoxy Resins
 LAR-13226 B85-10486 04
 Colorless, Transparent, Aromatic Polyimide Films
 LAR-13351 B85-10490 04
 Cobalt Ions Improve the Strength of Epoxy Resins
 LAR-13230 B85-10493 04
- ST. CLAIR, T. L.**
 Solvent-Resistant, Thermally Stable Poly(Carbonate-Imides)
 LAR-13292 B85-10485 04
 Chromium Ions Improve Moisture Resistance of Epoxy Resins
 LAR-13226 B85-10486 04
 Colorless, Transparent, Aromatic Polyimide Films
 LAR-13351 B85-10490 04
 Ultrasonic Mixing of Epoxy Curing Agents
 LAR-13307 B85-10498 04
- STALLINGS, J. M.**
 Soil/Structure Interactions in Earthquakes
 MFS-27078 B85-10479 03
- STALMACH, D. D.**
 Contact Heat Exchanger
 MSC-20419 B85-10092 06
- STANFIELD, C. E.**
 Apparatus for Sizing and Rewinding Graphite Fibers
 LAR-13323 B85-10556 08
- STAUGAITIS, C. L.**
 Spray Application of Rapidly Solidified Metals
 GSC-12880 B85-10131 08
- STEFANESCU, D. M.**
 Cast Iron With High Carbon Content
 MFS-28014 B85-10500 04
 Solidifying Cast Iron in Low Gravity
 MFS-27069 B85-10504 04
- STEIDEL, C. F.**
 Plug-In RF Selector Switch
 MSC-20572 B85-10292 01
- STEIDENSTICKER, R. G.**
 Adjustable Lid Aids Silicon-Ribbon Growth
 NPO-16354 B85-10275 08
- STEINKE, R. J.**
 Predicting the Performance of an Axial-Flow Compressor
 LEW-14025 B85-10531 06
- STELZRIED, C. T.**
 Recovering Microwave Cross-Polarization Losses
 NPO-15353 B85-10168 02
- STEPHENSON, J. G.**
 Insulating Cryogenic Pipes With Frost
 MSC-20426 B85-10249 07
- STICKEL, W. B.**
 Prototype Furnace for Automatic Production of Silicon Ribbon
 NPO-16175 B85-10272 08
- STIFFLER, J. J.**
 Computer-Aided Reliability Estimation
 LAR-13349 B85-10315 02

- STOAKLEY, D. M.**
 Chromium Ions Improve Moisture Resistance of Epoxy Resins
 LAR-13226 B85-10486 04
 Cobalt Ions Improve the Strength of Epoxy Resins
 LAR-13230 B85-10493 04
- STONEBURNER, J. D.**
 Controlling Sample Rotation in Acoustic Levitation
 NPO-15962 B85-10277 08
- STRAYER, D. M.**
 Coating a Sphere With Evaporated Metal
 NPO-16436 B85-10404 08
- STROUB, R. H.**
 Tilttable-Wing, Tilttable-Rotor Aircraft
 ARC-11420 B85-10373 06
- STUCK, D.**
 Sensitivities of Soap Solutions in Leak Detection
 MFS-19864 B85-10121 07
- STUCKENBERG, F. H.**
 Detecting Cracks in Rough Metal Surfaces
 MSC-20734 B85-10230 06
- STUDER, P.**
 Long-Life Cryogenic Cooler
 GSC-12697 B85-10116 07
- STURMAN, J. C.**
 Dynamic-RAM Data Storage Unit
 LEW-14017 B85-10030 02
 Remote Power Controllers For High-Power dc Switching
 LEW-14109 B85-10148 01
- SUGG, F. E.**
 Frequency-Discriminating Acoustic-Event Counter
 MSC-20467 B85-10160 02
 Hand-Held Electronic Gap-Measuring Tools
 MSC-20176 B85-10223 06
 Detecting Cracks in Rough Metal Surfaces
 MSC-20734 B85-10230 06
- SUNDBERG, G.**
 Fast-Recovery, High-Voltage Power Diode
 LEW-14036 B85-10016 01
- SURAMPUDI, S.**
 Improved Electrodes for Lithium Cells
 NPO-16397 B85-10201 04
- SUSZKO, S. F.**
 Study of Contact Resistances in Integrated Circuits
 NPO-16248 B85-10159 01
 Analyzing Microchips With Dark-Field Negative Photomicrography
 NPO-16299 B85-10179 03
- SZCZUR, M. R.**
 Transportable Applications Executive
 GSC-12881 B85-10422 09
- SZMYD, W. R.**
 Segmented Trough Reflector
 NPO-15026 B85-10173 03
- SZOFRAN, F. R.**
 Characterizing Semiconductor Alloys for Infrared Sensors
 MFS-27059 B85-10355 04
- SZUCH, J. R.**
 Data Manipulation and Display
 LEW-14101 B85-10424 09

PERSONAL AUTHOR INDEX

T

- TARN, R. B.**
 Vibrational Effects of Turbopump Housing Flexibility
 MFS-27083 B85-10552 07
- TATOM, F. B.**
 Plotting Lightning-Stroke Data
 MFS-26019 B85-10462 03
- TAUSWORTHE, R. C.**
 Algorithms for Software Development
 NPO-16079 B85-10134 09
- TAYLOR, A. H.**
 Fastening Parts Having Mismatched Thermal Coefficients
 LAR-13009 B85-10113 07
 Carbon/Carbon Pistons for Internal Combustion Engines
 LAR-13150 B85-10547 07
- TAYLOR, E. C.**
 Holder for Ultrasonic Evaluation of Small-Diameter Tubes
 LAR-13152 B85-10245 07
- TAYLOR, L. W.**
 A Quick Visual Power-Supply Monitor
 MFS-26014 B85-10436 01
- TAYLOR, M. S.**
 Epoxy/Fluoroether Composites
 ARC-11418 B85-10332 04
- TAYLOR, R. E.**
 Measuring Thermal Diffusivity of Molten Semiconductors
 MFS-28047 B85-10350 04
- TCHENG, P.**
 Determining Calibration Constants for Attitude Measurements
 LAR-13214 B85-10475 03
- TELL, R. G.**
 Fast Clock Recovery for Digital Communications
 NPO-16083 B85-10019 01
- TENNEY, J. B.**
 Development of a Prosthesis for Urinary Control
 MFS-27062 B85-10359 05
- TENNEY JR., J. B.**
 Prosthetic Sphincter Controls Urination
 MFS-25740 B85-10356 05
- TEW, J. R. C.**
 Kinematic Stirling Engine Performance
 LEW-14092 B85-10482 03
- THAKOOR, A. P.**
 Magnetron-Sputtered Amorphous Metallic Coatings
 NPO-16221 B85-10204 04
 Magnetron Sputtering Deposits Corrosion-Resistant Alloy
 NPO-15928 B85-10337 04
 Solid-State Detector for Trace Materials
 NPO-16450 B85-10469 03
- THEISS, J.**
 Precise Fabrication of Electromagnetic-Levitation Coils
 MFS-25986 B85-10126 08
- THEODORE, E. A.**
 Back-Pressure Regulator for Large Gas Flows
 MSC-20536 B85-10109 07

THOMAS, J. M.

Predicting the Fatigue life of Structures
MFS-27049 B85-10206 04

THOMAS, P. D.

Three-Dimensional Grids for Flow-Field Calculations
ARC-11394 B85-10413 09

THOMCHICK, J.

Calculating Charge Transport in Semiconductors
LAR-13201 B85-10338 04

THOMPSON, F. W.

Hand-Held Electronic Gap-Measuring Tools
MSC-20176 B85-10223 06

TIEN, J. S.

Modeling a Transient Catalytic Combustor
LEW-13723 B85-10212 04

TIETZ, J. C.

Finding Bright-Spot Coordinates in Television Images
MFS-25999 B85-10034 02

TIMOC, C. C.

Designing Test Chips for Custom Integrated Circuits
NPO-15988 B85-10032 02

TOMER, R. S.

Production Process for Strong, Light Ceramic Tiles
MSC-20602 B85-10200 04

TOMKIEWICZ, Z.

Development of a Prosthesis for Urinary Control
MFS-27062 B85-10359 05

TROVILLION, T. A.

Rocket-Booster Towing Simulation
KSC-11289 B85-10102 06

TRUDELL, R. W.

Statistical Energy Analysis Program
MFS-27035 B85-10231 06

TRUONG, T. K.

Systolic VLSI Reed-Solomon Decoder
NPO-16383 B85-10304 02

Single-Chip VLSI Reed-Solomon Encoder
NPO-16122 B85-10452 02

Multiplier Architecture for Coding Circuits
NPO-16363 B85-10456 02

TSUCHIYA, T.

Axial-Flow Compressor Performance With Water Ingestion
LEW-14026 B85-10532 06

TURNER, R.

Anvil for Flaring PCB Guide Pins
MSC-20345 B85-10258 07

TURNER, R. D.

Connectors and Wiring for Cryogenic Temperatures
LAR-13193 B85-10300 01

TWARD, E.

Adsorption of H₂, Ne, and N₂ on Activated Charcoal
NPO-16329 B85-10477 03

TYERYAR, J. R.

Melt-Pressed Films of Insoluble Semicrystalline Polymers
LAR-13212 B85-10351 04

U**UNNAM, J.**

X-Ray Diffraction Analysis Program
LAR-13276 B85-10483 03

UPPALURI, B. R.

Analysis of Spiral Bevel Gearing
LEW-14067 B85-10265 07

V**VACCARELLI, M. D.**

Controllers for Flow-Field Survey Apparatus
LAR-13180 B85-10310 02

VANDERPLAATS, G. N.

Automated Design Synthesis
LAR-13341 B85-10534 06

VANE, G. A.

Compact Imaging Spectrometer
NPO-16342 B85-10471 03

VANNIER, M. W. A. A.

Multispectral Analysis of NMR Imagery
KSC-11301 B85-10215 05

VANVALKENBURGH, C.

Universal Cable Brackets
MFS-26001 B85-10129 08

VARNELL, L. S.

Segmented Detector for Cosmic Gamma Rays
NPO-16245 B85-10053 03

VAVRUS, J. L.

Text File Display Program
NPO-16358 B85-10423 09

VERDERAIME, V.

Stiffness Study of Wound-Filament Pressure Vessels
MFS-27086 B85-10530 06

VESSOT, R. F. C.

Satellite Time- and Frequency-Transfer System
MFS-25991 B85-10169 02

VILNROTTER, V. A.

Synchronization for Optical PPM Signals
NPO-16256 B85-10037 02

VIVIAN, H. C.

Battery-Charge-State Model
NPO-16158 B85-10058 03

VOECKS, G. E.

Methanol Fuel Cell
NPO-15823 B85-10050 03

VON BUN, F.

Superconducting-Cavity Accelerometer
GSC-12797 B85-10096 06

VON ROOS, O.

Measuring Carrier Lifetime in GaAs by Luminescence
NPO-16337 B85-10334 04

VON TIESENHAUSEN, G.

Tethered Communication Satellites
MFS-28042 B85-10375 06

VONROOS, O.

Measuring Recombination Velocities in Solar Cells
NPO-16243 B85-10001 01

Modeling 'Soft' Errors in Bipolar Integrated Circuits
NPO-16375 B85-10158 01

VROMAN, G. A.

Predicting the Fatigue life of Structures
MFS-27049 B85-10206 04

W**WADE, W. R.**

Tester for Distress Beacons
GSC-12892 B85-10442 01

WAGNER, G.

Image Interpolation With Dedicated Digital Hardware
GSC-12882 B85-10312 02

WAGNER, K. H.

Point Simulator for Synthetic-Aperture Radar
NPO-16296 B85-10165 02

WAKELYN, N. T.

Solvent-Resistant, Thermally Stable Poly(Carbonate-Imides)
LAR-13292 B85-10485 04

WALIGORA, J.

Effect of Hydration on Nitrogen Washout in Humans
MSC-20686 B85-10087 05

WALKLEY, K. B.

Manipulation and Display of Panel-Method Geometry
LAR-13224 B85-10282 09

WALSH, J. V.

Quasi-Porous Plug With Vortex Chamber
NPO-16076 B85-10111 07

WANG, C. C.

Fast VLSI Viterbi Decoder
NPO-16365 B85-10311 02

Multiplier Architecture for Coding Circuits
NPO-16363 B85-10456 02

WANG, D. S.

Silicone-Rubber Stitching Seal
MSC-20708 B85-10269 08

WANG, T. G.

Centrifugal Generator of Filled Spherical Shells
NPO-16051 B85-10270 08

WARD, S. W.

Communications Headgear With Protective Features
LAR-13156 B85-10166 02

WARREN, A. D.

Cutting Guide for Fibrous Sheets
MSC-20798 B85-10132 08

WATERS, J. W.

Measuring Clouds With Microwaves and Infrared
NPO-16265 B85-10045 03

WAWRZYNEK, J. C.

Complementary-Logic Fault Detector
NPO-15410 B85-10017 01

WEATHERILL, W. T.

Noncontacting Measurement With a Thermocouple
MSC-20834 B85-10374 06

WEBSTER, C. R.

Monitoring Trace Gases in the Atmosphere
NPO-16278 B85-10175 03

Tracking System for Infrared Spectrometer
NPO-16440 B85-10464 03

WEBSTER, L. D.

Laser Altimeter for Flight Simulator
ARC-11312 B85-10323 03

WEINSTEIN, L. M.

Continuous Laminar-Smoke Generator
LAR-13014 B85-10090 06

Water-Thickness Gage
LAR-13342 B85-10508 06

WELLMAN, J. B.

PERSONAL AUTHOR INDEX

- WELLMAN, J. B.**
Compact Imaging Spectrometer
NPO-16342 B85-10471 03
- WELSH, J. P.**
High-Efficiency, Low-Weight Power Transformer
LEW-14074 B85-10403 08
- WHEELER, W. H.**
High-Strength, Low-Shrinkage Ceramic Tiles
MSC-20654 B85-10495 04
- WHITE, D. M.**
Blind-Side, High-Temperature Fastener Lock
LAR-13037 B85-10248 07
- WHITCOMB, J. D.**
Geometric and Material Nonlinear Structural Analysis
LAR-13279 B85-10381 06
- WHITE, P. R.**
Flowmeter for Clear and Translucent Fluids
MFS-28030 B85-10228 06
Flowmeter for Clear Fluids
MFS-28031 B85-10372 06
- WHITE, W. L.**
Drilling Holes in Graphite/Epoxy Composites
MFS-28044 B85-10398 07
- WHITE, W. T.**
Determining Fiber Orientation in Graphite-Reinforced Composites
MFS-28032 B85-10205 04
Adhesive-Bonded Fixture for Flexure Testing
MFS-28051 B85-10360 06
- WIEDEMANN, K. E.**
X-Ray Diffraction Analysis Program
LAR-13276 B85-10483 03
- WILCOX, B.**
Convolver for Pipelined-Image Processor
NPO-16462 B85-10451 02
Programmable Pipelined-Image Processor
NPO-16463 B85-10459 02
Function Generator for Image Processor
NPO-16461 B85-10460 02
- WILLIAMS, R. M.**
Recharging Batteries Chemically
NPO-16024 B85-10143 01
Magnetron Sputtering Deposits Corrosion-Resistant Alloy
NPO-15928 B85-10337 04
- WILSON, A. H.**
Supporting Structures for Flat Solar-Cell Arrays
NPO-15600 B85-10407 08
- WILSON, M. L.**
Apparatus for Sizing and Rewinding Graphite Fibers
LAR-13323 B85-10556 08
- WINN, E.**
Anvil for Flaring PCB Guide Pins
MSC-20345 B85-10258 07
- WINNER, F. E.**
Reed-Switch Position Indicator
KSC-11215 B85-10152 01
- WINSLOW, J. W.**
Synthetic Organic Materials in Nuclear Powerplants
NPO-16424 B85-10208 04
- WOLF, M. F.**
Melt Stirring by Horizontal Crucible Vibration
MFS-26005 B85-10069 04
- Air Bearing for Small Planar Vibrations
MFS-26003 B85-10110 07
- WOOD, C.**
High-Temperature Hall-Effect Apparatus
NPO-16279 B85-10038 02
Improved Thermal-Diffusivity-Measuring Apparatus
NPO-16280 B85-10182 03
Reduced-Stress Mounting for Thermocouples
NPO-16513 B85-10444 01
Measuring Thermoelectric Properties Automatically
NPO-16507 B85-10488 04
- WOOD, J. R.**
Three-Dimensional Turbomachine-Blade-Row Analysis Code
LEW-14061 B85-10400 07
- WOOLLAM, J. A.**
Intercalated-Carbon Low-Resistivity Fibers
NPO-16307 B85-10196 04
- WU, C.**
Compensating for Range Migration in Synthetic-Aperture Radar
NPO-15954 B85-10136 09
- WU, S. C.**
Doubly-Differenced Measurements for Orbit Determinations
NPO-16111 B85-10040 02
- YAMAMOTO, Y.**
Requirements Analysis for Information-Intensive Systems
NPO-15944 B85-10415 09
- YANO, L. I.**
Statistical Energy Analysis Program
MFS-27035 B85-10231 06
- YARIV, A.**
Damping Relaxation Oscillations in Laser Diodes
NPO-15980 B85-10010 01
Improved Waveguide Laser Array
NPO-16500 B85-10435 01
- YASUI, K. K.**
Improved Surface of Titanium Structure
LAR-13148 B85-10409 08
- YAVROUIAN, A.**
Nonyellowing Polycarbonate for Outdoor Use
NPO-15836 B85-10070 04
- YAVROUIAN, A. H.**
Intercalated-Carbon Low-Resistivity Fibers
NPO-16307 B85-10196 04
- YEN, S. P. S.**
Improved Electrodes for Lithium Cells
NPO-16397 B85-10201 04
- YOO, C. H.**
Soil/Structure Interactions in Earthquakes
MFS-27078 B85-10479 03
- YOSHIOKA, E. N.**
Waterproofing Agents for Silica Tiles
MSC-20364 B85-10080 04
- YOUNG, P. R.**
Resin Characterization in Cured Composite Materials
LAR-13172 B85-10072 04
- YUEN, J. H.**
Systolic VLSI Reed-Solomon Decoder
NPO-16383 B85-10304 02

Z

- ZELEZNIK, F. J.**
Prediction of Combustion Gas Deposit Compositions
LEW-14091 B85-10280 09
- ZOLTAN, A.**
High-Temperature Hall-Effect Apparatus
NPO-16279 B85-10038 02
Improved Thermal-Diffusivity-Measuring Apparatus
NPO-16280 B85-10182 03
- ZORZI, E.**
Mechanical Design Handbook for Elastomers
LEW-14160 B85-10502 04
- ZOUTENDYK, J.**
Modeling 'Soft' Errors in Bipolar Integrated Circuits
NPO-16375 B85-10158 01
- ZUVER, N. T.**
Detecting Cracks in Rough Metal Surfaces
MSC-20734 B85-10230 06
- ZWIENER, J. M.**
Research Furnace for Crystal Preparation
LAR-13302 B85-10496 04


Y

ORIGINATING CENTER NUMBER INDEX

INDEX TO NASA TECH BRIEFS

APRIL 1987

Typical Originating Center Number Index Listing



The left hand column identifies the originating Center number, to the right of each originating Center number is the Tech Brief number, e.g., B85-10511, followed by a two-digit number, e.g., 06, which identifies the subject category containing the entire citation.

LEW-12887	B85-10511 06	GSC-12899	B85-10384 07	LAR-13175	B85-10316 03
		GSC-12902	B85-10379 06	LAR-13179	B85-10218 06
		GSC-12911	B85-10187 03	LAR-13180	B85-10310 02
		GSC-12913	B85-10068 04	LAR-13183	B85-10213 04
		GSC-12923	B85-10180 03	LAR-13185	B85-10364 06
		GSC-12933	B85-10566 09	LAR-13192	B85-10368 06
		GSC-12937	B85-10176 03	LAR-13193	B85-10300 01
				LAR-13199	B85-10253 07
		KSC-11215	B85-10152 01	LAR-13201	B85-10338 04
		KSC-11289	B85-10102 06	LAR-13202	B85-10141 01
		KSC-11293	B85-10286 09	LAR-13208	B85-10366 06
		KSC-11301	B85-10215 05	LAR-13210	B85-10521 06
		KSC-11303	B85-10014 01	LAR-13211	B85-10406 08
		KSC-11308	B85-10352 04	LAR-13212	B85-10351 04
		KSC-11309	B85-10354 04	LAR-13213	B85-10149 01
				LAR-13214	B85-10475 03
				LAR-13219	B85-10362 06
				LAR-13220	B85-10470 03
		LAR-12633	B85-10009 01	LAR-13222	B85-10491 04
		LAR-12844	B85-10105 07	LAR-13223	B85-10541 06
		LAR-12937	B85-10224 06	LAR-13224	B85-10282 09
		LAR-12946	B85-10216 06	LAR-13226	B85-10486 04
		LAR-12947	B85-10216 06	LAR-13230	B85-10493 04
		LAR-12984	B85-10020 01	LAR-13242	B85-10516 06
		LAR-12993	B85-10057 03	LAR-13243	B85-10363 06
		LAR-13002	B85-10178 03	LAR-13254	B85-10463 03
		LAR-13006	B85-10039 02	LAR-13255	B85-10514 06
		LAR-13009	B85-10113 07	LAR-13256	B85-10319 03
		LAR-13014	B85-10090 06	LAR-13257	B85-10487 04
		LAR-13017	B85-10529 06	LAR-13259	B85-10523 06
		LAR-13019	B85-10095 06	LAR-13263	B85-10540 06
		LAR-13036	B85-10114 07	LAR-13264	B85-10414 09
		LAR-13037	B85-10248 07	LAR-13265	B85-10371 06
		LAR-13040	B85-10051 03	LAR-13268	B85-10447 02
		LAR-13047	B85-10099 06	LAR-13273	B85-10457 02
		LAR-13048	B85-10098 06	LAR-13276	B85-10483 03
		LAR-13072	B85-10003 01	LAR-13279	B85-10381 06
		LAR-13074	B85-10474 03	LAR-13292	B85-10485 04
		LAR-13080	B85-10219 06	LAR-13297	B85-10382 06
		LAR-13081	B85-10100 06	LAR-13299	B85-10535 06
		LAR-13090	B85-10130 08	LAR-13302	B85-10496 04
		LAR-13095	B85-10518 06	LAR-13306	B85-10517 06
		LAR-13098	B85-10222 06	LAR-13307	B85-10498 04
		LAR-13101	B85-10545 07	LAR-13321	B85-10431 01
		LAR-13105	B85-10336 04	LAR-13323	B85-10556 08
		LAR-13106	B85-10335 04	LAR-13327	B85-10472 03
		LAR-13115	B85-10115 07	LAR-13333	B85-10527 06
		LAR-13118	B85-10076 04	LAR-13334	B85-10418 09
		LAR-13121	B85-10526 06	LAR-13337	B85-10520 06
		LAR-13132	B85-10377 06	LAR-13341	B85-10534 06
		LAR-13136	B85-10273 08	LAR-13342	B85-10508 06
		LAR-13137	B85-10167 02	LAR-13349	B85-10315 02
		LAR-13139	B85-10405 08	LAR-13351	B85-10490 04
		LAR-13146	B85-10278 08		
		LAR-13147	B85-10515 06		
		LAR-13148	B85-10409 08		
		LAR-13150	B85-10547 07	LEW-12887	B85-10511 06
		LAR-13151	B85-10147 01	LEW-13294	B85-10093 06
		LAR-13152	B85-10245 07	LEW-13450	B85-10347 04
		LAR-13153	B85-10410 08	LEW-13467	B85-10401 07
		LAR-13154	B85-10225 06	LEW-13506	B85-10528 06
		LAR-13156	B85-10166 02	LEW-13723	B85-10212 04
		LAR-13169	B85-10507 06	LEW-13920	B85-10389 07
		LAR-13171	B85-10075 04	LEW-13925	B85-10232 06
		LAR-13172	B85-10072 04	LEW-13927	B85-10263 07
		LAR-13174	B85-10316 03	LEW-13978	B85-10537 06
				LEW-14000	B85-10191 03
ARC-11280	B85-10125 08				
ARC-11312	B85-10323 03				
ARC-11348	B85-10031 02				
ARC-11365	B85-10133 08				
ARC-11394	B85-10413 09				
ARC-11405	B85-10343 04				
ARC-11408	B85-10064 04				
ARC-11409	B85-10064 04				
ARC-11413	B85-10074 04				
ARC-11418	B85-10332 04				
ARC-11420	B85-10373 06				
ARC-11424	B85-10348 04				
ARC-11427	B85-10079 04				
ARC-11428	B85-10333 04				
ARC-11444	B85-10227 06				
ARC-11453	B85-10489 04				
ARC-11454	B85-10305 02				
ARC-11467	B85-10412 09				
ARC-11495	B85-10525 06				
ARC-11497	B85-10562 09				
ARC-11498	B85-10120 07				
ARC-11502	B85-10043 03				
ARC-11506	B85-10062 04				
ARC-11511	B85-10061 04				
FRC-11065	B85-10088 06				
GSC-12697	B85-10116 07				
GSC-12758	B85-10264 07				
GSC-12797	B85-10096 06				
GSC-12807	B85-10291 01				
GSC-12817	B85-10018 01				
GSC-12827	B85-10564 09				
GSC-12832	B85-10015 01				
GSC-12849	B85-10325 03				
GSC-12852	B85-10328 03				
GSC-12858	B85-10421 09				
GSC-12880	B85-10131 08				
GSC-12881	B85-10422 09				
GSC-12882	B85-10312 02				
GSC-12883	B85-10194 04				
GSC-12892	B85-10442 01				
GSC-12897	B85-10320 03				

CENTER

ORIGINATING CENTER/TECH BRIEF NUMBER INDEX

LEW-14002	B85-10420 09	MFS-27041	B85-10198 04	MSC-20602	B85-10200 04
LEW-14011	B85-10380 06	MFS-27043	B85-10084 04	MSC-20622	B85-10370 06
LEW-14017	B85-10030 02	MFS-27047	B85-10494 04	MSC-20640	B85-10035 02
LEW-14025	B85-10531 06	MFS-27049	B85-10206 04	MSC-20654	B85-10495 04
LEW-14026	B85-10532 06	MFS-27051	B85-10261 07	MSC-20668	B85-10294 01
LEW-14027	B85-10376 06	MFS-27052	B85-10101 06	MSC-20677	B85-10276 08
LEW-14032	B85-10344 04	MFS-27059	B85-10355 04	MSC-20684	B85-10394 07
LEW-14036	B85-10016 01	MFS-27062	B85-10359 05	MSC-20686	B85-10087 05
LEW-14050	B85-10028 02	MFS-27063	B85-10259 07	MSC-20703	B85-10378 06
LEW-14060	B85-10402 07	MFS-27065	B85-10499 04	MSC-20705	B85-10027 02
LEW-14061	B85-10265 07	MFS-27068	B85-10481 03	MSC-20706	B85-10221 06
LEW-14067	B85-10403 08	MFS-27069	B85-10504 04	MSC-20708	B85-10269 08
LEW-14074	B85-10538 06	MFS-27072	B85-10559 09	MSC-20709	B85-10154 01
LEW-14089	B85-10280 09	MFS-27078	B85-10479 03	MSC-20712	B85-10266 08
LEW-14091	B85-10482 03	MFS-27083	B85-10552 07	MSC-20714	B85-10078 04
LEW-14092	B85-10533 06	MFS-27084	B85-10555 08	MSC-20729	B85-10256 07
LEW-14095	B85-10399 07	MFS-27086	B85-10550 06	MSC-20734	B85-10230 06
LEW-14100	B85-10424 09	MFS-27094	B85-10480 03	MSC-20744	B85-10229 06
LEW-14101	B85-10252 07	MFS-28001	B85-10271 08	MSC-20759	B85-10117 07
LEW-14105	B85-10536 06	MFS-28002	B85-10118 07	MSC-20762	B85-10425 09
LEW-14106	B85-10148 01	MFS-28006	B85-10361 06	MSC-20769	B85-10172 02
LEW-14109	B85-10461 02	MFS-28007	B85-10217 06	MSC-20771	B85-10284 09
LEW-14128	B85-10492 04	MFS-28014	B85-10500 04	MSC-20777	B85-10565 09
LEW-14131	B85-10502 04	MFS-28018	B85-10145 01	MSC-20778	B85-10568 09
LEW-14160	B85-10539 06	MFS-28020	B85-10189 03	MSC-20795	B85-10274 08
LEW-14163	B85-10553 07	MFS-28021	B85-10185 03	MSC-20798	B85-10132 08
LEW-14167		MFS-28024	B85-10251 07	MSC-20834	B85-10374 06
		MFS-28030	B85-10228 06	MSC-20841	B85-10542 07
MFS-19767	B85-10250 07	MFS-28031	B85-10228 06	MSC-20847	B85-10506 05
MFS-19775	B85-10395 07	MFS-28032	B85-10372 06	MSC-20853	B85-10289 01
MFS-19864	B85-10121 07	MFS-28037	B85-10205 04	MSC-20855	B85-10427 09
MFS-19866	B85-10391 07	MFS-28040	B85-10369 06	MSC-20863	B85-10313 02
MFS-19876	B85-10108 07	MFS-28041	B85-10339 04	MSC-20869	B85-10438 01
MFS-19900	B85-10119 07	MFS-28042	B85-10346 04	MSC-20878	B85-10513 06
MFS-19909	B85-10103 07	MFS-28044	B85-10375 06	MSC-20907	B85-10550 07
MFS-19916	B85-10089 06	MFS-28046	B85-10398 07		
MFS-19925	B85-10026 02	MFS-28047	B85-10365 06		
MFS-19947	B85-10549 07	MFS-28048	B85-10350 04	NPO-13386	B85-10453 02
MFS-19948	B85-10331 04	MFS-28051	B85-10567 09	NPO-13506	B85-10004 01
MFS-19950	B85-10397 07	MFS-28053	B85-10360 06	NPO-14955	B85-10210 04
MFS-25207	B85-10150 01	MFS-28059	B85-10357 05	NPO-14956	B85-10210 04
MFS-25352	B85-10281 09	MFS-28060	B85-10392 07	NPO-15000	B85-10279 09
MFS-25678	B85-10254 07	MFS-28066	B85-10326 03	NPO-15026	B85-10173 03
MFS-25740	B85-10356 05	MFS-28076	B85-10522 06	NPO-15059	B85-10164 02
MFS-25750	B85-10301 02	MFS-28077	B85-10437 01	NPO-15131	B85-10186 03
MFS-25800	B85-10085 05	MFS-29000	B85-10484 04	NPO-15233	B85-10383 07
MFS-25925	B85-10195 04	MFS-29044	B85-10510 06	NPO-15308	B85-10056 03
MFS-25940	B85-10214 04	MFS-29048	B85-10554 08	NPO-15313	B85-10330 04
MFS-25976	B85-10307 02	MFS-29062	B85-10519 06	NPO-15353	B85-10168 02
MFS-25977	B85-10055 03		B85-10548 07	NPO-15354	B85-10168 02
MFS-25978	B85-10443 01			NPO-15410	B85-10017 01
MFS-25980	B85-10112 07	MSC-18866	B85-10183 03	NPO-15451	B85-10426 09
MFS-25984	B85-10047 03	MSC-18969	B85-10097 06	NPO-15537	B85-10011 01
MFS-25986	B85-10126 08	MSC-20006	B85-10157 01	NPO-15563	B85-10044 03
MFS-25987	B85-10285 09	MSC-20044	B85-10138 09	NPO-15567	B85-10144 01
MFS-25989	B85-10104 07	MSC-20056	B85-10142 01	NPO-15600	B85-10407 08
MFS-25991	B85-10169 02	MSC-20136	B85-10177 03	NPO-15657	B85-10122 08
MFS-25992	B85-10094 06	MSC-20175	B85-10268 08	NPO-15700	B85-10309 02
MFS-25995	B85-10197 04	MSC-20176	B85-10223 06	NPO-15719	B85-10151 01
MFS-25999	B85-10034 02	MSC-20195	B85-10008 01	NPO-15775	B85-10432 01
MFS-26000	B85-10267 08	MSC-20206	B85-10106 07	NPO-15779	B85-10433 01
MFS-26001	B85-10129 08	MSC-20232	B85-10135 09	NPO-15803	B85-10052 03
MFS-26003	B85-10110 07	MSC-20345	B85-10258 07	NPO-15805	B85-10168 02
MFS-26005	B85-10069 04	MSC-20357	B85-10161 02	NPO-15823	B85-10023 01
MFS-26006	B85-10071 04	MSC-20364	B85-10080 04	NPO-15836	B85-10050 03
MFS-26008	B85-10042 03	MSC-20369	B85-10137 09	NPO-15837	B85-10070 04
MFS-26013	B85-10465 03	MSC-20403	B85-10036 02	NPO-15859	B85-10306 02
MFS-26014	B85-10436 01	MSC-20419	B85-10092 06	NPO-15867	B85-10388 07
MFS-26015	B85-10546 07	MSC-20426	B85-10249 07	NPO-15871	B85-10303 02
MFS-26016	B85-10524 06	MSC-20444	B85-10128 08	NPO-15909	B85-10551 07
MFS-26019	B85-10462 03	MSC-20467	B85-10160 02	NPO-15914	B85-10146 01
MFS-27016	B85-10024 01	MSC-20477	B85-10220 06	NPO-15928	B85-10247 07
MFS-27020	B85-10199 04	MSC-20487	B85-10260 07	NPO-15944	B85-10337 04
MFS-27027	B85-10049 03	MSC-20536	B85-10109 07	NPO-15947	B85-10415 09
MFS-27030	B85-10082 04	MSC-20549	B85-10257 07	NPO-15953	B85-10455 02
MFS-27035	B85-10231 06	MSC-20552	B85-10066 04	NPO-15954	B85-10296 01
MFS-27037	B85-10081 04	MSC-20572	B85-10155 01	NPO-15962	B85-10136 09
			B85-10292 01		B85-10277 08

ORIGINATING CENTER/TECH BRIEF NUMBER INDEX


NPO-15980	B85-10010 01	NPO-16276	B85-10013 01	NPO-16440	B85-10464 03
NPO-15988	B85-10032 02	NPO-16278	B85-10175 03	NPO-16444	B85-10416 09
NPO-15992	B85-10077 04	NPO-16279	B85-10038 02	NPO-16446	B85-10563 09
NPO-16003	B85-10209 04	NPO-16280	B85-10182 03	NPO-16448	B85-10318 03
NPO-16019	B85-10041 03	NPO-16284	B85-10321 03	NPO-16450	B85-10469 03
NPO-16024	B85-10143 01	NPO-16287	B85-10060 04	NPO-16457	B85-10396 07
NPO-16030	B85-10002 01	NPO-16293	B85-10158 01	NPO-16461	B85-10460 02
NPO-16034	B85-10202 04	NPO-16296	B85-10165 02	NPO-16462	B85-10451 02
NPO-16038	B85-10393 07	NPO-16297	B85-10006 01	NPO-16463	B85-10459 02
NPO-16043	B85-10302 02	NPO-16299	B85-10179 03	NPO-16464	B85-10458 02
NPO-16051	B85-10270 08	NPO-16300	B85-10467 03	NPO-16466	B85-10544 07
NPO-16053	B85-10059 03	NPO-16304	B85-10170 02	NPO-16467	B85-10441 01
NPO-16057	B85-10029 02	NPO-16305	B85-10287 09	NPO-16468	B85-10470 02
NPO-16067	B85-10022 01	NPO-16306	B85-10192 04	NPO-16479	B85-10509 06
NPO-16072	B85-10046 03	NPO-16307	B85-10196 04	NPO-16480	B85-10503 04
NPO-16076	B85-10111 07	NPO-16310	B85-10174 03	NPO-16493	B85-10476 03
NPO-16079	B85-10134 09	NPO-16313	B85-10171 02	NPO-16496	B85-10478 03
NPO-16083	B85-10019 01	NPO-16314	B85-10387 07	NPO-16497	B85-10450 02
NPO-16091	B85-10124 08	NPO-16315	B85-10153 01	NPO-16499	B85-10445 01
NPO-16092	B85-10123 08	NPO-16318	B85-10246 07	NPO-16500	B85-10435 01
NPO-16094	B85-10262 07	NPO-16320	B85-10560 09	NPO-16507	B85-10488 04
NPO-16096	B85-10446 01	NPO-16321	B85-10385 07	NPO-16510	B85-10497 04
NPO-16097	B85-10226 06	NPO-16326	B85-10140 01	NPO-16513	B85-10444 01
NPO-16106	B85-10033 02	NPO-16328	B85-10255 07	NPO-16544	B85-10440 01
NPO-16108	B85-10324 03	NPO-16329	B85-10477 03	NPO-16550	B85-10449 02
NPO-16110	B85-10439 01	NPO-16330	B85-10025 01		
NPO-16111	B85-10040 02	NPO-16331	B85-10188 03		
NPO-16114	B85-10065 04	NPO-16336	B85-10349 04		
NPO-16116	B85-10163 02	NPO-16337	B85-10334 04		
NPO-16117	B85-10386 07	NPO-16339	B85-10558 09		
NPO-16121	B85-10073 04	NPO-16340	B85-10367 06		
NPO-16122	B85-10452 02	NPO-16342	B85-10471 03		
NPO-16126	B85-10021 01	NPO-16345	B85-10207 04		
NPO-16153	B85-10005 01	NPO-16349	B85-10358 05		
NPO-16158	B85-10058 03	NPO-16350	B85-10411 09		
NPO-16158	B85-10299 01	NPO-16352	B85-10298 01		
NPO-16165	B85-10193 04	NPO-16354	B85-10275 08		
NPO-16166	B85-10067 04	NPO-16355	B85-10329 03		
NPO-16167	B85-10054 03	NPO-16357	B85-10419 09		
NPO-16170	B85-10139 09	NPO-16358	B85-10423 09		
NPO-16173	B85-10473 03	NPO-16359	B85-10505 05		
NPO-16175	B85-10272 08	NPO-16362	B85-10297 01		
NPO-16176	B85-10434 01	NPO-16363	B85-10456 02		
NPO-16177	B85-10233 07	NPO-16364	B85-10162 02		
NPO-16178	B85-10234 07	NPO-16365	B85-10311 02		
NPO-16179	B85-10235 07	NPO-16373	B85-10327 03		
NPO-16180	B85-10236 07	NPO-16375	B85-10158 01		
NPO-16182	B85-10237 07	NPO-16377	B85-10417 09		
NPO-16183	B85-10238 07	NPO-16379	B85-10448 02		
NPO-16184	B85-10239 07	NPO-16383	B85-10304 02		
NPO-16185	B85-10240 07	NPO-16384	B85-10158 01		
NPO-16188	B85-10241 07	NPO-16385	B85-10341 04		
NPO-16189	B85-10242 07	NPO-16386	B85-10293 01		
NPO-16190	B85-10243 07	NPO-16388	B85-10184 03		
NPO-16194	B85-10244 07	NPO-16391	B85-10342 04		
NPO-16203	B85-10086 05	NPO-16393	B85-10543 07		
NPO-16211	B85-10308 02	NPO-16397	B85-10201 04		
NPO-16212	B85-10203 04	NPO-16399	B85-10211 04		
NPO-16216	B85-10091 06	NPO-16400	B85-10283 09		
NPO-16218	B85-10190 03	NPO-16401	B85-10390 07		
NPO-16221	B85-10204 04	NPO-16402	B85-10429 01		
NPO-16225	B85-10468 03	NPO-16403	B85-10428 01		
NPO-16226	B85-10345 04	NPO-16404	B85-10314 02		
NPO-16228	B85-10063 04	NPO-16406	B85-10561 09		
NPO-16230	B85-10295 01	NPO-16408	B85-10322 03		
NPO-16233	B85-10512 06	NPO-16409	B85-10501 04		
NPO-16243	B85-10001 01	NPO-16410	B85-10430 01		
NPO-16245	B85-10053 03	NPO-16411	B85-10353 04		
NPO-16248	B85-10159 01	NPO-16413	B85-10408 08		
NPO-16256	B85-10037 02	NPO-16416	B85-10557 08		
NPO-16257	B85-10107 07	NPO-16419	B85-10340 04		
NPO-16258	B85-10083 04	NPO-16424	B85-10208 04		
NPO-16265	B85-10045 03	NPO-16425	B85-10181 03		
NPO-16268	B85-10012 01	NPO-16429	B85-10288 01		
NPO-16269	B85-10007 01	NPO-16431	B85-10317 03		
NPO-16270	B85-10156 01	NPO-16434	B85-10466 03		
NPO-16273	B85-10048 03	NPO-16435	B85-10290 01		
NPO-16275	B85-10127 08	NPO-16436	B85-10404 06		

TECH BRIEF NUMBER INDEX

INDEX TO NASA TECH BRIEFS

APRIL 1987

Typical Tech Brief
Number Index Listing



The left hand column identifies the Tech Brief number, e.g., B85-10158, followed by a two-digit number, e.g., 01, which identifies the subject category containing the entire citation. Following the subject category number is the originating Center number.

B85-10001 01	NPO-16243	B85-10065 04	NPO-16114	B85-10109 07	MSC-20536
B85-10002 01	NPO-16030	B85-10066 04	MSC-20552	B85-10110 07	MFS-26003
B85-10003 01	LAR-13072	B85-10067 04	NPO-16166	B85-10111 07	NPO-16076
B85-10004 01	NPO-13506	B85-10068 04	GSC-12913	B85-10112 07	MFS-25980
B85-10005 01	NPO-16153	B85-10069 04	MFS-26005	B85-10113 07	LAR-13009
B85-10006 01	NPO-16297	B85-10070 04	NPO-15836	B85-10114 07	LAR-13036
B85-10007 01	NPO-16269	B85-10071 04	MFS-26006	B85-10115 07	LAR-13115
B85-10008 01	MSC-20195	B85-10072 04	LAR-13172	B85-10116 07	GSC-12697
B85-10009 01	LAR-12633	B85-10073 04	NPO-16121	B85-10117 07	MSC-20759
B85-10010 01	NPO-15980	B85-10074 04	ARC-11413	B85-10118 07	MFS-28002
B85-10011 01	NPO-15537	B85-10075 04	LAR-13171	B85-10119 07	MFS-19900
B85-10012 01	NPO-16268	B85-10076 04	LAR-13118	B85-10120 07	ARC-11498
B85-10013 01	NPO-16276	B85-10077 04	NPO-15992	B85-10121 07	MFS-19864
B85-10014 01	KSC-11303	B85-10078 04	MSC-20714	B85-10122 08	NPO-15657
B85-10015 01	GSC-12832	B85-10079 04	ARC-11427	B85-10123 08	NPO-16092
B85-10016 01	LEW-14036	B85-10080 04	MSC-20364	B85-10124 08	NPO-16091
B85-10017 01	NPO-15410	B85-10081 04	MFS-27037	B85-10125 08	ARC-11280
B85-10018 01	GSC-12817	B85-10082 04	MFS-27030	B85-10126 08	MFS-25986
B85-10019 01	NPO-16083	B85-10083 04	NPO-16258	B85-10127 08	NPO-16275
B85-10020 01	LAR-12984	B85-10084 04	MFS-27043	B85-10128 08	MSC-20444
B85-10021 01	NPO-16126	B85-10085 05	MFS-25800	B85-10129 08	MFS-26001
B85-10022 01	NPO-16067	B85-10086 05	NPO-16203	B85-10130 08	LAR-13090
B85-10023 01	NPO-15805	B85-10087 05	MSC-20686	B85-10131 08	GSC-12880
B85-10024 01	MFS-27016	B85-10088 06	FRC-11065	B85-10132 08	MSC-20798
B85-10025 01	NPO-16330	B85-10089 06	MFS-19916	B85-10133 08	ARC-11365
B85-10026 02	MFS-19925	B85-10090 06	LAR-13014	B85-10134 09	NPO-16079
B85-10027 02	MSC-20705	B85-10091 06	NPO-16216	B85-10135 09	MSC-20232
B85-10028 02	LEW-14050	B85-10092 06	MSC-20419	B85-10136 09	NPO-15954
B85-10029 02	NPO-16057	B85-10093 06	LEW-13294	B85-10137 09	MSC-20369
B85-10030 02	LEW-14017	B85-10094 06	MFS-25992	B85-10138 09	MSC-20044
B85-10031 02	ARC-11348	B85-10095 06	LAR-13019	B85-10139 09	NPO-16170
B85-10032 02	NPO-15988	B85-10096 06	GSC-12797	B85-10140 01	NPO-16326
B85-10033 02	NPO-16106	B85-10097 06	MSC-18969	B85-10141 01	LAR-13202
B85-10034 02	MFS-25999	B85-10098 06	LAR-13048	B85-10142 01	MSC-20056
B85-10035 02	MSC-20640	B85-10099 06	LAR-13047	B85-10143 01	NPO-16024
B85-10036 02	MSC-20403	B85-10100 06	LAR-13081	B85-10144 01	NPO-15567
B85-10037 02	NPO-16256	B85-10101 06	MFS-27052	B85-10145 01	MFS-28018
B85-10038 02	NPO-16279	B85-10102 06	KSC-11289	B85-10146 01	NPO-15909
B85-10039 02	LAR-13006	B85-10103 07	MFS-19909	B85-10147 01	LAR-13151
B85-10040 02	NPO-16111	B85-10104 07	MFS-25989	B85-10148 01	LEW-14109
B85-10041 03	NPO-16019	B85-10105 07	LAR-12844	B85-10149 01	LAR-13213
B85-10042 03	MFS-26008	B85-10106 07	MSC-20206	B85-10150 01	MFS-25207
B85-10043 03	ARC-11502	B85-10107 07	NPO-16257	B85-10151 01	NPO-15719
B85-10044 03	NPO-15563	B85-10108 07	MFS-19876	B85-10152 01	KSC-11215
				B85-10153 01	NPO-16315
				B85-10154 01	MSC-20709
				B85-10155 01	MSC-20562
				B85-10156 01	NPO-16270
				B85-10157 01	MSC-20006
				B85-10158 01	NPO-16293
					NPO-16375
					NPO-16384
					NPO-16248
					MSC-20467
					MSC-20357
					NPO-16364
					NPO-16116
					NPO-15059
					NPO-16296
					LAR-13156
					LAR-13137
					NPO-15353
					NPO-15354
					NPO-15803
					MFS-25991

NUMBER

TECH BRIEF/ORIGINATING CENTER NUMBER INDEX

B85-10170 02	NPO-16304	B85-10245 07	LAR-13152	B85-10321 03	NPO-16284
B85-10171 02	NPO-16313	B85-10246 07	NPO-16318	B85-10322 03	NPO-16408
B85-10172 02	MSC-20769	B85-10247 07	NPO-15914	B85-10323 03	ARC-11312
B85-10173 03	NPO-15026	B85-10248 07	LAR-13037	B85-10324 03	NPO-16108
B85-10174 03	NPO-16310	B85-10249 07	MSC-20426	B85-10325 03	GSC-12849
B85-10175 03	NPO-16278	B85-10250 07	MFS-19767	B85-10326 03	MFS-28060
B85-10176 03	GSC-12937	B85-10251 07	MFS-28024	B85-10327 03	NPO-16373
B85-10177 03	MSC-20136	B85-10252 07	LEW-14105	B85-10328 03	GSC-12852
B85-10178 03	LAR-13002	B85-10253 07	LAR-13199	B85-10329 03	NPO-16355
B85-10179 03	NPO-16299	B85-10254 07	MFS-25678	B85-10330 04	NPO-15313
B85-10180 03	GSC-12923	B85-10255 07	NPO-16328	B85-10331 04	MFS-19948
B85-10181 03	NPO-16425	B85-10256 07	MSC-20729	B85-10332 04	ARC-11418
B85-10182 03	NPO-16280	B85-10257 07	MSC-20549	B85-10333 04	ARC-11428
B85-10183 03	MSC-18866	B85-10258 07	MSC-20345	B85-10334 04	NPO-16337
B85-10184 03	NPO-16388	B85-10259 07	MFS-27063	B85-10335 04	LAR-13106
B85-10185 03	MFS-28021	B85-10260 07	MSC-20487	B85-10336 04	LAR-13105
B85-10186 03	NPO-15131	B85-10261 07	MFS-27051	B85-10337 04	NPO-15928
B85-10187 03	GSC-12911	B85-10262 07	NPO-16094	B85-10338 04	LAR-13201
B85-10188 03	NPO-16331	B85-10263 07	LEW-13927	B85-10339 04	MFS-28040
B85-10189 03	MFS-28020	B85-10264 07	GSC-12758	B85-10340 04	NPO-16419
B85-10190 03	NPO-16218	B85-10265 07	LEW-14067	B85-10341 04	NPO-16385
B85-10191 03	LEW-14000	B85-10266 08	MSC-20712	B85-10342 04	NPO-16391
B85-10192 04	NPO-16306	B85-10267 08	MFS-26000	B85-10343 04	ARC-11405
B85-10193 04	NPO-16165	B85-10268 08	MSC-20175	B85-10344 04	LEW-14032
B85-10194 04	GSC-12883	B85-10269 08	MSC-20708	B85-10345 04	NPO-16226
B85-10195 04	MFS-25925	B85-10270 08	NPO-16051	B85-10346 04	MFS-28041
B85-10196 04	NPO-16307	B85-10271 08	MFS-28001	B85-10347 04	LEW-13450
B85-10197 04	MFS-25995	B85-10272 08	NPO-16175	B85-10348 04	ARC-11424
B85-10198 04	MFS-27041	B85-10273 08	LAR-13136	B85-10349 04	NPO-16336
B85-10199 04	MFS-27020	B85-10274 08	MSC-20795	B85-10350 04	MFS-28047
B85-10200 04	MSC-20602	B85-10275 08	NPO-16354	B85-10351 04	LAR-13212
B85-10201 04	NPO-16397	B85-10276 08	MSC-20677	B85-10352 04	KSC-11308
B85-10202 04	NPO-16034	B85-10277 08	NPO-15962	B85-10353 04	NPO-16411
B85-10203 04	NPO-16212	B85-10278 08	LAR-13146	B85-10354 04	KSC-11309
B85-10204 04	NPO-16221	B85-10279 09	NPO-15000	B85-10355 04	MFS-27059
B85-10205 04	MFS-28032	B85-10280 09	LEW-14091	B85-10356 05	MFS-25740
B85-10206 04	MFS-27049	B85-10281 09	MFS-25352	B85-10357 05	MFS-28053
B85-10207 04	NPO-16345	B85-10282 09	LAR-13224	B85-10358 05	NPO-16349
B85-10208 04	NPO-16424	B85-10283 09	NPO-16400	B85-10359 05	MFS-27062
B85-10209 04	NPO-16003	B85-10284 09	MSC-20771	B85-10360 06	MFS-28051
B85-10210 04	NPO-14955	B85-10285 09	MFS-25987	B85-10361 06	MFS-28006
	NPO-14956	B85-10286 09	KSC-11293	B85-10362 06	LAR-13219
B85-10211 04	NPO-16399	B85-10287 09	NPO-16305	B85-10363 06	LAR-13243
B85-10212 04	LEW-13723	B85-10288 01	NPO-16429	B85-10364 06	LAR-13185
B85-10213 04	LAR-13183	B85-10289 01	MSC-20853	B85-10365 06	MFS-28046
B85-10214 04	MFS-25940	B85-10290 01	NPO-16435	B85-10366 06	LAR-13208
B85-10215 05	KSC-11301	B85-10291 01	GSC-12807	B85-10367 06	NPO-16340
B85-10216 06	LAR-12946	B85-10292 01	MSC-20572	B85-10368 06	LAR-13192
	LAR-12947	B85-10293 01	NPO-16386	B85-10369 06	MFS-28037
B85-10217 06	MFS-28007	B85-10294 01	MSC-20668	B85-10370 06	MSC-20622
B85-10218 06	LAR-13179	B85-10295 01	NPO-16230	B85-10371 06	LAR-13265
B85-10219 06	LAR-13080	B85-10296 01	NPO-15953	B85-10372 06	MFS-28031
B85-10220 06	MSC-20477	B85-10297 01	NPO-16362	B85-10373 06	ARC-11420
B85-10221 06	MSC-20706	B85-10298 01	NPO-16352	B85-10374 06	MSC-20834
B85-10222 06	LAR-13098	B85-10299 01	NPO-16158	B85-10375 06	MFS-28042
B85-10223 06	MSC-20176	B85-10300 01	LAR-13193	B85-10376 06	LEW-14027
B85-10224 06	LAR-12937	B85-10301 02	MFS-25750	B85-10377 06	LAR-13132
B85-10225 06	LAR-13154	B85-10302 02	NPO-16043	B85-10378 06	MSC-20703
B85-10226 06	NPO-16097	B85-10303 02	NPO-15867	B85-10379 06	GSC-12902
B85-10227 06	ARC-11444	B85-10304 02	NPO-16383	B85-10380 06	LEW-14011
B85-10228 06	MFS-28030	B85-10305 02	ARC-11454	B85-10381 06	LAR-13279
B85-10229 06	MSC-20744	B85-10306 02	NPO-15837	B85-10382 06	LAR-13297
B85-10230 06	MSC-20734	B85-10307 02	MFS-25976	B85-10383 07	NPO-15233
B85-10231 06	MFS-27035	B85-10308 02	NPO-16211	B85-10384 07	GSC-12899
B85-10232 06	LEW-13925	B85-10309 02	NPO-15700	B85-10385 07	NPO-16321
B85-10233 07	NPO-16177	B85-10310 02	LAR-13180	B85-10386 07	NPO-16117
B85-10234 07	NPO-16178	B85-10311 02	NPO-16365	B85-10387 07	NPO-16314
B85-10235 07	NPO-16179	B85-10312 02	GSC-12882	B85-10388 07	NPO-15859
B85-10236 07	NPO-16180	B85-10313 02	MSC-20863	B85-10389 07	LEW-13920
B85-10237 07	NPO-16182	B85-10314 02	NPO-16404	B85-10390 07	NPO-16401
B85-10238 07	NPO-16183	B85-10315 02	LAR-13349	B85-10391 07	MFS-19866
B85-10239 07	NPO-16184	B85-10316 03	LAR-13174	B85-10392 07	MFS-28059
B85-10240 07	NPO-16185		LAR-13175	B85-10393 07	NPO-16038
B85-10241 07	NPO-16188	B85-10317 03	NPO-16431	B85-10394 07	MSC-20684
B85-10242 07	NPO-16189	B85-10318 03	NPO-16448	B85-10395 07	MFS-19775
B85-10243 07	NPO-16190	B85-10319 03	LAR-13256	B85-10396 07	NPO-16457
B85-10244 07	NPO-16194	B85-10320 03	GSC-12897	B85-10397 07	MFS-19950

TECH BRIEF/ORIGINATING CENTER NUMBER INDEX

B85-10398 07	MFS-28044	B85-10475 03	LAR-13214	B85-10552 07	MFS-27083
B85-10399 07	LEW-14100	B85-10476 03	NPO-16493	B85-10553 07	LEW-14167
B85-10400 07	LEW-14061	B85-10477 03	NPO-16329	B85-10554 08	MFS-29044
B85-10401 07	LEW-13467	B85-10478 03	NPO-16496	B85-10555 08	MFS-27084
B85-10402 07	LEW-14060	B85-10479 03	MFS-27078	B85-10556 08	LAR-13323
B85-10403 08	LEW-14074	B85-10480 03	MFS-27094	B85-10557 08	NPO-16416
B85-10404 08	NPO-16436	B85-10481 03	MFS-27068	B85-10558 09	NPO-16339
B85-10405 08	LAR-13139	B85-10482 03	LEW-14092	B85-10559 09	MFS-27072
B85-10406 08	LAR-13211	B85-10483 03	LAR-13276	B85-10560 09	NPO-16320
B85-10407 08	NPO-15600	B85-10484 04	MFS-28077	B85-10561 09	NPO-16406
B85-10408 08	NPO-16413	B85-10485 04	LAR-13292	B85-10562 09	ARC-11497
B85-10409 08	LAR-13148	B85-10486 04	LAR-13226	B85-10563 09	NPO-16446
B85-10410 08	LAR-13153	B85-10487 04	LAR-13257	B85-10564 09	GSC-12827
B85-10411 09	NPO-16350	B85-10488 04	NPO-16507	B85-10565 09	MSC-20777
B85-10412 09	ARC-11467	B85-10489 04	ARC-11453	B85-10566 09	GSC-12933
B85-10413 09	ARC-11394	B85-10490 04	LAR-13351	B85-10567 09	MFS-28048
B85-10414 09	LAR-13264	B85-10491 04	LAR-13222	B85-10568 09	MSC-20778
B85-10415 09	NPO-15944	B85-10492 04	LEW-14131		
B85-10416 09	NPO-16444	B85-10493 04	LAR-13230		
B85-10417 09	NPO-16377	B85-10494 04	MFS-27047		
B85-10418 09	LAR-13334	B85-10495 04	MSC-20654		
B85-10419 09	NPO-16357	B85-10496 04	LAR-13302		
B85-10420 09	LEW-14002	B85-10497 04	NPO-16510		
B85-10421 09	GSC-12858	B85-10498 04	LAR-13307		
B85-10422 09	GSC-12881	B85-10499 04	MFS-27065		
B85-10423 09	NPO-16358	B85-10500 04	MFS-28014		
B85-10424 09	LEW-14101	B85-10501 04	NPO-16409		
B85-10425 09	MSC-20762	B85-10502 04	LEW-14160		
B85-10426 09	NPO-15451	B85-10503 04	NPO-16480		
B85-10427 09	MSC-20855	B85-10504 04	MFS-27069		
B85-10428 01	NPO-16403	B85-10505 05	NPO-16359		
B85-10429 01	NPO-16402	B85-10506 05	MSC-20847		
B85-10430 01	NPO-16410	B85-10507 06	LAR-13169		
B85-10431 01	LAR-13321	B85-10508 06	LAR-13342		
B85-10432 01	NPO-15775	B85-10509 06	NPO-16479		
B85-10433 01	NPO-15775	B85-10510 06	MFS-29000		
B85-10434 01	NPO-16176	B85-10511 06	LEW-12887		
B85-10435 01	NPO-16500	B85-10512 06	NPO-16233		
B85-10436 01	MFS-26014	B85-10513 06	MSC-20878		
B85-10437 01	MFS-28076	B85-10514 06	LAR-13255		
B85-10438 01	MSC-20869	B85-10515 06	LAR-13147		
B85-10439 01	NPO-16110	B85-10516 06	LAR-13242		
B85-10440 01	NPO-16544	B85-10517 06	LAR-13306		
B85-10441 01	NPO-16467	B85-10518 06	LAR-13095		
B85-10442 01	GSC-12892	B85-10519 06	MFS-29048		
B85-10443 01	MFS-25978	B85-10520 06	LAR-13337		
B85-10444 01	NPO-16513	B85-10521 06	LAR-13210		
B85-10445 01	NPO-16499	B85-10522 06	MFS-28066		
B85-10446 01	NPO-16096	B85-10523 06	LAR-13259		
B85-10447 02	LAR-13268	B85-10524 06	MFS-26016		
B85-10448 02	NPO-16379	B85-10525 06	ARC-11495		
B85-10449 02	NPO-16550	B85-10526 06	LAR-13121		
B85-10450 02	NPO-16497	B85-10527 06	LAR-13333		
B85-10451 02	NPO-16462	B85-10528 06	LEW-13506		
B85-10452 02	NPO-16122	B85-10529 06	LAR-13017		
B85-10453 02	NPO-13386	B85-10530 06	MFS-27086		
B85-10454 02	NPO-16468	B85-10531 06	LEW-14025		
B85-10455 02	NPO-15947	B85-10532 06	LEW-14026		
B85-10456 02	NPO-16363	B85-10533 06	LEW-14095		
B85-10457 02	LAR-13273	B85-10534 06	LAR-13341		
B85-10458 02	NPO-16464	B85-10535 06	LAR-13299		
B85-10459 02	NPO-16463	B85-10536 06	LEW-14106		
B85-10460 02	NPO-16461	B85-10537 06	LEW-13978		
B85-10461 02	LEW-14128	B85-10538 06	LEW-14089		
B85-10462 03	MFS-26019	B85-10539 06	LEW-14163		
B85-10463 03	LAR-13254	B85-10540 06	LAR-13263		
B85-10464 03	NPO-16440	B85-10541 06	LAR-13223		
B85-10465 03	MFS-26013	B85-10542 07	MSC-20841		
B85-10466 03	NPO-16434	B85-10543 07	NPO-16393		
B85-10467 03	NPO-16300	B85-10544 07	NPO-16466		
B85-10468 03	NPO-16225	B85-10545 07	LAR-13101		
B85-10469 03	NPO-16450	B85-10546 07	MFS-26015		
B85-10470 03	LAR-13220	B85-10547 07	LAR-13150		
B85-10471 03	NPO-16342	B85-10548 07	MFS-29062		
B85-10472 03	LAR-13327	B85-10549 07	MFS-19947		
B85-10473 03	NPO-16173	B85-10550 07	MSC-20907		
B85-10474 03	LAR-13074	B85-10551 07	NPO-15871		

